Order Report APIs

Covers: Order Book, Order History, Trade Book APIs

1. Introduction

Kotak Securities offers APIs to fetch your:

- **Order Book** (all open, completed, and rejected orders)
- **Order History** (all order status changes/updates for a particular order)
- **Trade Book** (details of completed trades for the trading day)

These APIs allow you to fetch and monitor all relevant trading activity programmatically.

2. API Endpoints

API	Endpoint (after <Base URL>)	Method
Order Book	`/quick/user/orders`	GET
Order History	`/quick/order/history`	POST
Trade Book	`/quick/user/trades`	GET

> *Replace `<Base URL>` with the relevant Kotak environment base URL provided in response from /tradeApiValidate api.*

3. Headers

Applicable to all three APIs:

Name	Type	Description
accept	string	Should always be `application/json`
Sid	string	session sid generated on login
Auth	string	session token generated on login
neo-fin-key	string	static value: neotradeapi
Content-Type	string	Always `application/x-www-form-urlencoded`

4. Request

4.1. GET Order Book

Example Request:

```
curl -X GET "<baseUrl>/quick/user/orders" \ -H "Auth: <session_token>" \ -H "Sid: <session_sid>" \ -H "neo-fin-key: neotradeapi"
```

> No request body or parameters required.

4.2. POST Order History

Request Body:

Send `jData` as url-encoded JSON.

Example:

```
curl -X GET "<baseUrl>/quick/user/order/history" \ -H "Auth: <session_token>" \ -H "Sid: <session_sid>" \ -H "neo-fin-key: neotradeapi" --data-urlencode 'jData={"nOrdNo":"250720000007242"}'
```

Field	Type	Description	Required
nOrdNo	string	Nest order number for which history is required	Yes

4.3. GET Trade Book

Example Request:

```
# Trade Book curl -X GET "<baseUrl>/quick/user/trades" \ -H "Auth: <session_token>" \ -H "Sid: <session_sid>" \ -H "neo-fin-key: neotradeapi"No request body or parameters required.
```

5. Response

5.1. GET Order Book Response

Success Example (truncated):

```
{ "stat": "Ok", "data": [ { "nOrdNo": "250720000007242", "ordSt": "rejected", "trdSym": "ITBEES-EQ", "qty": 1, "prc": "0.00", "avgPrc": "0.00", "trnsTp": "B", "prcTp": "L", "vldt": "DAY", ... }, { "nOrdNo": "250720000007588", "ordSt": "after market order req received", "trdSym": "ITBEES-EQ", "qty": 1, "prc": "0.00", "avgPrc": "0.00", ... } ], "stCode": 200 }
```

Important Fields (Truncated and Simplified)

Field	Type	Description
nOrdNo	string	Nest order number
ordSt / stat	string	Order status ("open", "rejected", etc.)
trdSym	string	Trading symbol e.g., "ITBEES-EQ"
qty	int	Quantity
prc	string	Placed price
avgPrc	string	Average traded price
trnsTp	string	Transaction type - "B"=Buy, "S"=Sell
prcTp	string	Order type: "L"=Limit, "MKT"=Market, etc.
vldt	string	Validity (DAY/IOC)
rejRsn	string	Rejection reason if any
exSeg	string	Exchange segment e.g., "nse_cm"
ordGenTp	string	"AMO" for after-market orders, else blank
ordDtTm	string	Order date/time
stat	string	Overall status at top level: "Ok" for success

The order book contains all available fields per order as per API glossary.

5.2. POST Order History Response

Success Example (truncated):

```
{ "stat": "Ok", "stCode": 200, "data": [ { "nOrdNo": "250720000007242",
"flDtTm": "20-Jul-2025 20:21:42", "ordSt": "rejected", "rejRsn": "ADAPTER
is down", "qty": 1, "prc": "0.00", "avgPrc": "0.00", "prod": "MIS",
"trnsTp": "B", "prcTp": "L", ... }, { "nOrdNo": "250720000007242",
"flDtTm": "20-Jul-2025 20:21:42", "ordSt": "open pending", ... } ] }
```

Field	Type	Description
nOrdNo	string	Nest order number
ordSt	string	Status at this stage
flDtTm	string	Date/time for the update
qty	int	Order quantity at this status
prc	string	Order price at this status
avgPrc	string	Average price at this stage
prod	string	Product type ("MIS", "CNC")
trnsTp	string	Transaction type ("B"=Buy, "S"=Sell)
prcTp	string	Order type ("L", "MKT", etc.)
rejRsn	string	Rejection reason if applicable

Full list of all response fields is available in Order Book API Glossary, as most fields are common.

5.3. GET Trade Book Response

Success Example (truncated):

```
{ "stat": "Ok", "stCode": 200, "data": [ { "nOrdNo": "221007000000354",
"trdSym": "TCS-EQ", "qty": 11, "avgPrc": "3194.00", "fldQty": 11, "flDt":
"07-Oct-2022", "exOrdId": "1100000000047870", "exTm": "07-Oct-2022
13:04:14", "prcTp": "L", "prod": "CNC", "ordDur": "DAY", "trnsTp": "B",
"usrId": "PRABHAT", ... } ] }
```

Field	Type	Description
nOrdNo	string	Nest order number
trdSym	string	Trading symbol
qty	int	Trade quantity
avgPrc	string	Average execution price
fldQty	int	Filled quantity
flDt	string	Trade date
exOrdId	string	Exchange order ID
exTm	string	Trade execution datetime
prcTp	string	Order type (L/MKT/SL/etc.)
prod	string	Product code ("CNC","MIS", etc.)
ordDur	string	Order validity (DAY/IOC)
trnsTp	string	Transaction type (B/S)
usrId	string	User/client ID

Additional fields are available and can be referenced from the API glossary.

Common Response Fields

Field	Type	Description