

SQL[DDL, DML] assignment

-- CUSTOMERS TABLE

```
CREATE TABLE customers (  
customer_id SERIAL PRIMARY KEY,  
name VARCHAR(100) NOT NULL,  
email VARCHAR(100) UNIQUE NOT NULL,  
phone VARCHAR(15) UNIQUE NOT NULL,  
address TEXT NOT NULL,  
created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
);
```

-- RESTAURANTS TABLE

```
CREATE TABLE restaurants (  
restaurant_id SERIAL PRIMARY KEY,  
name VARCHAR(100) NOT NULL,  
city VARCHAR(50) NOT NULL,  
rating DECIMAL(2,1) CHECK (rating >= 0 AND rating <= 5),  
is_active BOOLEAN DEFAULT TRUE  
);
```

-- MENU ITEMS TABLE

```
CREATE TABLE menu_items (  
item_id SERIAL PRIMARY KEY,  
restaurant_id INT NOT NULL,  
item_name VARCHAR(100) NOT NULL,  
price DECIMAL(10,2) CHECK (price > 0),  
is_available BOOLEAN DEFAULT TRUE,  
FOREIGN KEY (restaurant_id) REFERENCES restaurants(restaurant_id)  
);
```

-- DELIVERY PARTNERS TABLE

```
CREATE TABLE delivery_partners (  
    partner_id SERIAL PRIMARY KEY,  
    name VARCHAR(100) NOT NULL,  
    phone VARCHAR(15) UNIQUE NOT NULL,  
    vehicle_type VARCHAR(50) NOT NULL,  
    is_available BOOLEAN DEFAULT TRUE  
);
```

-- ORDERS TABLE

```
CREATE TABLE orders (  
    order_id SERIAL PRIMARY KEY,  
    customer_id INT NOT NULL,  
    restaurant_id INT NOT NULL,  
    partner_id INT NOT NULL,  
    order_time TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
    total_amount DECIMAL(10,2),  
    order_status VARCHAR(50) NOT NULL,  
    FOREIGN KEY (customer_id) REFERENCES customers(customer_id),  
    FOREIGN KEY (restaurant_id) REFERENCES restaurants(restaurant_id),  
    FOREIGN KEY (partner_id) REFERENCES delivery_partners(partner_id)  
);
```

-- ORDER ITEMS TABLE

```
CREATE TABLE order_items (  
    order_item_id SERIAL PRIMARY KEY,  
    order_id INT NOT NULL,  
    item_id INT NOT NULL,  
    quantity INT CHECK (quantity > 0),  
    FOREIGN KEY (order_id) REFERENCES orders(order_id),  
    FOREIGN KEY (item_id) REFERENCES menu_items(item_id)  
);
```

-- PAYMENTS TABLE

```
CREATE TABLE payments (  
    payment_id SERIAL PRIMARY KEY,  
    order_id INT UNIQUE NOT NULL,  
    payment_method VARCHAR(50) NOT NULL,  
    payment_status VARCHAR(50) NOT NULL,  
    payment_time TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
    FOREIGN KEY (order_id) REFERENCES orders(order_id)  
);
```

