

CSS Selectors

1. **Element Selector**
2. **Id Selector**
3. **Class Selector**
4. **Universal Selector**
5. **Child selector**
6. **Descendant Selector**
7. **Pseudo Selector**
8. **Grouping Selector**

1. The CSS element Selector

The element selector selects HTML elements based on the element name.

```
p {  
  text-align: center;  
  color: red;  
}
```

2. The CSS id Selector

The id selector uses the id attribute of an HTML element to select a specific element.

The id of an element is unique within a page, so the id selector is used to select one unique element!

To select an element with a specific id, write a hash (#) character, followed by the id of the element

The CSS rule below will be applied to the HTML element with id="para1":

```
#para1 {  
    text-align: center;  
    color: red;  
}
```

3. The CSS class Selector

The class selector selects HTML elements with a specific class attribute.

To select elements with a specific class, write a period (.) character, followed by the class name.

In this example all HTML elements with class="center" will be red and center-aligned:

```
.center {  
    text-align: center;  
    color: red;  
}
```

4. The CSS Universal Selector

The universal selector (*) selects all HTML elements on the page.

```
* {  
  text-align: center;  
  color: blue;  
}
```

The CSS Grouping Selector

The grouping selector selects all the HTML elements with the same style definitions.

Look at the following CSS code (the h1, h2, and p elements have the same style definitions):

```
h1, h2, p {  
  text-align: center;  
  color: red;  
}
```

<!DOCTYPE html>

<html lang="en">

<head>

<meta charset="UTF-8" />

<meta name="viewport"
content="width=device-width, initial-
scale=1.0" />

```
<title>CSS</title>
```

```
<style>
```

```
/* Element Selector */
```

```
h1 {
```

```
    color: red;
```

```
}
```

```
/* class Selector */
```

```
.div1 {
```

```
    color: red;
```

```
}
```

```
/* id Selector */
```

```
#div2 {
```

```
    color: blue;
```

```
}
```

```
/* child selector */
```

```
div > p {
```

```
    color: red;
```

```
}  
  
/* descendant Selector */  
div p {  
    color: red;  
    background-color: black;  
}  
  
/* universal selector */  
* {  
    margin: 0;  
    padding: 0;  
}  
  
/* Pseudo Selector */  
a:link {  
    background-color: black;  
}  
  
a:hover {  
    background-color: blueviolet;
```

```
}  
p:first-child {  
  color: red;  
}  
</style>  
</head>  
<body>  
  <!-- <h1>We are learning Selectors in  
CSS</h1>  
  
  <div>  
    <span>  
      <p>  
        Lorem ipsum dolor sit, amet  
consectetur adipisicing elit. Id veniam  
consectetur illum voluptatem error  
cum similique porro aut quae  
voluptatum?
```

</p>

</div>

Google
 -->

<div>

<p>i m in div</p>

<p>

 Lorem ipsum dolor sit, amet
consectetur adipisicing elit. Incidunt,
 tempore.

</p>

</div>

<p>l m in span</p>

<p>

Lorem ipsum dolor sit, amet
consectetur adipisicing elit. Temporibus,
culpa.

</p>

</body>

</html>