

CSS transition Property

The **transition-property CSS property** sets which CSS properties will have a transition effect, enabling smooth animations for specified properties when they change, without altering the layout or requiring JavaScript.

This property is a combination of four sub-properties

- transition-property
- transition-duration
- transition-timing-function
- transition-delay

Note: The transition effect can be defined in two states (hover and active) using pseudo-classes like `hover` or `active` or classes dynamically set by using JavaScript.

Property Values

Property	Description
transition-property	Specifies the CSS properties to which a transition effect should be applied.
transition-duration	Specifies the length of time a transition animation should take to complete.
transition-timing-function	Specifies the speed curve of the transition effect.
transition-delay	Specifies the delay before the transition effect starts.

```
<style>
.mydiv {
  width: 200px;
```

```
        height: 200px;
        background-color: red;
        border: 5px solid greenyellow;
    }
    .mydiv:hover {
        background-color: white;
    }
</style>
</head>
<body>
    <div class="mydiv"></div>
</body>
```

```
<style>
    .mydiv {
        width: 200px;
        height: 200px;
        background-color: red;
        border: 5px solid greenyellow;
        /* transition: background-color;
        transition-duration: 1s;
        transition-timing-function: ease;
        transition-delay: 1s; */
        transition: background-color 2s ease-in;
    }
    .mydiv:hover {
        background-color: white;
    }
</style>
</head>
<body>
    <div class="mydiv"></div>
```

```
<style>
    .mydiv {
        width: 200px;
        height: 200px;
        background-color: red;
        border: 5px solid greenyellow;
        transition: width 2s ease-in;
    }
    .mydiv:hover {
        width: 300px;
        height: 300px;
    }
}
```

```
</style>
</head>
<body>
  <div class="mydiv"></div>
```

What is the purpose of the Transition Property in CSS

The [Transition](#) property in CSS is used to smoothly animate changes in property values over a specified duration. It enhances the user experience by creating fluid and visually appealing transitions between different states of an element.

Features

- **Smooth Animations:** `transition` allows for smooth and gradual changes in property values.
 - **Properties:** You can specify multiple properties to transition simultaneously.
 - **Duration:** Defines the time it takes for the transition to complete (e.g., `0.5s` for half a second).
 - **Timing Functions:** Specifies the acceleration and deceleration of the transition (e.g., `ease-in-out`).
 - **Delay:** Optional delay before the transition starts.
-

```
<style>
  .mydiv {
    width: 200px;
    height: 200px;
    background-color: red;
    border: 5px solid greenyellow;
    transition: height 2s ease-in;
  }
  .mydiv:hover {
    /* width: 300px; */
    height: 300px;
  }
</style>
</head>
<body>
```

```
<div class="mydiv"></div>
</body>
```

```
<style>
  div {
    height: 75px;
    width: 75px;
    background: yellowgreen;
    color: red;
    transition: width 5s;
  }

  #div1 {
    transition-timing-function: linear;
  }

  #div2 {
    transition-timing-function: ease;
  }

  #div3 {
    transition-timing-function: ease-in;
  }

  #div4 {
    transition-timing-function: ease-out;
  }

  div:hover {
    width: 300px;
  }
</style>
</head>
<body>
  <h1>The transition-timing-function Property.</h1>
  <p>
    This is an example for the linear value in the transition-timing-function
    property.
  </p>
  <div id="div1">linear</div>

  <p>
    This is an example for the ease value in the transition-timing-function
    property.
  </p>
  <div id="div2">ease</div>

  <p>
    This is an example for the ease-in value in the transition-timing-function
    property.
```

```
</p>
<div id="div3">ease-in</div>

<p>
  This is an example for the ease-out value in the
  transition-timing-function property.
</p>
<div id="div4">ease-out</div>
```

There are many different values that we can give to this property, some of them are:

Value	Description
linear	Animation progresses at a constant speed.
ease-in	Animation starts slowly and speeds up at the end.
ease-out	Animation starts quickly and slows down at the end.
initial	Sets the property to its default value (ease).