
# **Objectives**

After completing this lesson, you should be able to do the following:

- Describe SET operators
- Use a SET operator to combine multiple queries into a single query
- · Control the order of rows returned

## The SET Operators



#### The SET Operators

The SET operators combine the results of two or more component queries into one result. Queries containing SET operators are called *compound queries*.

Operator	Returns
UNION	All distinct rows selected by either query
UNION ALL	All rows selected by either query, including all duplicates
INTERSECT	All distinct rows selected by both queries
MINUS	All distinct rows that are selected by the first SELECT statement and that
	are not selected in the second SELECT statement

All SET operators have equal precedence. If a SQL statement contains multiple SET operators, the Oracle server evaluates them from left (top) to right (bottom) if no parentheses explicitly specify another order. You should use parentheses to specify the order of evaluation explicitly in queries that use the INTERSECT operator with other SET operators.

Note: In the slide, the light color (grey) in the diagram represents the query result.

#### Tables Used in This Lesson

The tables used in this lesson are:

- EMPLOYEES: Provides details regarding all current employees
- JOB\_HISTORY: When an employee switches jobs, the details of the start date and end date of the former job, the job identification number and department are recorded in this table

The structure and the data from the EMPLOYEES and the JOB\_HISTORY tables are shown on the next page.

There have been instances in the company of people who have held the same position more than once during their tenure with the company. For example, consider the employee Taylor, who joined the company on 24-MAR-1998. Taylor held the job title SA\_REP for the period 24-MAR-98 to 31-DEC-98 and the job title SA\_MAN for the period 01-JAN-99 to 31-DEC-99. Taylor moved back into the job title of SA\_REP, which is his current job title.

Similarly consider the employee Whalen, who joined the company on 17-SEP-1987. Whalen held the job title AD\_ASSI for the period 17-SEP-87 to 17-JUN-93 and the job title AC\_ACCOUNT for the period 01-JUL-94 to 31-DEC-98. Taylor moved back into the job title of AD\_ASSI, which is his current job title.

## Tables Used in This Lesson (continued)

DESC employees

Name	Null?	Туре
EMPLOYEE_ID	NOT NULL	NUMBER(6)
FIRST_NAME		VARCHAR2(20)
LAST_NAME	NOT NULL	VARCHAR2(25)
EMAL	NOT NULL	VARCHAR2(25)
PHONE_NUMBER		VARCHAR2(20)
HIRE_DATE	NOT NULL	DATE
JOB_ID	NOT NULL	VARCHAR2(10)
SALARY		NUMBER(B,2)
COMMISSION_PCT		NUMBER(2,2)
MANAGER_ID		NUMBER(6)
DEPARTMENT_ID		NUMBER(4)

SELECT employee\_id, last\_name, job\_id, hire\_date, department\_id
FROM employees;

EMPLOYEE_ID	LAST_NAME	JOB_ID	HIRE_DATE	DEPARTMENT_ID
100	King	AD_PRES	17-JUN-B7	90
101	Kochhar	AD_VP	21-SEP-89	90
102	De Haan	AD_VP	13-JAN-93	90
103	Hunold	IT_PROG	03-JAN-90	60
104	Ernst	IT_PROG	21-MAY-91	60
107	Lorentz	IT_PROG	07-FEB-99	60
124	Mourgos	ST_MAN	16-NDV-99	50
141	Rajs	ST_CLERK	17-OCT-95	50
142	Davies	ST_CLERK	29-JAN-97	50
143	Matos	ST_CLERK	15-MAR-98	50
144	Vargas	ST_CLERK	09-JUL-9B	50
149	Zlotkey	SA_MAN	29-JAN-00	80
174	Abel	SA_REP	11-MAY-96	80
176	Taylor	SA REP	24-MAR-98	80
178	Grant	SA_REP	24-MAY-99	
200	Whalen	AD ASST	17-SEP-87	10
201	Hartstein	MK_MAN	17-FEB-96	20
202	Fay	MK_REP	17-AUG-97	20
205	Higgins	AC_MGR	07-JUN-94	110
206	Gietz	AC_ACCOUNT	07-JUN-94	110

20 rows selected.

## Tables Used in This Lesson (continued)

DESC job\_history


Name	Nul?	Туре
EMPLOYEE_ID	NOT NULL	NUMBER(6)
START_DATE	NOT NULL	DATE
END_DATE	NOT YULL	DATE
JOB_ID	NOT YULL	VARCHAR2(10)
DEPARTMENT_ID		NUMBER(4)

SELECT \* FROM job\_history;

EMPLOYEE_ID	START_DAT	END_DATE	JOB_ID	DEPARTMENT_ID
102	13-JAN-93	24-JUL-9B	IT_PROG	60
101	21-SEP-89	27-OCT-93	AC_ACCOUNT	110
101	20-OCT-90	15-MAR-97	AC_MGR	110
201	17-FEE-96	19-DEC-99	MK_REP	20
114	24-MAR-98	31-DEC-99	ST_CLERK	50
122	01-JAN-99	31-DE0-99	ST_CLERK	50
200	17-SEP-87	17-JUN-93	AC_ASST	90
176	24-MAR-98	31-DEC-98	SA_REP	BU
17G	01-JAN-90	DY-DEC-00	GA_MAN	00
200	D151UL94	31-DEC-98	AC_ACCOUNT	91

10 rows selected.

# The UNION SET Operator



The UNION operator returns results from both queries after eliminating duplications.

#### The UNION SET Operator

The UNION operator returns all rows selected by either query. Use the UNION operator to return all rows from multiple tables and eliminate any duplicate rows.

#### Guidelines

- The number of columns and the data types of the columns being selected must be identical in all the SELECT statements used in the query. The names of the columns need not be identical.
- UNION operates over all of the columns being selected.
- NULL values are not ignored during duplicate checking.
- The IN operator has a higher precedence than the UNION operator.
- By default, the output is sorted in ascending order of the first column of the SELECT clause.

## Using the UNION Operator

# Display the current and previous job details of all employees. Display each employee only once.


```
SELECT employee_id, job_id
FROM employees
UNION
SELECT employee_id, job_id
FROM job_history;
```

10	AC_ACCOUNT
	I AD_VH B SA_REP
200	AC_ACCOUNT
200	D AD ASST

#### Consider the following example:

```
SELECT employee_id, job_id, department_id
FROM employees
UNION
SELECT employee_id, job_id, department_id
FROM job history;
```

## The UNION ALL Operator



The UNION ALL operator returns results from both queries including all duplications.

### The UNION ALL Operator

Use the UNION ALL operator to return all rows from multiple queries.

#### Guidelines

- · Unlike UNION, duplicate rows are not eliminated and the output is not sorted by default.
- · The DISTINCT keyword cannot be used.

Note: With the exception of the above, the guidelines for UNION and UNION ALL are the same.

## Using the UNION ALL Operator

# Display the current and previous departments of all employees.

SELECT employee_id, job_id, department_id	
FROM employees	
UNION ALL	
SELECT employee id, job id, department id	
FROM job history	
ORDER BY employee_id;	

EMPLOYEE_ID	JOB_ID	DEPARTMENT_ID
100	AD_PRES	90
174	SA_REF	1
176	SA_REP	80
176	SA_MAN	80
176	SA_REP	80
205	AC_MGR	110
206	AC_ACCOUNT	110
30 raws selected		

#### The UNION ALL Operator (continued)


In the example, 30 rows are selected. The combination of the two tables totals to 30 rows. The UNION ALL operator does not eliminate duplicate records. The duplicate records are highlighted in the output shown in the slide. UNION returns all distinct rows selected by either query. UNION ALL returns all rows selected by either query, including all duplicates. Consider the query on the slide, now written with the UNION clause:

```
SELECT employee_id, job_id,department_id
FROM employees
UNION
SELECT employee_id, job_id,department_id
FROM job_history
ORDER BY employee id;
```

The preceding query returns 29 rows. This is because it eliminates the following row (as it is a duplicate):

EMPL/OYEE_ID	JOB_ID	DEPARTMENT_ID
176	SA_REP	80

### The INTERSECT Operator



The INTERSECT operator returns results that are common to both queries.

#### The INTERSECT Operator

Use the INTERSECT operator to return all rows common to multiple queries.

#### Guidelines

- The number of columns and the data types of the columns being selected by the SELECT statements in the queries must be identical in all the SELECT statements used in the query. The names of the columns need not be identical.
- · Reversing the order of the intersected tables does not alter the result.
- INTERSECT does not ignore NULL values.

#### Using the INTERSECT Operator

Display the employee IDs and job IDs of employees who are currently in a job title that they have held once before during their tenure with the company

```
SELECT employee_id, job_id
FROM employees
INTERSECT
SELECT employee_id, job_id
FROM job_history;
```

EMPLOYEE_ID	J0B_ID
176	BA_REP
200	AD_ASST

In the example in this slide, the query returns only the records that have the same values in the selected columns in both tables.

What will be the results if you add the DEPARTMENT\_ID column to the SELECT statement from the EMPLOYEES table and add the DEPARTMENT\_ID column to the SELECT statement from the JOB\_HISTORY table and run this query? The results may be different because of the introduction of another column whose values may or may not be duplicates.


#### Example

```
SELECT employee_id, job_id, department_id
FROM employees
INTERSECT
SELECT employee_id, job_id, department_id
FROM job history;
```

EMPLOYEE_ID	JOB_ID	DEPARTMENT_ID
176	SA_REP	80

Employee 200 is no longer part of the results because the EMPLOYEES.DEPARTMENT\_ID value is different from the JOB HISTORY.DEPARTMENT ID value.

## The MINUS Operator



The MINUS operator returns rows from the first query that are not present in the second query.

#### The MINUS Operator


Use the MINUS operator to return rows returned by the first query that are not present in the second query (the first SELECT statement MINUS the second SELECT statement).

#### Guidelines

- The number of columns and the data types of the columns being selected by the SELECT statements
  in the queries must be identical in all the SELECT statements used in the query. The names of the
  columns need not be identical.
- All of the columns in the WHERE clause must be in the SELECT clause for the MINUS operator to work.

## The MINUS Operator

Display the employee IDs of those employees who have not changed their jobs even once.



EMPLOYEE_ID	JOB_ID
100	AD_PRES
101	AD_VP
	To the
_	_
	MK_MAN
.202	MK_MAN MK_REP AC_MGR

In the example in the slide, the employee IDs in the JOB\_HISTORY table are subtracted from those in the EMPLOYEES table. The results set displays the employees remaining after the subtraction; they are represented by rows that exist in the EMPLOYEES table but do not exist in the JOB\_HISTORY table. These are the records of the employees who have not changed their jobs even once.

## SET Operator Guidelines

- The expressions in the SELECT lists must match in number and data type.
- Parentheses can be used to alter the sequence of execution.
- The ORDER BY clause:
  - Can appear only at the very end of the statement
  - Will accept the column name, aliases from the first SELECT statement, or the positional notation

#### SET Operator Guidelines

 The expressions in the select lists of the queries must match in number and datatype. Queries that use UNION, UNION ALL, INTERSECT, and MINUS SET operators in their WHERE clause must have the same number and type of columns in their SELECT list. For example:

```
SELECT employee_id, department_id
FROM employees
WHERE (employee_id, department_id)
IN (SELECT employee_id, department_id
FROM employees
UNION
SELECT employee_id, department_id
FROM job history);
```

- The ORDER BY clause:
  - Can appear only at the very end of the statement
  - Will accept the column name, an alias, or the positional notation
- The column name or alias, if used in an ORDER BY clause, must be from the first SELECT list.
- SET operators can be used in subqueries.

## The Oracle Server and SET Operators

- Duplicate rows are automatically eliminated except in UNION ALL.
- Column names from the first query appear in the result.
- The output is sorted in ascending order by default except in UNION ALL.


When a query uses SET operators, the Oracle Server eliminates duplicate rows automatically except in the case of the UNION ALL operator. The column names in the output are decided by the column list in the first SELECT statement. By default, the output is sorted in ascending order of the first column of the SELECT clause.

The corresponding expressions in the select lists of the component queries of a compound query must match in number and datatype. If component queries select character data, the data type of the return values are determined as follows:

- If both queries select values of datatype CHAR, the returned values have datatype CHAR.
- If either or both of the queries select values of datatype VARCHAR2, the returned values have datatype VARCHAR2.

## Matching the SELECT Statements

Using the UNION operator, display the department ID, location, and hire date for all employees.




27 rows selected

As the expressions in the select lists of the queries must match in number , you can use dummy columns and the data type conversion functions to comply with this rule. In the slide, the name location is given as the dummy column heading. The TO\_NUMBER function is used in the first query to match the NUMBER data type of the LOCATION\_ID column retrieved by the second query. Similarly, the TO\_DATE function in the second query is used to match the DATE datatype of the HIRE\_DATE column retrieved by the second query.

## Matching the SELECT Statement

Using the UNION operator, display the employee ID, job ID, and salary of all employees.



EMPLOYEE_ID	JOB_ID	SALARY
100	AD_PRES	24000
101	AC_ACCOUNT	0
101	AC_MGR	0
Y CONTRACTOR OF THE PROPERTY O		

205 AU_MIGR	12005
208 AC_ACCOUNT	8300

The EMPLOYEES and JOB\_HISTORY tables have several columns in common; for example, EMPLOYEE\_ID, JOB\_ID and DEPARTMENT\_ID. But what if you want the query to display the EMPLOYEE\_ID, JOB\_ID, and SALARY using the UNION operator, knowing that the salary exists only in the EMPLOYEES table?

The code example in the slide matches the EMPLOYEE\_ID and the JOB\_ID columns in the EMPLOYEES and in the JOB\_HISTORY tables. A literal value of 0 is added to the JOB\_HISTORY SELECT statement to match the numeric SALARY column in the EMPLOYEES SELECT statement.

In the preceding results, each row in the output that corresponds to a record from the JOB\_HISTORY table contains a 0 in the SALARY column.

## Controlling the Order of Rows

# Produce an English sentence using two UNION operators.

```
COLUMN a_dummy NOPRINT
SELECT 'sing' AS "My dream", 3 a_dummy
FROM dual
UNION
SELECT 'I''d like to teach', 1
FROM dual
UNION
SELECT 'the world to', 2
FROM dual
ORDER BY 2;

My dream

[Id like to teach
the world to
```

By default, the output is sorted in ascending order on the first column. You can use the ORDER BY clause to change this.

#### Using ORDER BY to Order Rows

sing

The ORDER BY clause can be used only once in a compound query. If used, the ORDER BY clause must be placed at the end of the query. The ORDER BY clause accepts the column name, an alias, or the positional notation. Without the ORDER BY clause, the code example in the slide produces the following output in the alphabetical order of the first column:

	My dream	
I'd like to teach		
sing		
the world to		

Note: Consider a compound query where the UNION SET operator is used more than once. In this case, the ORDER BY clause can use only positions rather than explicit expressions.

### **ASSIGNMENTS**

 List the department IDs for departments that do not contain the job ID ST\_CLERK, using SET operators.

10
20
60
80
90
110
190

Display the country ID and the name of the countries that have no departments located in them, using SET operators.

CO	COUNTRY_NAME	
DE	Germany	

Produce a list of jobs for departments 10, 50, and 20, in that order. Display job ID and department ID, using SET operators.

JOB_ID	DEPARTMENT_ID
AD_ASST	10
ST_CLERK	50
ST_MAN	50
MK_MAN	20
MK_REP	20

List the employee IDs and job IDs of those employees who are currently in the job title that
they have held once before during their tenure with the company.

EMPLOYEE_ID	JOB_ID
176	SA_REP
200	AD_ASST

- 5. Write a compound query that lists the following:
  - Last names and department ID of all the employees from the EMPLOYEES table, irrespective
    of the fact whether they belong to any department or not
  - Department ID and department name of all the departments from the DEPARTMENTS table, irrespective of the fact whether they have employees working in them or not.

LAST_NAME	DEPARTMENT_ID	TO_CHAR(NULL)
Abel	80	
Davies	50	
De Haan	90	
Ernst	60	
Fay	20	
Gietz	110	
Grant		
Hartstein	20	
Higgins	110	
Hunold	60	
King	90	
Kochhar	90	
Lorentz	60	
Matos	50	
Maurgos	-50	
Rajs	-50	
Taylor	80	
Vargas	50	
Whalen	10	
Zlotkey	80	
	10	Administration
	20	Marketing
	50	Shipping
	60	IT
	80	Sales
	90	Executive
	110	Accounting
	190	Contracting

28 rows selected.