

## Statistical Analysis System: Class 17

Dated: 28 Apr, 2018



### Global & Local Options in SAS

- If defined once, works for all the datasets in the sas editor until the session is closed
- If global option is overwritten, then updated global option will be functional for the rest of the code in the editor.
- If a dataset has local option, the same will be functional only and not the global option.
- By default global option has MAX range.
- Practical application is the SRP (sample run of production).

SAS Program	Explanation
<b>Prog 1</b> options obs=2; data a; set sasuser.admit; run;	<b>Explained For 1</b> Global option defined is OBS = 2 Output dataset “a” will have only 2 Observations.  NOTE: There were 2 observations read from the data set SASUSER.ADMIT. NOTE: The data set WORK.A has 2 observations and 9 variables. NOTE: DATA statement used (Total process time): real time        1.56 seconds cpu time         1.40 seconds
<b>Prog 2</b> options obs=5; data b; set sasuser.admit; run;	<b>Explained For 2</b> Global option overwritten, is OBS = 5 Output dataset “b” will have only 5 Observations.  NOTE: There were 5 observations read from the data set SASUSER.ADMIT. NOTE: The data set WORK.B has 5 observations and 9 variables. NOTE: DATA statement used (Total process time): real time        0.07 seconds cpu time         0.04 seconds
<b>Prog 3</b> data c; set sasuser.admit(obs=10) ; run;	<b>Explained For 3</b> Global option overwritten, is set to OBS = 5 (from Prog 2). But Local option sets, OBS=10 and nullifies Global option, OBS=5, but only for this particular dataset. Output dataset “c” will have 10 Observations.  NOTE: There were 10 observations read from the data set SASUSER.ADMIT. NOTE: The data set WORK.C has 10 observations and 9 variables. NOTE: DATA statement used (Total process time): real time        0.04 seconds cpu time         0.04 seconds
<b>Prog 4</b> data k; set sasuser.admit; run;	<b>Explained For 4</b> Global option, OBS=5 (continues from Prog 2) Output “K” has 5 observations.  NOTE: There were 5 observations read from the data set SASUSER.ADMIT. NOTE: The data set WORK.K has 5 observations and 9 variables. NOTE: DATA statement used (Total process time): real time        0.04 seconds cpu time         0.04 seconds

<p><b>Prog 5</b></p> <pre>options obs=max; data d; set sasuser.admit; run;</pre>	<p><b>Explained For 5</b></p> <p>Global option, OBS=max ( Obs=max, is the default range for global option) Output “d” has 21 observations.</p> <p>NOTE: There were 21 observations read from the data set SASUSER.ADMIT. NOTE: The data set WORK.D has 21 observations and 9 variables. NOTE: DATA statement used (Total process time):</p> <table> <tr> <td>real time</td><td>0.03 seconds</td></tr> <tr> <td>cpu time</td><td>0.03 seconds</td></tr> </table> <p><b>Explained For 6</b></p> <p>Global option, OBS=max ( Obs=max, continued from Prog 5) Output “e” has 21 observations.</p> <p>NOTE: There were 21 observations read from the data set SASUSER.ADMIT. NOTE: The data set WORK.E has 21 observations and 9 variables. NOTE: DATA statement used (Total process time):</p> <table> <tr> <td>real time</td><td>0.03 seconds</td></tr> <tr> <td>cpu time</td><td>0.03 seconds</td></tr> </table>	real time	0.03 seconds	cpu time	0.03 seconds	real time	0.03 seconds	cpu time	0.03 seconds
real time	0.03 seconds								
cpu time	0.03 seconds								
real time	0.03 seconds								
cpu time	0.03 seconds								
<p><b>Prog 6</b></p> <pre>data e; set sasuser.admit; run;</pre>									

## PROC SQL:

- SQL stands for Structured Query Language.
- Query is a code written with SQL
- Proc sql goes with following 6 keywords:
  1. Select ( select \*, denotes selection of every variable from the specified table)
  2. From
  3. Where
  4. Group By
  5. Having
  6. Order By

/\* **Prog 7: Simple sql query for creating a table** \*/

Sql Query	Base SAS equivalent (datastep / Procstep)
<pre>proc sql; create table a as select * from sasuser.admit; quit;</pre>	<pre>data a; set sasuser.admit; run;</pre>

**Explained:** This Sql Query will create a table “a” with all the variables and all observations from S.A.

NOTE: Table WORK.A1 created, with 21 rows and 9 columns.

NOTE: PROCEDURE SQL used (Total process time):

real time	1.23 seconds
cpu time	1.14 seconds

## OUTPUT:

	ID	Name	Sex	Age	Date	Height	Weight	ActLevel	Fee
1	2458	Murray, W	M	27	1	72	168	HIGH	85.20
2	2462	Almers, C	F	34	3	66	152	HIGH	124.80
3	2501	Bonaventure, T	F	31	17	61	123	LOW	149.75
4	2523	Johnson, R	F	43	31	63	137	MOD	149.75
5	2539	LaMance, K	M	51	4	71	158	LOW	124.80
6	2544	Jones, M	M	29	6	76	193	HIGH	124.80
7	2552	Reberson, P	F	32	9	67	151	MOD	149.75
8	2555	King, E	M	35	13	70	173	MOD	149.75
9	2563	Pitts, D	M	34	22	73	154	LOW	124.80
10	2568	Eberhardt, S	F	49	27	64	172	LOW	124.80
11	2571	Nunnelly, A	F	44	19	66	140	HIGH	149.75
12	2572	Oberon, M	F	28	17	62	118	LOW	85.20
13	2574	Peterson, V	M	30	6	69	147	LOW	149.75
14	2575	Quigley, M	F	40	8	69	163	HIGH	124.80
15	2578	Cameron, L	M	47	5	72	173	NA	124.80
16	2579	Underwood, K	M	60	22	71	191	LOW	149.75
17	2584	Takahashi, Y	F	43	29	65	123	MODY	124.80
18	2586	Derber, B	M	25	23	75	188	HIGH	85.20
19	2588	Ivan, H	F	22	20	63	139	LOW	85.20
20	2589	Wilcox, E	F	41	16	67	141	HIGH	149.75
21	2595	Warren, C	M	54	7	71	183	MOD	149.75

/\* **Prog 8:** Subsetting through sql \*/

Sql Query	Base SAS equivalent (dataset / Procstep)
<pre>proc sql; create table b as select id,name from sasuser.admit; quit;</pre>	<pre>data b (keep=id name); set sasuser.admit; run;</pre>

**Explained:** This SQL query will create a table “b” but selecting only 2 variables (id, name) given after SELECT keyword from S.A.

NOTE: Table WORK.B created, with 21 rows and 2 columns.

NOTE: PROCEDURE SQL used (Total process time):

real time            0.01 seconds  
cpu time

## OUTPUT:

	ID	Name
1	2458	Murray, W
2	2462	Almers, C
3	2501	Bonaventure, T
4	2523	Johnson, R
5	2539	LaMance, K
6	2544	Jones, M
7	2552	Reberson, P
8	2555	King, E
9	2563	Pitts, D
10	2568	Eberhardt, S
11	2571	Nunnelly, A
12	2572	Oberon, M
13	2574	Peterson, V
14	2575	Quigley, M
15	2578	Cameron, L
16	2579	Underwood, K
17	2584	Takahashi, Y
18	2586	Derber, B
19	2588	Ivan, H
20	2589	Wilcox, E
21	2595	Warren, C

/\* **Prog 9:** Print through sql \*/

Sql Query	Base SAS equivalent (datastep / Procstep)
<pre>proc sql; select * from sasuser.admit; quit;</pre>	<pre>proc print data=sasuser.admit; run;</pre>

**Explained:** This SQL query will print a table of the contents of S.A

NOTE: PROCEDURE SQL used (Total process time):

real time 0.37 seconds

cpu time 0.35 seconds

**OUTPUT:**

The SAS System						18:43 Friday, May 1, 2009		
ID	Name	Sex	Age	Date	Height	Weight	Act Level	Fee
2458	Murray, W	M	27	1	72	168	HIGH	85.20
2462	Almers, C	F	34	3	66	152	HIGH	124.80
2501	Bonaventure, T	F	31	17	61	123	LOW	149.75
2523	Johnson, R	F	43	31	63	137	MOD	149.75
2539	LaMance, K	M	51	4	71	158	LOW	124.80
2544	Jones, M	M	29	6	76	193	HIGH	124.80
2552	Reberson, P	F	32	9	67	151	MOD	149.75
2555	King, E	M	35	13	70	173	MOD	149.75
2563	Pitts, D	M	34	22	73	154	LOW	124.80
2568	Eberhardt, S	F	49	27	64	172	LOW	124.80
2571	Nunnelly, A	F	44	19	66	140	HIGH	149.75
2572	Oberon, M	F	28	17	62	118	LOW	85.20
2574	Peterson, V	M	30	6	69	147	LOW	149.75
2575	Quigley, M	F	40	8	69	163	HIGH	124.80
2578	Cameron, L	M	47	5	72	173	NA	124.80
2579	Underwood, K	M	60	22	71	191	LOW	149.75
2584	Takahashi, Y	F	43	29	65	123	MODY	124.80
2586	Derber, B	M	25	23	75	188	HIGH	85.20
2588	Ivan, H	F	22	20	63	139	LOW	85.20
2589	Wilcox, E	F	41	16	67	141	HIGH	149.75
2595	Warren, C	M	54	7	71	183	MOD	149.75

/\* **Prog 10:** Selective print through sql \*/

Sql Query	Base SAS equivalent (datastep / Procstep)
<pre>proc sql; select id,name from sasuser.admit; quit;</pre>	<pre>proc print data=sasuser.admit; var id name; run;</pre>

**Explained:** This SQL query will print a table from S.A but only with variables id, name as stated after select keyword.

NOTE: PROCEDURE SQL used (Total process time):

real time 0.00 seconds

cpu time 0.00 seconds

**OUTPUT:**

ID	Name
2458	Murray, W
2462	Almers, C
2501	Bonaventure, T
2523	Johnson, R
2539	LaMance, K
2544	Jones, M
2552	Reberson, P
2555	King, E
2563	Pitts, D
2568	Eberhardt, S
2571	Nunnelly, A
2572	Oberon, M
2574	Peterson, V
2575	Quigley, M
2578	Cameron, L
2579	Underwood, K
2584	Takahashi, Y
2586	Derber, B
2588	Ivan, H
2589	Wilcox, E
2595	Warren, C

/\* **Prog 11:** Selective print through sql \*/

Sql Query	Base SAS equivalent (datastep / Procstep)
<pre>proc sql; select id,name,age from sasuser.admit; quit;</pre>	<pre>proc print data=sasuser.admit; var id name age; run;</pre>

**Explained:** Just like Prog 10, this will give variables: id, name,age as stated after select keyword.

NOTE: PROCEDURE SQL used (Total process time):

real time	0.00 seconds
cpu time	0.00 seconds

## OUTPUT:

The SAS System		18:43 Friday, May 1, 2009
ID	Name	Age
2458	Murray, W	27
2462	Almers, C	34
2501	Bonaventure, T	31
2523	Johnson, R	43
2539	LaMance, K	51
2544	Jones, M	29
2552	Reberson, P	32
2555	King, E	35
2563	Pitts, D	34
2568	Eberhardt, S	49
2571	Nunnelly, A	44
2572	Oberon, M	28
2574	Peterson, V	30
2575	Quigley, M	40
2578	Cameron, L	47
2579	Underwood, K	60
2584	Takahashi, Y	43
2586	Derber, B	25
2588	Ivan, H	22
2589	Wilcox, E	41
2595	Warren, C	54

/\* **Prog 12: Drop in SQL** \*/

Sql Query	Base SAS equivalent (datastep / Procstep)
<pre>proc sql; create table a as select * from sasuser.admit(drop=id name); quit;</pre>	<pre>data a(drop=id name); set sasuser.admit; run;</pre>

**Explained:** Drop, can be used as dataset option in Proc SQL to filter unwanted variables from any table, here id, name are dropped.

NOTE: Table WORK.A created, with 21 rows and 7 columns.

NOTE: PROCEDURE SQL used (Total process time):

real time        0.01 seconds  
cpu time        0.01 seconds

## OUTPUT:

	Sex	Age	Date	Height	Weight	ActLevel	Fee
1	M	27	1	72	168	HIGH	85.20
2	F	34	3	66	152	HIGH	124.80
3	F	31	17	61	123	LOW	149.75
4	F	43	31	63	137	MOD	149.75
5	M	51	4	71	158	LOW	124.80
6	M	29	6	76	193	HIGH	124.80
7	F	32	9	67	151	MOD	149.75
8	M	35	13	70	173	MOD	149.75
9	M	34	22	73	154	LOW	124.80
10	F	49	27	64	172	LOW	124.80
11	F	44	19	66	140	HIGH	149.75
12	F	28	17	62	118	LOW	85.20
13	M	30	6	69	147	LOW	149.75
14	F	40	8	69	163	HIGH	124.80
15	M	47	5	72	173	NA	124.80
16	M	60	22	71	191	LOW	149.75
17	F	43	29	65	123	MODY	124.80
18	M	25	23	75	188	HIGH	85.20
19	F	22	20	63	139	LOW	85.20
20	F	41	16	67	141	HIGH	149.75
21	M	54	7	71	183	MOD	149.75

/\* **Prog 13: Multiple Table creation in SQL** \*/

Sql Query	Base SAS equivalent (datastep / Procstep)
<pre>proc sql; create table a as select * from sasuser.admit; create table b as select * from sasuser.admit; create table c as select * from sasuser.admit; quit;</pre>	<pre>data a b c; set sasuser.admit; run;</pre> <p><b>Note:</b> for Multiple table creation Base SAS is more efficient as can be seen by the no of lines in the codes to avoid writing repetitive queries in SQL</p>

**Explained:** All the 3 datasets (a,b,c) will have all variables and observations from S.A.

**OUTPUT:** output will be same as Prog 7 above for all 3 datasets (a,b,c).

**/\* Prog 14: Multiple Table creation in SQL\*/**

Sql Query	Base SAS equivalent (datastep / Procstep)
<pre>proc sql; create table a as select * from sasuser.admit; create table b as select id,name from sasuser.admit; create table c as select * from sasuser.admit(drop=age); quit;</pre>	<pre>data a b(keep=id name) c(drop=age); set sasuser.admit; run;</pre>

**Explained:** Dataset a, will have 21 obs and 9 variables from S.A

Dataset b, will have id, name as the only 2 variables and 21 observations from S.A.

Dataset c, will have 8 variables (excluding “age”) and 21 observations from S.A.

**OUPTUT:**

Output dataset a, is same as output for Prog 7 above.

Output dataset b, is same as output for Prog 10 above.

Output dataset c, is same as Prog 7 above, except the “age” variable since age is dropped in dataset “c”.

**Creating new variable in SQL query is done as:**

If a logical equation to create a new variable is suppose,

$age\_m = age * 12;$

Here, L.H.S = Age\_m

R.H.S = age\*12

SQL query will use R.H.S first and then L.H.S, considering that this new variable does not exist already in the parent dataset, therefore the SQL query becomes:

Create table (table\_name) as select (specific variable name or \*, can use as per the need),(R.H.S of the logical equation) as (L.H.S / new variable\_name) from (parent dataset name).

**/\* Prog 15: Creating new variable in SQL\*/**

Sql Query	Base SAS equivalent (datastep / Procstep)
<pre>proc sql; create table a as select *,age*12 as age_m from sasuser.admit; quit;</pre>	<pre>data a; set sasuser.admit; age_m=age*12; run;</pre>

**Explained:** this query, creates a table with all the contents from S.A, adding a new variable, age\_m to it.

**OUTPUT:**

	ID	Name	Sex	Age	Date	Height	Weight	ActLevel	Fee	age_m
1	2458	Murray, W	M	27	1	72	168	HIGH	85.20	324
2	2462	Almers, C	F	34	3	66	152	HIGH	124.80	408
3	2501	Bonaventure, T	F	31	17	61	123	LOW	149.75	372
4	2523	Johnson, R	F	43	31	63	137	MOD	149.75	516
5	2539	LaMance, K	M	51	4	71	158	LOW	124.80	612
6	2544	Jones, M	M	29	6	76	193	HIGH	124.80	348
7	2552	Reberson, P	F	32	9	67	151	MOD	149.75	384
8	2555	King, E	M	35	13	70	173	MOD	149.75	420
9	2563	Pitts, D	M	34	22	73	154	LOW	124.80	408
10	2568	Eberhardt, S	F	49	27	64	172	LOW	124.80	588
11	2571	Nunnelly, A	F	44	19	66	140	HIGH	149.75	528
12	2572	Oberon, M	F	28	17	62	118	LOW	85.20	336
13	2574	Peterson, V	M	30	6	69	147	LOW	149.75	360
14	2575	Quigley, M	F	40	8	69	163	HIGH	124.80	480
15	2578	Cameron, L	M	47	5	72	173	NA	124.80	564
16	2579	Underwood, K	M	60	22	71	191	LOW	149.75	720
17	2584	Takahashi, Y	F	43	29	65	123	MODY	124.80	516
18	2586	Derber, B	M	25	23	75	188	HIGH	85.20	300
19	2588	Ivan, H	F	22	20	63	139	LOW	85.20	264
20	2589	Wilcox, E	F	41	16	67	141	HIGH	149.75	492
21	2595	Warren, C	M	54	7	71	183	MOD	149.75	648

/\* **Prog 16:** Creating new variable in SQL\*/

Sql Query	Base SAS equivalent (datastep / Procstep)
<pre>proc sql; create table a as select id,name,age*12 as age_m,height/weight as bmi from sasuser.admit where age gt 40; quit;</pre>	<pre>data a(keep=id name age_m bmi); set sasuser.admit; age_m=age*12; bmi=height/weight; where age gt 40; run;</pre>

**Explained:** This query, creates a table with variables id, name, age\_m, bmi from S.A while also checking for the condition of age > 40.

**OUTPUT:**

	ID	Name	age_m	bmi
1	2523	Johnson, R	516	0.4598540146
2	2539	LaMance, K	612	0.4493670886
3	2568	Eberhardt, S	588	0.3720930233
4	2571	Nunnelly, A	528	0.4714285714
5	2578	Cameron, L	564	0.4161849711
6	2579	Underwood, K	720	0.3717277487
7	2584	Takahashi, Y	516	0.5284552846
8	2589	Wilcox, E	492	0.475177305
9	2595	Warren, C	648	0.3879781421



/\* **Prog 17:** Sql equivalent for below 3 codes in Base Sas \*/

Sql Query	Base SAS equivalent (datastep / Procstep)
<pre>proc sql;  create table a11 as select id,name,age*12 as age_m,height/weight as bmi from sasuser.admit where age gt 40; /* this statement Modifies dataset*/  create table b as select * from a; /* this statement creates new dataset*/  select * from a; /* this statement prints the dataset*/  quit;</pre>	<pre>data a(keep=id name age_m bmi); set sasuser.admit; age_m=age*12; bmi=height/weight; where age gt 40; run; .....  data b; set a; run; .....  proc print data=a; run;</pre>

**Explained:** This query explains how sql query simplifies, modifying a dataset, creating new dataset from the existing and also printing the dataset.

#### OUTPUT:

The SAS System		18:43 Friday, May	
ID	Name	age_m	bmi
2523	Johnson, R	516	0.459854
2539	LaMance, K	612	0.449367
2568	Eberhardt, S	588	0.372093
2571	Nunnelly, A	528	0.471429
2578	Cameron, L	564	0.416185
2579	Underwood, K	720	0.371728
2584	Takahashi, Y	516	0.528455
2589	Wilcox, E	492	0.475177
2595	Warren, C	648	0.387978

/\* **Prog 18:** for the below Base SAS code while applying conditional formatting on a newly created variable, methods to write sql queries\*/

**Note:** Where does not work with a newly created variable within the datastep therefore If is used for any conditional formatting.

#### Base SAS Code:

```
data a;
set sasuser.admit;
age_m=age*12;
if age_m gt 400;
run;
```

## **SQL Queries:**

**Method 1:** Applying conditional formatting (where) with the R.H.S of the logical equation.

```
proc sql;
create table a1 as select *,age*12 as age_m from sasuser.admit where
age*12 gt 400;
quit;
```

**Method 2:** Creating the new variable in 1<sup>st</sup> query in a table and then applying conditional formatting in the 2<sup>nd</sup> query..

```
proc sql;
create table a as select *,age*12 as age_m from sasuser.admit;
create table b as select * from a where age_m gt 400;
quit;
```

**Method 3:** Using **Calculated** Keyword with (where) for formatting.

```
proc sql;
create table a as select *,age*12 as age_m from sasuser.admit
where calculated age_m gt 400;
quit;
```

**Method 4: Inline view:** where view is a table but not physically present. This method first creates a table with the new variable in it (but this table has no physical presence) and then the where condition is applied on the new table created from the view table

```
proc sql;
create table a as select * from
(
select *,age*12 as age_m from sasuser.admit
)where age_m gt 400;
quit;
```