RAJALAKSHMI ENGINEERING COLLEGE

RAJALAKSHMI NAGAR, THANDALAM – 602 105



CS23331 - DESIGN AND ANALYSIS OF ALGORITHMS

Laboratory Record Note Book

Name : Deepan Sarvesh H

Year / Branch / Section : 2nd Year / CSE

University Register No. 2116250701131

College Roll No. : 250701131

Semester : 3rd Sem

Academic Year : 2026-27

INDEX PAGE

Exp.No	Name of the Experiment	Date of Completion
1	Counter Method - While Loop	
2	Counter Method - Nested Loop (break)	
3	Counter Method - Factors of a Number	
4	Counter Method - Triple Nested Loop	
5	Counter Method - Reverse a Number	
6	Greedy - Minimum Coins/Notes Change	
7	Greedy - Assign Cookies	
8	Greedy - Burger Calories & Distance	
9	Greedy - Maximize Sum of arr[i]*i	
10	Greedy - Minimum Sum of Products	
11	D&C - Count Zeroes in Array	
12	D&C - Majority Element	
13	D&C - Floor of x in Sorted Array	
14	D&C - Pair with Sum x	
15	D&C - Quick Sort	
16	DP - Playing with Numbers	
17	DP - Playing with Chessboard	
18	DP - Longest Common Subsequence	
19	DP - Longest Non-decreasing Subseq.	
20	CP - Find Duplicate in Array	
21	CP - Intersection of Sorted Arrays	
22	CP - Pair with Difference k	

ALGORITHM PROBLEM SOLUTIONS

C Programming • Problem Statements • Sample Cases • Solutions

TOPICS INCLUDED

Finding Time Complexity · Greedy Algorithm · Divide and Conquer · Dynamic Programming · Competitive Programming

A clean, GitHub-ready reference document with clearly separated questions and formatted C source code.

Prepared from the supplied source text

Contents

Browse the document by topic. Each question includes its original problem statement and the provided answer code.

01 Greedy Algorithm

02 Divide and Conquer

03 Dynamic Programming

04 Competitive Programming

Formatting note: the problem statements and solutions are organized for readability. The source content has been retained; this document is a formatting pass, not a code-validation report.

FINDING TIME COMPLEXITY:

Question 1:

Convert the following algorithm into a program and find its time complexity using the counter method.

void function (int n)

{

int i= 1;

int s =1;

while(s <= n)

{

i++;

s += i;

}

}

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input Result

9

12

SOLUTION CODE

```
#include <stdio.h>

int main()
{
    int n;
    scanf("%d", &n);

    int i = 1;
    int s = 1;
    int counter = 2;

    while (s <= n)
    {
        counter++;

        i++;
        counter++;

        s += i;
        counter++;
    }

    counter++;

    printf("%d", counter);

    return 0;
}
```

Question 2:

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
if(n==1)
{
printf("*");
}
else
{
for(int i=1; i<=n; i++)
{
for(int j=1; j<=n; j++)
{
printf("*");
printf("*");
break;
}
}
}
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

SOLUTION CODE

```
#include <stdio.h>

int main()
{
    int n;
    scanf("%d", &n);

    int count = 0;

    count++;

    if(n == 1)
    {

    }
    else
    {
        for(int i = 1; i <= n; i++)
        {
            count++;
            count++;
            count++;
            count++;
            count++;
        }
        count++;
    }

    printf("%d", count);

    return 0;
}
```

Question 3:

Convert the following algorithm into a program and find its time complexity using counter method.

Factor(num) {

{

for (i = 1; i <= num;++i)

{

if (num % i== 0)

{

printf("%d ", i);

}

}

}

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

SOLUTION CODE

```
#include <stdio.h>

int main()
{
    int num,count=0;
    scanf("%d",&num);

    for(int i=1;i<=num;i++)
    {
        count++;
        count++;
        if(num%i==0)
        {
            count++;
        }
    }
    count++;

    printf("%d",count);
    return 0;
}
```

Question 4:

Convert the following algorithm into a program and find its time

complexity using counter method.

void function(int n)

{

int c= 0;

for(int i=n/2; i<n; i++)

for(int j=1; j<n; j = 2 * j)

for(int k=1; k<n; k = k * 2)

c++;

}

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

SOLUTION CODE

```
#include <stdio.h>

int main()
{
    int n,count=1;
    scanf("%d",&n);

    for(int i=n/2;i<n;i++)
    {
        count++;
        for(int j=1;j<n;j=j*2)
        {
            count++;
            for(int k=1;k<n;k=k*2)
            {
                count++;
                count++;
            }
            count++;
        }
        count++;
    }
    count++;

    printf("%d",count);
    return 0;
}
```

Question 5:

Convert the following algorithm into a program and find its time complexity using counter method.

void reverse(int n)

{

int rev = 0, remainder;

while (n != 0)

{

remainder = n % 10;

rev = rev * 10 + remainder;

n/= 10;

}

print(rev);

}

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

SOLUTION CODE

```
#include <stdio.h>

int main()
{
    int n,count=1;
    scanf("%d",&n);

    while(n!=0)
    {

        count++;
        count++;
        count++;
        count++;
        n/=10;
    }
    count++;
    count++;



    printf("%d",count);
    return 0;
}
```

Greedy Algorithm

Problem statements and supplied C solutions

Question 1:

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

SOLUTION CODE

```
#include <stdio.h>

int main() {
    int v, count = 0;
    int a[] = {1000, 500, 100, 50, 20, 10, 5, 2, 1};

    scanf("%d", &v);

    for(int i = 0; i < 9; i++) {
        count += v / a[i];
        v = v % a[i];
    }

    printf("%d", count);

    return 0;
}
```

Question 2:

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor g[i], which is the minimum size of a cookie that the child will be content with; and each cookie j has a size s[j]. If s[j] >= g[i], we can assign the cookie j to the child i, and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input:

3

1 2 3

2

1 1

Output:

1

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Constraints:

1 <= g.length <= 3 * 10^4

0 <= s.length <= 3 * 10^4

1 <= g[i], s[j] <= 2^31 - 1

SOLUTION CODE

```
#include <stdio.h>
#include <stdlib.h>

int compare(const void *a, const void *b) {
    return (*(int *)a - *(int *)b);
}

int main() {
    int n, m;

    scanf("%d", &n);

    int g[n];
    for(int i = 0; i < n; i++) {
        scanf("%d", &g[i]);
    }

    scanf("%d", &m);

    int s[m];
    for(int i = 0; i < m; i++) {
        scanf("%d", &s[i]);
    }

    qsort(g, n, sizeof(int), compare);
    qsort(s, m, sizeof(int), compare);

    int i = 0, j = 0, count = 0;

    while(i < n && j < m) {
        if(s[j] >= g[i]) {
            count++;
            i++;
            j++;
        } else {
            j++;
        }
    }

    printf("%d", count);

    return 0;
}
```

Question 3:

A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the person needs to run a distance to burn out his calories.

If he has eaten i burgers with c calories each, then he has to run at least 3i * c kilometers to burn out the calories. For example, if he ate 3

burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are (30 * 1) + (31 * 3) + (32 * 2) = 1 + 9 + 18 = 28.

But this is not the minimum, so need to try out other orders of consumption and choose the minimum value. Determine the minimum distance

he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm.Apply greedy approach to solve the problem.

Input Format

First Line contains the number of burgers

Second line contains calories of each burger which is n space-separate integers

Output Format

Print: Minimum number of kilometers needed to run to burn out the calories

Sample Input

3

5 10 7

Sample Output

76

For example:

Test Input Result

Test Case 1

3

1 3 2

18

SOLUTION CODE

```
#include <stdio.h>
#include <math.h>

int main(){
    int n,i,j,temp;
    int sum=0;
    scanf("%d",&n);

    int arr[n];

    for(i=0;i<n;i++){
        scanf("%d",&arr[i]);
    }

    for(i=0;i<n;i++){
        for(j=i+1;j<n;j++){
            if(arr[i]<arr[j]){
                temp=arr[i];
                arr[i]=arr[j];
                arr[j]=temp;
            }
        }
    }

    for(i=0;i<n;i++){
        sum=sum+pow(n,i)*arr[i];
    }

    printf("%d",sum);

    return 0;
}
```

Question 4:

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

SOLUTION CODE

```
#include <stdio.h>
#include <stdlib.h>

int compare(const void *a, const void *b) {
    return *(int *)a - *(int *)b;
}

int main() {
    int n;
    scanf("%d", &n);

    int a[n];

    for(int i = 0; i < n; i++)
        scanf("%d", &a[i]);

    qsort(a, n, sizeof(int), compare);

    int sum = 0;

    for(int i = 0; i < n; i++)
        sum += a[i] * i;

    printf("%d", sum);

    return 0;
}
```

Question 5:

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input Result

3

1

2

3

4

5

6

28

SOLUTION CODE

```
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int a[n], b[n];

    for(int i = 0; i < n; i++)
        scanf("%d", &a[i]);

    for(int i = 0; i < n; i++)
        scanf("%d", &b[i]);

    for(int i = 0; i < n; i++) {
        for(int j = i + 1; j < n; j++) {
            if(a[i] > a[j]) {
                int temp = a[i];
                a[i] = a[j];
                a[j] = temp;
            }

            if(b[i] < b[j]) {
                int temp = b[i];
                b[i] = b[j];
                b[j] = temp;
            }
        }
    }

    int sum = 0;

    for(int i = 0; i < n; i++)
        sum += a[i] * b[i];

    printf("%d", sum);

    return 0;
}
```

Divide and Conquer

Problem statements and supplied C solutions

Question 1:

Problem Statement

Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Divide and Conquer to Count the number of zeroes in the given array.

Input Format

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

Output Format

First Line Contains Integer – Number of zeroes present in the given array.

SOLUTION CODE

```
#include<stdio.h>
int firstzero(int arr[],int low,int high){
    if (low > high){
        return -1;
    }
    int mid=(low+high)/2;
    if(arr[mid]==0 && (mid==0 || arr[mid-1]==1)){
        return mid;
    }
    if(arr[mid]==1){
        return firstzero(arr,mid+1,high);
    }
    return firstzero(arr,low,mid-1);
}
int main(){
    int n;
    scanf("%d",&n);
    int arr[n];
    for(int i=0;i<n;i++){
        scanf("%d",&arr[i]);
    }
    int index=firstzero(arr,0,n-1);
    if (index==-1){
        printf("0");
    }
    else{
        printf("%d",n-index);
    }
    return 0;
}
```

Question 2:

Given an array nums of size n, return the majority element.

The majority element is the element that appears more than ■n / 2■ times. You may assume that the majority element always exists in the array.

Example 1:

Input: nums = [3,2,3]

Output: 3

Example 2:

Input: nums = [2,2,1,1,1,2,2]

Output: 2

Constraints:

n == nums.length

1 <= n <= 5 * 104

-231 <= nums[i] <= 231 - 1

For example:

Input Result

3

3 2 3

3

7

2 2 1 1 1 2 2

2

SOLUTION CODE

```
#include <stdio.h>
int majorityElement(int arr[], int n) {
    int candidate = arr[0];
    int count = 1;
    for (int i = 1; i < n; i++) {
        if (arr[i] == candidate)
            count++;
        else
            count--;

        if (count == 0) {
            candidate = arr[i];
            count = 1;
        }
    }
    return candidate;
}

int main() {
    int n;
    scanf("%d", &n);
    int arr[n];
    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);
    printf("%d", majorityElement(arr, n));
    return 0;
}
```

Question 3:

Problem Statement:

Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and conquer algorithm to find floor of x.

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Value for x

Output Format

First Line Contains Integer – Floor value for x

SOLUTION CODE

```
#include <stdio.h>
int findFloor(int arr[], int low, int high, int x) {
    if (low > high)
        return -1;
    int mid = (low + high) / 2;
    if (arr[mid] == x)
        return arr[mid];

    if (arr[mid] < x) {
        int result = findFloor(arr, mid + 1, high, x);

        if (result == -1)
            return arr[mid];

        return result;
    }
    return findFloor(arr, low, mid - 1, x);
}

int main() {
    int n, x;
    scanf("%d", &n);
    int arr[n];
    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);
    scanf("%d", &x);
    int result = findFloor(arr, 0, n - 1, x);
    printf("%d", result);
    return 0;
}
```

Question 4:

Problem Statement:

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwise print as “No”.

Note: Write a Divide and Conquer Solution

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Sum Value

Output Format

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value “x”)

SOLUTION CODE

```
#include <stdio.h>
int findPair(int arr[], int left, int right, int x) {
    if (left >= right)
        return 0;
    int sum = arr[left] + arr[right];
    if (sum == x) {
        printf("%d\n", arr[left]);
        printf("%d\n", arr[right]);
        return 1;
    }
    if (sum < x)
        return findPair(arr, left + 1, right, x);

    return findPair(arr, left, right - 1, x);
}

int main() {
    int n, x;
    scanf("%d", &n);
    int arr[n];
    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);
    scanf("%d", &x);
    if (!findPair(arr, 0, n - 1, x))
        printf("No");
    return 0;
}
```

Question 5:

Write a Program to Implement the Quick Sort Algorithm

Input Format:

The first line contains the no of elements in the list-n

The next n lines contain the elements.

Output:

Sorted list of elements

For example:

Input Result

5

67 34 12 98 78

12 34 67 78 98

SOLUTION CODE

```
#include <stdio.h>
void quickSort(int arr[], int low, int high) {
    if (low < high) {
        int pivot = arr[high];
        int i = low - 1;
        int temp;
        for (int j = low; j < high; j++) {
            if (arr[j] < pivot) {
                i++;

                temp = arr[i];
                arr[i] = arr[j];
                arr[j] = temp;
            }
        }

        temp = arr[i + 1];
        arr[i + 1] = arr[high];
        arr[high] = temp;

        int p = i + 1;
        quickSort(arr, low, p - 1);
        quickSort(arr, p + 1, high);
    }
}

int main() {
    int n;
    scanf("%d", &n);
    int arr[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }
    quickSort(arr, 0, n - 1);
    for (int i = 0; i < n; i++) {
        printf("%d ", arr[i]);
    }
    return 0;
}
```

Dynamic Programming

Problem statements and supplied C solutions

Question 1:

Playing with Numbers:

Ram and Sita are playing with numbers by giving puzzles to each other. Now it was Ram term, so he gave Sita a positive integer ‘n’ and two numbers 1 and 3. He asked her to find the possible ways by which the number n can be represented using 1 and 3.Write any efficient algorithm to find the possible ways.

Example 1:

Input: 6

Output:6

Explanation: There are 6 ways to 6 represent number with 1 and 3

1+1+1+1+1+1

3+3

1+1+1+3

1+1+3+1

1+3+1+1

3+1+1+1

Input Format

First Line contains the number n

Output Format

Print: The number of possible ways ‘n’ can be represented using 1 and 3

Sample Input

6

Sample Output

6

SOLUTION CODE

```
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);
    if (n < 0) {
        printf("0");
        return 0;
    }
    long long dp[n + 1];
    dp[0] = 1;
    for (int i = 1; i <= n; i++) {
        dp[i] = dp[i - 1];

        if (i >= 3)
            dp[i] += dp[i - 3];
    }
    printf("%lld", dp[n]);
    return 0;
}
```

Question 2:

Playing with Chessboard:

Ram is given with an n*n chessboard with each cell with a monetary value. Ram stands at the (0,0), that the position of the top left white rook. He is been given a task to reach the bottom right black rook position (n-1, n-1) constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one step down the board. Help ram to achieve it by providing an efficient DP algorithm.

Example:

Input

3

1 2 4

2 3 4

8 7 1

Output:

19

Explanation:

Totally there will be 6 paths among that the optimal is

Optimal path value:1+2+8+7+1=19

Input Format

First Line contains the integer n

The next n lines contain the n*n chessboard values

Output Format

Print Maximum monetary value of the path

SOLUTION CODE

```
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);
    long long a[n][n];
    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%lld", &a[i][j]);

    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            if (i == 0 && j == 0)
                continue;

            if (i == 0)
                a[i][j] += a[i][j - 1];
            else if (j == 0)
                a[i][j] += a[i - 1][j];
            else
                a[i][j] += (a[i - 1][j] > a[i][j - 1]) ? a[i - 1][j] : a[i][j - 1];
        }
    }
    printf("%lld", a[n - 1][n - 1]);
    return 0;
}
```

Question 3:

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

s1 a g

g

t

a

b

s2

g

x

t

x

a

y

b

The length is 4

Solveing it using Dynamic Programming

For example:

Input Result

aab

azb

2

SOLUTION CODE

```
#include <stdio.h>
#include <string.h>
int main() {
    char s1[1000], s2[1000];
    scanf("%s", s1);
    scanf("%s", s2);
    int m = strlen(s1);
    int n = strlen(s2);
    int dp[m + 1][n + 1];

    for (int i = 0; i <= m; i++)
        dp[i][0] = 0;

    for (int j = 0; j <= n; j++)
        dp[0][j] = 0;

    for (int i = 1; i <= m; i++) {
        for (int j = 1; j <= n; j++) {
            if (s1[i - 1] == s2[j - 1])
                dp[i][j] = dp[i - 1][j - 1] + 1;
            else
                dp[i][j] = dp[i - 1][j] > dp[i][j - 1] ? dp[i - 1][j] : dp[i][j - 1];
        }
    }
    printf("%d", dp[m][n]);
    return 0;
}
```

Question 4:

Problem statement:

Find the length of the Longest Non-decreasing Subsequence in a given Sequence.

Eg:

Input:9

Sequence:[-1,3,4,5,2,2,2,2,3]

the subsequence is [-1,2,2,2,2,3]

Output:6

SOLUTION CODE

```
#include <stdio.h>
int main() {
    int n;
    scanf("%d", &n);
    int a[n], dp[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &a[i]);
        dp[i] = 1;
    }
    int value = 1;
    for (int i = 1; i < n; i++) {
        for (int j = 0; j < i; j++) {
            if (a[j] <= a[i] && dp[j] + 1 > dp[i])
                dp[i] = dp[j] + 1;
        }
        if (dp[i] > value)
            value = dp[i];
    }
    printf("%d", value);
    return 0;
}
```

Competitive Programming

Problem statements and supplied C solutions

Question 1:

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input Result

5

1 1 2 3 4

1

SOLUTION CODE

```
#include <stdio.h>

int main(){
    int n,i,j;
    scanf("%d",&n);

    int arr[n];

    for(i=0;i<n;i++){
        scanf("%d",&arr[i]);
    }

    for(i=0;i<n;i++){
        for(j=i+1;j<n;j++){
            if(arr[i]==arr[j]){
                printf("%d",arr[i]);
                return 0;
            }
        }
    }

    return 0;
}
```

Question 2:

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input Result

5

1 1 2 3 4

1

SOLUTION CODE

```
#include <stdio.h>

int main(){
    int n,i;
    scanf("%d",&n);

    int arr[n];

    for(i=0;i<n;i++){
        scanf("%d",&arr[i]);
    }

    int slow=arr[0];
    int fast=arr[0];

    do{
        slow=arr[slow];
        fast=arr[arr[fast]];
    }while(slow!=fast);

    slow=arr[0];

    while(slow!=fast){
        slow=arr[slow];
        fast=arr[fast];
    }

    printf("%d",slow);

    return 0;
}
```

Question 3:

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array

2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input Result

1

3 10 17 57

6

2 7 10 15 57 246

10 57

SOLUTION CODE

```
#include <stdio.h>
int main() {
    int t;
    scanf("%d",&t);

    while(t--) {
        int n1,n2;
        scanf("%d",&n1);
        int a[n1];
        for(int i=0;i<n1;i++)
            scanf("%d",&a[i]);

        scanf("%d",&n2);
        int b[n2];
        for(int i=0;i<n2;i++)
            scanf("%d",&b[i]);
        int i=0,j=0;
        while(i<n1 && j<n2) {
            if(a[i]==b[j]) {
                printf("%d ",a[i]);
                i++;
                j++;
            }
            else if(a[i]<b[j]) {
                i++;
            }
            else {
                j++;
            }
        }

        printf("\n");
    }
    return 0;
}
```

Question 4:

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input Result

1

3 10 17 57

6

2 7 10 15 57 246

10 57

SOLUTION CODE

```
#include <stdio.h>
int main() {
    int T;
    scanf("%d",&T);
    while(T--) {
        int n1,n2;
        scanf("%d",&n1);
        int a[n1];
        for(int i=0;i<n1;i++)
            scanf("%d",&a[i]);

        scanf("%d",&n2);
        int b[n2];
        for(int i=0;i<n2;i++)
            scanf("%d",&b[i]);

        int i=0,j=0;
        while(i<n1 && j<n2) {
            if(a[i]==b[j]) {
                printf("%d ",a[i]);
                i++;
                j++;
            }
            else if(a[i]<b[j]) {
                i++;
            }
            else {
                j++;
            }
        }
        printf("\n");
    }
    return 0;
}
```

Question 5:

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input Result

3

1 3 5

4

1

SOLUTION CODE

```
#include <stdio.h>
int main() {
    int n,k;
    scanf("%d",&n);
    int a[n];
    for(int i=0;i<n;i++)
        scanf("%d",&a[i]);

    scanf("%d",&k);
    int i=0,j=1;
    while(i<n && j<n) {
        if(i==j) {
            j++;
        }
        else if(a[j]-a[i]==k) {
            printf("1");
            return 0;
        }
        else if(a[j]-a[i]<k) {
            j++;
        }
        else {
            i++;
        }
    }
    printf("0");
    return 0;
}
```

Question 6:

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input Result

3

1 3 5

4

1

SOLUTION CODE

```
#include <stdio.h>
int main() {
    int n,k;
    scanf("%d",&n);
    int a[n];
    for(int i=0;i<n;i++)
        scanf("%d",&a[i]);

    scanf("%d",&k);
    int i=0,j=1;
    while(i<n && j<n) {
        if(i==j) {
            j++;
        }
        else if(a[j]-a[i]==k) {
            printf("1");
            return 0;
        }
        else if(a[j]-a[i]<k) {
            j++;
        }
        else {
            i++;
        }
    }
    printf("0");
    return 0;
}
```