Skip to main content

CS23336/GE23231/GE23233-IPP/PUP/PSPP

Status	Finished
Started	Tuesday, 22 September 2026, 3:28 PM
Completed	Thursday, 1 October 2026, 8:20 PM
Duration	9 days 4 hours
Grade	**9.00** out of 10.00 (**90**%)

Question 1

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Assume that the given string has enough memory.

Don't use any extra space(IN-PLACE)

Sample Input 1

```
a2b4c6
```

Sample Output 1

```
aabbbbccccccc
```

Answer:(penalty regime: 0 %)

```
s=input()
result=""
i=0
while i<len(s):
    ch=s[i]
    i+=1
    num=""
    while i<len(s) and s[i].isdigit():
        num+=s[i]
        i+=1
    result+=ch*int(num)
print(result)
```

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Feedback

Input	Expected	Got
a2b4c6	aabbbbccccccc	aabbbbccccccc
a12b3d4	aaaaaaaaaaaabbbdddd	aaaaaaaaaaaabbbdddd

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 2

Correct
Mark 1.00 out of 1.00
Flag question

Question text

A pangram is a sentence where every letter of the English alphabet appears at least once.

Given a string sentence containing only lowercase English letters, return true if sentence is a pangram, or false otherwise.

Example 1:

Input:

thequickbrownfoxjumpsoverthelazydog

Output:

true

Explanation: sentence contains at least one of every letter of the English alphabet.

Example 2:

Input:

arvijayakumar

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Output: false

Constraints:

1 <= sentence.length <= 1000

sentence consists of lowercase English letters.

For example:

Test	Result
`print(checkPangram('thequickbrownfoxjumpsoverthelazydog'))`	`true`
`print(checkPangram('arvijayakumar'))`	`false`

Answer:(penalty regime: 0 %)

Reset answer

```
def checkPangram(s):
    if len(set(s))==26:
        return "true"
    return "false"
```

Feedback

Test	Expected	Got
`print(checkPangram('thequickbrownfoxjumpsoverthelazydog'))`	`true`	`true`

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Test	Expected	Got
`print(checkPangram('arvijayakumar'))`	`false`	`false`

Passed all tests!
Correct
Marks for this submission: 1.00/1.00.

Question 3

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Given a string S which is of the format USERNAME@DOMAIN.EXTENSION, the program must print the EXTENSION, DOMAIN, USERNAME in the reverse order.

Input Format:

The first line contains S.

Output Format:

The first line contains EXTENSION.
The second line contains DOMAIN.
The third line contains USERNAME.

Boundary Condition:

1 <= Length of S <= 100

Example Input/Output 1:

Input:

abcd@gmail.com

Output:

com
gmail
abcd

For example:

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Input	Result
arvijayakumar@rajalakshmi.edu.in	edu.in rajalakshmi arvijayakumar

Answer:(penalty regime: 0 %)

```
s = input()

parts = s.split("@")
username = parts[0]
domain_ext = parts[1]

domain, extension = domain_ext.split(".", 1)

print(extension)
print(domain)
print(username)
```

Feedback

Input	Expected	Got
abcd@gmail.com	com gmail abcd	com gmail abcd
arvijayakumar@rajalakshmi.edu.in	edu.in rajalakshmi arvijayakumar	edu.in rajalakshmi arvijayakumar

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 4

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Find if a String2 is substring of String1. If it is, return the index of the first occurrence. else return -1.

Sample Input 1

```
thistest123string
123
```

Sample Output 1

```
8
```

Answer:(penalty regime: 0 %)

```
s1 = input()
s2 = input()
print(s1.find(s2))
```

Feedback

Input	Expected	Got
thistest123string 123	8	8

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 5

Incorrect
Mark 0.00 out of 1.00
Flag question

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Question text

Given a **non-empty** string s and an abbreviation abbr, return whether the string matches with the given abbreviation.

A string such as "word" contains only the following valid abbreviations:

["word", "1ord", "w1rd", "wo1d", "wor1", "2rd", "w2d", "wo2", "1o1d", "1or1", "w1r1", "1o2", "2r1", "3d", "w3", "4"]

Notice that only the above abbreviations are valid abbreviations of the string "word". Any other string is not a valid abbreviation of "word".

Note:

Assume s contains only lowercase letters and abbr contains only lowercase letters and digits.

Example 1:

Input

internationalization

i12iz4n

Output

true

Explanation

Given **s** = "internationalization", **abbr** = "i12iz4n":

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Return true.

Example 2:

Input

apple

a2e

Output

false

Explanation

Given **s** = "apple", **abbr** = "a2e":

Return false.

Answer:(penalty regime: 0 %)

```
def validAbbreviation(s, abbr):
    i = 0
    j = 0

    while i < len(s) and j < len(abbr):
        if abbr[j].isalpha():
            if s[i] != abbr[j]:
                return False
            i += 1
            j += 1
        else:
            if abbr[j] == '0':
                return False

            num = 0
            while j < len(abbr) and abbr[j].isdigit():
                num = num * 10 + int(abbr[j])
                j += 1

```

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

```
            i += num

    return i == len(s) and j == len(abbr)


s = input()
abbr = input()

print(validAbbreviation(s, abbr))
```

Feedback

Input	Expected	Got
internationalization i12iz4n	true	True
apple a2e	false	False

Some hidden test cases failed, too.
Your code must pass all tests to earn any marks. Try again.
Show differences

Incorrect
Marks for this submission: 0.00/1.00.

Question 6

Correct
Mark 1.00 out of 1.00
Flag question

Question text

The program must accept **N** series of keystrokes as string values as the input. The character ^ represents undo action to clear the last entered keystroke. The program must print the string typed after applying the undo operations as the output. If there are no characters in the string then print **-1** as the output.

Boundary Condition(s):

1 <= N <= 100
1 <= Length of each string <= 100

Input Format:

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

The first line contains the integer N.
The next N lines contain a string on each line.

Output Format:

The first N lines contain the string after applying the undo operations.

Example Input/Output 1:

Input:

3
Hey ^ goooo^^glee^
lucke^y ^charr^ms
ora^^nge^^^^

Output:

Hey google
luckycharms
-1

Answer:(penalty regime: 0 %)

```
n = int(input())

for _ in range(n):
    s = input()
    result = []

    for ch in s:
        if ch == '^':
            if result:
                result.pop()
        else:
            result.append(ch)

    if result:
        print(''.join(result))
    else:
        print(-1)
```

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Feedback

Input	Expected	Got
3 Hey ^ goooo^^glee^ lucke^y ^charr^ms ora^^nge^^^^	Hey google luckycharms -1	Hey google luckycharms -1

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 7

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Consider the below words as key words and check the given input is key word or not.

keywords: {break, case, continue, default, defer, else, for, func, goto, if, map, range, return, struct, type, var}

Input format:

Take string as an input from stdin.

Output format:

Print the word is key word or not.

Example Input:

break

Output:

break is a keyword

Example Input:

IF

Output:

IF is not a keyword

For example:

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Input	Result
break	break is a keyword
IF	IF is not a keyword

Answer:(penalty regime: 0 %)

```
x=input()
if x in['break','case','contine','defer','else','for','func','goto','if','map','range','return
    print(x,"is a keyword")
else:
    print(x,"is not a keyword")
```

Feedback

Input	Expected	Got
break	break is a keyword	break is a keyword
IF	IF is not a keyword	IF is not a keyword

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 8

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Write a Python program to get one string and reverses a string. The input string is given as an array of characters `char[]`.

You may assume all the characters consist of printable ascii characters.

Example 1:

```
Input:
hello
Output:
olleh
```

Example 2:

```
Input:
Hannah
Output:
hannaH
```

Answer:(penalty regime: 0 %)

```
1 s=input()
2 print(s[::-1])
```

Feedback

Input	Expected	Got
hello	olleh	olleh
Hannah	hannaH	hannaH

Passed all tests!

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Correct
Marks for this submission: 1.00/1.00.

Question 9

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Given a string, determine if it is a palindrome, considering only alphanumeric characters and ignoring cases.

Note: For the purpose of this problem, we define empty string as valid palindrome.

Example 1:

```
Input:
A man, a plan, a canal: Panama

Output:
1
```

Example 2:

```
Input:
race a car

Output:
0
```

Constraints:

- `s` consists only of printable ASCII characters.

Answer:(penalty regime: 0 %)

```
s = input()

s = ''.join(ch.lower() for ch in s if ch.isalnum())

if s == s[::-1]:
    print(1)
else:
    print(0)
```

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Feedback

Input	Expected	Got
`A man, a plan, a canal: Panama`	`1`	`1`
`race a car`	`0`	`0`

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 10

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Given a string s containing just the characters '(', ')', '{', '}', '[' and ']', determine if the input string is valid.

An input string is valid if:

Open brackets must be closed by the same type of brackets.

Open brackets must be closed in the correct order.

Constraints:

1 <= s.length <= 10^4

s consists of parentheses only '()[]{}'.

For example:

Test	Result
`print(ValidParenthesis("()"))`	`true`
`print(ValidParenthesis("()[]{}"))`	`true`
`print(ValidParenthesis("("))`	`false`

Answer:(penalty regime: 0 %)

Reset answer

```
1 def ValidParenthesis(s):
```

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

```
    stack=[]
    for ch in s:
        if ch in "([{":
            stack.append(ch)
        elif not stack or "([{".index(stack.pop()) !=")]}".index(ch):
            return "false"
    return "true" if not stack else "false"
```

Feedback

Test	Expected	Got
`print(ValidParenthesis("()"))`	`true`	`true`
`print(ValidParenthesis("()[]{}"))`	`true`	`true`
`print(ValidParenthesis("("))`	`false`	`false`

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.
Finish review

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF