SDN-LAB

Topology:



Step 2: Configure the ONOS Controller eth0 and eth1 IP address



Step 3: Assign the static IP address on eth0 port of Open Switch -1



Step 4: Assign the static IP address on eth0 port of Open Switch -2



Step 5: Start the Cisco Switch first and wait till it come up.

Step 6: Start the ONOS Controller once SW come up

Step 7: Post ONOS come up, run the command ifconfig eth 0 and ifconfig eth1 and verify the IP



Step 8: Go to browser and open the URL 172.20.0.254:8181/onos/ui



Step 9: Start both the open switch

Step 10: check the IP in both the switch via ifconfig eth0 command





Step 11: Ping the controller IP 10.0.0.1 from both the SW





Step 12: Configure the SW with controller information
Setup protocol: ovs-vsctl set bridge br0 protocols=OpenFlow13
Setup controller: ovs-vsctl set-controller br0 tcp:10.0.0.1:6633





Step 13: Set the IP on both the PC and PING – It will be successful
PC1: IP 192.168.1.1/24
PC2: ip 192.168.1.2/24





Step 14: Go to ONOS GUI and enable the OpenFlow base application, provider suit and OpenFlow overlay in application TAB





Step 15: Check in Open switch , controller in connected mode and Ping from PC1 to PC2 fail ovs-vsctl show





Step 16: Ping PC1 to PC2 – Ping Fail as Open V switch is connected with ONOS Controller and all the forwarding decision is not moved to ONOS Controller.





Step 17: Enable reactive forwarding in application and check, PC1 to PC2 ping should be successful.







Step 18: Check the Devices , Topology on ONOS GUI



Step 19: Connect to Postman

http://172.20.0.254:8181/onos/v1/devices
http://172.20.0.254:8181/onos/v1/flows
http://172.20.0.254:8181/onos/v1/links
http://172.20.0.254:8181/onos/v1/topology

http://172.20.0.254:8181/onos/v1/devices



http://172.20.0.254:8181/onos/v1/flows



http://172.20.0.254:8181/onos/v1/links



http://172.20.0.254:8181/onos/v1/topology