Edge Computing Lab

Class: TY-AIEC

School of Computing, MIT Art Design Technology University

Academic Year: 2024-25

Extra Lab - 04

Title

Setting Up MQTT Broker on Raspberry Pi and Reading DHT11 / Air Quality Sensor Data

Objective

This lab aims to teach participants how to set up a Mosquitto MQTT broker on a Raspberry Pi, interface with a DHT11 temperature and humidity sensor, and publish the sensor data to an MQTT topic. Participants will also learn to subscribe to this topic using an MQTT client on an Android device.

Equipment and Materials

- Raspberry Pi (with Raspbian OS installed and internet connection)
- DHT11 Temperature and Humidity Sensor
- Android Device with MQTT Client App installed (e.g., MQTT Dash, MQTT Client)

Pre-lab Setup

Ensure the Raspberry Pi is set up with Raspbian OS, connected to the internet, and accessible via SSH or a monitor and keyboard. Install an MQTT client app on the Android device.

Lab Sections

Section 1: Setting Up the MQTT Broker

- 1. Update and Upgrade Raspberry Pi:
- Open the terminal and execute 'sudo apt-get update' and 'sudo apt-get upgrade'.
- 2. Install Mosquitto MQTT Broker:
- Run 'sudo apt-get install -y mosquitto mosquitto-clients'.
- 3. Enable Mosquitto Service:
- Use 'sudo systematl enable mosquitto.service'.
- 4. Start Mosquitto Service:
- Execute 'sudo systemctl start mosquitto.service'.
- 5. Test Installation:
- Subscribe to a test topic in one terminal using `mosquitto_sub -h localhost -t test/topic`. Publish
- a message from another terminal with 'mosquitto pub -h localhost -t test/topic -m "Hello MQTT"'.
- Confirm "Hello MQTT" message appears in the subscriber terminal.

Section 2: Interfacing with DHT11 Sensor

- 1. Connect DHT11 to Raspberry Pi:
- Connect VCC to 5V, Data to GPIO4, and GND to Ground.
- 2. Install Python Libraries:
- Install Adafruit DHT and paho-mqtt using 'sudo pip3 install Adafruit DHT paho-mqtt'.

Section 3: Publishing Sensor Data to MQTT

- 1. Write Python Script:
- Create `dht11 mqtt publisher.py` to read sensor data and publish it to `home/sensor/dht11` topic.
- 2. Run the Script:
- Execute the script with 'python3 dht11 mqtt publisher.py'.

Section 4: Subscribing with an Android MQTT Client

- 1. Configure MQTT Client App:
- Set the Raspberry Pi's IP as the MQTT server and subscribe to `home/sensor/dht11`.
- 2. Receive Data:
- Observe the temperature and humidity data published from the Raspberry Pi on the Android device. Section 5: Enhancements and Troubleshooting
- Discuss JSON formatting, security with TLS/SSL, error handling, and MQTT client configuration. Troubleshoot common issues related to sensor readings, MQTT connections, and data reception.

Lab Tasks

- Complete the setup and confirm successful data publication and subscription. Experiment with different topics and QoS levels.
- (Optional) Implement JSON formatting for sensor data.

Further Exploration

- Explore bridging Mosquitto to an external MQTT broker.
- Integrate sensor data into IoT platforms or home automation systems.

Submission Requirements

- Provide screenshots of the terminal showing successful Mosquitto installation, Python script execution, and MQTT messages on the Android client.
- Submit a short report discussing the setup process, encountered challenges, and how they were overcome.

References

- Mosquitto Documentation: https://mosquitto.org/documentation/
- Adafruit DHT Sensor Library:

https://github.com/adafruit/Adafruit_Python_DHT - Paho MQTT Client: https://www.eclipse.org/paho/clients/python/

- https://www.youtube.com/watch?v=BFyPzC6No8k&t=1s
- 1. sudo apt update
- 2. sudo apt upgrade
- 3. sudo apt-get install mosquitto mosquitto-clients
- 4. sudo systemctl enable mosquitto.service
- 5. mosquitto sub -d -t "binary/updates"
- 6. mosquitto pub -d -t "binary/updates" -m "Hello MITADT" // On 2nd terminal
- 7. sudo nano /etc/mosquitto/mosquitto.conf
 - a. add line over here as listener 1883 allow anonymous true
- 8. sudo boot
- 9. Open Terminal on Desktop PC as "MQTT Explorer"
- 1. sudo git clone https://github.com/binaryupdates/mqttclient.git
- 2. sudo pip3 install paho-mqtt

Conclusion: - Understood and Implemented Mosquitto MQTT broker on a Raspberry Pi, interface

with a DHT11 temperature and humidity sensor

FAQ's:

MIT SCHOOL OF ENGINEERING Rajbaug, Loni-Kalbhor, Pune



	Name: Deepika Hodgi
	Batch: TY AIEC C
	Roll no: 2223928
	Subject: EC lab.
	Experiment 4: MOTT with Rouphorry Pi.
	The state of the s
	Questions:
0.5	I what is MOTT and why is it commonly used
	in tot applications?
-An	y. HOTT is Message Queing Telemetry transpor
	a lightweight publish subscribe messaging
	protocol.
	i] Lightweight: works on Low-bandwidth networ
	iij Efficient: Uses minimal power, Ideal for Iot
	devices.
	iii-J Reliable: Supports Qus (Quality of Service
	levels for message delivery.
	ivil Scalable: (an handle mutiple device)
	communicating in real life.
	and the state of t
0	I Explain the role of MOTI broker, publisher
	and subscriber in on Tot system.
4100	· i] NOTT broker:
7400	Manages message distribution end
	ex. Edipse mosquitto,
Mary Pro	ii] Aublister (Douta serder):
	Sends message to an MOTT topic.
State of	Ex. Rospborry Pi publishing tensor doctor

MIT SCHOOL OF ENGINEERING Rajbaug, Loni-Kalbhor, Pune

FIRE MARKET TO PROPER COMME



-	2 10 th
	iii J Subscriber (Deute, Rockiver):
_	Subscriber to a topic and receives message in
	real tippe.
	Ex. A mobile app subscribing to senson
	data,
	A second of the
0	How can you mostall and set up the
	Mosquitto MOTT broker on Rospherry Pi?
Du	. 9.7 Update Rospherory Pi:
	sudo apt aparte le suda apt apgrade - y
	ii) Install Mosquitto e client took:
-3	sudo apt Install mosquitto mosquito-clients
	iii J Enable Mosquitto as a Background Service
	sudo systemati enable magquitto.
	sudo systemeth start mosquitto.
	in Test NOTT Broker:
	Open Terminal I:
	mosquitto_sub -h localhost -t test/top
	Open Terminal 2;
	mosquitto-bub - h local host -+ test
	topic - m "Hello, MQTII
	v3 If set up correctly terminal I will display.
	Hello, NOTTI

MIT SCHOOL OF ENGINEERING

Rajbaug, Loni-Kalbhor, Pune



	data from a DHT1) sensor to an NOTT topic.
Ans.	
₩.	e al most aligned of most
	amport paha.matt.client as matt
	import Adafruit_OHT
	emport time-
	Broker : "booker. hiverng. com"
	TOPI c = "sensor / temperature"
	DHT=SENSOR = Adafruit-OHT. DHTI
	DAT PIN = 7
100	
	client = mq++. (lien+()
-	client. comped (BROWER, 1883, 60).
	cerile True:
	humidity, temperature = Adatruit-DHT.
	MODEL CONT-SENSOR. DHT-DEND.
	if humidity is not None and temperature
	is not none:
	payload = f "Temperature : & tempera
	Humidity : Lheemidite 1962
	dient. publish CTOPIC payload)
	print (f" published = tpayload 1 ")
	time. sleep(s)-
ar:	How can you substitute, to an MOTT tropic from
The same	conother device to receive real time forcer
	updates?


MIT SCHOOL OF ENGINEERING

Rajbaug, Loni-Kalbhor, Pune



4.	If the this command on another device .
	magnitto-sub-h brokenhiveng-com
	-+ lensor/femperature.
Electron Co.	AT Putton Remote
100	
100	import pahamet dient as met
	Broker = "Inthor nivers com"
and the same of th	TOPIC = "sensor / temperature"
4 5 - May 2	
- X	det on mussage (thient, werdots, message):
AND REST	price (= " Received: 4 message, possocial.
	decoder() }")
-	chertage. Client()
	Chent ten menage = on menage.
	client connect (Broker, 1853, 60)
	chiest-subscribe CTGPIC).
	print (" Waiting for message")
	client. loop fore-ext)

MIT SCHOOL OF ENGINEERING Rajbaug, Loni-Kalbhor, Pune





	mosquitto-sub-h broken, hireng. com
	-+ sensor/temperature,
	iil Python script.
	import paho. mett. client as mett
	BROKER = 11 broken hiverng .com"
	TOPEC = "sensor / tempe rature"
A	det on-message (client, werdata, message):
	point (f" Received: 4 message, payload.
	decode() t")
7.2.	clienters gtt. Client()
	client. con-message = on-message.
Æ.	dient. connect (Broker, 1883, 60)
	client. subscribe CTGPIC).
	print ("Waiting for messages")
	client. loop forever()
2 24	
100	
-30	