HOVR DRIVER - CUCUMBER FEATURE SPECIFICATIONS
Generated: 2026-10-14 Branch: fix/co-commute

PART A - UI FEATURES (integration_test/features/)

1.	authentication.feature	18 scenarios
2.	driver_onboarding.feature	10 scenarios
3.	documents.feature	6 scenarios
4.	location_and_permissions.feature	5 scenarios
5.	ride_status_and_offers.feature	13 scenarios
6.	trip.feature	16 scenarios
7.	scheduled_trips.feature	14 scenarios
8.	co_commute.feature	24 scenarios
9.	account_and_settings.feature	15 scenarios
10.	earnings_and_wallet.feature	8 scenarios
11.	membership.feature	4 scenarios
12.	refer_and_earn.feature	11 scenarios
13.	alerts_and_notifications.feature	10 scenarios
14.	help_and_support.feature	7 scenarios

PART B - API ENDPOINT FEATURES (integration_test/features/api/)

15.	api/auth_service.feature	11 scenarios
16.	api/profile_notification_calling.feature	7 scenarios
17.	api/onboarding_documents_vehicle.feature	11 scenarios
18.	api/ride_driver_service.feature	14 scenarios
19.	api/trip_service.feature	18 scenarios
20.	api/neighbour_service.feature	19 scenarios
21.	api/wallet_referral_service.feature	9 scenarios
22.	api/alerts_inbox_service.feature	8 scenarios

Total scenarios: 258
Endpoint flow diagrams: api_flow_diagrams.pdf

```
=================== authentication.feature ===================

@authentication
Feature: Driver sign up and sign in
  As a new or returning Hovr driver
  I want to sign in with my phone number
  So that I can access the driver app

  Background:
    Given the app is freshly installed
    And the driver launches the app

  @smoke
  Scenario: Landing page is shown on first launch
    Then the landing page is shown
    And the "Get Started" button is shown

  @smoke
  Scenario: Returning driver signs in with phone number and OTP
    Given a registered driver with phone number "+14165550100"
    When the driver taps "Get Started"
    Then the text "Enter your phone number" is shown
    When the driver enters phone number "4165550100"
    And the driver taps "Continue"
    Then the text "Enter the 6-digit code sent to you at +14165550100." is shown
    When the driver enters the valid OTP
    Then the driver home screen is shown

  @otp @negative
  Scenario: Invalid OTP is rejected
    Given the driver is on the OTP verification screen
    When the driver enters an invalid OTP
    Then an OTP error message is shown
    And the driver stays on the OTP verification screen

  @otp
  Scenario: Resend code is available after the countdown
    Given the driver is on the OTP verification screen
    Then the "Resend code" button shows a countdown
    When the countdown ends
    And the driver taps "Resend code"
    Then a new OTP is sent

  @otp
  Scenario: Driver changes the phone number from the OTP screen
    Given the driver is on the OTP verification screen
    When the driver taps "I have a new phone number"
    Then the text "Enter your phone number" is shown

  @registration @smoke
  Scenario: New driver completes registration
    Given a new driver with phone number "+14165550101"
    When the driver signs in with a valid OTP
    Then the text "What's your name?" is shown
    When the driver enters first name "Alex" and last name "Morgan"
    And the driver taps "Continue"
    Then the text "What's your email?" is shown
    When the driver enters email "alex.morgan@example.com"
    And the driver taps "Continue"
    Then the text "Accept HOVR's Terms of Service" is shown
    When the driver accepts the terms
    And the driver taps "Agree and continue"
```

```
    Then the driver onboarding screen is shown

  @registration @validation
  Scenario Outline: Name validation
    Given the driver is on the "What’s your name?" screen
    When the driver enters first name "<first>" and last name "<last>"
    And the driver taps "Continue"
    Then the error "<error>" is shown

    Examples:
      | first | last   | error                 |
      |       | Morgan | Enter your first name |
      | Alex  |        | Enter your last name  |

  @registration @validation
  Scenario: Placeholder name is rejected
    Given the driver is on the "What’s your name?" screen
    When the driver enters first name "Test" and last name "Driver"
    And the driver taps "Continue"
    Then the dialog "Please update your name" is shown
    And the "Save name" button is shown

  @registration @validation
  Scenario Outline: Email validation
    Given the driver is on the "What’s your email?" screen
    When the driver enters email "<email>"
    And the driver taps "Continue"
    Then the error "<error>" is shown

    Examples:
      | email          | error
                                 |
      |                | Email field is empty
                                |
      | not-an-email   | Sorry, we couldn’t use this email. Please ensure you’ve
 entered it using the format name@email.com. |

  @registration @email
  Scenario: Driver verifies the email address
    Given the driver has entered email "alex.morgan@example.com"
    When the driver opens the verify email screen
    And the driver enters the valid email code
    Then the email is marked as verified

  @registration @email
  Scenario: Driver changes the email address
    Given the driver is on the verify email screen
    When the driver chooses to change the email
    And the driver enters email "alex.new@example.com"
    And the driver taps "Continue"
    Then a verification code is sent to "alex.new@example.com"

  @registration @validation
  Scenario: Terms must be accepted
    Given the driver is on the terms screen
    When the driver taps "Agree and continue" without accepting the terms
    Then the error "You must agree to the Terms of Service to continue." is show
n

  @registration
  Scenario Outline: Terms links open the legal pages
    Given the driver is on the terms screen
```

```
  When the driver taps "<link>"
  Then the "<link>" page is opened

  Examples:
    | link             |
    | Terms of Service |
    | Privacy Policy   |

@payment-method
Scenario: Driver skips adding a payment method
  Given the driver is on the payment method screen
  Then the text "Select your preferred payment method" is shown
  When the driver taps "Do this later"
  Then the next onboarding screen is shown

@payment-method
Scenario: Driver adds a credit card
  Given the driver is on the payment method screen
  When the driver taps "Credit or debit card"
  And the driver enters valid card details
  And the driver taps "Add"
  Then the card is saved

@region @negative
Scenario: Driver outside a supported region
  Given the driver's location is outside the service area
  When the driver signs in
  Then the text "We’re not in your area... yet." is shown
  And the "Get Updates" button is shown

@logout
Scenario: Driver logs out
  Given the driver is logged in
  When the driver opens the profile screen
  And the driver taps "Logout"
  Then the landing page is shown
  And the trip stream is closed

@delete-account
Scenario: Driver cancels account deletion
  Given the driver is logged in
  When the driver opens the profile screen
  And the driver taps "Delete Account"
  Then the dialog "Confirm Account Deletion" is shown
  When the driver taps "Cancel"
  Then the driver stays on the profile screen
```

```
=================== driver_onboarding.feature ===================

@onboarding
Feature: Driver onboarding
  As a newly registered driver
  I want to complete my onboarding steps
  So that I can go online and accept rides

  Background:
    Given the driver is logged in
    And the driver has not completed onboarding

  @smoke
  Scenario: Onboarding checklist is shown
    When the driver opens the app
    Then the text "Welcome, Alex" is shown
    And the text "Here's what you need to do to set up your account." is shown
    And the onboarding steps are listed:
      | step                |
      | Driver              |
      | Vehicle             |
      | City Requirements   |
      | Membership          |
      | Banking             |
      | Training            |

  Scenario: Rideshare and Co-Commute tabs are shown
    When the driver opens the onboarding screen
    Then the "Rideshare" tab is shown
    And the "Co-Commute" tab is shown

  Scenario Outline: Driver opens each onboarding step
    When the driver taps the "<step>" step
    Then the "<title>" screen is shown
    And the text "Please submit the following documents to continue." is shown

    Examples:
      | step              | title              |
      | Driver            | Driver Documents   |
      | Vehicle           | Vehicle Documents  |
      | City Requirements | City Requirements  |
      | Training          | Training Documents |
      | Banking           | Banking Documents  |

  @upload
  Scenario: Driver uploads a document from the camera
    Given the driver is on the "Driver Documents" screen
    When the driver taps "Upload" on "Driver's licence"
    And the driver chooses "Camera"
    And the driver captures a photo
    Then the text "Uploading document…" is shown
    And the document status becomes "Submitted"

  @upload
  Scenario Outline: Document status badges
    Given a driver document with status "<status>"
    When the driver opens the "Driver Documents" screen
    Then the document shows the "<badge>" badge

    Examples:
      | status    | badge        |
      | missing   | Missing      |
```

```
      | submitted | Submitted    |
      | review    | Under review |
      | approved  | Approved     |
      | rejected  | Rejected     |

  @upload @negative
  Scenario: Rejected document shows the reason
    Given a driver document was rejected with reason "Image is blurry"
    When the driver opens the rejected document
    Then the "Reason" section shows "Image is blurry"
    And the "Upload" button is shown

  @status
  Scenario: Driver refreshes the onboarding status
    Given the driver is on the onboarding screen
    When the driver taps "Refresh status"
    Then the onboarding checklist is reloaded

  @locked
  Scenario: Locked features before onboarding is complete
    Given the driver is on the onboarding screen
    Then the text "Complete rideshare onboarding to unlock this." is shown on lo
cked features
    And the "Referral Program" card shows "Verify your ID to start earning rewar
ds"
    And the "Member Benefits" card shows "Verify your ID and subscribe to access
 your benefits"

  @locked @negative
  Scenario: Driver cannot go online until documents are approved
    Given the driver documents are not approved
    When the driver opens the home screen
    Then the text "Need to get driver documents approved." is shown

  @complete @smoke
  Scenario: Driver with approved onboarding lands on home
    Given all onboarding steps are approved
    When the driver opens the app
    Then the driver home screen is shown
    And the "Go Online" button is shown
```

```
==================== documents.feature ====================

@documents
Feature: Driver documents
  As an approved driver
  I want to view and update my documents
  So that my account stays compliant

  Background:
    Given the driver is logged in
    And the driver opens "Account"
    And the driver taps "Documents"

  @smoke
  Scenario: All documents approved
    Given all driver documents are approved
    Then the text "Documents" is shown
    And the text "All of your documents have been successfully uploaded and appr
oved. Drive safe!" is shown

  Scenario: No documents found
    Given the driver has no documents
    Then the text "No document found!" is shown

  @negative
  Scenario: Documents fail to load
    Given the documents request returns an error
    Then the text "Something went wrong!" is shown

  Scenario: Driver views the documents for a scope
    Given the driver has vehicle documents
    When the driver opens the "Vehicle" document scope
    Then the vehicle documents are listed with their status

  Scenario: Driver re-uploads an expiring document
    Given a document with status "Attention Required"
    When the driver opens the document
    And the driver uploads a new photo
    Then the document status becomes "Submitted"

  @negative
  Scenario: Download link cannot be opened
    Given the device has no app that can open the download link
    When the driver opens a document download link
    Then the text "No app found to open download link." is shown
```

```
=================== location_and_permissions.feature ===================

@location @permissions
Feature: Location and device permissions
  As a driver
  I want the app to ask for the permissions it needs
  So that ride matching and navigation work

  Background:
    Given the driver is logged in

  @smoke
  Scenario: Location services are off
    Given location services are turned off on the device
    When the driver opens the home screen
    Then the text "Turn On Location Services to Allow \"Hovr Driver\" to Determi
ne Your Location" is shown
    When the driver taps "Settings"
    Then the device location settings are opened

  Scenario: Location permission is granted
    Given location permission has not been asked
    When the driver opens the home screen
    And the driver allows location access
    Then the driver's current location is shown on the map

  @negative
  Scenario: Location permission is denied
    Given location permission is denied
    When the driver taps "Go Online"
    Then the driver is asked to enable location
    And the driver stays offline

  Scenario: Notification permission prompt
    Given notification permission has not been asked
    When the driver opens the app
    Then the notification permission prompt is shown

  Scenario: Camera permission for document upload
    Given camera permission has not been asked
    When the driver uploads a document with the camera
    Then the camera permission prompt is shown
```

```
=================== ride_status_and_offers.feature ===================

@ride @home
Feature: Going online and receiving ride offers
  As an approved driver
  I want to go online and receive ride requests
  So that I can earn money

  Background:
    Given the driver is logged in
    And the driver is approved for rideshare
    And location permission is granted
    And the driver is on the home screen

  @smoke
  Scenario: Driver is offline by default
    Then the text "You're offline" is shown
    And the text "Go online to get ride requests" is shown
    And the "Go Online" button is shown

  @smoke
  Scenario: Driver goes online
    When the driver taps "Go Online"
    Then the text "You're online" is shown
    And the text "Finding rides" is shown
    And the driver location stream is started

  @smoke
  Scenario: Driver goes offline
    Given the driver is online
    When the driver taps "Go Offline"
    Then the text "You're offline" is shown
    And the driver location stream is stopped

  @negative
  Scenario: Driver with pending actions cannot go online
    Given the driver has pending actions
    When the driver taps "Go Online"
    Then the text "Can't go online pending actions or not approved!" is shown
    And the driver stays offline

  @negative
  Scenario: Driver blocked by duty policy
    Given the driver is blocked by the duty policy
    When the driver taps "Go Online"
    Then the text "Driver blocked by duty policy!" is shown

  @negative
  Scenario: Activation fails
    Given the activate driver request returns an error
    When the driver taps "Go Online"
    Then the text "Something went wrong while activating driver!" is shown

  @offer @smoke
  Scenario: Driver accepts a ride offer
    Given the driver is online
    When a ride offer is received
    Then the ride offer bottom sheet is shown
    And the pickup and dropoff are shown
    And the estimated fare is shown
    When the driver taps "Accept"
    Then the text "Drive to pickup spot" is shown
```

```
@offer
Scenario: Driver declines a ride offer
  Given the driver is online
  When a ride offer is received
  And the driver declines the offer
  Then the ride offer bottom sheet is closed
  And the text "Finding rides" is shown

@offer
Scenario: Ride offer expires
  Given the driver is online
  When a ride offer is received
  And the driver does not respond before the offer times out
  Then the text "Offer expired" is shown
  And the driver keeps receiving offers

@offer @negative
Scenario: Accepted trip is no longer available
  Given the driver is online
  And a ride offer is received
  And the rider cancels before the driver accepts
  When the driver taps "Accept"
  Then the text "Trip is no longer available!" is shown

@resume
Scenario: Active trip is restored after app restart
  Given the driver has an active trip
  When the driver kills and relaunches the app
  Then the active trip screen is restored

@logout
Scenario: Driver logs out while online
  Given the driver is online
  When the driver logs out
  Then the driver is set offline
  And all trip and location streams are closed
  And the landing page is shown

@background
Scenario: Driver location updates continue in the background
  Given the driver is online
  When the app is sent to the background for 2 minutes
  Then location updates are still sent
  When the app is brought to the foreground
  Then the text "You're online" is shown
```

```
==================== trip.feature ====================

@trip
Feature: Completing a rideshare trip
  As a driver with an accepted ride
  I want to pick up, drive and drop off my rider
  So that the trip is completed and I get paid

  Background:
    Given the driver is logged in
    And the driver is online
    And the driver has accepted a ride offer

  @smoke
  Scenario: Full trip from pickup to drop off
    Then the text "Drive to pickup spot" is shown
    When the driver reaches the pickup location
    And the driver swipes to "Arrive"
    Then the driver waiting bottom sheet is shown
    When the rider gets in
    And the driver starts the trip
    Then the text "Heading to Destination" is shown
    When the driver reaches the destination
    And the driver swipes to "Drop Off"
    Then the rating screen is shown

  @navigation
  Scenario Outline: Driver chooses a navigation app
    Given the driver is heading to the pickup
    When the driver opens navigation
    Then the "Navigate with" sheet is shown
    When the driver chooses "<app>"
    Then navigation opens with "<app>"

    Examples:
      | app                |
      | Google Maps        |
      | In App Navigation  |

  @navigation @ios
  Scenario: Apple Maps is offered on iOS
    Given the device is an iPhone
    And the driver is heading to the pickup
    When the driver opens navigation
    Then "Apple Maps" is listed in the "Navigate with" sheet

  @waiting
  Scenario: Rider no-show after waiting
    Given the driver has arrived at pickup
    When the wait time runs out
    And the driver reports a no-show
    Then the trip is cancelled
    And the driver returns to the home screen

  @cancel
  Scenario Outline: Driver cancels the trip with a reason
    Given the driver is heading to the pickup
    When the driver taps "Cancel ride"
    Then the dialog "Cancel ride?" is shown
    When the driver selects reason "<reason>"
    And the driver confirms the cancellation
    Then the trip status is "Canceled by you"
```

```
  Examples:
    | reason                 |
    | Rider kept me waiting  |
    | Overly intoxicated     |
    | Other                  |

Scenario: Rider cancels the trip
  Given the driver is heading to the pickup
  When the rider cancels the trip
  Then the trip status is "Canceled by rider"
  And the driver returns to the home screen

@stops
Scenario: Trip with an extra stop
  Given the rider added a stop to the trip
  When the driver starts the trip
  Then the text "Heading to Stop" is shown
  When the driver completes the stop
  Then the text "Heading to Destination" is shown

Scenario: Rider changes the destination during the trip
  Given the trip is in progress
  When the rider changes the destination
  Then the new destination is shown
  And the route is updated

@chat
Scenario: Driver chats with the rider
  Given the driver is heading to the pickup
  When the driver opens the chat
  And the driver sends the message "I'm here"
  Then the message "I'm here" appears in the chat

@chat
Scenario: Driver receives a rider message notification
  Given the driver is heading to the pickup
  When the rider sends a message
  Then the notification "Message from your rider" is shown

@rating @smoke
Scenario: Driver rates the rider with a compliment
  Given the driver has dropped off the rider
  When the driver gives 5 stars
  And the driver selects the compliment "Polite rider"
  And the driver submits the rating
  Then the driver returns to the home screen
  And the text "You're online" is shown

@rating
Scenario: Driver rates the rider with a complaint
  Given the driver has dropped off the rider
  When the driver gives 2 stars
  And the driver selects the complaint "Disrespectful"
  And the driver submits the rating
  Then the driver returns to the home screen

@rating
Scenario: Driver skips rating
  Given the driver has dropped off the rider
  When the driver taps "Skip"
  Then the driver returns to the home screen
```

```
  @rating @negative
  Scenario: Rating submission fails
    Given the submit rating request returns an error
    And the driver has dropped off the rider
    When the driver submits the rating
    Then the text "Something went wrong while submiting rating!" is shown

  @negative
  Scenario Outline: Trip actions fail
    Given the "<request>" request returns an error
    When the driver performs "<action>"
    Then the text "<error>" is shown

    Examples:
      | request      | action          | error
        |
      | startTrip    | start the trip  | Something went wrong while starting tri
p!      |
      | completeTrip | drop off        | Something went wrong while completing t
he trip! |

  @trip-status
  Scenario Outline: Trip status labels
    Given the trip status is "<status>"
    When the driver opens the trip information screen
    Then the text "<label>" is shown

    Examples:
      | status      | label              |
      | accepted    | Accepted           |
      | arriving    | En route to pickup |
      | arrived     | Arrived at pickup  |
      | in_progress | Trip in progress   |
      | completed   | Completed          |
```

```
=================== scheduled_trips.feature ===================

@scheduled-trips
Feature: Scheduled trips
  As a driver
  I want to accept rides booked in advance
  So that I can plan my schedule

  Background:
    Given the driver is logged in
    And the driver is approved for rideshare

  @smoke
  Scenario: Driver views scheduled rides
    When the driver opens "Scheduled trips"
    Then the text "Scheduled Rides" is shown
    And the text "Browse available and accepted scheduled rides for your schedul
e." is shown
    And the rides for today are listed

  Scenario: No scheduled rides for the selected day
    Given there are no scheduled rides for tomorrow
    When the driver opens "Scheduled trips"
    And the driver selects tomorrow
    Then the text "No scheduled rides for this day." is shown
    When the driver taps "Today"
    Then today is selected

  Scenario Outline: Driver filters scheduled trips
    Given the driver has scheduled trips with different statuses
    When the driver opens "Scheduled trips"
    And the driver opens "Filter trips"
    And the driver selects "<filter>"
    Then only trips with status "<filter>" are listed

    Examples:
      | filter    |
      | Pending   |
      | Accepted  |
      | Cancelled |

  Scenario: Filter with no results
    Given the driver has no cancelled trips today
    When the driver filters scheduled trips by "Cancelled"
    Then the text "No trips match this filter for this day." is shown

  @offer @smoke
  Scenario: Driver accepts a scheduled trip offer
    Given a new scheduled trip offer is available
    When the driver opens the scheduled trip offer
    Then the text "New scheduled trip" is shown
    And the "YOU'LL EARN (EST.)" amount is shown
    And the "Respond in" countdown is shown
    When the driver taps "Accept Trip"
    Then the snackbar "Scheduled trip accepted" is shown
    And the trip is listed under "Accepted rides"

  @offer
  Scenario: Driver declines a scheduled trip offer
    Given a new scheduled trip offer is available
    When the driver opens the scheduled trip offer
    And the driver taps "Decline"
```

```
    Then the offer is removed from the list

  @offer @negative
  Scenario: Accepting a scheduled trip fails
    Given the accept offer request returns an error
    When the driver accepts a scheduled trip offer
    Then the text "Could not accept scheduled trip" is shown

  @accepted
  Scenario: Accepted trip details before pickup window
    Given the driver has an accepted scheduled trip 3 hours from now
    When the driver opens the accepted trip
    Then the text "Available closer to pickup" is shown
    And the text "What unlocks then" is shown
    And the unlock features are listed:
      | feature                          |
      | Directions to the pickup location |
      | Exact pickup address             |
      | Start trip controls              |

  @accepted
  Scenario: Accepted trip fare breakdown
    Given the driver has an accepted scheduled trip
    When the driver opens the accepted trip
    Then "Trip fare", "Platform fee*" and "You'll earn (est.)" are shown
    And the text "*HOVR retains this amount alone." is shown

  @accepted @smoke
  Scenario: Driver starts an accepted scheduled trip
    Given the driver has an accepted scheduled trip inside the pickup window
    When the driver opens the accepted trip
    And the driver taps "Start trip"
    Then the text "Drive to pickup spot" is shown

  @accepted
  Scenario: Driver gets directions to the pickup
    Given the driver has an accepted scheduled trip inside the pickup window
    When the driver opens the accepted trip
    And the driver taps "Get Directions to Pickup"
    Then navigation to the pickup is opened

  @accepted @cancel
  Scenario: Driver cancels an accepted scheduled trip
    Given the driver has an accepted scheduled trip
    When the driver opens the accepted trip
    And the driver taps "Cancel this trip"
    Then the text "Are you sure you want to cancel this scheduled trip?" is show
n
    When the driver confirms
    Then the snackbar "Scheduled trip cancelled" is shown

  @accepted @negative
  Scenario: Starting a scheduled trip fails
    Given the start trip request returns an error
    When the driver starts an accepted scheduled trip
    Then the text "Could not start trip. Try again." is shown

  @accepted
  Scenario: No accepted rides for the day
    Given the driver has no accepted scheduled rides today
    When the driver opens "Accepted rides"
    Then the text "No accepted scheduled rides for this day." is shown
```

```
=================== co_commute.feature ===================

@co-commute @neighbours
Feature: Co-Commute (Neighbours) for drivers
  As a Hovr driver
  I want to share my daily commute with neighbours going the same way
  So that I can earn from seats on trips I am already making

  Background:
    Given the driver is logged in
    And the driver is on the home screen

  # ------------------------------------------------------------ Eligibility

  @eligibility @smoke
  Scenario: Eligible driver opens Co-Commute
    Given the driver is eligible for Co-Commute
    When the driver opens "Co-Commute" from the drawer
    Then the "Nearby Rides" tab is shown
    And the "My trips" tab is shown
    And the "My booking" tab is shown
    And the "History" tab is shown

  @eligibility
  Scenario: Ineligible driver sees blocking requirements
    Given the driver is not eligible for Co-Commute
    And the driver has pending Co-Commute requirements
    When the driver opens "Co-Commute" from the drawer
    Then the text "Not eligible for Co-Commute" is shown
    And the text "Complete these requirements before posting a commute." is show
n
    And the pending requirements are listed
    And the "Start onboarding" button is shown

  @eligibility @negative
  Scenario: Eligibility check fails
    Given the eligibility check returns an error
    When the driver opens "Co-Commute" from the drawer
    Then the text "Could not check Co-Commute eligibility." is shown
    When the driver taps "Try again"
    Then the eligibility check is retried

  # ------------------------------------------------------------ Post commute

  @post-commute @smoke
  Scenario: Driver posts a commute with "Leave at"
    Given the driver is eligible for Co-Commute
    And the driver is on the "My trips" tab
    When the driver taps "Post your own commute"
    Then the text "Where are you heading?" is shown
    When the driver searches destination "Work"
    And the driver selects the first search result
    And the driver confirms the pickup location
    Then the text "Choose a time" is shown
    When the driver selects "Leave at"
    And the driver picks a time 45 minutes from now
    And the driver taps "Confirm and continue"
    Then the snackbar "Commute posted." is shown
    And the posted commute appears under "My trips" with status "Open"

  @post-commute
  Scenario: Driver posts a commute with "Arrive by"
```

```
  Given the driver has selected origin and destination
  And the commute duration is 25 minutes
  When the driver selects "Arrive by"
  And the driver picks a time 90 minutes from now
  Then the summary shows "Arrive by" the selected time
  And the departure time is 25 minutes before the selected time
  When the driver taps "Confirm and continue"
  Then the snackbar "Commute posted." is shown

@post-commute
Scenario: Driver sets destination on the map
  Given the driver is on the "Where are you heading?" screen
  When the driver taps "Set location on map"
  And the driver moves the map pin to a new location
  And the driver taps "Use this location"
  Then the selected location is used as the destination

@post-commute
Scenario: Recent places are shown on the destination screen
  Given the driver has previously searched destinations
  When the driver opens the "Where are you heading?" screen
  Then the "SAVED & RECENT" section is shown
  And at most 8 recent places are listed

@post-commute @validation
Scenario Outline: Pickup time validation
  Given the driver has selected origin and destination
  When the driver picks a time <minutes> minutes from now
  And the driver taps "Confirm and continue"
  Then <outcome>

  Examples:
    | minutes | outcome                                      |
    | 10      | the dialog "Too soon" is shown               |
    | 29      | the dialog "Too soon" is shown               |
    | 30      | the snackbar "Commute posted." is shown      |
    | 120     | the snackbar "Commute posted." is shown      |

@post-commute @validation
Scenario: Time picker does not allow more than 14 days ahead
  Given the driver is on the "Choose a time" screen
  Then the latest selectable date is 14 days from today
  And the minutes are selectable in 5-minute steps

@post-commute @negative
Scenario: Posting a commute fails
  Given the post commute request returns an error
  And the driver has selected origin, destination and a valid time
  When the driver taps "Confirm and continue"
  Then the text "Could not post your commute. Please try again." is shown

# ------------------------------------------------------- Manage my trips

@my-trips
Scenario: No posted commutes
  Given the driver has no posted commutes
  When the driver opens the "My trips" tab
  Then the text "No posted commutes yet." is shown

@my-trips @bookings
Scenario: Driver approves a pending booking
  Given the driver has a posted commute with a booking "Pending approval"
```

```
  When the driver opens the posted commute
  And the driver taps "Approve" on the booking
  Then the snackbar "Booking updated." is shown
  And the booking status is "Confirmed"

@my-trips @bookings
Scenario: Driver declines a pending booking
  Given the driver has a posted commute with a booking "Pending approval"
  When the driver opens the posted commute
  And the driver taps "Decline" on the booking
  Then the snackbar "Booking updated." is shown
  And the booking status is "Declined"

@my-trips @bookings
Scenario: Commute without bookings
  Given the driver has a posted commute with no bookings
  When the driver opens the posted commute
  Then the text "No bookings yet." is shown
  And the text "Fare shows once a rider books" is shown

@my-trips @earnings
Scenario: Driver views booking earnings and price breakdown
  Given the driver has a posted commute with a confirmed booking
  When the driver opens the posted commute
  Then the "Earnings" card is shown
  And "You earn" amount is shown
  When the driver opens the "Price breakdown"
  Then "Rider pays" amount is shown
  And "Platform fee" amount is shown
  And "You earn" equals "Rider pays" minus "Platform fee"

@my-trips @journey
Scenario: Driver starts the journey
  Given the driver has a posted commute with a confirmed booking
  And the departure time has arrived
  When the driver opens the posted commute
  And the driver taps "Start journey"
  Then the text "Live trip started." is shown
  And the commute status is "Departed"

@my-trips @cancel
Scenario: Driver cancels a posted commute
  Given the driver has a posted commute with status "Open"
  When the driver opens the posted commute
  And the driver taps "Cancel trip"
  Then the snackbar "Trip cancelled." is shown
  And the commute status is "Cancelled"

@my-trips @details
Scenario Outline: Driver copies an identifier from trip detail
  Given the driver has a posted commute with a confirmed booking
  When the driver opens the posted commute
  And the driver taps the "<label>" value
  Then the snackbar "<message>" is shown

  Examples:
    | label             | message                    |
    | Trip ID           | Trip ID copied             |
    | Booking ID        | Booking ID copied          |
    | Neighbour trip ID | Neighbour trip ID copied   |

# ---------------------------------------------- Nearby rider requests
```

```
  @nearby
  Scenario: Driver sees nearby rider requests
    Given there are rider requests near the driver within the next 2 hours
    When the driver opens the "Nearby Rides" tab
    Then the "Nearby rider requests" list is shown

  @nearby
  Scenario: No nearby rider requests
    Given there are no rider requests near the driver
    When the driver opens the "Nearby Rides" tab
    Then the text "No nearby requests." is shown

  @nearby @request-detail
  Scenario: Driver accepts a nearby rider request
    Given there is a rider request near the driver
    When the driver opens the rider request
    Then the text "Ride request" is shown
    And the "Route", "Time window", "Distance" and "Price breakdown" sections ar
e shown
    When the driver taps "Accept"
    Then the snackbar "Request accepted." is shown
    And the request appears under "My booking"

  @nearby @request-detail
  Scenario: Driver contacts the rider from request detail
    Given the driver has an accepted rider request
    When the driver opens the rider request
    Then the "Call rider" action is shown
    And the "Message rider" action is shown

  # ---------------------------------------------------------------- History

  @history
  Scenario Outline: Finished commutes appear in history
    Given the driver has a commute with status "<status>"
    When the driver opens the "History" tab
    Then the commute is listed with status "<status>"

    Examples:
      | status    |
      | Completed |
      | Cancelled |
      | Expired   |

  @negative
  Scenario: Commute detail fails to load
    Given the trip detail request returns an error
    When the driver opens a posted commute
    Then the text "Could not load this commute." is shown
```

```
=================== account_and_settings.feature ===================

@account
Feature: Account, profile and app settings
  As a driver
  I want to manage my profile, vehicle, banking and app settings
  So that my account information is correct

  Background:
    Given the driver is logged in
    And the driver opens "Account" from the drawer

  @smoke
  Scenario: Account menu items are shown
    Then the following items are shown:
      | item             |
      | My Vehicle       |
      | Alerts           |
      | Banking          |
      | Documents        |
      | App settings     |
      | Update the app   |

  @profile
  Scenario: Driver views the profile
    When the driver opens the profile
    Then the text "Profile" is shown
    And "Rides", "Rating" and "Driver ID" are shown
    And "Legal Name", "Phone" and "Email" are shown

  @profile
  Scenario: New driver has no rating yet
    Given the driver has completed no rides
    When the driver opens the profile
    Then the text "No rating yet" is shown

  @profile
  Scenario: Driver updates the preferred name
    When the driver opens the profile
    And the driver edits "Preferred name" to "AJ"
    And the driver taps "Update"
    Then the text "Updated successfully!" is shown
    And the preferred name is "AJ"

  @profile @negative
  Scenario: Profile update fails
    Given the update profile request returns an error
    When the driver updates the profile
    Then the text "Something went wrong!" is shown

  @profile
  Scenario: Driver changes the profile photo
    When the driver opens the profile
    And the driver picks a new profile photo
    Then the text "Uploading Image!" is shown
    And the new photo is shown

  @vehicle
  Scenario: Driver views vehicle details
    Given the driver has a registered vehicle
    When the driver taps "My Vehicle"
    Then "Make", "Model", "Year", "Type of Body", "Plate" and "Colour" are shown
```

```
@vehicle
Scenario: Driver without a vehicle
  Given the driver has no vehicle
  When the driver taps "My Vehicle"
  Then the text "No vehicle available!" is shown

@banking
Scenario: Driver with an active bank account
  Given the driver's banking account is active
  When the driver taps "Banking"
  Then the text "Banking Details" is shown
  And the text "Account is Active" is shown
  And the "Capabilities" section is shown
  And the "Manage Bank Account" button is shown

@language
Scenario Outline: Driver changes the app language
  When the driver taps "App settings"
  And the driver taps "Language"
  And the driver selects "<language>"
  Then the text "Language updated to <language>" is shown
  And the app is displayed in "<language>"

  Examples:
    | language        |
    | English (US)    |
    | French (Canada) |
    | Spanish         |
    | Turkish         |
    | Hindi           |
    | Punjabi         |
    | Arabic          |

@language @rtl
Scenario: Arabic switches the layout to right-to-left
  When the driver changes the language to "Arabic"
  Then the app layout is right-to-left

@ota
Scenario: App is up to date
  Given there is no new over-the-air update
  When the driver taps "Update the app"
  And the driver taps "Check for update"
  Then the text "You're on the latest update." is shown
  And "App version", "Build" and "Patch" are shown

@ota
Scenario: Over-the-air update is downloaded
  Given a new over-the-air update is available
  When the driver taps "Update the app"
  And the driver taps "Check for update"
  Then the text "Update downloaded. Restart the app to apply it." is shown
  When the driver taps "Restart now"
  Then the dialog "Update ready" is shown

@ota
Scenario: OTA update prompt while not on a trip
  Given a new over-the-air update was downloaded
  And the driver is not on a trip
  When the driver opens the app
  Then the text "A fix is ready. Restart the app to apply it when you are not
```

```
on a trip." is shown
    When the driver taps "Later"
    Then the prompt is closed

  @ota
  Scenario: OTA is not available on this build
    Given the build does not support over-the-air updates
    When the driver taps "Update the app"
    Then the text "Not available on this build" is shown
```

```
==================== earnings_and_wallet.feature ====================

@earnings @wallet
Feature: Earnings and wallet payouts
  As a driver
  I want to see my earnings and withdraw my balance
  So that I get paid for my trips

  Background:
    Given the driver is logged in

  @earnings @smoke
  Scenario: Driver views earnings
    Given the driver completed trips this week
    When the driver opens "Earnings" from the drawer
    Then "Sessions", "Trips" and "Distance Travelled" are shown

  @earnings
  Scenario: Driver with no sessions
    Given the driver has no driving sessions
    When the driver opens "Earnings" from the drawer
    Then the text "No session Found" is shown

  @earnings
  Scenario: Driver opens a trip from earnings
    Given the driver completed trips this week
    When the driver opens "Earnings" from the drawer
    And the driver opens a completed trip
    Then the text "Trip Details" is shown
    And the pickup and dropoff are shown
    And "You earn" is shown

  @wallet @smoke
  Scenario: Driver withdraws the available balance
    Given the driver has an available balance of "$120.00"
    And the driver has an active bank account
    When the driver opens the wallet
    And the driver taps "Withdraw to bank"
    Then the "Minimum payout" and "Maximum payout" are shown
    When the driver taps "Confirm withdrawal"
    Then the payout appears in "Payout history" with status "Requested"

  @wallet
  Scenario: Driver views payout details
    Given the driver has a payout with status "Paid out"
    When the driver opens the wallet
    And the driver opens the payout
    Then the text "Payout details" is shown
    And "Payout ID", "Amount" and "Status" are shown

  @wallet
  Scenario: No payouts yet
    Given the driver has no payouts
    When the driver opens the wallet
    Then the text "No payouts yet" is shown

  @wallet
  Scenario: Payout history paging
    Given the driver has more than one page of payouts
    When the driver opens the wallet
    And the driver taps "Load more"
    Then more payouts are listed
```

```
  @wallet @negative
  Scenario Outline: Withdrawal is blocked
    Given <precondition>
    When the driver opens the wallet
    And the driver taps "Withdraw to bank"
    Then the text "<message>" is shown

    Examples:
      | precondition                                  | message
                        |
      | the driver has no banking details             | Add or finish your bankin
g details to withdraw. |
      | a payout is already in progress               | A payout is already in pr
ogress.                |
      | payouts are disabled for the driver account   | Payouts are not available
 for this account.     |
```

```
=================== membership.feature ===================

@membership
Feature: Driver membership
  As a driver
  I want to see and subscribe to membership benefits
  So that I can access partner perks

  Background:
    Given the driver is logged in

  @smoke
  Scenario: Driver views membership benefits
    When the driver opens "Membership" from the drawer
    Then the text "MEMBERSHIP" is shown
    And the text "Member Benefits include:" is shown
    And the benefits are listed:
      | benefit          |
      | Health Insurance |
      | Fitness Access   |
      | Phone Savings    |
      | More coming soon |

  Scenario: Driver opens membership options
    When the driver opens "Membership" from the drawer
    And the driver taps "See membership options"
    Then the membership subscribe page is shown

  Scenario: Driver subscribes to a membership
    Given the driver is on the membership subscribe page
    When the driver selects a membership plan
    And the driver completes the payment
    Then the membership is active
    And the "Back to HOVR" button is shown

  Scenario: Pending driver can access perks while waiting
    Given the driver documents are in review
    When the driver opens "Membership" from the drawer
    Then the text "Access perks while you wait for approval" is shown
```

```
==================== refer_and_earn.feature ====================

@referral
Feature: Refer and earn
  As a driver
  I want to invite riders with my referral code
  So that I earn rewards

  Background:
    Given the driver is logged in
    And the driver is approved for rideshare
    And the driver opens "Refer a friend" from the drawer

  @smoke
  Scenario: Referral screen is shown
    Then the text "Refer and earn" is shown
    And the "Referral link" is shown
    And the "Share with Rider" button is shown
    And the "How it works" steps are listed:
      | step                                                |
      | Share your link                                     |
      | Your friend signs up and takes their first 3 rides  |
      | Claim your reward!                                  |

  Scenario: Driver copies the referral link
    When the driver taps the referral link
    Then the snackbar "Copied to clipboard!" is shown

  Scenario: Driver shares the referral link
    When the driver taps "Share with Rider"
    Then the share sheet opens with "ridehovr.com/invite/"

  Scenario: Driver opens the referral terms
    When the driver taps "See terms and conditions"
    Then the referral terms are shown

  @redeem
  Scenario: Driver redeems a referral code
    When the driver taps "Enter a referral code"
    Then the text "Enter referral code" is shown
    When the driver enters the code "HOVR123"
    And the driver taps "Redeem"
    Then the text "Redeemed successfully!" is shown

  @redeem @negative
  Scenario: Empty referral code
    When the driver taps "Enter a referral code"
    And the driver taps "Redeem"
    Then the text "Enter the referral code!" is shown

  @redeem @negative
  Scenario: Referral code cannot be redeemed
    Given the redeem request returns an error
    When the driver redeems the code "BADCODE"
    Then the text "Can't redeem at the moment!" is shown

  @redeem
  Scenario: Driver scans a referral QR code
    When the driver taps "Enter a referral code"
    And the driver scans a referral QR code
    Then the referral code is filled in
```

```
@progress
Scenario: Driver views referral progress
  Given the driver has referred riders
  When the driver taps "View progress"
  Then the text "Referral progress" is shown
  And each referral shows completed rides as "x/3 rides"

@progress
Scenario: No referrals yet
  Given the driver has not referred anyone
  When the driver taps "View progress"
  Then the text "No referrals yet" is shown
  And the text "Refer a friend to start earning" is shown

@wallet
Scenario: Referral wallet balances
  Given the driver has referral rewards
  Then "Total", "Available", "Pending" and "Locked" are shown
```

```
==================== alerts_and_notifications.feature ====================

@alerts @notifications
Feature: Alerts, notifications and inbox
  As a driver
  I want to see alerts and messages from HOVR
  So that I can act on account issues

  Background:
    Given the driver is logged in

  @alerts @smoke
  Scenario: Driver views alerts
    Given the driver has alerts
    When the driver opens "Account"
    And the driver taps "Alerts"
    Then the text "Alerts" is shown
    And each alert shows "Status" and "Severity"

  @alerts
  Scenario: No alerts
    Given the driver has no alerts
    When the driver opens the alerts list
    Then the text "No alerts found!" is shown

  @alerts
  Scenario: Driver marks an alert as read
    Given the driver has an unread alert
    When the driver opens the alert
    And the driver taps "Mark as read"
    Then the alert is marked as read

  @alerts
  Scenario: Driver dismisses an alert
    Given the driver has an alert
    When the driver opens the alert
    And the driver taps "Dismiss"
    Then the alert is removed from the list

  @alerts
  Scenario Outline: Alert action opens the right screen
    Given the driver has an alert of type "<type>"
    When the driver opens the alert
    And the driver taps "<action>"
    Then the "<screen>" screen is shown

    Examples:
      | type         | action             | screen          |
      | banking      | Go to banking      | Banking Details |
      | document     | Go to Document     | Documents       |
      | subscription | Go to Subscription | Membership      |

  @alerts
  Scenario: Alerts are shown on the home screen
    Given the driver has an active alert
    When the driver opens the home screen
    Then the alert banner is shown

  @alerts @negative
  Scenario: Alerts fail to load
    Given the list alerts request returns an error
    When the driver opens the alerts list
```

```
  Then the text "Something went wrong while getting alerts!" is shown

@inbox
Scenario: Empty inbox
  Given the driver has no messages
  When the driver opens "Inbox"
  Then the text "You’re all caught up." is shown
  And the text "No new messages." is shown

@inbox
Scenario: Driver opens a notification
  Given the driver has a notification
  When the driver opens "Inbox"
  And the driver opens the notification
  Then the notification detail is shown

@push
Scenario: Tapping a push notification opens the app
  Given the app is in the background
  When the driver receives a push notification
  And the driver taps the push notification
  Then the app opens on the related screen
```

```
==================== help_and_support.feature ====================

@help
Feature: Help and support
  As a driver
  I want to find answers and contact support
  So that I can solve problems quickly

  Background:
    Given the driver is logged in
    And the driver opens "Help"

  @smoke
  Scenario: Help screen sections
    Then the text "Help" is shown
    And the sections are shown:
      | section       |
      | Support cases |
      | FAQ           |
      | Other         |

  Scenario Outline: Driver opens an FAQ category
    When the driver taps "<category>"
    Then the questions for "<category>" are listed

    Examples:
      | category             |
      | App and features     |
      | Account and data     |
      | Payments and pricing |
      | Using HOVR           |

  Scenario: Driver searches help
    When the driver searches "cancel" in "Search Help"
    Then matching help articles are listed

  Scenario: Empty support inbox
    Given the driver has no open support conversations
    When the driver taps "Inbox"
    Then the text "No open conversations with HOVR Support" is shown

  Scenario: Driver opens support tickets
    When the driver taps "Get in touch with us"
    Then the text "Support tickets" is shown

  Scenario: About HOVR shows the app version
    When the driver taps "About HOVR"
    Then the text "About HOVR" is shown
    And the app version is shown

  Scenario Outline: Legal pages
    When the driver taps "<page>"
    Then the "<page>" page is opened

    Examples:
      | page             |
      | Terms of Service |
      | Privacy Policy   |
```

```
==================== api/auth_service.feature ====================

@api @auth
Feature: API - iam.auth.v1.AuthService
  Login, token refresh, profile and app version endpoints.
  Called from core/network/otp_login_api.dart, core/network/client_manager.dart,
  core/session/driver_session_repository.dart and app_version_sync_coordinator.

  Background:
    Given the API base URL for the "dev" environment
    And the "Content-Type" header is "application/proto"

  @smoke
  Scenario: CreateVerificationChallenge sends an OTP
    When I call "iam.auth.v1.AuthService/CreateVerificationChallenge" with:
      | field        | value         |
      | phone_number | +14165550100 |
    Then the response code is "ok"
    And an OTP is sent to "+14165550100"

  @negative
  Scenario: CreateVerificationChallenge rejects an invalid phone number
    When I call "iam.auth.v1.AuthService/CreateVerificationChallenge" with:
      | field        | value |
      | phone_number | 123   |
    Then the response code is "invalid_argument"

  @smoke
  Scenario: VerifyVerificationChallenge returns tokens for a valid OTP
    Given a verification challenge was created for "+14165550100"
    When I call "iam.auth.v1.AuthService/VerifyVerificationChallenge" with:
      | field        | value                  |
      | phone_number | +14165550100           |
      | otp_code     | <valid otp>            |
      | user_type    | USER_TYPE_DRIVER       |
      | device_token | <fcm token>            |
      | lat_lng      | 43.6532,-79.3832       |
    Then the response code is "ok"
    And the response contains an access token
    And the response contains a refresh token

  @negative
  Scenario: VerifyVerificationChallenge rejects a wrong OTP
    Given a verification challenge was created for "+14165550100"
    When I call "iam.auth.v1.AuthService/VerifyVerificationChallenge" with:
      | field        | value             |
      | phone_number | +14165550100     |
      | otp_code     | 000000           |
      | user_type    | USER_TYPE_DRIVER |
    Then the response code is "unauthenticated" or "invalid_argument"

  @token
  Scenario: RefreshAccessToken issues a new access token
    Given a valid refresh token
    When I call "iam.auth.v1.AuthService/RefreshAccessToken" with:
      | field         | value           |
      | refresh_token | <refresh token> |
    Then the response code is "ok"
    And the response contains a new access token

  @token @negative
  Scenario: RefreshAccessToken rejects an expired refresh token
```

```
  When I call "iam.auth.v1.AuthService/RefreshAccessToken" with:
    | field         | value                     |
    | refresh_token | <expired refresh token> |
  Then the response code is "unauthenticated"

@token
Scenario: App retries a call after refreshing the token
  Given the access token has expired
  And a valid refresh token
  When the app calls any authenticated endpoint
  Then the first response code is "unauthenticated"
  And "iam.auth.v1.AuthService/RefreshAccessToken" is called once
  And the original call is retried with the new access token

Scenario: GetActiveProfile returns the driver profile
  Given an authenticated driver session
  When I call "iam.auth.v1.AuthService/GetActiveProfile" with:
    | field   | value            |
    | lat_lng | 43.6532,-79.3832 |
  Then the response code is "ok"
  And the response contains the driver profile

Scenario: GetAppVersion returns the minimum supported version
  When I call "iam.auth.v1.AuthService/GetAppVersion" with:
    | field    | value       |
    | app_name | hovr_driver |
    | platform | android     |
  Then the response code is "ok"
  And the response contains the latest and minimum app version

Scenario: GetPaymentUrl returns a membership checkout URL
  Given an authenticated driver session
  When I call "iam.auth.v1.AuthService/GetPaymentUrl" with:
    | field       | value                     |
    | id          | <membership plan id>   |
    | success_url | <app success deeplink> |
  Then the response code is "ok"
  And the response contains an https payment URL

@security
Scenario Outline: Authenticated endpoints reject calls without a token
  Given no Authorization header
  When I call "<endpoint>" with an empty request
  Then the response code is "unauthenticated"

  Examples:
    | endpoint                                                  |
    | iam.auth.v1.AuthService/GetActiveProfile                  |
    | iam.driver.v1.DriverProfileService/GetDriverProfile |
    | ride.v1.driver.DriverService/GetDriverStatus              |
    | ride.v1.trip.TripService/GetActiveTrip                    |
    | iam.wallet.v1.WalletService/GetWallet                     |
    | neighbour.v1.driver.NeighbourDriverService/ListMyNeighbourTrips |
```

```
==================== api/profile_notification_calling.feature ================
==

@api @profile
Feature: API - driver profile, device tokens and masked calling
  iam.driver.v1.DriverProfileService (driver_profile_bloc, auth_bloc),
  iam.notification.v1.NotificationSettingsService (driver_notification_registrat
ion, logout_coordinator),
  iam.twilio.v1.MaskedCallingService (auth_bloc).

  Background:
    Given the API base URL for the "dev" environment
    And an authenticated driver session

  @smoke
  Scenario: GetDriverProfile returns the driver
    When I call "iam.driver.v1.DriverProfileService/GetDriverProfile" with:
      | field | value       |
      | id    | <driver id> |
    Then the response code is "ok"
    And the response contains first name, last name, phone and email

  Scenario: UpdateDriverProfile updates the preferred name
    When I call "iam.driver.v1.DriverProfileService/UpdateDriverProfile" with:
      | field          | value       |
      | id             | <driver id> |
      | preferred_name | AJ          |
    Then the response code is "ok"
    And "GetDriverProfile" returns preferred name "AJ"

  @negative
  Scenario: UpdateDriverProfile rejects another driver's id
    When I call "iam.driver.v1.DriverProfileService/UpdateDriverProfile" with:
      | field      | value           |
      | id         | <other driver id>  |
      | first_name | Mallory         |
    Then the response code is "permission_denied"

  Scenario: ChangeEmail then VerifyEmail
    When I call "iam.driver.v1.DriverProfileService/ChangeEmail" with email "ale
x.new@example.com"
    Then the response code is "ok"
    When I call "iam.driver.v1.DriverProfileService/VerifyEmail" with the code s
ent to "alex.new@example.com"
    Then the response code is "ok"
    And the driver email is "alex.new@example.com"

  @notification
  Scenario: RegisterDeviceToken after login
    When I call "iam.notification.v1.NotificationSettingsService/RegisterDeviceT
oken" with:
      | field       | value       |
      | fcm_token   | <fcm token> |
      | platform    | android     |
      | app_version | <version>   |
      | locale      | en_US       |
      | latitude    | 43.6532     |
      | longitude   | -79.3832    |
    Then the response code is "ok"

  @notification
  Scenario: UnregisterDeviceToken on logout
```

```
    Given the device token is registered
    When I call "iam.notification.v1.NotificationSettingsService/UnregisterDevic
eToken" with:
      | field     | value       |
      | fcm_token | <fcm token> |
    Then the response code is "ok"
    And no push notifications are sent to that device

  @calling
  Scenario: SetupMapping then MakeMaskedCall to the rider
    Given the driver has an active trip with a rider
    When I call "iam.twilio.v1.MaskedCallingService/SetupMapping" with:
      | field    | value          |
      | caller   | <driver phone> |
      | receiver | <rider phone>  |
    Then the response code is "ok"
    When I call "iam.twilio.v1.MaskedCallingService/MakeMaskedCall" with:
      | field  | value          |
      | caller | <driver phone> |
    Then the response code is "ok"
    And the rider's real number is not returned
```

```
==================== api/onboarding_documents_vehicle.feature ================
==

@api @onboarding
Feature: API - onboarding, documents and vehicles
  driver.v1.driver.DriverService (driver_session_repository, driver_onboarding_f
eature_bloc),
  driver.v1.onboarding.OnboardingService and driver.v1.document.DcoumentService
  (driver_onboarding_feature_bloc, documents_feature_bloc, neighbour_eligibility
_cubit),
  driver.v1.vehicle.VehicleService (driver_profile_bloc, my_vehicle_details).

  Background:
    Given the API base URL for the "dev" environment
    And an authenticated driver session

  @smoke
  Scenario: GetDriver returns the onboarding driver record
    When I call "driver.v1.driver.DriverService/GetDriver" with:
      | field     | value       |
      | driver_id | <driver id> |
    Then the response code is "ok"

  Scenario: GetDriverStatus returns status for the marketplace
    When I call "driver.v1.driver.DriverService/GetDriverStatus" with:
      | field          | value            |
      | driver_id      | <driver id>      |
      | marketplace_id | <marketplace id> |
    Then the response code is "ok"
    And the response contains the driver approval status

  @banking
  Scenario: GetDriverBankingStatus and GetBankingOnboardingUrl
    When I call "driver.v1.driver.DriverService/GetDriverBankingStatus" with:
      | field          | value            |
      | driver_id      | <driver id>      |
      | marketplace_id | <marketplace id> |
    Then the response code is "ok"
    When I call "driver.v1.driver.DriverService/GetBankingOnboardingUrl" with:
      | field          | value            |
      | driver_id      | <driver id>      |
      | marketplace_id | <marketplace id> |
    Then the response code is "ok"
    And the response contains an https URL

  @session
  Scenario: StartOnboarding creates a session that is listed
    Given the driver has no onboarding session for "<marketplace id>"
    When I call "driver.v1.onboarding.OnboardingService/StartOnboarding" with:
      | field          | value            |
      | driver_id      | <driver id>      |
      | marketplace_id | <marketplace id> |
    Then the response code is "ok"
    When I call "driver.v1.onboarding.OnboardingService/ListOnboardingSessions"
with:
      | field     | value       |
      | driver_id | <driver id> |
      | page_size | 20          |
    Then the new session is listed

  @session
  Scenario: GetOnboardingChecklist returns the steps
```

```
    Given an onboarding session "<session id>"
    When I call "driver.v1.onboarding.OnboardingService/GetOnboardingChecklist"
with:
      | field      | value        |
      | session_id | <session id> |
    Then the response code is "ok"
    And the checklist contains Driver, Vehicle, City Requirements, Membership, B
anking and Training

  @upload @smoke
  Scenario: Document upload sequence
    Given an onboarding session "<session id>" with requirement "<requirement id
>"
    When I call "driver.v1.document.DcoumentService/StartDocumentUpload" with:
      | field          | value              |
      | driver_id      | <driver id>        |
      | requirement_id | <requirement id>   |
      | marketplace_id | <marketplace id>   |
      | content_type   | image/jpeg         |
      | file_name      | licence.jpg        |
      | size_bytes     | 204800             |
    Then the response code is "ok"
    And the response contains an upload id and an upload URL
    When I upload the file to the upload URL
    And I call "driver.v1.document.DcoumentService/CompleteDocumentUpload" with:
      | field     | value       |
      | upload_id | <upload id> |
    Then the response code is "ok"
    When I call "driver.v1.onboarding.OnboardingService/SubmitRequirementDocumen
t" with:
      | field          | value            |
      | session_id     | <session id>     |
      | requirement_id | <requirement id> |
      | storage_key    | <storage key>    |
    Then the response code is "ok"
    And the requirement status becomes "submitted"

  @upload @negative
  Scenario Outline: StartDocumentUpload rejects bad files
    When I call "driver.v1.document.DcoumentService/StartDocumentUpload" with co
ntent type "<type>" and size <size>
    Then the response code is "invalid_argument"

    Examples:
      | type            | size      |
      | application/zip | 204800    |
      | image/jpeg      | 0         |
      | image/jpeg      | 104857600 |

  @upload @negative
  Scenario: CompleteDocumentUpload with an unknown upload id
    When I call "driver.v1.document.DcoumentService/CompleteDocumentUpload" with
:
      | field     | value   |
      | upload_id | unknown |
    Then the response code is "not_found"

  @documents
  Scenario: ListRequirementStatuses returns document statuses
    When I call "driver.v1.document.DcoumentService/ListRequirementStatuses" wit
h:
      | field          | value            |
```

```
    | driver_id      | <driver id>      |
    | marketplace_id | <marketplace id> |
  Then the response code is "ok"
  And each requirement has a status

@vehicle
Scenario: ListVehicles returns the driver's vehicles
  When I call "driver.v1.vehicle.VehicleService/ListVehicles" with:
    | field     | value       |
    | driver_id | <driver id> |
    | page_size | 20          |
  Then the response code is "ok"

@vehicle
Scenario: DeleteVehicle removes a vehicle
  Given the driver has a vehicle "<vehicle id>"
  When I call "driver.v1.vehicle.VehicleService/DeleteVehicle" with:
    | field      | value        |
    | vehicle_id | <vehicle id> |
  Then the response code is "ok"
  And "ListVehicles" no longer returns "<vehicle id>"
```

```
================== api/ride_driver_service.feature ==================

@api @ride-driver
Feature: API - ride.v1.driver.DriverService, LocationService and RideService
  Going online, offers, sessions and scheduled rides.
  Callers: home_bloc, ride_activation_handler, ride_offer_handler, driver_profil
e_bloc,
  scheduled_trips_cubit, scheduled_trip_offer_cubit, core/isolates/driver_stream
,
  core/services/location_stream_service.dart (location isolate).

  Background:
    Given the API base URL for the "dev" environment
    And an authenticated driver session for an approved driver

  @smoke
  Scenario: GetDriverStatus returns the online state
    When I call "ride.v1.driver.DriverService/GetDriverStatus" with:
      | field   | value       |
      | user_id | <driver id> |
    Then the response code is "ok"
    And the response contains the driver online status

  @smoke
  Scenario: ActivateDriver sets the driver online
    Given the driver is offline
    When I call "ride.v1.driver.DriverService/ActivateDriver" with:
      | field     | value             |
      | driver_id | <driver id>       |
      | position  | 43.6532,-79.3832  |
    Then the response code is "ok"
    And "GetDriverStatus" shows the driver online

  @negative
  Scenario: ActivateDriver is refused for a driver with pending documents
    Given the driver has unapproved documents
    When I call "ride.v1.driver.DriverService/ActivateDriver" for the driver
    Then the response code is "failed_precondition"

  Scenario: DeactivateDriver sets the driver offline
    Given the driver is online
    When I call "ride.v1.driver.DriverService/DeactivateDriver" with:
      | field     | value            |
      | driver_id | <driver id>      |
      | position  | 43.6532,-79.3832 |
    Then the response code is "ok"
    And "GetDriverStatus" shows the driver offline

  @stream
  Scenario: StreamDriver delivers a ride offer
    Given the driver is online
    And I open the bidi stream "ride.v1.driver.DriverService/StreamDriver"
    When a rider requests a ride near the driver
    Then the stream receives an offer with a trip id

  @stream
  Scenario: StreamDriver reconnects after the connection drops
    Given an open "StreamDriver" stream
    When the network drops for 10 seconds
    Then the client reopens the stream
    And no offer is lost
```

```
  @offer
  Scenario: AcceptOffer assigns the trip to the driver
    Given the driver received an offer for trip "<trip id>"
    When I call "ride.v1.driver.DriverService/AcceptOffer" with:
      | field      | value            |
      | driver_id  | <driver id>      |
      | offer_name | <offer name>     |
      | trip_id    | <trip id>        |
      | position   | 43.6532,-79.3832 |
    Then the response code is "ok"
    And "ride.v1.trip.TripService/GetActiveTrip" returns trip "<trip id>"

  @offer
  Scenario: RejectOffer frees the trip for other drivers
    Given the driver received an offer for trip "<trip id>"
    When I call "ride.v1.driver.DriverService/RejectOffer" with:
      | field       | value            |
      | offer_name  | <offer name>     |
      | trip_id     | <trip id>        |
      | reason_code | <reason code>    |
      | position    | 43.6532,-79.3832 |
    Then the response code is "ok"

  @offer @negative
  Scenario Outline: AcceptOffer fails for an offer that is no longer valid
    Given the offer for trip "<trip id>" is <state>
    When I call "ride.v1.driver.DriverService/AcceptOffer" for that offer
    Then the response code is "<code>"

    Examples:
      | state                   | code                |
      | expired                 | failed_precondition |
      | cancelled by the rider  | failed_precondition |
      | accepted by another driver | already_exists  |

  @location @stream
  Scenario: StreamLocation sends position updates
    Given the driver is online
    When I open the bidi stream "ride.v1.location.LocationService/StreamLocation
"
    And I send 5 location updates 1 second apart
    Then the server accepts all updates
    And the driver position is updated on the server

  @earnings
  Scenario: ListDriverSessions pages through sessions
    When I call "ride.v1.driver.DriverService/ListDriverSessions" with:
      | field     | value       |
      | driver_id | <driver id> |
    Then the response code is "ok"
    When I call it again with the returned "next_pagination_token"
    Then the next page of sessions is returned

  @scheduled
  Scenario: ListUpcomingScheduledRides and AcceptScheduledRide
    When I call "ride.v1.driver.DriverService/ListUpcomingScheduledRides" with:
      | field       | value       |
      | driver_id   | <driver id> |
      | active_only | true        |
    Then the response code is "ok"
    When I call "ride.v1.driver.DriverService/AcceptScheduledRide" with:
      | field      | value        |
```

```
      | request_id | <uuid>       |
      | booking_id | <booking id> |
    Then the response code is "ok"
    And the booking is listed as accepted

  @scheduled @idempotency
  Scenario: AcceptScheduledRide is idempotent on request_id
    Given I accepted booking "<booking id>" with request_id "<uuid>"
    When I call "ride.v1.driver.DriverService/AcceptScheduledRide" again with th
e same request_id
    Then the response code is "ok"
    And the booking is accepted only once

  @scheduled
  Scenario: ListScheduledRides near the driver
    When I call "ride.v1.ride.RideService/ListScheduledRides" with:
      | field           | value            |
      | marketplace_id  | <marketplace id> |
      | driver_location | 43.6532,-79.3832 |
    Then the response code is "ok"
```

```
=================== api/trip_service.feature ===================

@api @trip
Feature: API - ride.v1.trip.TripService
  Trip lifecycle endpoints. Callers: ride_trip_lifecycle_handler, ride_service_b
loc,
  core/isolates/trip_stream, rating views, session_list_view, notification_detai
l_view.
  Mutating calls send request_id (idempotency) and etag (optimistic concurrency)
.

  Background:
    Given the API base URL for the "dev" environment
    And an authenticated driver session
    And the driver has accepted trip "<trip id>"

  @smoke
  Scenario: Full trip lifecycle
    When I call "ride.v1.trip.TripService/MarkArriving" with trip_id, request_id
 and etag
    Then the response code is "ok"
    And the trip status is "arriving"
    When I call "ride.v1.trip.TripService/MarkArrived" with trip_id, request_id
and etag
    Then the trip status is "arrived"
    When I call "ride.v1.trip.TripService/StartTrip" with:
      | field          | value     |
      | trip_id        | <trip id> |
      | request_id     | <uuid>    |
      | waypoint_index | 0         |
      | etag           | <etag>    |
    Then the trip status is "in_progress"
    When I call "ride.v1.trip.TripService/CompleteTrip" with trip_id, request_id
 and etag
    Then the trip status is "completed"
    When I call "ride.v1.trip.TripService/SubmitRating" with:
      | field      | value     |
      | trip_id    | <trip id> |
      | value      | 5         |
      | request_id | <uuid>    |
    Then the response code is "ok"

  @stream
  Scenario: StreamTrip pushes trip updates
    When I open the bidi stream "ride.v1.trip.TripService/StreamTrip" for "<trip
 id>"
    And the rider changes the destination
    Then the stream receives an update with the new destination

  @stream
  Scenario: StreamTrip closes when the trip ends
    Given an open "StreamTrip" stream for "<trip id>"
    When the trip is completed
    Then the stream sends the final trip state
    And the stream is closed

  Scenario: GetActiveTrip restores the current trip
    When I call "ride.v1.trip.TripService/GetActiveTrip" with:
      | field   | value       |
      | user_id | <driver id> |
    Then the response code is "ok"
    And the response trip id is "<trip id>"
```

```
  Scenario: GetActiveTrip with no active trip
    Given the driver has no active trip
    When I call "ride.v1.trip.TripService/GetActiveTrip" for the driver
    Then the response code is "not_found" or the trip is empty

  Scenario: GetTrip returns a trip
    When I call "ride.v1.trip.TripService/GetTrip" with:
      | field   | value     |
      | trip_id | <trip id> |
    Then the response code is "ok"

  Scenario: ListTrips pages through past trips
    When I call "ride.v1.trip.TripService/ListTrips" with a status filter "compl
eted"
    Then the response code is "ok"
    And a "pagination_token" is returned when there are more trips

  @cancel
  Scenario: CancelTrip by the driver
    When I call "ride.v1.trip.TripService/CancelTrip" with:
      | field       | value         |
      | trip_id     | <trip id>     |
      | reason_code | <reason code> |
      | details     | Rider kept me waiting |
      | request_id  | <uuid>        |
      | etag        | <etag>        |
    Then the response code is "ok"
    And the trip status is "driver_canceled"

  @no-show
  Scenario: ReportNoShow after waiting at pickup
    Given the trip status is "arrived"
    And the wait time has passed
    When I call "ride.v1.trip.TripService/ReportNoShow" with:
      | field         | value     |
      | trip_id       | <trip id> |
      | rider_no_show | true      |
      | request_id    | <uuid>    |
      | etag          | <etag>    |
    Then the response code is "ok"

  @no-show @negative
  Scenario: ReportNoShow before the wait time ends
    Given the trip status is "arrived"
    When I call "ride.v1.trip.TripService/ReportNoShow" immediately
    Then the response code is "failed_precondition"

  Scenario: EndTripEarly during a trip
    Given the trip status is "in_progress"
    When I call "ride.v1.trip.TripService/EndTripEarly" with trip_id, request_id
, etag and a reason_code
    Then the response code is "ok"
    And the trip is completed at the current location

  Scenario: UpdateTrip with an update mask
    When I call "ride.v1.trip.TripService/UpdateTrip" with a trip and update_mas
k "notes"
    Then the response code is "ok"
    And only the masked fields are changed

  @negative @concurrency
```

```
  Scenario: Stale etag is rejected
    Given the trip was updated by the rider after I read it
    When I call "ride.v1.trip.TripService/StartTrip" with the old etag
    Then the response code is "aborted" or "failed_precondition"

  @idempotency
  Scenario: Repeating CompleteTrip with the same request_id
    Given I completed the trip with request_id "<uuid>"
    When I call "ride.v1.trip.TripService/CompleteTrip" again with the same requ
est_id
    Then the response code is "ok"
    And the rider is charged once

  @negative
  Scenario Outline: Lifecycle calls in the wrong order are rejected
    Given the trip status is "<status>"
    When I call "ride.v1.trip.TripService/<method>" for the trip
    Then the response code is "failed_precondition"

    Examples:
      | status    | method       |
      | accepted  | StartTrip    |
      | accepted  | CompleteTrip |
      | completed | MarkArrived  |
      | completed | CancelTrip   |

  @negative
  Scenario: Another driver cannot change the trip
    Given an authenticated session for a different driver
    When I call "ride.v1.trip.TripService/MarkArrived" for "<trip id>"
    Then the response code is "permission_denied"

  @rating @negative
  Scenario Outline: SubmitRating validates the value
    Given the trip is completed
    When I call "ride.v1.trip.TripService/SubmitRating" with value <value>
    Then the response code is "invalid_argument"

    Examples:
      | value |
      | 0     |
      | 6     |

  @not-used-in-ui
  Scenario Outline: Stop, destination and tip endpoints
    When I call "ride.v1.trip.TripService/<method>" for an in-progress trip
    Then the response code is "ok"

    Examples:
      | method            |
      | AddStop           |
      | RemoveStop        |
      | ChangeDestination |
      | AddTip            |
```

```
=================== api/neighbour_service.feature ===================

@api @neighbour @co-commute
Feature: API - Co-Commute (Neighbour) services
  neighbour.v1.eligibility.NeighbourEligibilityService and neighbour.v1.driver.N
eighbourDriverService.
  Callers: lib/features/neighbours-feature/presentation/cubit/*.

  Background:
    Given the API base URL for the "dev" environment
    And an authenticated driver session
    And the Co-Commute marketplace id "<neighbour marketplace id>"

  @eligibility @smoke
  Scenario: CheckNeighbourEligibility for an eligible driver
    Given the driver meets all Co-Commute requirements
    When I call "neighbour.v1.eligibility.NeighbourEligibilityService/CheckNeigh
bourEligibility" with:
      | field                  | value                       |
      | driver_id              | <driver id>                 |
      | current_marketplace_id | <marketplace id>            |
      | neighbour_marketplace_id | <neighbour marketplace id> |
    Then the response code is "ok"
    And the driver is eligible with no blocking reasons

  @eligibility
  Scenario: CheckNeighbourEligibility for an ineligible driver
    Given the driver is missing a Co-Commute requirement
    When I call "CheckNeighbourEligibility" for the driver
    Then the driver is not eligible
    And the response lists the blocking reasons

  @post @smoke
  Scenario: PostNeighbourTrip creates an open commute
    When I call "neighbour.v1.driver.NeighbourDriverService/PostNeighbourTrip" w
ith:
      | field                | value                       |
      | request_id           | <uuid>                      |
      | marketplace_id       | <neighbour marketplace id> |
      | origin               | 43.6532,-79.3832            |
      | destination          | 43.7615,-79.4111            |
      | depart_at            | now + 45 minutes            |
      | depart_window_seconds | 900                        |
    Then the response code is "ok"
    And the trip status is "open"
    And "ListMyNeighbourTrips" returns the new trip

  @post @negative
  Scenario Outline: PostNeighbourTrip validates the departure time
    When I call "PostNeighbourTrip" with depart_at "<depart_at>"
    Then the response code is "invalid_argument"

    Examples:
      | depart_at         |
      | now + 10 minutes  |
      | now + 15 days     |
      | now - 1 hour      |

  @post @idempotency
  Scenario: PostNeighbourTrip is idempotent on request_id
    Given I posted a commute with request_id "<uuid>"
    When I call "PostNeighbourTrip" again with the same request_id
```

```
    Then only one commute exists

  @post @negative
  Scenario: Ineligible driver cannot post a commute
    Given the driver is not eligible for Co-Commute
    When I call "PostNeighbourTrip" with a valid commute
    Then the response code is "permission_denied" or "failed_precondition"

  Scenario: UpdateNeighbourTrip changes the departure window
    Given the driver has an open commute "<neighbour trip id>"
    When I call "neighbour.v1.driver.NeighbourDriverService/UpdateNeighbourTrip"
 with:
      | field                  | value                |
      | neighbour_trip_id      | <neighbour trip id> |
      | depart_window_seconds | 1200                 |
    Then the response code is "ok"

  @my-trips
  Scenario: ListMyNeighbourTrips returns upcoming commutes
    When I call "neighbour.v1.driver.NeighbourDriverService/ListMyNeighbourTrips
" with:
      | field         | value |
      | upcoming_only | true  |
      | page_size     | 20    |
    Then the response code is "ok"

  @bookings
  Scenario: ListBookingsOnMyTrip returns pending bookings
    Given the commute "<neighbour trip id>" has a pending booking
    When I call "neighbour.v1.driver.NeighbourDriverService/ListBookingsOnMyTrip
" with:
      | field             | value                |
      | neighbour_trip_id | <neighbour trip id> |
      | pending_only      | true                 |
    Then the response code is "ok"
    And the booking includes the rider price, platform fee and driver earnings

  @bookings
  Scenario: ApproveNeighbourBooking confirms the booking
    Given a pending booking "<booking id>"
    When I call "neighbour.v1.driver.NeighbourDriverService/ApproveNeighbourBook
ing" with:
      | field                | value        |
      | neighbour_booking_id | <booking id> |
    Then the response code is "ok"
    And the booking status is "confirmed"

  @bookings
  Scenario: DeclineNeighbourBooking with a reason
    Given a pending booking "<booking id>"
    When I call "neighbour.v1.driver.NeighbourDriverService/DeclineNeighbourBook
ing" with:
      | field                | value        |
      | neighbour_booking_id | <booking id> |
      | reason               | Route change |
    Then the response code is "ok"
    And the booking status is "declined"

  @bookings @negative
  Scenario: Approving an already declined booking
    Given a declined booking "<booking id>"
    When I call "ApproveNeighbourBooking" for it
```

```
    Then the response code is "failed_precondition"

  @journey
  Scenario: StartNeighbourJourney starts a live trip
    Given a confirmed booking "<booking id>" on commute "<neighbour trip id>"
    When I call "neighbour.v1.driver.NeighbourDriverService/StartNeighbourJourne
y" with:
      | field               | value               |
      | request_id          | <uuid>              |
      | neighbour_booking_id | <booking id>       |
      | neighbour_trip_id   | <neighbour trip id> |
    Then the response code is "ok"
    And the response contains a live trip id
    And "ride.v1.trip.TripService/GetActiveTrip" returns that trip

  @cancel
  Scenario: CancelNeighbourTrip cancels the commute
    Given the driver has an open commute "<neighbour trip id>"
    When I call "neighbour.v1.driver.NeighbourDriverService/CancelNeighbourTrip"
 with:
      | field             | value               |
      | neighbour_trip_id | <neighbour trip id> |
      | reason            | Plans changed       |
    Then the response code is "ok"
    And the trip status is "canceled"
    And all bookings on it are cancelled

  @nearby
  Scenario: ListNeighbourRequests near the driver
    When I call "neighbour.v1.driver.NeighbourDriverService/ListNeighbourRequest
s" with:
      | field           | value                       |
      | marketplace_id  | <neighbour marketplace id> |
      | driver_location | 43.6532,-79.3832            |
      | within_seconds  | 7200                        |
      | page_size       | 20                          |
    Then the response code is "ok"
    And only requests within the next 2 hours are returned

  @nearby
  Scenario: AcceptNeighbourRequest books the rider
    Given an open rider request "<neighbour request id>"
    When I call "neighbour.v1.driver.NeighbourDriverService/AcceptNeighbourReque
st" with:
      | field                | value                  |
      | request_id           | <uuid>                 |
      | neighbour_request_id | <neighbour request id> |
    Then the response code is "ok"
    And "ListMyNeighbourBookings" returns the booking

  @nearby @negative
  Scenario: AcceptNeighbourRequest for a request taken by another driver
    Given the rider request was accepted by another driver
    When I call "AcceptNeighbourRequest" for it
    Then the response code is "failed_precondition" or "already_exists"

  @my-bookings
  Scenario: ListMyNeighbourBookings returns the driver's bookings
    When I call "neighbour.v1.driver.NeighbourDriverService/ListMyNeighbourBooki
ngs" with:
      | field         | value |
      | upcoming_only | false |
```

```
      | page_size     | 20    |
    Then the response code is "ok"

  @pagination
  Scenario Outline: List endpoints page with page_token
    Given more than 20 items exist for "<method>"
    When I call "neighbour.v1.driver.NeighbourDriverService/<method>" with page_
size 20
    Then 20 items and a next page token are returned
    When I call it again with that page token
    Then the next items are returned without duplicates

    Examples:
      | method                   |
      | ListMyNeighbourTrips     |
      | ListMyNeighbourBookings  |
      | ListNeighbourRequests    |
```

```
==================== api/wallet_referral_service.feature ====================

@api @wallet @referral
Feature: API - wallet payouts and referrals
  iam.wallet.v1.WalletService (wallet_cubit) and iam.referral.v1.ReferralService
  (referral_bloc, redeem_referral_cubit).

  Background:
    Given the API base URL for the "dev" environment
    And an authenticated driver session

  @wallet @smoke
  Scenario: GetWallet returns balances
    When I call "iam.wallet.v1.WalletService/GetWallet" with:
      | field   | value       |
      | user_id | <driver id> |
    Then the response code is "ok"
    And the response contains the available balance

  @wallet @smoke
  Scenario: Quote then create a payout
    Given the driver has an available balance of 120.00
    And the driver has an active bank account
    When I call "iam.wallet.v1.WalletService/GetWalletPayoutQuote" with:
      | field | value              |
      | code  | <payout method>    |
    Then the response code is "ok"
    And the quote contains the minimum and maximum payout
    When I call "iam.wallet.v1.WalletService/CreateWalletPayout" with:
      | field      | value           |
      | request_id | <uuid>          |
      | amount     | 120.00          |
      | code       | <payout method> |
    Then the response code is "ok"
    And the payout status is "requested"

  @wallet @negative
  Scenario Outline: CreateWalletPayout is refused
    Given <precondition>
    When I call "iam.wallet.v1.WalletService/CreateWalletPayout" with amount <am
ount>
    Then the response code is "<code>"

    Examples:
      | precondition                          | amount  | code                 |
      | the driver has no bank account        | 50.00   | failed_precondition  |
      | a payout is already in progress       | 50.00   | failed_precondition  |
      | the available balance is 20.00        | 50.00   | failed_precondition  |
      | the minimum payout is 10.00           | 1.00    | invalid_argument     |

  @wallet @idempotency
  Scenario: CreateWalletPayout is idempotent on request_id
    Given I created a payout with request_id "<uuid>"
    When I call "CreateWalletPayout" again with the same request_id
    Then only one payout exists

  @wallet
  Scenario: ListWalletPayouts and GetWalletPayout
    When I call "iam.wallet.v1.WalletService/ListWalletPayouts" with:
      | field     | value |
      | page_size | 20    |
    Then the response code is "ok"
```

```
    When I call "iam.wallet.v1.WalletService/GetWalletPayout" with the first pay
out_id
    Then the response code is "ok"
    And the payout id, amount and status are returned

  @referral
  Scenario: GetReferralProfile returns the referral code
    When I call "iam.referral.v1.ReferralService/GetReferralProfile" with:
      | field   | value       |
      | user_id | <driver id> |
    Then the response code is "ok"
    And the response contains a referral code

  @referral
  Scenario: ListReferralReward pages through rewards
    When I call "iam.referral.v1.ReferralService/ListReferralReward" with no pag
ination_token
    Then the response code is "ok"

  @referral
  Scenario: RedeemReferral with a valid code
    When I call "iam.referral.v1.ReferralService/RedeemReferral" with:
      | field         | value   |
      | referral_code | HOVR123 |
    Then the response code is "ok"

  @referral @negative
  Scenario Outline: RedeemReferral is refused
    When I call "iam.referral.v1.ReferralService/RedeemReferral" with referral_c
ode "<code>"
    Then the response code is "<status>"

    Examples:
      | code          | status              |
      |               | invalid_argument    |
      | BADCODE       | not_found           |
      | <own code>    | failed_precondition |
      | <already used>| already_exists      |
```

```
=================== api/alerts_inbox_service.feature ===================

@api @alerts @inbox
Feature: API - alerts and inbox
  driver.v1.alerts.AlertsService (alerts_service_bloc) and
  notification.v1.inbox.InboxService (notification_feature_bloc).

  Background:
    Given the API base URL for the "dev" environment
    And an authenticated driver session

  @alerts @smoke
  Scenario: ListAlerts returns the driver's alerts
    When I call "driver.v1.alerts.AlertsService/ListAlerts" with:
      | field          | value             |
      | driver_id      | <driver id>       |
      | marketplace_id | <marketplace id> |
      | page_size      | 20                |
    Then the response code is "ok"
    And each alert has a status and severity

  @alerts
  Scenario: ListAlerts with unread_only
    Given the driver has 2 unread and 3 read alerts
    When I call "driver.v1.alerts.AlertsService/ListAlerts" with unread_only tru
e
    Then 2 alerts are returned

  @alerts
  Scenario: GetAlert, MarkAlertRead and DismissAlert
    Given an unread alert "<alert id>"
    When I call "driver.v1.alerts.AlertsService/GetAlert" with alert_id "<alert
id>"
    Then the response code is "ok"
    When I call "driver.v1.alerts.AlertsService/MarkAlertRead" with alert_id "<a
lert id>"
    Then the alert is read
    When I call "driver.v1.alerts.AlertsService/DismissAlert" with:
      | field    | value       |
      | alert_id | <alert id>  |
      | reason   | Resolved    |
    Then the response code is "ok"
    And "ListAlerts" no longer returns "<alert id>"

  @alerts @negative
  Scenario: GetAlert with an unknown id
    When I call "driver.v1.alerts.AlertsService/GetAlert" with alert_id "unknown
"
    Then the response code is "not_found"

  @alerts @negative
  Scenario: Driver cannot read another driver's alert
    Given an alert "<other alert id>" that belongs to another driver
    When I call "driver.v1.alerts.AlertsService/GetAlert" with alert_id "<other
alert id>"
    Then the response code is "permission_denied" or "not_found"

  @inbox
  Scenario: ListNotifications returns notifications
    When I call "notification.v1.inbox.InboxService/ListNotifications" with:
      | field       | value |
      | page        | 1     |
```

```
    | unread_only | false |
  Then the response code is "ok"

@inbox
Scenario: ListBroadcasts returns broadcasts
  When I call "notification.v1.inbox.InboxService/ListBroadcasts" with:
    | field | value |
    | page  | 1     |
  Then the response code is "ok"

@inbox
Scenario: Empty inbox
  Given the driver has no notifications
  When I call "notification.v1.inbox.InboxService/ListNotifications" with page
1
  Then the response code is "ok"
  And the list is empty
```