HOVR Rider App

Cucumber / Gherkin API (gRPC/ConnectRPC) feature files for automation testing

Generated 2026-10-14 from the hovr_rider Flutter app (lib/features, routes and app_en.arb strings). RPC names are taken from the hovr_sdk clients used in lib/; status codes are standard gRPC codes; tags: @smoke for the critical path, one tag per module.

#	Feature file	Scenarios
1	01_auth_service.feature	10
2	02_rider_profile_service.feature	10
3	03_payment_api.feature	6
4	04_ride_service.feature	7
5	05_trip_service.feature	20
6	06_neighbour_rider_service.feature	12
7	07_wallet_referral_service.feature	7
8	08_notification_activity_service.feature	9
9	09_helpdesk_api.feature	5
	Total	**86**

01_auth_service.feature

```
@api @iam
Feature: AuthService (IAM) API
  Rider sign-in uses OTP verification over gRPC/ConnectRPC.
  Client: AuthServiceClient (lib/core/network/otp_login_api.dart, bare_iam_client.dart)

  Background:
    Given the API base URL is configured for the "staging" environment
    And I use a gRPC/ConnectRPC client with protobuf encoding

  @smoke
  Scenario: Create OTP challenge for a valid phone
    When I call "AuthService/CreateVerificationChallenge" with:
      | phone    | +14165550123 |
      | userType | RIDER        |
    Then the response status is "OK"
    And the response contains a non-empty challenge id

  Scenario Outline: Create OTP challenge with invalid phone
    When I call "AuthService/CreateVerificationChallenge" with phone "<phone>"
    Then the response status is "INVALID_ARGUMENT"

    Examples:
      | phone      |
      | 12345      |
      |            |
      | +1abc55501 |

  Scenario: OTP rate limit
    Given I have requested OTP the maximum number of times today for "+14165550123"
    When I call "AuthService/CreateVerificationChallenge" with phone "+14165550123"
    Then the response status is "RESOURCE_EXHAUSTED"

  @smoke
  Scenario: Verify OTP with correct code
    Given an OTP challenge exists for "+14165550123"
    When I call "AuthService/VerifyVerificationChallenge" with:
      | phone       | +14165550123   |
      | otpCode     | <valid code>   |
      | deviceToken | <fcm token>    |
      | userType    | RIDER          |
    Then the response status is "OK"
    And the response contains an access token and a refresh token

  Scenario: Verify OTP with wrong code
    Given an OTP challenge exists for "+14165550123"
    When I call "AuthService/VerifyVerificationChallenge" with otpCode "000000"
    Then the response status is "INVALID_ARGUMENT" or "UNAUTHENTICATED"
    And no tokens are returned

  Scenario: Refresh access token
    Given I hold a valid refresh token
    When I call "AuthService/RefreshAccessToken"
    Then the response status is "OK"
    And a new access token is returned

  Scenario: Refresh with expired or revoked token
    Given I hold a revoked refresh token
    When I call "AuthService/RefreshAccessToken"
    Then the response status is "UNAUTHENTICATED"

  Scenario: Get active profile
    Given I am authenticated as a rider
    When I call "AuthService/GetActiveProfile"
    Then the response status is "OK"
    And the response contains my rider id

  Scenario: Get app version
    When I call "AuthService/GetAppVersion" with the current platform
    Then the response contains the latest and minimum supported version

  Scenario Outline: Protected RPC without valid token
    Given my access token is "<token>"
```

```
    When I call "AuthService/GetActiveProfile"
    Then the response status is "UNAUTHENTICATED"

    Examples:
      | token      |
      | missing    |
      | expired    |
      | malformed  |
```

02_rider_profile_service.feature

```
@api @profile
Feature: RiderProfileService API
  Profile, preferences and saved places.
  Client: RiderProfileServiceClient (home_view_remote_data_source.dart)

  Background:
    Given I am authenticated as a rider with id "<riderId>"

  @smoke
  Scenario: Get rider profile
    When I call "RiderProfileService/GetRiderProfile" with riderId "<riderId>"
    Then the response status is "OK"
    And the profile contains first name, last name, phone and email

  Scenario: Get another rider's profile is forbidden
    When I call "RiderProfileService/GetRiderProfile" with another rider's id
    Then the response status is "PERMISSION_DENIED"

  Scenario: Update rider profile
    When I call "RiderProfileService/UpdateRiderProfile" with:
      | firstName     | Jane             |
      | lastName      | Doe              |
      | preferredName | JD               |
      | email         | jane@example.com |
    Then the response status is "OK"
    And GetRiderProfile returns the updated values

  Scenario Outline: Update profile validation
    When I call "RiderProfileService/UpdateRiderProfile" with <field> "<value>"
    Then the response status is "INVALID_ARGUMENT"

    Examples:
      | field     | value         |
      | email     | not-an-email  |
      | firstName |               |

  Scenario: Update rider preferences
    When I call "RiderProfileService/UpdateRiderPrefs" with language "es"
    Then the response status is "OK"

  Scenario: Update safety preferences
    When I call "RiderProfileService/UpdateRiderSafetyPrefs" with:
      | wheelchairAssistance | true |
      | verifyRidePin        | true |
    Then the response status is "OK"

  @smoke
  Scenario: Saved place lifecycle
    When I call "RiderProfileService/CreateSavedPlace" with name "Gym" and a valid address with lat/lng
    Then the response status is "OK"
    And the response contains a saved place id
    When I call "RiderProfileService/GetSavedPlace" with that id
    Then the place name is "Gym"
    When I call "RiderProfileService/UpdateSavedPlace" with name "Gym 2"
    Then ListSavedPlaces contains "Gym 2"
    When I call "RiderProfileService/DeleteSavedPlace" with that id
    Then ListSavedPlaces does not contain "Gym 2"

  Scenario: Create saved place without coordinates
    When I call "RiderProfileService/CreateSavedPlace" with name "Gym" and no lat/lng
    Then the response status is "INVALID_ARGUMENT"

  Scenario: Get a non-existent saved place
    When I call "RiderProfileService/GetSavedPlace" with id "does-not-exist"
    Then the response status is "NOT_FOUND"

  Scenario: Payment methods list
    When I call "RiderProfileService/ListPaymentMethods" with riderId "<riderId>"
    Then the response status is "OK"
    And at most one method is marked default
```

03_payment_api.feature

```gherkin
@api @payment
Feature: Payment methods API
  Adyen session and card management.
  Data source: payment_remote_data_source.dart

  Background:
    Given I am authenticated as a rider with id "<riderId>"

  Scenario: Create Adyen payment session
    When I call "CreateAdyenPaymentSession" with riderId "<riderId>"
    Then the response status is "OK"
    And the response contains a session id and session data
    And the call completes within 30 seconds

  Scenario: List payment methods for new rider
    Given the rider has no saved cards
    When I call "ListPaymentMethods"
    Then the response contains an empty list

  @smoke
  Scenario: Set default payment method
    Given the rider has two saved cards "A" and "B" with "A" default
    When I call "SetDefaultPaymentMethod" with paymentMethodId of "B"
    Then the response status is "OK"
    And ListPaymentMethods shows "B" as default and "A" not default

  Scenario: Set default with unknown card
    When I call "SetDefaultPaymentMethod" with paymentMethodId "unknown"
    Then the response status is "NOT_FOUND"

  Scenario: Delete payment method
    Given the rider has a saved card "A"
    When I call "DeletePaymentMethod" with paymentMethodId of "A"
    Then the response status is "OK"
    And ListPaymentMethods does not contain "A"

  Scenario: Delete another rider's card
    When I call "DeletePaymentMethod" with a card owned by another rider
    Then the response status is "PERMISSION_DENIED"
```

04_ride_service.feature

```
@api @ride
Feature: RideService API
  Ride quotes, scheduling and nearby drivers.
  Client: RideServiceClient (ride_remote_data_source.dart, nearby_drivers_isolate_worker.dart)

  Background:
    Given I am authenticated as a rider with a default payment method

  @smoke
  Scenario: Find ride options for a valid route
    When I call "RideService/FindRide" with:
      | pickup  | 43.6453,-79.3806 |
      | dropoff | 43.6629,-79.3957 |
    Then the response status is "OK"
    And the response contains at least one ride service
    And each ride service has a fare estimate and pickup ETA

  Scenario: Find ride with pickup outside service area
    When I call "RideService/FindRide" with pickup outside the service area
    Then the response status is "FAILED_PRECONDITION" or "OUT_OF_RANGE"

  Scenario: Find ride with no drivable route
    When I call "RideService/FindRide" with a dropoff unreachable by road
    Then the response status is "NOT_FOUND"

  Scenario: Find ride with multiple stops
    When I call "RideService/FindRide" with 2 intermediate stops
    Then the fare estimate includes all stops

  Scenario: Schedule a ride
    When I call "RideService/ScheduleRide" with a pickup time 2 hours from now
    Then the response status is "OK"
    And the response contains a scheduled trip id

  Scenario Outline: Schedule ride with invalid time
    When I call "RideService/ScheduleRide" with a pickup time <time>
    Then the response status is "INVALID_ARGUMENT"

    Examples:
      | time                  |
      | 5 minutes from now    |
      | 8 days from now       |
      | 1 hour in the past    |

  Scenario: Find nearby drivers
    When I call "RideService/FindNearbyDrivers" with my current location
    Then the response status is "OK"
    And each driver has a location and a heading
```

05_trip_service.feature

```
@api @trip
Feature: TripService API
  Trip lifecycle, live streaming, tips and ratings.
  Client: TripServiceClient (trip_feature_remote_data_source.dart, trip stream isolate)

  Background:
    Given I am authenticated as a rider with a default payment method
    And a ride quote exists for a valid route

  @smoke
  Scenario: Create a trip
    When I call "TripService/CreateTrip" with the selected ride service
    Then the response status is "OK"
    And the trip status is "SEARCHING" or equivalent

  Scenario: Create a trip while another trip is active
    Given I already have an active trip
    When I call "TripService/CreateTrip"
    Then the response status is "ALREADY_EXISTS" or "FAILED_PRECONDITION"

  Scenario: Get active trip
    Given I have an active trip
    When I call "TripService/GetActiveTrip"
    Then the response contains that trip id

  Scenario: Get active trip when none
    Given I have no active trip
    When I call "TripService/GetActiveTrip"
    Then the response contains no trip or status "NOT_FOUND"

  @smoke
  Scenario: Stream trip updates
    Given I have an active trip
    When I open the "TripService/StreamTrip" server stream
    And the driver accepts, arrives, starts and completes the trip
    Then I receive status updates in order:
      | DRIVER_ASSIGNED |
      | ARRIVING        |
      | ARRIVED         |
      | IN_PROGRESS     |
      | COMPLETED       |
    And the stream closes after completion

  Scenario: Stream reconnects after network drop
    Given I am streaming an active trip
    When the connection drops for 10 seconds
    Then the client reconnects within the TripStreamLimits retry budget
    And the latest trip status is delivered

  Scenario Outline: Cancel a trip
    Given I have an active trip in status "<status>"
    When I call "TripService/CancelTrip" with reason "<reason>"
    Then the response status is "OK"
    And the trip status becomes "CANCELED"
    And the cancellation fee is "<fee>"

    Examples:
      | status          | reason             | fee        |
      | SEARCHING       | RIDE_NOT_NEEDED    | none       |
      | DRIVER_ASSIGNED | WAIT_TOO_LONG      | per policy |

  Scenario: Cancel a completed trip
    Given I have a completed trip
    When I call "TripService/CancelTrip"
    Then the response status is "FAILED_PRECONDITION"

  Scenario: Add and remove a stop
    Given I have a trip in progress
    When I call "TripService/AddStop" with a valid location
    Then the trip has 1 stop
    When I call "TripService/RemoveStop" for that stop
    Then the trip has 0 stops
```

```gherkin
Scenario: Change destination
  Given I have a trip in progress
  When I call "TripService/ChangeDestination" with a new dropoff
  Then the response status is "OK"
  And the fare estimate is recalculated

Scenario: Update trip
  Given I have an active trip
  When I call "TripService/UpdateTrip" with new pickup notes
  Then the response status is "OK"

Scenario: Trip state transitions (driver side, test harness)
  Given I have a trip with an assigned driver
  When the driver calls "MarkArriving", "MarkArrived", "StartTrip" and "CompleteTrip" in order
  Then each call returns "OK"
  And out-of-order transitions return "FAILED_PRECONDITION"

Scenario: End trip early
  Given I have a trip in progress
  When I call "TripService/EndTripEarly"
  Then the trip status becomes "COMPLETED"

Scenario: Report no-show
  Given the driver has arrived and the rider did not show up
  When "TripService/ReportNoShow" is called
  Then the trip status becomes "CANCELED"

@smoke
Scenario: Submit rating
  Given I have a completed trip
  When I call "TripService/SubmitRating" with 5 stars and compliment "DROVE_SAFELY"
  Then the response status is "OK"
  And GetTrip shows my rating as 5

Scenario Outline: Rating validation
  Given I have a completed trip
  When I call "TripService/SubmitRating" with <stars> stars
  Then the response status is "INVALID_ARGUMENT"

  Examples:
    | stars |
    | 0     |
    | 6     |

Scenario Outline: Add tip
  Given I have a completed trip
  When I call "TripService/AddTip" with amount <amount>
  Then the response status is "<status>"

  Examples:
    | amount | status           |
    | 5.00   | OK               |
    | 100.00 | OK               |
    | 150.00 | INVALID_ARGUMENT |
    | -1.00  | INVALID_ARGUMENT |

Scenario: List past trips
  Given I have completed and canceled trips
  When I call "TripService/ListTrips"
  Then the response contains both completed and canceled trips
  And trips are ordered newest first

Scenario: Get trip receipt
  Given I have a completed trip
  When I call "TripService/GetTrip" with that trip id
  Then the response contains fare breakdown, fees, tax and total

Scenario: Get another rider's trip
  When I call "TripService/GetTrip" with a trip id owned by another rider
  Then the response status is "PERMISSION_DENIED" or "NOT_FOUND"
```

06_neighbour_rider_service.feature

```
@api @co-commute
Feature: NeighbourRiderService API (Co-Commute)
  Client: NeighbourRiderServiceClient (co_commute_feature_remote_data_source.dart)

  Background:
    Given I am authenticated as a rider with a default payment method

  @smoke
  Scenario: Search neighbour trips
    When I call "NeighbourRiderService/SearchNeighbourTrips" with my location
    Then the response status is "OK"
    And each journey has leave time, seats left and price

  Scenario: Get neighbour trip
    Given a neighbour journey exists
    When I call "NeighbourRiderService/GetNeighbourTrip" with its id
    Then the response contains driver, route and seats

  Scenario: Get platform fee
    When I call "NeighbourRiderService/GetNeighbourPlatformFee"
    Then the response contains the held fee amount

  @smoke
  Scenario: Book a seat
    Given a neighbour journey with 2 seats left
    When I call "NeighbourRiderService/BookNeighbourSeat"
    Then the response status is "OK"
    And the booking status is "PENDING_APPROVAL" or "CONFIRMED"
    And the platform fee is held, not captured
    And the journey has 1 seat left

  Scenario: Book a full journey
    Given a neighbour journey with 0 seats left
    When I call "NeighbourRiderService/BookNeighbourSeat"
    Then the response status is "FAILED_PRECONDITION" or "RESOURCE_EXHAUSTED"

  Scenario: Concurrent booking of the last seat
    Given a neighbour journey with 1 seat left
    When two riders call "BookNeighbourSeat" at the same time
    Then exactly one booking succeeds
    And the other fails with a "seat taken" error

  Scenario: Book with declined card
    Given my default card will be declined
    When I call "NeighbourRiderService/BookNeighbourSeat"
    Then the response indicates a declined payment
    And no booking is created

  Scenario: Cancel a booking
    Given I have a confirmed neighbour booking
    When I call "NeighbourRiderService/CancelNeighbourBooking"
    Then the booking status becomes "CANCELED"
    And the held fee is released

  Scenario: List my bookings
    Given I have 2 neighbour bookings
    When I call "NeighbourRiderService/ListMyNeighbourBookings"
    Then the response contains 2 bookings

  Scenario: Post a commute request
    When I call "NeighbourRiderService/PostNeighbourRequest" with pickup, dropoff, leave time and seats 1
    Then the response status is "OK"
    And the request status is "OPEN"

  Scenario: Post a commute request without leave time
    When I call "NeighbourRiderService/PostNeighbourRequest" without leave time
    Then the response status is "INVALID_ARGUMENT"

  Scenario: Cancel a commute request
    Given I have an open commute request
    When I call "NeighbourRiderService/CancelNeighbourRequest"
    Then the request status becomes "CANCELED"
```

```
    And ListMyNeighbourRequests shows it as canceled
```

07_wallet_referral_service.feature

```
@api @wallet @referral
Feature: WalletService and ReferralService API
  Clients: WalletServiceClient, ReferralServiceClient

  Background:
    Given I am authenticated as a rider with id "<riderId>"

  Scenario: Get wallet
    When I call "WalletService/GetWallet" with userId "<riderId>"
    Then the response status is "OK"
    And the response contains available, pending and locked balances

  Scenario: Get another user's wallet
    When I call "WalletService/GetWallet" with another user's id
    Then the response status is "PERMISSION_DENIED"

  @smoke
  Scenario: Get referral profile
    When I call "ReferralService/GetReferralProfile"
    Then the response contains my referral code and invite link

  Scenario: Redeem a valid referral code
    Given another rider has referral code "FRIEND5"
    When I call "ReferralService/RedeemReferral" with code "FRIEND5"
    Then the response status is "OK"

  Scenario Outline: Redeem invalid referral codes
    When I call "ReferralService/RedeemReferral" with code "<code>"
    Then the response status is "<status>"

    Examples:
      | code           | status              |
      |                | INVALID_ARGUMENT    |
      | NOPE000        | NOT_FOUND           |
      | <my own code>  | FAILED_PRECONDITION |

  Scenario: Redeem twice
    Given I already redeemed a referral code
    When I call "ReferralService/RedeemReferral" again
    Then the response status is "ALREADY_EXISTS" or "FAILED_PRECONDITION"

  Scenario: List referral rewards
    When I call "ReferralService/ListReferralReward"
    Then each reward shows rides completed out of total and amount
```

08_notification_activity_service.feature

```
@api @notifications
Feature: Notification, Inbox, Activity and Masked Calling APIs
  Clients: NotificationSettingsServiceClient, InboxServiceClient,
  ActivityServiceClient, MaskedCallingServiceClient

  Background:
    Given I am authenticated as a rider

  Scenario: Register device token
    When I call "NotificationSettingsService/RegisterDeviceToken" with a valid FCM token and platform
    Then the response status is "OK"

  Scenario: Unregister device token on logout
    Given my device token is registered
    When I call "NotificationSettingsService/UnregisterDeviceToken"
    Then the response status is "OK"

  Scenario: Get notification preferences
    When I call "NotificationSettingsService/GetNotificationPrefs"
    Then the response contains receipts, promotions and partner offer settings

  Scenario: List notifications
    When I call "InboxService/ListNotifications"
    Then the response status is "OK"
    And notifications are ordered newest first

  Scenario: Get a notification
    Given I have a notification
    When I call "InboxService/GetNotification" with its id
    Then the response contains its title and body

  Scenario: List broadcasts
    When I call "InboxService/ListBroadcasts"
    Then the response status is "OK"

  Scenario: List activity
    When I call "ActivityService/ListActivity"
    Then the response status is "OK"

  Scenario: Set up masked call mapping
    Given I have an active trip with an assigned driver
    When I call "MaskedCallingService/SetupMapping"
    Then the response contains a proxy phone number

  Scenario: Make masked call without active trip
    Given I have no active trip
    When I call "MaskedCallingService/MakeMaskedCall"
    Then the response status is "FAILED_PRECONDITION"
```

09_helpdesk_api.feature

```
@api @helpdesk
Feature: Helpdesk ticket API
  Repository: hovr_helpdesk_repository.dart

  Background:
    Given I am authenticated as a rider

  Scenario: List open tickets
    When I call "ListOpenTickets"
    Then the response status is "OK"

  @smoke
  Scenario: Create a ticket
    When I call "CreateTicket" with:
      | subject     | Driver didn't arrive                  |
      | description | Waited 20 minutes, driver never came. |
    Then the response contains a ticket id
    And ListOpenTickets contains that ticket

  Scenario Outline: Create ticket validation
    When I call "CreateTicket" with subject "<subject>" and description "<description>"
    Then the response status is "INVALID_ARGUMENT"

    Examples:
      | subject | description          |
      |         | Some detail here ok  |
      | Driver  |                      |

  Scenario: Reply to a ticket
    Given I have an open ticket
    When I call "TicketArticle" to add a reply "Any update?"
    Then ListTicketArticles for that ticket contains "Any update?"

  Scenario: Read someone else's ticket
    When I call "ListTicketArticles" for a ticket owned by another rider
    Then the response status is "PERMISSION_DENIED" or "NOT_FOUND"
```