

DevOps lab Program 3:

Dockerfile:



A terminal window titled "1RV24MC075_Pragathi_h_r@dell: ~/DevOps/prg3" showing a Dockerfile being edited in nano 6.2. The Dockerfile content is as follows:

```
FROM python:latest
WORKDIR /app
COPY requirements.txt requirements.txt
RUN pip install --no-cache-dir -r requirements.txt
COPY . .
EXPOSE 5000
CMD ["python", "app.py"]
```

The bottom status bar of the nano editor shows various keyboard shortcuts: ^G Help, ^X Exit, ^O Write Out, ^R Read File, ^W Where Is, ^\ Replace, ^K Cut, ^U Paste, [Read 11 lines], ^T Execute, ^J Justify, ^C Location, ^_ Go To Line, M-U Undo, M-E Redo, M-A Set Mark, and M-6 Copy.

requirements.txt



A terminal window titled "1RV24MC075_Pragathi_h_r@dell: ~/DevOps/prg3" showing requirements.txt being edited in nano 6.2. The file content is:

```
flask==2.3.3
```

The bottom status bar of the nano editor shows various keyboard shortcuts: ^G Help, ^X Exit, ^O Write Out, ^R Read File, ^W Where Is, ^\ Replace, ^K Cut, ^U Paste, [Read 1 line], ^T Execute, ^J Justify, ^C Location, ^_ Go To Line, M-U Undo, M-E Redo, M-A Set Mark, and M-6 Copy.

app.py

```
1RV24MC075_Pragathi_h_r@dell: ~/DevOps/prg3
GNU nano 6.2 app.py
from flask import Flask
app = Flask(__name__)

@app.route("/")
def home():
    return "Hello from Flask in Docker!"

if __name__ == "__main__":
    app.run(host="0.0.0.0", port=5000)

[ Read 9 lines ]
^G Help      ^O Write Out  ^W Where Is   ^K Cut        ^T Execute    ^C Location   M-U Undo     M-A Set Mark
^X Exit      ^R Read File  ^\ Replace    ^U Paste      ^J Justify    ^/_ Go To Line M-E Redo     M-6 Copy
```

```
1RV24MC075_Pragathi_h_r@dell: ~/DevOps/prg3
1RV24MC075_Pragathi_h_r@dell:~$ cd DevOps
1RV24MC075_Pragathi_h_r@dell:~/DevOps$ cd prg3
1RV24MC075_Pragathi_h_r@dell:~/DevOps/prg3$ nano Dockerfile
1RV24MC075_Pragathi_h_r@dell:~/DevOps/prg3$ nano requirements.txt
1RV24MC075_Pragathi_h_r@dell:~/DevOps/prg3$ nano app.py
1RV24MC075_Pragathi_h_r@dell:~/DevOps/prg3$ docker build -t flask-app .
[+] Building 2.9s (10/10) FINISHED
=> [internal] load build definition from Dockerfile                                docker:default
=> => transferring dockerfile: 211B                                              0.0s
=> [internal] load metadata for docker.io/library/python:latest                  2.7s
=> [internal] load .dockerignore                                                 0.0s
=> => transferring context: 2B                                                    0.0s
=> [1/5] FROM docker.io/library/python:latest@sha256:97aa8cc0b87a4a312a294d2d4d7b20f6e2a21ed6d4e64ef08c03088c4aa9890f 0.0s
=> => resolve docker.io/library/python:latest@sha256:97aa8cc0b87a4a312a294d2d4d7b20f6e2a21ed6d4e64ef08c03088c4aa9890f 0.0s
=> [internal] load build context                                                0.0s
=> => transferring context: 93B                                                  0.0s
=> CACHED [2/5] WORKDIR /app                                                    0.0s
=> CACHED [3/5] COPY requirements.txt requirements.txt                          0.0s
=> CACHED [4/5] RUN pip install --no-cache-dir -r requirements.txt              0.0s
=> CACHED [5/5] COPY . .                                                        0.0s
=> exporting to image                                                            0.0s
=> => exporting layers                                                            0.0s
=> => writing image sha256:db6984869f36f28aa32e96ff3cf803fed7636659925fdb04206bd03baefeb0ae 0.0s
=> => naming to docker.io/library/flask-app                                     0.0s
1RV24MC075_Pragathi_h_r@dell:~/DevOps/prg3$ docker run -p 5000:5000 flask-app
* Serving Flask app 'app'
* Debug mode: off
WARNING: This is a development server. Do not use it in a production deployment. Use a production WSGI server instead.
* Running on all addresses (0.0.0.0)
* Running on http://127.0.0.1:5000
* Running on http://172.18.0.2:5000
Press CTRL+C to quit
```

Output:

