

Program-9/

├── namespaces.yaml

└── pods.yaml

Step 1: namespaces.yaml

```
apiVersion: v1
kind: Namespace
metadata:
  name: dev
```

```
apiVersion: v1
kind: Namespace
metadata:
  name: prod
```

Step 2: pods.yaml

```
apiVersion: v1
kind: Pod
metadata:
  name: frontend-pod
  namespace: dev
  labels:
    app: frontend
    env: dev
```

```
spec:
  containers:
  - name: frontend
    image: nginx
    ports:
    - containerPort: 80
```

```
apiVersion: v1
kind: Pod
metadata:
  name: backend-pod
  namespace: dev
  labels:
    app: backend
    env: dev
```

```
spec:
  containers:
  - name: backend
    image: nginx
    ports:
    - containerPort: 80
```

```
---
apiVersion: v1
kind: Pod
metadata:
  name: frontend-pod
  namespace: prod
  labels:
    app: frontend
    env: prod
spec:
  containers:
  - name: frontend
    image: nginx
    ports:
    - containerPort: 80
```

```
---
apiVersion: v1
kind: Pod
metadata:
  name: backend-pod
  namespace: prod
  labels:
    app: backend
    env: prod
spec:
  containers:
  - name: backend
    image: nginx
    ports:
    - containerPort: 80
```

Step 3: Apply YAML files

```
kubectl apply -f namespaces.yaml
kubectl apply -f pods.yaml
```

step 4: Verify Pods by Namespace

```
kubectl get pods -n dev
kubectl get pods -n prod
```

Step 5: Filter Pods by Label

List frontend pods in dev

```
kubectl get pods -n dev -l app=frontend
```

List backend pods in prod

```
kubectl get pods -n prod -l app=backend
```

output

```
~/Desktop/Home/RV/devOps/program9 -- ~/D/H/R/d/program9 -- fish  ~/Desktop/Home/RV/devOps/program9 -- minikube dashboard ~/D/H/R/d/program9 -- kubectl - minikube dashboard +

srikanths@Srikanths-MacBook-Air ~/D/H/R/d/program9> kubectl get pods -n dev
NAME          READY   STATUS    RESTARTS   AGE
backend-pod   1/1     Running   0           69s
frontend-pod  1/1     Running   0           69s
srikanths@Srikanths-MacBook-Air ~/D/H/R/d/program9> kubectl get pods -n prod
NAME          READY   STATUS    RESTARTS   AGE
backend-pod   1/1     Running   0           74s
frontend-pod  1/1     Running   0           74s
srikanths@Srikanths-MacBook-Air ~/D/H/R/d/program9> kubectl get pods -n dev -l app=frontend
NAME          READY   STATUS    RESTARTS   AGE
frontend-pod  1/1     Running   0           83s
srikanths@Srikanths-MacBook-Air ~/D/H/R/d/program9> kubectl get pods -n dev -l app=backend
NAME          READY   STATUS    RESTARTS   AGE
backend-pod   1/1     Running   0           88s
srikanths@Srikanths-MacBook-Air ~/D/H/R/d/program9> █

I
```