

Program8: Create kubernetes pods using yaml Descriptions

Step1: Create a [server.js](#)

```
const http = require('http');
const PORT = 3000;
const server = http.createServer((req, res) => {
  res.end('Hello from Node.js server running behind Nginx!\n');
});

server.listen(PORT, () => {
  console.log(`Server is running on port ${PORT}`);
});
```

Step2: create a Configmap for code

```
apiVersion: v1
kind: ConfigMap
metadata:
  name: nginx-config
Data:
  server.js: |
Const http= require("http");
Const port = 3000;
Const server = http.createServer((req,res) => {
res.send("Hello from node.js running inside kubernetes");
});
```

Step3: create the Pod yaml using [node.js](#) as base image.

```
apiVersion: apps/v1
kind: Deployment
Metadata:
  name: nginx-deployment
labels:
  app: nginx
spec:
  replicas: 3
selector:
  matchLabels:
    app: nginx
  template:
    metadata:
      labels:
        app: nginx
    spec:
      containers:
        - name: nginx
          image: nginx:latest
```

ports:
- containerPort: 80

Step4: Apply the yaml files

Kubectl apply -f nodejs-configmap.yaml

Kubectl apply -f nodejs-pod.yaml

Step5: Check status

Kubectl get pods

Step6: expose as service

Kubectl port-forward pod/nodejs-pod 3000:3000



