

## MergeSort Part 2 Quiz

Score: \_\_\_\_\_

1. `al = [1, 2, 3, 4]`What is the result of `al[:2]`?

- ☐ A [1, 2]
- ☐ B [1, 2, 3]
- ☐ C [] (list with no elements)
- ☐ D None of the above

2. If `al = [1, 2, 3, 4]`, then `al[2:]` is equal to

- ☐ A [2, 1]
- ☐ B [3, 4]
- ☐ C [2, 3, 4]
- ☐ D [2]
- ☐ E None of the above

3. The value of `mid` in the given code snippet is

- ☐ A 0
- ☐ B 1
- ☐ C 2
- ☐ D 1.5

```
2 al = [1, 2, 3, 4]
3 mid = len(al) // 2
4 newlist = al[:mid] + al[mid:]
5 assert newlist == al
```

4. If you replace Line 3 with `mid = int(len(al)/2)`, the value of `mid` will remain the same.

- ☐ A True
- ☐ B False

```
2 al = [1, 2, 3, 4]
3 mid = len(al) // 2
4 newlist = al[:mid] + al[mid:]
5 assert newlist == al
```

5. `newlist` will *not* contain the same number of elements as `al`.

- ☐ A True
- ☐ B False

```
2 al = [1, 2, 3, 4]
3 mid = len(al) // 2
4 newlist = al[:mid] + al[mid:]
5 assert newlist == al
```

6. The assertion in Line 5 will not produce an error.

- ☐ A True
- ☐ B False

```
2 al = [1, 2, 3, 4]
3 mid = len(al) // 2
4 newlist = al[:mid] + al[mid:]
5 assert newlist == al
```

7. Line number 14 will produce what output?

- ☐ A [1, 2], [1, 2]
- ☐ B [1, 2], [4, 5]
- ☐ C [1, 2], [3, 4, 5]
- ☐ D None of the above

```
11 al = [1, 2, 3, 4, 5]
12 mid = len(al) // 2
13 left, right = al[:mid], al[mid:]
14 print(left, right)
```

8. The list `al` is an example of nested list. It has a length of

- ☐ A 5
- ☐ B 2
- ☐ C 1
- ☐ D 4

```
al = [1, [2, [3, [4, [5, None]]]]]
```

9. The `printRec` is a valid recursive function and it has one terminal case.

- ☐ A True
- ☐ B False

```
13 al = [1, [2, [3, [4, [5, None]]]]]
14 def printRec (alist):
15     if not alist[1]:
16         print(alist[0], end=".\\n")
17         return
18
19     print(alist[0], end=" ", " ")
20     printRec(alist[1])
21
22 printRec(al)
```

10. The line number 22 will produce what output?

- ☐ A 1, 2, 3, 4, 5.
- ☐ B 5, 4, 3, 2, 1.
- ☐ C None of the above.

```
13 al = [1, [2, [3, [4, [5, None]]]]]
14 def printRec (alist):
15     if not alist[1]:
16         print(alist[0], end=".\\n")
17         return
18
19     print(alist[0], end=" ", " ")
20     printRec(alist[1])
21
22 printRec(al)
```

11. The `sum` function is

- ☐ A a **recursive** function but not a fruitful function
- ☐ B a **recursive** and **fruitful** function
- ☐ C non-recursive function
- ☐ D none of the above

```
16 def sum(alist):
17     if not alist:
18         return 0
19     if len(alist) == 1:
20         return alist[0]
21
22     remaining = alist[1:]
23     return alist[0] + sum(remaining)
24
25 print(sum([1, 2, 3, 4, 5]))
```

12. The `sum` function has one terminal case.

- ☐ A True
- ☐ B False

```
16 def sum(alist):
17     if not alist:
18         return 0
19     if len(alist) == 1:
20         return alist[0]
21
22     remaining = alist[1:]
23     return alist[0] + sum(remaining)
24
25 print(sum([1, 2, 3, 4, 5]))
```

13. The output from Line 48 will be [5, 4, 3, 2, 1, 0]

- ☐ A True
- ☐ B False

```
27 def merge(A, B):
28     return [
29         (A if A[0] < B[0] else B).pop(0)
30         for _ in A+B if A and B
31     ] + A + B
32
33 def some_func(ulist):
34     if len(ulist) < 2:
35         return ulist
36
37     mid = len(ulist)//2
38     left = ulist[:mid]
39     right = ulist[mid:]
40
41     sorted_left = some_func(left)
42     sorted_right = some_func(right)
43     print(sorted_left, sorted_right)
44
45     slist = merge(sorted_left, sorted_right)
46     return slist
47
48 print(some_func([5, 0, 2, 1, 3, 4]))
```

14. The recursive `some_func` has only one terminal case.

- ☐ A True
- ☐ B False

```
27 def merge(A, B):
28     return [
29         (A if A[0] < B[0] else B).pop(0)
30         for _ in A+B if A and B
31     ] + A + B
32
33 def some_func(ulist):
34     if len(ulist) < 2:
35         return ulist
36
37     mid = len(ulist)//2
38     left = ulist[:mid]
39     right = ulist[mid:]
40
41     sorted_left = some_func(left)
42     sorted_right = some_func(right)
43     print(sorted_left, sorted_right)
44
45     slist = merge(sorted_left, sorted_right)
46     return slist
47
48 print(some_func([5, 0, 2, 1, 3, 4]))
```

15. The intermediary output caused by Line 43 will be as shown here.

- ☐ A True
- ☐ B False

```
[0] [2]
[5] [0, 2]
[3] [4]
[1] [3, 4]
[0, 2, 5] [1, 3, 4]
```

16. The most appropriate name that can replace `some_func()` is

- ☐ A `insertion_sort`
- ☐ B `selection_sort`
- ☐ C `merge_sort`
- ☐ D `histogram`

```
27 def merge(A, B):
28     return [
29         (A if A[0] < B[0] else B).pop(0)
30         for _ in A+B if A and B
31     ] + A + B
32
33 def some_func(ulist):
34     if len(ulist) < 2:
35         return ulist
36
37     mid = len(ulist)//2
38     left = ulist[:mid]
39     right = ulist[mid:]
40
41     sorted_left = some_func(left)
42     sorted_right = some_func(right)
43     print(sorted_left, sorted_right)
44
45     slist = merge(sorted_left, sorted_right)
46     return slist
47
48 print(some_func([5, 0, 2, 1, 3, 4]))
```

17. Assume `al = [2, 1, 4, 3, 6, 5, 8, 7]` and we want to mergesort it. After the first conquer step, we will have `[1, 2]`, `[3, 4]`, and `[5, 6]`, `[7, 8]`.

On visual examination, it is obvious all that needs to be done is merge the sublists to get the sorted list.

This illustrative example can be a source for inspiration to improve the **merge algorithm** so that it can be very efficient when dealing with almost sorted lists. What will you do?

---

---

---

18. Modify the **mergesort** algorithm to eliminate duplicate elements during the process of sorting.

If `al = [4, 5, 6, 1, 2, 1, 2, 3]`, then after the sorting is complete the result must be `al = [1, 2, 3, 4, 5, 6]`.

---

---

---