

PIZZA SALES SQL QUERIES

A. KPI's

1. Total Revenue:

```
SELECT SUM(total_price) AS Total_Revenue FROM pizza_sales;
```

Results		Messages	
		Total_Revenue	
1		817860.05083847	

2. Average Order Value

```
SELECT (SUM(total_price) / COUNT(DISTINCT order_id)) AS Avg_order_Value  
FROM pizza_sales
```

Results		Messages	
		Avg_Order_Value	
1		38.3072623343546	

3. Total Pizzas Sold

```
SELECT SUM(quantity) AS Total_pizza_sold FROM pizza_sales
```

Results		Messages	
		Total_Pizzas_Sold	
1		49574	

4. Total Orders

```
SELECT COUNT(DISTINCT order_id) AS Total_Orders FROM pizza_sales
```

Results		Messages	
		Total_Orders	
1		21350	

5. Average Pizzas Per Order

```
SELECT CAST(CAST(SUM(quantity) AS DECIMAL(10,2)) /  
CAST(COUNT(DISTINCT order_id) AS DECIMAL(10,2)) AS DECIMAL(10,2))  
AS Avg_Pizzas_per_order  
FROM pizza_sales
```

Results		Messages	
		Avg_Pizzas_Per_Order	
1		2.32	

B. Daily Trend for Total Orders

```
SELECT DATENAME(DW, order_date) AS order_day, COUNT(DISTINCT order_id) AS  
total_orders
```

```
FROM pizza_sales
GROUP BY DATENAME(DW, order_date)
```

Output:

	Order_Day	Total_Orders
1	Saturday	2624
2	Wednesday	3239
3	Monday	2973
4	Sunday	2794
5	Friday	3158
6	Thursday	3538
7	Tuesday	3024

C. Hourly Trend for Orders

```
SELECT DATEPART(HOUR, order_time) as order_hours, COUNT(DISTINCT order_id)
as total_orders
from pizza_sales
group by DATEPART(HOUR, order_time)
order by DATEPART(HOUR, order_time)
```

Output

	Order_Hour	Total_Orders
1	9	1
2	10	8
3	11	1231
4	12	2520
5	13	2455
6	14	1472
7	15	1468
8	16	1920
9	17	2336
10	18	2399
11	19	2009
12	20	1642
13	21	1198
14	22	663
15	23	28

D. % of Sales by Pizza Category

```
SELECT pizza_category, CAST(SUM(total_price) AS DECIMAL(10,2)) as
total_revenue,
CAST(SUM(total_price) * 100 / (SELECT SUM(total_price) from pizza_sales)
AS DECIMAL(10,2)) AS PCT
FROM pizza_sales
GROUP BY pizza_category
```

Output

	pizza_category	Total_Revenue	Sales_Percentage
1	Classic	220053.10	26.91
2	Chicken	195919.50	23.96
3	Veggie	193690.45	23.68
4	Supreme	208197.00	25.46

E. % of Sales by Pizza Size

```
SELECT pizza_size, CAST(SUM(total_price) AS DECIMAL(10,2)) as
total_revenue,
CAST(SUM(total_price) * 100 / (SELECT SUM(total_price) from pizza_sales)
AS DECIMAL(10,2)) AS PCT
FROM pizza_sales
GROUP BY pizza_size
ORDER BY pizza_size
```

Output

	pizza_size	Total_Revenue	Sales_Percentage
1	L	375318.70	45.89
2	M	249382.25	30.49
3	S	178076.50	21.77
4	XL	14076.00	1.72
5	XXL	1006.60	0.12

F. Total Pizzas Sold by Pizza Category

```
SELECT pizza_category, SUM(quantity) as Total_Quantity_Sold
FROM pizza_sales
WHERE MONTH(order_date) = 2
GROUP BY pizza_category
ORDER BY Total_Quantity_Sold DESC
```

Output

	pizza_category	Total_Quantity_Sold
1	Classic	1178
2	Supreme	964
3	Veggie	944
4	Chicken	875

G. Top 5 Best Sellers by Total Pizzas Sold

```
SELECT Top 5 pizza_name, SUM(quantity) AS Total_Pizza_Sold
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Pizza_Sold DESC
```

Output

Results Messages		
	pizza_name	Total_Pizzas_Sold
1	The Classic Deluxe Pizza	2453
2	The Barbecue Chicken Pizza	2432
3	The Hawaiian Pizza	2422
4	The Pepperoni Pizza	2418
5	The Thai Chicken Pizza	2371

H. Bottom 5 Best Sellers by Total Pizzas Sold

```
SELECT TOP 5 pizza_name, SUM(quantity) AS Total_Pizza_Sold
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Pizza_Sold ASC
```

Output

Results Messages		
	pizza_name	Total_Pizzas_Sold
1	The Brie Carre Pizza	490
2	The Mediterranean Pizza	934
3	The Calabrese Pizza	937
4	The Spinach Supreme Pizza	950
5	The Soppresata Pizza	961

NOTE

If you want to apply the Month, Quarter, Week filters to the above queries you can use WHERE clause. Follow some of below examples

```
SELECT DATENAME(DW, order_date) AS order_day, COUNT(DISTINCT order_id) AS total_orders
FROM pizza_sales
WHERE MONTH(order_date) = 1
GROUP BY DATENAME(DW, order_date)
```

	Order_Day	Total_Orders
1	Friday	303
2	Monday	242
3	Saturday	199
4	Sunday	220
5	Thursday	330
6	Tuesday	222
7	Wednesday	329

**Here MONTH(order_date) = 1 indicates that the output is for the month of January. MONTH(order_date) = 4 indicates output for Month of April.*

```
SELECT DATENAME(DW, order_date) AS order_day, COUNT(DISTINCT order_id) AS total_orders
FROM pizza_sales
WHERE DATEPART(QUARTER, order_date) = 1
GROUP BY DATENAME(DW, order_date)
```

	Order_Day	Total_Orders
1	Saturday	682
2	Wednesday	796
3	Monday	787
4	Sunday	743
5	Friday	766
6	Thursday	885
7	Tuesday	711

**Here DATEPART(QUARTER, order_date) = 1 indicates that the output is for the Quarter 1. MONTH(order_date) = 3 indicates output for Quarter 3.*