01 — Upload & intake

What it does: accepts one PDF at a time into a case, validates it, stores the original immutably, records its hash, and fans out the automated pipeline. It detects nothing itself; it is the chain-of-custody starting point.

Code: `api/documents.py` (`upload_document`), `services/upload_validation.py` , `services/storage_service.py` , `services/usage_service.py` , `models/document.py` , frontend `pages/NewCasePage.tsx` + `components/upload/FileDropzone.tsx` + `lib/uploadLimits.ts` .

Flow

1. The UI creates the case (`POST /cases`), then uploads each selected file with its own `POST /cases/{case_id}/documents` (multipart field `file`) using `XMLHttpRequest` for progress. Files upload in parallel; a failed file can be retried without recreating the case, dismissed using the remove icon (`[X]`), or discarded completely via `Reset form` which cleanly restores the intake form and unlocks case type selection.
2. The endpoint 404s on an unknown case (or one of another company, or — for a `user` — one they did not submit; platform admins get 403), then **validates the file synchronously** (next section). A rejected file is never stored, never gets a `documents` row or audit event, never counts toward usage and never queues a task, so it costs no worker slot and no Azure call. A valid file's `sha256(content)` is computed.
3. It writes the bytes to Blob Storage at `companies/{company_id}/cases/{case_id}/documents/{document_id}_{sha256}{original_extension}` with `overwrite=False` . The path embeds the hash and the document's own id, so collisions are impossible even if a filename repeats. A storage failure is a **502**.
4. It inserts a `documents` row (`processing_status = pending` , `content_type = application/pdf`) and flushes, writes the audit event `document_uploaded` with `{original_filename, file_hash, file_size_bytes}` , bumps the company's usage counters (`documents_uploaded` , `files_stored` , `storage_bytes`) in the same transaction, and commits.
5. It enqueues six Celery tasks — each as `(document_id, company_id)` with a fair-share priority — and returns **201**:

Task	Queue	Module	Depends on	Notes
`process_document`	`extraction_queue`	`tasks/document_processing.py`	—	OCR + classify + extract, then the font and spelling checks (they need its OCR words); chains into `run_document_checks`
`run_metadata_forensics`	`forensics_queue`	`tasks/metadata_forensics_task.py`	file only	
`run_tampering_checks`	`forensics_queue`	`tasks/tampering_checks_task.py`	file only	ELA + copy-move share one render
`run_duplicate_check_task`	`forensics_queue`	`tasks/duplicate_check_task.py`	file only	compares within the company only
`run_visual_inconsistency_review_task`	`vision_queue`	`tasks/visual_inconsistency_task.py`	file only	also carries the AI-generation question

Task	Queue	Module	Depends on	Notes
`run_signature_detection`	`vision_queue`	`tasks/signature_detection_task.py`	file only	

6. The response contains a fresh signed download URL (if signing fails it falls back to the durable URL; the upload itself has already succeeded).

Afterwards the UI offers an **optional** step to draw a reference signature (see 09).

Upload validation

`services/upload_validation.py`, called before anything is stored. **Only PDF documents are accepted** (decision of 2026-10-03: every forensic check is PDF-based, so an image would only ever get OCR and no tamper analysis). The checks run in this order and the first failure wins. Each rejection returns `detail: {"code", "message", ...}`, and the UI shows `message` as-is next to the file.

#	Check	HTTP	`code`	Message / extra fields
1	0 bytes	400	`file_empty`	"The file is empty (0 bytes)."
2	Over **the company's** per-file limit (`companies.max_file_size_mb`; default **10 MB** = 10,485,760 bytes for a new company)	413	`file_too_large`	States both sizes and the limit in effect for that company, e.g. "The file is 12.0 MB; the maximum allowed size is 10.0 MB."; `size_bytes`, `max_size_bytes`
3	Content is not a PDF, judged by the **header bytes** (`%PDF-`), never the name or declared MIME type	415	`unsupported_file_type`	"This file is a JPEG image. Only PDF files are accepted — please save or scan the document as a PDF." (the type is named when recognised: JPEG, PNG, TIFF, GIF, BMP images, ZIP/Office files)
4	A PDF whose name carries another type's extension (`.png`, `.docx`, …)	415	`file_type_mismatch`	`detected_type`, `extension`
5	The PDF needs a password to open	422	`file_password_protected`	"This file is password-protected. Please remove the password and re-upload."
6	The PDF can't be parsed locally (PyMuPDF)	422	`file_corrupted`	"The file appears to be corrupted or unreadable."

Details:

- **Magic bytes.** `%PDF-` anywhere in the first 1024 bytes (the PDF spec allows junk before the header; Acrobat and MuPDF accept it). An image renamed to `.pdf` is refused as an image.
- **Extensions.** Only a *recognised* file-type extension (images, Office, text, archives, …) is compared with the content. An unrecognised suffix (the ".2026" in "Invoice 12.03.2026") and a name with no extension are accepted on the content alone; `.PDF` in upper case is fine.
- **Parse.** PyMuPDF — the same library the pipeline renders pages with — opens the file and parses every page's content stream. MuPDF silently "repairs" a truncated file, so two cases count as corrupted: a file it repairs into **0**

pages, and a file it had to repair that has **no `%%EOF` marker in its last 1024 bytes** (a cut-off file can otherwise yield a few pages and silently lose the rest). A merely sloppy PDF with wrong cross-reference offsets still ends in `%%EOF` and is accepted. All 38 sample PDFs pass, including the 12 tampered samples (incremental saves).

- **Password policy: reject-and-ask** (🔶 decision, 2026-10-03). The server never asks for or applies a password, so the system never handles other people's document passwords. A PDF with only an **owner** password (print/copy restrictions; it opens without a password) is accepted. To revisit: the alternative is a password field on upload plus server-side decryption.
- **Stored `content_type`** is always `application/pdf` (the detected type), not the browser-declared one.
- The endpoint reads at most limit + 1 bytes into memory and parses in a worker thread, so the event loop isn't blocked. Uvicorn still receives (and spools to a temp file) the *whole* request body before the endpoint runs — cap the request size at the ingress / reverse proxy in production too (production deployment).
- **Per-company limits:** the size limits are not constants. Each company has `max_file_size_mb` and `max_zip_size_mb` on its row (10 / 300 for a new company, from `DEFAULT_MAX_FILE_SIZE_MB` / `DEFAULT_MAX_ZIP_SIZE_MB`), changed only by a platform admin (Platform › Companies › Edit; `PATCH /platform/companies/{id}`, audited as `company_updated` with old → new values; any positive whole number of MB, no upper ceiling). `services/upload_limits.py` is the single source the single-file endpoint, the bulk-zip endpoint and the bulk ingestion task all read, fresh on every request, so a change applies to the company's next upload without a new sign-in.
- **Frontend:** `lib/uploadLimits.ts` refuses files that are not named/typed as PDF, empty files and files over the company's limit before sending (the server check is the one that counts). The limit comes from `GET /auth/me/upload-limits` (`hooks/useUploadLimits.ts`); no size is hardcoded in the frontend. The file picker only offers PDFs and the drop zone states the rules ("PDF only · max file size: 20.0 MB each · not password-protected").
- Tests: `tests/test_upload_validation.py` .

Output shape

`DocumentResponse` (`schemas/document.py`):

```
{
  "id": "uuid", "case_id": "uuid",
  "original_filename": "Invoice.pdf",
  "content_type": "application/pdf",       // detected from the file's header bytes
  "file_size_bytes": 184223,
  "file_hash": "e3b0c4…",                  // SHA-256 hex, 64 chars
  "file_url": "https://…?sv=…&sig=…",      // short-lived SAS URL
  "uploaded_at": "2026-09-20T17:08:40Z",
  "processing_status": "pending"           // pending | processing | complete | failed
}
```

`documents.blob_storage_path` stores the **durable** (unsigned) blob URL. The container is private, so anything that needs the file mints a SAS URL with `StorageService.get_download_url()` (15 min default; 30 min for OCR); `ensure_company_blob()` refuses to sign a path under another company's prefix.

Invariants

- **Originals are write-once.** `StorageService` has `upload()` and `download_bytes()` but no overwrite/delete path. Every later stage only *reads* the original.
- **`file_hash` is the integrity anchor.** It is recomputed and compared when a report is generated (`HashVerification` in the report appendix).

- **Byte-identical re-uploads are not blocked.** `file_hash` is indexed but there is no uniqueness constraint; exact duplicates are caught by the *perceptual* check (10), not at upload.

Known limitations

- No page-count limit and no antivirus scan (type, size, corruption and password checks exist; see above).
- Any company user can create a case, but only its owner or a reviewer of the company can add to it.
- Documents stored before the PDF-only rule may be images; they were OCR'd but no forensic check runs on them, and `pipeline_status` only requires forensic checks for PDFs, so such a case can still be scored.
- One task failing to enqueue (Redis down) after the DB commit leaves a `pending` document that never progresses; there is no sweeper.
- If every file of a new case is rejected, the case itself (created first) remains, with no documents.

Bulk upload

A zip of many cases goes through the same validation and the same store → record → queue code (`services/document_intake.py`), one case at a time. See 01a.

Risk rules fed

None directly. It produces the documents every rule evaluates.