API endpoint reference

FDDT — Fraud Document Detection Tool API · version 0.1.0 · OpenAPI 3.1.0

46 operations across 37 paths and 68 data models. This reference is generated from the API definition itself (docs/api/openapi.json).

Conventions

- **Authentication:** endpoints marked Bearer JWT need the header `Authorization: Bearer <token>`. Obtain a token from `POST /auth/login` (email and password).
- **Roles** (ranked, each includes everything below it): `user` (submitter) < `reviewer_l1` < `reviewer_l2` < `admin`. "Reviewer/admin" means `reviewer_l1` or above. On a case escalated to L2 (`assigned_tier` = `l2`) only `reviewer_l2` and `admin` may approve, reject or escalate; a `reviewer_l1` gets 403 there but can still read the case. Role rules for each endpoint are stated in its description.
- **Errors:** every operation lists its documented error responses. 422 is a request-validation error.
- **Formats:** requests and responses are JSON (file uploads are `multipart/form-data`); identifiers are UUIDs; timestamps are ISO 8601.

Endpoint index

Method	Path	Summary
Health		
GET	`/health`	Liveness check
Authentication		
POST	`/auth/login`	Log in and obtain a JWT
GET	`/auth/me`	Get the current user
GET	`/auth/me/upload-limits`	Get my company's upload limits
Cases		
POST	`/cases`	Create a case
GET	`/cases`	List cases (the case queue)
GET	`/cases/{case_id}`	Get case detail
GET	`/cases/{case_id}/audit-log`	Get a case's activity timeline
Documents		
POST	`/cases/{case_id}/documents`	Upload a document to a case
GET	`/cases/{case_id}/documents/{document_id}/file-url`	Get a fresh signed URL for a document
Case actions (review decisions)		
POST	`/cases/{case_id}/approve`	Approve a case

Method	Path	Summary
POST	`/cases/{case_id}/reject`	Reject a case
POST	`/cases/{case_id}/escalate`	Escalate a case
Signature references & matches		
POST	`/cases/{case_id}/documents/{document_id}/signature-references`	Create a signature reference
GET	`/cases/{case_id}/signature-references`	List a case's signature references
GET	`/cases/{case_id}/signature-matches`	List a case's signature comparison results
Audit log		
GET	`/audit-log`	Search the audit log
GET	`/audit-log/event-types`	List audit event types
Case reports		
POST	`/cases/{case_id}/reports`	Generate a case report (PDF)
GET	`/cases/{case_id}/reports`	List a case's generated reports
Settings (admin)		
GET	`/settings/issuers`	List issuers
POST	`/settings/issuers`	Create an issuer
PATCH	`/settings/issuers/{issuer_id}`	Update or deactivate an issuer
GET	`/settings/risk-rules`	List current risk rules
POST	`/settings/risk-rules`	Create a risk rule
GET	`/settings/risk-rule-options`	Get the options for the Add-rule form
GET	`/settings/risk-rules/{rule_id}/history`	Get a risk rule's version history
PATCH	`/settings/risk-rules/{rule_id}`	Change a risk rule's weight, severity or active flag
GET	`/settings/risk-thresholds`	Get the risk tier thresholds
PUT	`/settings/risk-thresholds`	Set the risk tier thresholds
GET	`/settings/users`	List users
POST	`/settings/users`	Create a user
PATCH	`/settings/users/{user_id}`	Change a user's role, company or active flag
POST	`/settings/users/{user_id}/reset-password`	Reset user password (platform admin only)
Other		
POST	`/bulk-uploads`	Bulk upload: a zip of cases
GET	`/bulk-uploads`	List bulk uploads
GET	`/bulk-uploads/{bulk_upload_id}`	Bulk upload summary (live per-case status)

Method	Path	Summary
GET	`/platform/companies`	List companies
POST	`/platform/companies`	Create a company
PATCH	`/platform/companies/{company_id}`	Rename, suspend/reactivate, or change a company's upload limits
GET	`/platform/risk-rule-templates`	List the platform risk-rule template
POST	`/platform/risk-rule-templates`	Add a rule to the platform template
PATCH	`/platform/risk-rule-templates/{rule_id}`	Edit a platform template rule
GET	`/platform/usage`	Billing & usage by company
POST	`/platform/usage/reconcile`	Reconcile usage counters now
GET	`/platform/queues`	Processing queue monitor

Health

GET `/health`

Liveness check Public

Unauthenticated. Returns `{status: ok, environment}`; does not touch the database, Redis or Azure.

Responses

Status	Description	Body
`200`	Successful Response	map of string

Authentication

POST `/auth/login`

Log in and obtain a JWT Public

Exchanges email + password for a bearer token (HS256; lifetime from JWT_ACCESS_TOKEN_EXPIRE_MINUTES). The token carries `role`, `company_id` (null for a platform admin) and `is_platform_admin`. An unknown email, a wrong password, a deactivated account and a suspended company all return the same 401 so accounts cannot be enumerated.

Request body

LoginRequest

Responses

Status	Description	Body
`200`	Successful Response	TokenResponse
`401`	Incorrect email or password (or the account/company is inactive).	—
`422`	Validation Error	HTTPValidationError

GET `/auth/me`

Get the current user Bearer JWT

Returns the authenticated user's profile, role and company. The role and company are re-read from the database on every request rather than trusted from the token, so a demotion, deactivation or company suspension takes effect immediately.

Responses

Status	Description	Body
`200`	Successful Response	CurrentUserResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—

GET `/auth/me/upload-limits`

Get my company's upload limits Bearer JWT

The per-file and per-zip limits the caller's company is held to (set per company by a platform admin). Read fresh on every request, so upload screens always show the limit that will actually be enforced. Platform admins belong to no company: 404.

Responses

Status	Description	Body
`200`	Successful Response	UploadLimitsResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`404`	Platform admins have no company and therefore no upload limits.	—

Cases

POST `/cases`

Create a case Bearer JWT

Opens an empty case (status `submitted`) owned by the caller, in the caller's company; any company role may create one (platform admins may not — 403). The case number is `CASE-` plus the first 8 hex characters of the case UUID. Attach documents afterwards with POST /cases/{case_id}/documents. Writes a `case_created` audit event.

Request body

CaseCreateRequest

Responses

Status	Description	Body
`201`	Successful Response	CaseResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Platform admins cannot create cases.	—
`422`	Validation Error	HTTPValidationError

GET /cases

List cases (the case queue) Bearer JWT

Only the caller's company. Reviewers see every case of their company; a `user` sees only the cases they submitted. A platform admin must pass `company_id` (one company at a time, audited) — there is no cross-company case list. For `reviewer_l2` and platform admins, open cases escalated to L2 sort first; otherwise newest first. Optional filters: `status`, `case_type`, `assigned_tier`, and `actionable=true` (only cases the caller may act on — for a `reviewer_l1` that excludes L2 cases). Each item carries `can_act`. For submitters `risk_tier` is null and `flag` is a neutral 'In review' marker, so scoring signals are never disclosed to them.

Parameters

Name	In	Type	Required	Description
`status`	query	CaseStatus (nullable)	no	
`case_type`	query	CaseType (nullable)	no	
`assigned_tier`	query	CaseTier (nullable)	no	
`actionable`	query	boolean	no	Only cases the caller may approve/reject/escalate.
`company_id`	query	string (uuid) (nullable)	no	Platform admins only (required for them): the company to act on. Company users are always confined to their own company.

Responses

Status	Description	Body
`200`	Successful Response	array of CaseListItem
`400`	A platform admin did not pass `company_id`.	—
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`404`	`company_id` names an unknown company (or, for a company user, not theirs).	—
`422`	Validation Error	HTTPValidationError

GET /cases/{case_id}

Get case detail Bearer JWT

Everything the case detail page needs in one call: documents (with signed download URLs, extracted fields and per-document check results), cross-document findings, forensic findings, the latest risk assessment, pipeline progress (`pipeline.complete` / `pipeline.pending`) and reviewer actions. A submitter does not receive the risk assessment and sees only approve/reject actions. A case of another company, or owned by someone else, is a 404, not a 403, so ids cannot be probed. A platform admin may read any company's case; each such access is written to that company's audit log.

Parameters

Name	In	Type	Required	Description
`case_id`	path	string (uuid)	yes	

Responses

Status	Description	Body
`200`	Successful Response	CaseDetail
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`404`	No such case (or, for a `user`, not one they submitted).	—
`422`	Validation Error	HTTPValidationError

GET `/cases/{case_id}/audit-log`

Get a case's activity timeline

Bearer JWT

Chronological feed for the case detail page's activity timeline — System Specification section 3.5. Reads the same append-only `audit_log` rows every check task and case/document endpoint already writes; this adds no new events, just a way to read the ones that exist.

Parameters

Name	In	Type	Required	Description
`case_id`	path	string (uuid)	yes	

Responses

Status	Description	Body
`200`	Successful Response	array of AuditLogEntrySchema
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`404`	No such case (or, for a `user`, not one they submitted).	—
`422`	Validation Error	HTTPValidationError

Documents

POST `/cases/{case_id}/documents`

Upload a document to a case

Bearer JWT

One file per request (multipart field `file`). The original bytes are stored immutably in Blob Storage at `companies/{company_id}/cases/{case_id}/documents/{document_id}_{sha256}{ext}`, a `documents` row is written with the file's SHA-256, then the Celery pipeline is enqueued (extraction, metadata forensics, ELA/copy-move, duplicate detection, visual review, signature detection). The response returns immediately with `processing_status: pending`; poll GET /cases/{case_id} for progress. Before anything is stored or queued the file is validated: at most the company's per-file limit (`max_file_size_mb`, set by a platform admin; 10 MB by default), not empty, a PDF by its header bytes (not its name), a matching extension, and locally parseable (not corrupted, not password-protected). A rejection returns `detail: {code, message, ...}` with one of the codes `file_empty`, `file_too_large`, `unsupported_file_type`, `file_type_mismatch`, `file_corrupted`, `file_password_protected`. Each pipeline step is its own task on a shared, FIFO queue (see app/tasks/celery_app.py). A `user` may upload only to a case they submitted; reviewers to any case of their company; platform admins never (403).

Parameters

Name	In	Type	Required	Description
`case_id`	path	string (uuid)	yes	

Request body

Body_upload_document_cases__case_id__documents_post (multipart/form-data)

Responses

Status	Description	Body
`201`	Successful Response	DocumentResponse
`400`	`file_empty` : the file is 0 bytes.	—
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Platform admins have read-only access.	—
`404`	No such case (or, for a `user`, not one they submitted).	—
`413`	`file_too_large` : over the size limit (`size_bytes` , `max_size_bytes`).	—
`415`	`unsupported_file_type` (not a PDF by content; images are refused) or `file_type_mismatch` (extension names a different type than the content).	—
`422`	`file_corrupted` (cannot be parsed) or `file_password_protected` .	—
`502`	Blob Storage rejected the upload.	—

GET `/cases/{case_id}/documents/{document_id}/file-url`

Get a fresh signed URL for a document

Bearer JWT

Mint a fresh signed URL for a document's original file — the URL handed back at upload time expires after a few minutes, which a reviewer working through the post-upload screen can easily outlast.

Parameters

Name	In	Type	Required	Description
`case_id`	path	string (uuid)	yes	
`document_id`	path	string (uuid)	yes	

Responses

Status	Description	Body
`200`	Successful Response	DocumentFileUrlResponse

Status	Description	Body
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`404`	No such document in this case (or, for a `user`, not their case).	—
`422`	Validation Error	HTTPValidationError
`502`	Blob Storage failed to sign the URL.	—

Case actions (review decisions)

POST `/cases/{case_id}/approve`

Approve a case Bearer JWT

Company reviewers only (platform admins: 403). Requires the automated pipeline to have finished and a risk assessment to exist (409 otherwise). Above `low` risk a written justification (`note`, at least 10 characters) is required (422). Approving an already-decided case is a 409. Writes a `case_actions` row and an audit event.

Parameters

Name	In	Type	Required	Description
`case_id`	path	string (uuid)	yes	

Request body

ApproveRequest

Responses

Status	Description	Body
`200`	Successful Response	CaseDecisionResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires a company reviewer role; a `reviewer_l1` also gets 403 on a case escalated to L2.	—
`404`	No such case in your company.	—
`409`	Case already decided, checks still running, or an invalid state transition.	—
`422`	Case is above low risk and no justification of at least 10 characters was given.	—

POST `/cases/{case_id}/reject`

Reject a case Bearer JWT

Company reviewers only (platform admins: 403). A `reason` is required. Rejecting an already-decided case is a 409. Writes a `case_actions` row and an audit event.

Parameters

Name	In	Type	Required	Description
`case_id`	path	string (uuid)	yes	

Request body

RejectRequest

Responses

Status	Description	Body
`200`	Successful Response	CaseDecisionResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires a company reviewer role; a `reviewer_l1` also gets 403 on a case escalated to L2.	—
`404`	No such case in your company.	—
`409`	Invalid state transition (e.g. already decided).	—
`422`	Validation Error	HTTPValidationError

POST `/cases/{case_id}/escalate`

Escalate a case

Bearer JWT

Company reviewers only (platform admins: 403). Moves the case to the L2 tier (`assigned_tier` = `l2`); `status` is unchanged. A `reviewer_l1` then keeps read access but can no longer act on it. There is no de-escalation — an L2 reviewer approves or rejects it. A `reason` is required. Escalating an already-escalated or decided case is a 409.

Parameters

Name	In	Type	Required	Description
`case_id`	path	string (uuid)	yes	

Request body

EscalateRequest

Responses

Status	Description	Body
`200`	Successful Response	CaseDecisionResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires a company reviewer role; a `reviewer_l1` also gets 403 on a case escalated to L2.	—
`404`	No such case in your company.	—
`409`	Invalid state transition (e.g. already decided).	—
`422`	Validation Error	HTTPValidationError

Signature references & matches

POST `/cases/{case_id}/documents/{document_id}/signature-references`

Create a signature reference

Bearer JWT

Create a signature reference from a reviewer-drawn bounding box.

Crops the signature region from the document's PDF, uploads it to Blob Storage, inserts the signature_references row, then immediately enqueues the in-case comparison Celery task for this reference.

`person_name` is required and must be typed by the reviewer — the system does not attempt to auto-extract it (System Specification §2.3).

Parameters

Name	In	Type	Required	Description
`case_id`	path	string (uuid)	yes	
`document_id`	path	string (uuid)	yes	

Request body

SignatureReferenceCreate

Responses

Status	Description	Body
`201`	Successful Response	SignatureReferenceResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Platform admins have read-only access.	—
`404`	No such case (or, for a `user`, not one they submitted), or the document is not in this case.	—
`422`	Validation Error	HTTPValidationError

GET `/cases/{case_id}/signature-references`

List a case's signature references Bearer JWT

All signature references created for this case. Used by the upload screen to list what references were set during this session.

Parameters

Name	In	Type	Required	Description
`case_id`	path	string (uuid)	yes	

Responses

Status	Description	Body
`200`	Successful Response	array of SignatureReferenceResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`404`	No such case (or, for a `user`, not one they submitted).	—
`422`	Validation Error	HTTPValidationError

GET `/cases/{case_id}/signature-matches`

List a case's signature comparison results Bearer JWT

All in-case signature match results for this case, enriched with the reference person_name. Filtered to comparison_scope='in_case' only — library-scope matches are not generated yet (System Specification §2.3).

Parameters

Name	In	Type	Required	Description
`case_id`	path	string (uuid)	yes	

Responses

Status	Description	Body
`200`	Successful Response	array of SignatureMatchResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`404`	No such case (or, for a `user`, not one they submitted).	—
`422`	Validation Error	HTTPValidationError

Audit log

GET `/audit-log`

Search the audit log

Bearer JWT

Newest-first, paged read of the append-only `audit_log`, confined to the caller's company. Filters: `event_type`, `case_id` and free-text `q` (event type, case number, actor name/email). Company reviewers, and platform admins (`company_id` = one company's log, audited; omitted = the platform-level log).

Parameters

Name	In	Type	Required	Description
`event_type`	query	string (nullable)	no	
`case_id`	query	string (uuid) (nullable)	no	
`q`	query	string (nullable)	no	Matches event type, case number, actor name/email
`company_id`	query	string (uuid) (nullable)	no	Platform admins only.
`limit`	query	integer	no	
`offset`	query	integer	no	

Responses

Status	Description	Body
`200`	Successful Response	AuditPage
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires a reviewer (L1 or L2) or platform admin role.	—
`422`	Validation Error	HTTPValidationError

GET `/audit-log/event-types`

List audit event types

Bearer JWT

Distinct `event_type` values present in the caller's company's audit log (platform admins: the chosen company's, or the platform log), for the filter dropdown.

Parameters

Name	In	Type	Required	Description
`company_id`	query	string (uuid) (nullable)	no	Platform admins only.

Responses

Status	Description	Body
`200`	Successful Response	array of string
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires a reviewer (L1 or L2) or platform admin role.	—
`422`	Validation Error	HTTPValidationError

Case reports

POST `/cases/{case_id}/reports`

Generate a case report (PDF) Bearer JWT

Company reviewers only. Renders the per-case forensic report PDF, stores it in Blob Storage under the company's `companies/{company_id}/cases/{case_id}/reports/` prefix, records a `case_reports` row (with the file's SHA-256) and returns it with a signed download URL. Every call creates a new report; earlier ones are kept.

Parameters

Name	In	Type	Required	Description
`case_id`	path	string (uuid)	yes	

Responses

Status	Description	Body
`201`	Successful Response	CaseReportResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires a reviewer (L1 or L2) or `admin` role.	—
`404`	No such case.	—
`422`	Validation Error	HTTPValidationError
`502`	Blob Storage failed while saving or signing the report.	—

GET `/cases/{case_id}/reports`

List a case's generated reports Bearer JWT

Report history for the case, newest first.

Parameters

Name	In	Type	Required	Description
`case_id`	path	string (uuid)	yes	

Responses

Status	Description	Body
`200`	Successful Response	array of CaseReportResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires a reviewer (L1 or L2) or `admin` role.	—
`404`	No such case.	—
`422`	Validation Error	HTTPValidationError
`502`	Blob Storage failed while signing a download URL.	—

Settings (admin)

GET `/settings/issuers`

List issuers Bearer JWT

The company's issuer registry, ordered by name. Pass `include_inactive=false` to hide deactivated entries. Reviewer L2 (own company) or platform admin (`company_id`).

Parameters

Name	In	Type	Required	Description
`include_inactive`	query	boolean	no	
`company_id`	query	string (uuid) (nullable)	no	Platform admins only (required for them): the company to act on. Company users are always confined to their own company.

Responses

Status	Description	Body
`200`	Successful Response	array of IssuerResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the Reviewer L2 role (or platform admin).	—
`422`	Validation Error	HTTPValidationError

POST `/settings/issuers`

Create an issuer Bearer JWT

Adds a known vendor/school/etc. to the company's registry used by issuer verification. Names are unique (case-insensitively) among the company's active issuers.

Parameters

Name	In	Type	Required	Description
`company_id`	query	string (uuid) (nullable)	no	Platform admins only (required for them): the company to act on. Company users are always confined to their own company.

Request body

IssuerCreate

Responses

Status	Description	Body
`201`	Successful Response	IssuerResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the Reviewer L2 role (or platform admin).	—
`409`	An active issuer with this name already exists.	—
`422`	Validation Error	HTTPValidationError

PATCH `/settings/issuers/{issuer_id}`

Update or deactivate an issuer Bearer JWT

Partial update: only the fields sent are changed. Issuers are never deleted; set `is_active=false` to retire one. A request that changes nothing is a no-op. An issuer of another company is a 404.

Parameters

Name	In	Type	Required	Description
`issuer_id`	path	string (uuid)	yes	
`company_id`	query	string (uuid) (nullable)	no	Platform admins only (required for them): the company to act on. Company users are always confined to their own company.

Request body

IssuerUpdate

Responses

Status	Description	Body
`200`	Successful Response	IssuerResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the Reviewer L2 role (or platform admin).	—
`404`	No such issuer.	—
`422`	Validation Error	HTTPValidationError

GET `/settings/risk-rules`

List current risk rules Bearer JWT

The CURRENT version of every rule (active or not) of the company, by category.

Parameters

Name	In	Type	Required	Description
`company_id`	query	string (uuid) (nullable)	no	Platform admins only (required for them): the company to act on. Company users are always confined to their own company.

Responses

Status	Description	Body
`200`	Successful Response	array of RiskRuleResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the Reviewer L2 role (or platform admin).	—
`422`	Validation Error	HTTPValidationError

POST `/settings/risk-rules`

Create a risk rule Bearer JWT

A new rule at version 1, for this company only. It applies to the company's cases scored from now on; nothing already scored changes (assessments freeze the versions that produced them).

Parameters

Name	In	Type	Required	Description
`company_id`	query	string (uuid) (nullable)	no	Platform admins only (required for them): the company to act on. Company users are always confined to their own company.

Request body

RiskRuleCreate

Responses

Status	Description	Body
`201`	Successful Response	RiskRuleResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the Reviewer L2 role (or platform admin).	—
`409`	A rule with this `rule_id` already exists in the company.	—
`422`	The chosen match/parameters cannot be evaluated by the engine.	—

GET `/settings/risk-rule-options`

Get the options for the Add-rule form Bearer JWT

Everything the Add-rule form offers, so it never has to hardcode (or guess) what the checks can produce.

Responses

Status	Description	Body
`200`	Successful Response	object

Status	Description	Body
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the Reviewer L2 role (or platform admin).	—

GET `/settings/risk-rules/{rule_id}/history`

Get a risk rule's version history Bearer JWT

Every version of one of the company's rules, newest first — the per-rule audit trail (who changed what, when). The same edits are also in `audit_log`.

Parameters

Name	In	Type	Required	Description
`rule_id`	path	string	yes	
`company_id`	query	string (uuid) (nullable)	no	Platform admins only (required for them): the company to act on. Company users are always confined to their own company.

Responses

Status	Description	Body
`200`	Successful Response	array of RiskRuleResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the Reviewer L2 role (or platform admin).	—
`404`	No such rule.	—
`422`	Validation Error	HTTPValidationError

PATCH `/settings/risk-rules/{rule_id}`

Change a risk rule's weight, severity or active flag Bearer JWT

Rules are versioned: an edit inserts a new immutable row (`version` + 1) and leaves the old one untouched, so every historical assessment stays truthful. Only `weight`, `severity` and `is_active` can be changed; at least one must differ. Only the company's own rule is affected.

Parameters

Name	In	Type	Required	Description
`rule_id`	path	string	yes	
`company_id`	query	string (uuid) (nullable)	no	Platform admins only (required for them): the company to act on. Company users are always confined to their own company.

Request body

RiskRuleUpdate

Responses

Status	Description	Body
`200`	Successful Response	RiskRuleResponse
`400`	Nothing to change.	—
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the Reviewer L2 role (or platform admin).	—
`404`	No such rule.	—
`409`	The rule was changed concurrently; reload and retry.	—
`422`	Validation Error	HTTPValidationError

GET `/settings/risk-thresholds`

Get the risk tier thresholds

Bearer JWT

The company's scores at which a case becomes `medium` and `high` risk (defaults 30 and 60). The row is created on first read if it does not exist.

Parameters

Name	In	Type	Required	Description
`company_id`	query	string (uuid) (nullable)	no	Platform admins only (required for them): the company to act on. Company users are always confined to their own company.

Responses

Status	Description	Body
`200`	Successful Response	RiskThresholdsResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the Reviewer L2 role (or platform admin).	—
`422`	Validation Error	HTTPValidationError

PUT `/settings/risk-thresholds`

Set the risk tier thresholds

Bearer JWT

Safe for history: each assessment embeds the thresholds it used.

Parameters

Name	In	Type	Required	Description
`company_id`	query	string (uuid) (nullable)	no	Platform admins only (required for them): the company to act on. Company users are always confined to their own company.

Request body

RiskThresholds

Responses

Status	Description	Body
`200`	Successful Response	RiskThresholdsResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the Reviewer L2 role (or platform admin).	—
`422`	Validation Error	HTTPValidationError

GET `/settings/users`

List users Bearer JWT

Every account on the platform, ordered by company then email; filter with `company_id`. Platform admin only.

Parameters

Name	In	Type	Required	Description
`company_id`	query	string (uuid) (nullable)	no	

Responses

Status	Description	Body
`200`	Successful Response	array of UserAdminResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the platform admin role.	—
`422`	Validation Error	HTTPValidationError

POST `/settings/users`

Create a user Bearer JWT

Creates an account and assigns it to a company + role. Company roles (`user` , `reviewer_l1` , `reviewer_l2`) need a `company_id` ; a `platform_admin` must have none. Platform admin only.

Request body

UserCreate

Responses

Status	Description	Body
`201`	Successful Response	UserAdminResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the platform admin role.	—
`404`	No such company.	—
`409`	An account with that email already exists.	—
`422`	Company/role combination is invalid.	—

PATCH `/settings/users/{user_id}`

Change a user's role, company or active flag

Bearer JWT

Partial update of `role`, `company_id` and/or `is_active`. A platform admin cannot change their own role or deactivate themselves (this also guarantees a platform admin always remains). Changing a user's company or role invalidates their existing tokens (they must sign in again). There is no self-service signup and no password-reset endpoint. Platform admin only.

Parameters

Name	In	Type	Required	Description
`user_id`	path	string (uuid)	yes	

Request body

UserAdminUpdate

Responses

Status	Description	Body
`200`	Successful Response	UserAdminResponse
`400`	Attempted to change your own role or deactivate yourself.	—
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the platform admin role.	—
`404`	No such user (or company).	—
`422`	Company/role combination is invalid.	—

POST `/settings/users/{user_id}/reset-password`

Reset user password (platform admin only)

Bearer JWT

Resets the password for any user account. The new password is stored hashed. Only platform admins have access to this action. Action is logged in the audit trail.

Parameters

Name	In	Type	Required	Description
`user_id`	path	string (uuid)	yes	

Request body

UserPasswordReset

Responses

Status	Description	Body
`200`	Successful Response	UserAdminResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the platform admin role.	—
`404`	No such user.	—

Status	Description	Body
`422`	Validation Error	HTTPValidationError

Other

POST `/bulk-uploads`

Bulk upload: a zip of cases

Bearer JWT

Request body: the zip file itself (`Content-Type: application/zip`), not multipart. Query: `case_type` (applied to every case) and `filename` (the zip's name, for display). The zip holds one top-level folder per case, each containing that case's documents directly. The response (202) returns once the zip is stored: it lists every case folder found, with structural failures already marked (subfolder in a case folder, empty folder, empty or file over the company's per-file limit). Documents are then extracted, validated with the same checks as a single upload, and each valid case is created and queued, one case at a time. Poll GET /bulk-uploads/{id}. Partial success: a bad file is rejected on its own and a case with no valid file fails on its own. Zip rejections return `detail: {code, message, ...}` with `zip_empty` , `zip_too_large` (over the company's zip limit, `max_zip_size_mb` , 300 MB by default, decided from Content-Length before the body is read), `not_a_zip` , `zip_corrupted` , `zip_too_many_entries` or `zip_no_case_folders` .

Parameters

Name	In	Type	Required	Description
`case_type`	query	CaseType	yes	Case type for every case in the zip.
`filename`	query	string	yes	The zip's file name.

Responses

Status	Description	Body
`202`	Successful Response	BulkUploadDetail
`400`	`zip_empty` .	—
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Platform admins have read-only access.	—
`413`	`zip_too_large` (`size_bytes` , `max_size_bytes`).	—
`415`	`not_a_zip` .	—
`422`	`zip_corrupted` , `zip_too_many_entries` , `zip_no_case_folders` .	—
`502`	Blob Storage rejected the upload.	—

GET `/bulk-uploads`

List bulk uploads

Bearer JWT

Newest first. A `user` sees only their own; reviewers see their company's. Platform admins pass `company_id` (audited).

Parameters

Name	In	Type	Required	Description
`limit`	query	integer	no	
`company_id`	query	string (uuid) (nullable)	no	Platform admins only (required for them): the company to act on. Company users are always confined to their own company.

Responses

Status	Description	Body
`200`	Successful Response	array of BulkUploadSummary
`422`	Validation Error	HTTPValidationError

GET `/bulk-uploads/{bulk_upload_id}`

Bulk upload summary (live per-case status) Bearer JWT

Every case folder of the zip with its outcome (created / failed and why, per file) and, for created cases, live progress (queued → processing → done / flagged). Poll until `settled`. Another user's upload (for a `user`) or another company's is a 404.

Parameters

Name	In	Type	Required	Description
`bulk_upload_id`	path	string (uuid)	yes	
`company_id`	query	string (uuid) (nullable)	no	Platform admins only (required for them): the company to act on. Company users are always confined to their own company.

Responses

Status	Description	Body
`200`	Successful Response	BulkUploadDetail
`422`	Validation Error	HTTPValidationError

GET `/platform/companies`

List companies Bearer JWT

Responses

Status	Description	Body
`200`	Successful Response	array of CompanyResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the platform admin role.	—

POST `/platform/companies`

Create a company Bearer JWT

Creates a client company and copies every active platform rule template into its own risk rules, plus default tier thresholds (its own independent copy, which its Reviewer L2s can then tune; later template edits don't affect it). The issuer registry starts empty. Users are added separately (Settings > Users).

Request body

CompanyCreate

Responses

Status	Description	Body
`201`	Successful Response	CompanyResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the platform admin role.	—
`409`	A company with this name already exists.	—
`422`	Validation Error	HTTPValidationError

PATCH `/platform/companies/{company_id}`

Rename, suspend/reactivate, or change a company's upload limits Bearer JWT

`is_active=false` suspends the company: its users can no longer sign in, and existing tokens stop working on the next request. Data is kept. `max_file_size_mb` / `max_zip_size_mb` change the company's upload limits (any positive whole number of MB; no upper ceiling), effective on its next upload with no new sign-in. Every change is written to the platform audit log as `company_updated` with old → new values.

Parameters

Name	In	Type	Required	Description
`company_id`	path	string (uuid)	yes	

Request body

CompanyUpdate

Responses

Status	Description	Body
`200`	Successful Response	CompanyResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the platform admin role.	—
`404`	No such company.	—
`409`	Name taken.	—
`422`	Validation Error	HTTPValidationError

GET `/platform/risk-rule-templates`

List the platform risk-rule template Bearer JWT

The default rule set copied into every NEW company's own risk rules at creation time. Editing it never changes companies that already exist.

Responses

Status	Description	Body
`200`	Successful Response	array of RuleTemplateResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the platform admin role.	—

POST `/platform/risk-rule-templates`

Add a rule to the platform template Bearer JWT

Same rule builder as a company's Add-rule form. Applies to companies created from now on.

Request body

RiskRuleCreate

Responses

Status	Description	Body
`201`	Successful Response	RuleTemplateResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the platform admin role.	—
`409`	A template rule with this rule_id already exists.	—
`422`	Validation Error	HTTPValidationError

PATCH `/platform/risk-rule-templates/{rule_id}`

Edit a platform template rule Bearer JWT

Changes weight, severity, wording or active flag. Existing companies keep their own copies unchanged; only companies created afterwards start from the new values.

Parameters

Name	In	Type	Required	Description
`rule_id`	path	string	yes	

Request body

RuleTemplateUpdate

Responses

Status	Description	Body
`200`	Successful Response	RuleTemplateResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—

Status	Description	Body
`403`	Requires the platform admin role.	—
`404`	No such template rule.	—
`422`	Validation Error	HTTPValidationError

GET /platform/usage

Billing & usage by company

Bearer JWT

One row per company for the period: cases created, documents uploaded, files stored (documents + generated reports) and bytes stored during the period, plus each company's current all-time storage. Read from incrementally-maintained daily counters (company_usage_stats), not live scans of the case tables; a nightly job reconciles them against the source data. Periods use UTC days.

Parameters

Name	In	Type	Required	Description
`period`	query	string: `"this_month"`, `"last_month"`, `"last_30_days"`, `"this_year"`, `"all_time"`, `"custom"`	no	
`start`	query	string (date) (nullable)	no	custom period only
`end`	query	string (date) (nullable)	no	custom period only

Responses

Status	Description	Body
`200`	Successful Response	UsageResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the platform admin role.	—
`422`	Validation Error	HTTPValidationError

POST /platform/usage/reconcile

Reconcile usage counters now

Bearer JWT

Recomputes every company's daily counters from the cases/documents/reports tables and corrects any drift (the same job runs nightly). Returns what was corrected; a correction is also written to the platform audit log.

Responses

Status	Description	Body
`200`	Successful Response	ReconcileResponse
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the platform admin role.	—

GET `/platform/queues`

Processing queue monitor Bearer JWT

Per queue (extraction / vision / forensics): tasks waiting and running, age of the oldest waiting task, average / p95 / max wait over the window, average run time, the rate limit in force and the limiter's counters (calls throttled, Azure 429s), and the worker processes consuming it. Wait times are measured from enqueue to start.

Parameters

Name	In	Type	Required	Description
`window_minutes`	query	integer	no	

Responses

Status	Description	Body
`200`	Successful Response	object
`401`	Missing, invalid or expired bearer token, or the user is inactive.	—
`403`	Requires the platform admin role.	—
`422`	Validation Error	HTTPValidationError

Data models

ApproveRequest

Field	Type	Required	Description
`note`	string (nullable)	no	Justification. Optional for low-risk cases; at least 10 characters (after trimming) is required to approve a medium- or high-risk case.

AuditEventResponse

Field	Type	Required	Description
`id`	string (uuid)	yes	
`created_at`	string (date-time)	yes	
`event_type`	string	yes	
`actor_name`	string (nullable)	yes	
`actor_email`	string (nullable)	yes	
`case_id`	string (uuid) (nullable)	yes	
`case_number`	string (nullable)	yes	
`document_id`	string (uuid) (nullable)	yes	
`document_filename`	string (nullable)	yes	
`event_data`	object (nullable)	yes	

AuditLogEntrySchema

One `audit_log` row scoped to a case — System Specification section 3.5's "review history/timeline ... built from the same audit log." Every event_type here is a real one already written by app/services/ audit_service.py's call sites (case creation, uploads, and each Celery check task) — nothing here is synthesized for display.

Field	Type	Required	Description
`id`	string (uuid)	yes	
`event_type`	string	yes	
`actor_name`	string (nullable)	yes	
`document_id`	string (uuid) (nullable)	yes	
`event_data`	object (nullable)	yes	
`created_at`	string (date-time)	yes	

AuditPage

Field	Type	Required	Description
`items`	array of AuditEventResponse	yes	
`total`	integer	yes	

Body_upload_document_cases__case_id__documents_post

Field	Type	Required	Description
`file`	string (binary)	yes	

BoundingBoxSchema

Normalized bounding box — page-fraction (0-1) coordinates, same convention as every other bounding box in this codebase (ELA, copy-move, visual inconsistency). `page` is 1-based.

Field	Type	Required	Description
`page`	integer	yes	
`x`	number	yes	
`y`	number	yes	
`width`	number	yes	
`height`	number	yes	

BulkUploadCaseSchema

Field	Type	Required	Description
`index`	integer	yes	
`folder`	string	yes	
`status`	string: `"pending"`, `"created"`, `"failed"`	yes	
`error_code`	string (nullable)	no	
`error_message`	string (nullable)	no	
`case_id`	string (uuid) (nullable)	no	
`case_number`	string (nullable)	no	
`files`	array of BulkUploadFileSchema	yes	
`live_status`	string: `"validating"`, `"failed"`, `"queued"`, `"processing"`, `"done"`, `"flagged"`	yes	
`case_status`	CaseStatus (nullable)	no	
`documents_total`	integer	no	
`documents_finished`	integer	no	
`flag`	CaseFlagSchema (nullable)	no	

BulkUploadDetail

Field	Type	Required	Description
`id`	string (uuid)	yes	
`original_filename`	string	yes	
`case_type`	CaseType	yes	
`status`	BulkUploadStatus	yes	
`error_code`	string (nullable)	yes	
`error_message`	string (nullable)	yes	
`zip_size_bytes`	integer	yes	
`case_folder_count`	integer (nullable)	yes	
`cases_created`	integer	yes	
`cases_failed`	integer	yes	
`documents_accepted`	integer	yes	
`documents_rejected`	integer	yes	
`uploaded_by`	UserSummary (nullable)	yes	
`created_at`	string (date-time)	yes	
`started_at`	string (date-time) (nullable)	yes	
`finished_at`	string (date-time) (nullable)	yes	
`wrapper_folder`	string (nullable)	no	
`ignored_entries`	array of string	no	
`ignored_entry_count`	integer	no	
`warnings`	array of string	no	
`progress`	BulkUploadProgress	yes	
`settled`	boolean	yes	
`cases`	array of BulkUploadCaseSchema	yes	

BulkUploadFileSchema

Field	Type	Required	Description
`name`	string	yes	
`status`	string: `"pending"`, `"accepted"`, `"rejected"`, `"skipped"`	yes	
`code`	string (nullable)	no	
`message`	string (nullable)	no	
`size_bytes`	integer (nullable)	no	
`document_id`	string (uuid) (nullable)	no	

BulkUploadProgress

Field	Type	Required	Description
`validating`	integer	no	
`failed`	integer	no	
`queued`	integer	no	
`processing`	integer	no	
`done`	integer	no	
`flagged`	integer	no	

BulkUploadStatus

Allowed values: `"queued"`, `"ingesting"`, `"complete"`, `"failed"`

BulkUploadSummary

Field	Type	Required	Description
`id`	string (uuid)	yes	
`original_filename`	string	yes	
`case_type`	CaseType	yes	
`status`	BulkUploadStatus	yes	
`error_code`	string (nullable)	yes	
`error_message`	string (nullable)	yes	
`zip_size_bytes`	integer	yes	
`case_folder_count`	integer (nullable)	yes	
`cases_created`	integer	yes	
`cases_failed`	integer	yes	
`documents_accepted`	integer	yes	
`documents_rejected`	integer	yes	
`uploaded_by`	UserSummary (nullable)	yes	
`created_at`	string (date-time)	yes	
`started_at`	string (date-time) (nullable)	yes	
`finished_at`	string (date-time) (nullable)	yes	

CaseActionSchema

A reviewer decision/note on the case (approve/reject/escalate).

Field	Type	Required	Description
`id`	string (uuid)	yes	
`action_type`	string	yes	
`actor_name`	string (nullable)	yes	
`actor_role`	string (nullable)	no	Display label of the actor's role when they acted, e.g. 'Reviewer L1'.
`notes`	string (nullable)	yes	
`created_at`	string (date-time)	yes	

CaseCreateRequest

Field	Type	Required	Description
`case_type`	CaseType	yes	Case-level category chosen at submission. Independent of each document's own `document_type`, which the classification step fills in later.

CaseDecisionResponse

Field	Type	Required	Description
`case_id`	string (uuid)	yes	
`status`	CaseStatus	yes	
`assigned_tier`	CaseTier	yes	
`action`	CaseActionSchema	yes	

CaseDetail

Field	Type	Required	Description
`id`	string (uuid)	yes	
`case_number`	string	yes	
`case_type`	CaseType	yes	
`status`	CaseStatus	yes	
`assigned_tier`	CaseTier	yes	
`risk_tier`	RiskTier (nullable)	yes	
`submitted_by`	UserSummary (nullable)	no	
`created_at`	string (date-time)	yes	
`document_count`	integer	yes	
`flag`	CaseFlagSchema	yes	
`can_act`	boolean	yes	Whether the caller may approve/reject/escalate this case given its tier. False for submitters, and for a `reviewer_l1` on an L2-assigned case (read-only). Does not reflect status — a decided case is still `can_act` but every action is a 409.
`documents`	array of CaseDocumentSummary	yes	
`cross_document_findings`	array of CrossDocumentFindingSummary	yes	
`forensic_findings`	array of ForensicFindingSummary	yes	
`assessment`	RiskAssessmentSchema (nullable)	yes	
`pipeline`	PipelineStatusSchema	yes	
`actions`	array of CaseActionSchema	yes	

CaseDocumentSummary

A document as shown on the case-detail page. `file_url` here is a short-lived signed URL (see StorageService.get_download_url) — the storage container is private, so the durable URL alone isn't browser-fetchable.

`document_type` and `extracted_fields` are filled in by the OCR + classification + extraction Celery pipeline (app/tasks/document_ processing.py) — both stay null until `processing_status` reaches "complete". `extracted_fields` shape: {"document_type_confidence": float, "core_fields": {name: {value, confidence, uncertain}}, "additional_fields": [{field_name, value, confidence, uncertain}]}.

`checks` is filled in afterward by app/tasks/document_checks.py (field_validation, issuer_verification, and later the forensic checks) — empty until those complete.

Field	Type	Required	Description
`id`	string (uuid)	yes	
`original_filename`	string	yes	
`document_type`	string (nullable)	yes	
`processing_status`	string	yes	
`extracted_fields`	object (nullable)	yes	
`processing_error`	string (nullable)	yes	
`content_type`	string (nullable)	yes	
`file_size_bytes`	integer (nullable)	yes	
`file_hash`	string	yes	
`file_url`	string	yes	
`uploaded_at`	string (date-time)	yes	
`checks`	array of DocumentCheckSummary	yes	

CaseFlagSchema

Wire shape of app/services/case_flag_service.py's CaseFlag: the case's real risk tier (low/medium/high), or "pending" until scored.

Field	Type	Required	Description
`flag`	string: `"low"`, `"medium"`, `"high"`, `"pending"`	yes	
`label`	string	yes	
`description`	string	yes	
`score`	integer (nullable)	no	

CaseListItem

Field	Type	Required	Description
`id`	string (uuid)	yes	
`case_number`	string	yes	
`case_type`	CaseType	yes	
`status`	CaseStatus	yes	
`assigned_tier`	CaseTier	yes	
`risk_tier`	RiskTier (nullable)	yes	
`submitted_by`	UserSummary (nullable)	no	
`created_at`	string (date-time)	yes	
`document_count`	integer	yes	
`flag`	CaseFlagSchema	yes	
`can_act`	boolean	yes	Whether the caller may approve/reject/escalate this case given its tier. False for submitters, and for a `reviewer_l1` on an L2-assigned case (read-only). Does not reflect status — a decided case is still `can_act` but every action is a 409.

CaseReportResponse

One generated report. `download_url` is a short-lived signed URL (the container is private — see app/services/storage_service.py), so it is minted fresh on every response rather than stored.

Field	Type	Required	Description
`id`	string (uuid)	yes	
`case_id`	string (uuid)	yes	
`generated_by_name`	string (nullable)	yes	
`generated_at`	string (date-time)	yes	
`file_size_bytes`	integer	yes	
`page_count`	integer	yes	
`report_sha256`	string	yes	
`risk_tier`	string (nullable)	yes	
`risk_score`	integer (nullable)	yes	
`download_url`	string	yes	

CaseResponse

Field	Type	Required	Description
`id`	string (uuid)	yes	
`case_number`	string	yes	
`case_type`	CaseType	yes	
`status`	CaseStatus	yes	
`assigned_tier`	CaseTier	yes	
`risk_tier`	RiskTier (nullable)	yes	
`submitted_by_user_id`	string (uuid)	yes	
`created_at`	string (date-time)	yes	

CaseStatus

Allowed values: `"submitted"`, `"under_automated_review"`, `"pending_manual_review"`, `"auto_approved"`, `"escalated"`, `"under_investigation"`, `"approved"`, `"rejected"`, `"closed"`

CaseTier

Which reviewer tier owns the case — orthogonal to `status`. Every case starts at `l1`; escalating it moves it to `l2` (one-directional, there is no de-escalation). On an `l2` case a `reviewer_l1` keeps read access but every action endpoint returns 403; `reviewer_l2` and `admin` can act on cases of either tier.

Allowed values: `"l1"`, `"l2"`

CaseType

Case-level category, selected at submission time (System Specification section 3.6's document-type coverage list). This is separate from a document's own `document_type`, which is filled in later by the classification step — a case can hold documents of more than one type (e.g. an invoice plus its approval voucher).

Allowed values: `"school_document"`, `"vendor_invoice"`, `"commercial_invoice"`, `"procurement_documentation"`, `"quotation"`, `"travel_reimbursement"`, `"other"`

CompanyCreate

Field	Type	Required	Description
`name`	string	yes	
`max_file_size_mb`	integer (nullable)	no	Max document size in MB (per company).
`max_zip_size_mb`	integer (nullable)	no	Max bulk-upload zip size in MB (per company).

CompanyResponse

Field	Type	Required	Description
`id`	string (uuid)	yes	
`name`	string	yes	
`is_active`	boolean	yes	
`created_at`	string (date-time)	yes	
`user_count`	integer	yes	
`max_file_size_mb`	integer	yes	Largest document this company may upload, in MB.
`max_zip_size_mb`	integer	yes	Largest bulk-upload zip this company may upload, in MB.

CompanyUpdate

Field	Type	Required	Description
`name`	string (nullable)	no	
`is_active`	boolean (nullable)	no	
`max_file_size_mb`	integer (nullable)	no	Max document size in MB (per company).
`max_zip_size_mb`	integer (nullable)	no	Max bulk-upload zip size in MB (per company).

CompanyUsageRow

Field	Type	Required	Description
`company_id`	string (uuid)	yes	
`company_name`	string	yes	
`is_active`	boolean	yes	
`cases_created`	integer	yes	
`documents_uploaded`	integer	yes	
`files_stored`	integer	yes	
`storage_bytes`	integer	yes	
`total_storage_bytes`	integer	yes	
`total_files_stored`	integer	yes	

CrossDocumentFindingSummary

One `cross_document_findings` row (System Specification section 3.1, "Cross-document validation & reconciliation") — a shared field (amount/date/issuer) that disagreed between two of this case's documents. Case-level, not per-document — see app/services/ cross_document_service.py and app/tasks/document_checks.py.

Field	Type	Required	Description
`id`	string (uuid)	yes	
`field_name`	string	yes	
`finding_type`	string	yes	
`severity`	string	yes	
`description`	string	yes	
`document_ids`	array of string (nullable)	yes	
`created_at`	string (date-time)	yes	
`regions`	array of object	no	

CurrentUserResponse

Field	Type	Required	Description
`id`	string (uuid)	yes	
`email`	string (email)	yes	
`full_name`	string (nullable)	yes	Display name, if one was set.
`role`	UserRole	yes	`user` (submitter), `reviewer_l1`, `reviewer_l2` (company roles) or `platform_admin`.
`role_label`	string	yes	Display label, e.g. "Reviewer L2".
`is_active`	boolean	yes	Deactivated accounts are rejected on every request.
`is_platform_admin`	boolean	yes	True for platform admins, who belong to no company.
`company_id`	string (uuid) (nullable)	yes	The user's company; null for a platform admin.
`company_name`	string (nullable)	yes	Display name of the user's company.

DocumentCheckSummary

One `document_checks` row (System Specification sections 2.2/3.1/3.2 — field_validation, issuer_verification, and later the forensic checks). `result` holds whatever shape that check_type produces — see the individual check services (e.g. app/services/field_validation_service.py) for what's inside — the frontend's Checks panel renders it generically rather than assuming a fixed schema per check_type.

Field	Type	Required	Description
`id`	string (uuid)	yes	
`check_type`	string	yes	
`status`	string	yes	
`result`	object (nullable)	yes	
`error_message`	string (nullable)	yes	
`created_at`	string (date-time)	yes	
`summary`	object (nullable)	no	

DocumentFileUrlResponse

A fresh short-lived signed URL for one document's original file.

Field	Type	Required	Description
`file_url`	string	yes	

DocumentResponse

Field	Type	Required	Description
`id`	string (uuid)	yes	
`case_id`	string (uuid)	yes	
`original_filename`	string	yes	
`content_type`	string (nullable)	yes	
`file_size_bytes`	integer (nullable)	yes	
`file_hash`	string	yes	
`file_url`	string	yes	
`uploaded_at`	string (date-time)	yes	
`processing_status`	string	yes	

EscalateRequest

Field	Type	Required	Description
`reason`	string	yes	Why the case needs an L2 reviewer. Required and must not be blank.

ForensicFindingSummary

One medium/high-severity finding from a flagged metadata_forensics/ error_level_analysis/copy_move_detection check — the per-document counterpart to CrossDocumentFindingSummary, both shown together in the case detail "Explainable findings" panel. See app/services/ case_flag_service.py's get_forensic_findings for what feeds this and why it's a temporary stand-in for the real risk-scoring engine.

Field	Type	Required	Description
`document_id`	string (uuid)	yes	
`document_filename`	string	yes	
`check_type`	string	yes	
`check_type_label`	string	yes	
`finding`	string	yes	
`severity`	string	yes	
`description`	string	yes	

HTTPValidationError

Field	Type	Required	Description
`detail`	array of ValidationError	no	

IssuerCreate

Field	Type	Required	Description
`name`	string	yes	English/Latin issuer name.
`name_arabic`	string (nullable)	no	Arabic-script name, matched separately during issuer verification.
`tax_id`	string (nullable)	no	Tax/VAT registration number, if known.
`type`	IssuerType	no	Kind of issuer (vendor, school, ...).

IssuerResponse

Field	Type	Required	Description
`id`	string (uuid)	yes	
`name`	string	yes	
`name_arabic`	string (nullable)	yes	
`tax_id`	string (nullable)	yes	
`type`	IssuerType	yes	
`is_active`	boolean	yes	
`created_at`	string (date-time)	yes	
`updated_at`	string (date-time)	yes	

IssuerType

Allowed values: `"vendor"`, `"school"`, `"government"`, `"other"`

IssuerUpdate

Field	Type	Required	Description
`name`	string (nullable)	no	
`name_arabic`	string (nullable)	no	
`tax_id`	string (nullable)	no	
`type`	IssuerType (nullable)	no	
`is_active`	boolean (nullable)	no	

LoginRequest

Field	Type	Required	Description
`email`	string (email)	yes	Account email (matched exactly as stored).
`password`	string	yes	Account password.

PipelineStatusSchema

Whether every automated check has finished. `pending` names what is still outstanding — shown to the reviewer when Approve is disabled.

Field	Type	Required	Description
`complete`	boolean	yes	
`pending`	array of string	yes	

ReconcileResponse

Field	Type	Required	Description
`rows_checked`	integer	yes	
`rows_corrected`	integer	yes	
`drift`	array of object	yes	

RejectRequest

Field	Type	Required	Description
`reason`	string	yes	Why the case is rejected. Required and must not be blank.

RiskAssessmentSchema

Field	Type	Required	Description
`id`	string (uuid)	yes	
`score`	integer	yes	
`raw_score`	number	yes	
`tier`	RiskTier	yes	
`computed_at`	string (date-time)	yes	
`triggered_reasons`	array of RiskReasonSchema	yes	
`thresholds`	map of integer	yes	
`group_caps`	map of map of number	no	

RiskReasonSchema

One fired rule, as frozen at scoring time (rendered text, weight and rule version) — see app/models/case_risk_assessment.py.

Field	Type	Required	Description
`rule_id`	string	yes	
`rule_version`	integer	yes	
`category`	string	yes	
`check_type`	string	yes	
`severity`	string	yes	
`weight`	number	yes	
`reason`	string	yes	
`document_id`	string (uuid) (nullable)	yes	
`document_filename`	string (nullable)	yes	
`title`	string	no	
`short`	string	no	

RiskRuleCreate

A brand-new rule (version 1). The admin picks a rule TYPE and its parameters from the catalog (GET /settings/risk-rule-options); the API builds and validates the engine `condition` from them — nobody writes JSON, and a choice the engine can't evaluate is rejected.

Field	Type	Required	Description
`rule_id`	string	yes	Stable key, lower-case with a dot: e.g. custom.editing_tool_seen
`category`	string: `"forensics"`, `"consistency"`, `"verification"`, `"duplication"`	yes	
`match`	string: `"finding"`, `"check_result"`, `"sub_check"`, `"cross_document"`, `"signature_match"`	yes	
`check_type`	string (nullable)	no	
`finding`	string (nullable)	no	
`severity_in`	array of string: `"low"`, `"medium"`, `"high"` (nullable)	no	
`sub_check`	string (nullable)	no	
`field_name`	string (nullable)	no	
`signature_result`	string (nullable)	no	
`weight`	number	yes	
`severity`	string: `"low"`, `"medium"`, `"high"`	yes	
`reason_template`	string	yes	
`is_active`	boolean	no	
`change_note`	string (nullable)	no	

RiskRuleResponse

One (current or historical) version of a rule.

Field	Type	Required	Description
`id`	string (uuid)	yes	
`rule_id`	string	yes	
`category`	string	yes	
`check_type`	string	yes	
`weight`	number	yes	
`severity`	string	yes	
`reason_template`	string	yes	
`is_active`	boolean	yes	
`version`	integer	yes	
`effective_from`	string (date-time)	yes	
`updated_by_name`	string (nullable)	yes	
`change_note`	string (nullable)	yes	

RiskRuleUpdate

An edit. Never mutates the existing row: the API inserts version+1.

Field	Type	Required	Description
`weight`	number (nullable)	no	Points added to the case score when the rule fires.
`severity`	string: `"low"`, `"medium"`, `"high"` (nullable)	no	Severity shown beside the rule's reason.
`is_active`	boolean (nullable)	no	Inactive rules are evaluated but never fire.
`change_note`	string (nullable)	no	Why the change was made.

RiskThresholds

Field	Type	Required	Description
`medium_threshold`	integer	yes	Score at or above which a case is `medium` risk.
`high_threshold`	integer	yes	Score at or above which a case is `high` risk. Must exceed the medium threshold.
`metadata_score_cap`	integer (nullable)	no	Most points the metadata rules (`metadata.*`) may add together — one edit leaves several metadata traces. 100 = no cap. Omitted: unchanged.

RiskThresholdsResponse

Field	Type	Required	Description
`medium_threshold`	integer	yes	Score at or above which a case is `medium` risk.
`high_threshold`	integer	yes	Score at or above which a case is `high` risk. Must exceed the medium threshold.
`metadata_score_cap`	integer	yes	
`updated_at`	string (date-time)	yes	
`updated_by_name`	string (nullable)	yes	

RiskTier

Allowed values: `"low"`, `"medium"`, `"high"`

RuleTemplateResponse

Field	Type	Required	Description
`id`	string (uuid)	yes	
`rule_id`	string	yes	
`category`	string	yes	
`check_type`	string	yes	
`condition`	object	yes	
`weight`	number	yes	
`severity`	string	yes	
`reason_template`	string	yes	
`is_active`	boolean	yes	
`updated_at`	string (date-time)	yes	

RuleTemplateUpdate

Field	Type	Required	Description
`weight`	number (nullable)	no	
`severity`	string: `"low"`, `"medium"`, `"high"` (nullable)	no	
`reason_template`	string (nullable)	no	
`is_active`	boolean (nullable)	no	

SignatureMatchResponse

One signature_matches row returned by the API, enriched with the reference's person_name so the frontend can show "compared against [name]" without a separate reference lookup.

Field	Type	Required	Description
`id`	string (uuid)	yes	
`document_id`	string (uuid)	yes	
`case_id`	string (uuid)	yes	
`signature_reference_id`	string (uuid)	yes	
`reference_person_name`	string	yes	
`comparison_scope`	string	yes	
`result`	string	yes	
`result_label`	string	yes	
`reasoning`	string (nullable)	yes	
`compared_at`	string (date-time)	yes	

SignatureReferenceCreate

Request body for POST /cases/{case_id}/documents/{document_id}/ signature-references.

`person_name` is required and must be provided by the reviewer — the system never attempts to auto-extract or pre-fill it (System Specification §2.3).

Field	Type	Required	Description
`person_name`	string	yes	Name of the person whose signature this is, typed by the reviewer. Required — the system does not attempt to auto-extract this field.
`bounding_box`	BoundingBoxSchema	yes	
`is_library`	boolean	no	Defaults to True: every reference is saved to the permanent signature library. False is still accepted (case-only reference). Either way, at this phase a reference is only compared against other documents in its own case — no cross-case/library-wide comparison logic runs yet.

SignatureReferenceResponse

One signature_references row returned by the API.

Field	Type	Required	Description
`id`	string (uuid)	yes	
`person_name`	string	yes	
`signature_image_url`	string (nullable)	yes	
`bounding_box`	object (nullable)	yes	
`source_document_id`	string (uuid)	yes	
`source_case_id`	string (uuid)	yes	
`created_by`	string (uuid)	yes	
`is_library`	boolean	yes	
`created_at`	string (date-time)	yes	

TokenResponse

Field	Type	Required	Description
`access_token`	string	yes	JWT. Send as `Authorization: Bearer <token>`.
`token_type`	string	no	Always `bearer`.

UploadLimitsResponse

The calling company's upload limits, as enforced on its next upload.

Field	Type	Required	Description
`max_file_size_mb`	integer	yes	Largest document, in MB (1 MB = 1,048,576 bytes).
`max_zip_size_mb`	integer	yes	Largest bulk-upload zip, in MB.
`max_file_size_bytes`	integer	yes	
`max_zip_size_bytes`	integer	yes	

UsageResponse

Field	Type	Required	Description
`period`	string: `"this_month"`, `"last_month"`, `"last_30_days"`, `"this_year"`, `"all_time"`, `"custom"`	yes	
`start`	string (date) (nullable)	yes	First UTC day included (null = from the beginning).
`end`	string (date) (nullable)	yes	Last UTC day included (null = up to today).
`companies`	array of CompanyUsageRow	yes	
`totals`	UsageTotals	yes	

UsageTotals

Field	Type	Required	Description
`cases_created`	integer	yes	
`documents_uploaded`	integer	yes	
`files_stored`	integer	yes	
`storage_bytes`	integer	yes	
`total_storage_bytes`	integer	yes	
`total_files_stored`	integer	yes	

UserAdminResponse

Field	Type	Required	Description
`id`	string (uuid)	yes	
`email`	string (email)	yes	
`full_name`	string (nullable)	yes	
`role`	UserRole	yes	
`is_active`	boolean	yes	
`created_at`	string (date-time)	yes	
`company_id`	string (uuid) (nullable)	yes	Null for platform admins.
`company_name`	string (nullable)	yes	

UserAdminUpdate

Field	Type	Required	Description
`role`	UserRole (nullable)	no	New role. Cannot be changed on your own account.
`company_id`	string (uuid) (nullable)	no	Move the user to another company (company roles only).
`is_active`	boolean (nullable)	no	False deactivates the account. Not allowed on yourself.

UserCreate

An account created by an administrator (there is no self-service sign-up). The password is set here and only ever stored hashed.

Field	Type	Required	Description
`email`	string (email)	yes	Login email. Unique regardless of letter case.
`full_name`	string (nullable)	no	Display name (optional).
`role`	UserRole	no	`user`, `reviewer_l1`, `reviewer_l2` or `platform_admin`.
`company_id`	string (uuid) (nullable)	no	Required for company roles; must be empty for `platform_admin`.
`password`	string	yes	Initial password (8-128 chars); stored hashed.

UserPasswordReset

Field	Type	Required	Description
`password`	string	yes	New password (8-128 chars); stored hashed.

UserRole

Allowed values: `"user"`, `"reviewer_l1"`, `"reviewer_l2"`, `"platform_admin"`

UserSummary

Field	Type	Required	Description
`id`	string (uuid)	yes	
`email`	string	yes	
`full_name`	string (nullable)	yes	

ValidationError

Field	Type	Required	Description
`loc`	array of string | integer	yes	
`msg`	string	yes	
`type`	string	yes	