

Our Solution(s)

Run Code

Your Solutions

Run Code

Solution 1

Solution 2

```
1 // Copyright © 2020 AlgoExpert, LLC. All rights reserved.
2
3 #include <vector>
4 #include <climits>
5 using namespace std;
6
7 // O(nk) time | O(n) space
8 int maxProfitWithKTransactions(vector<int> prices, int k) {
9     if (prices.size() == 0) {
10         return 0;
11     }
12     int *evenProfits = new int[prices.size()];
13     int *oddProfits = new int[prices.size()];
14     for (int i = 0; i < prices.size(); i++) {
15         evenProfits[i] = 0;
16         oddProfits[i] = 0;
17     }
18     for (int t = 1; t < k + 1; t++) {
19         int maxThusFar = INT_MIN;
20         int *currentProfits = new int[prices.size()];
21         int *previousProfits = new int[prices.size()];
22         if (t % 2 == 1) {
23             currentProfits = oddProfits;
24             previousProfits = evenProfits;
25         } else {
26             currentProfits = evenProfits;
27             previousProfits = oddProfits;
28         }
29         for (int d = 1; d < prices.size(); d++) {
30             maxThusFar = max(maxThusFar, previousProfits[d - 1] - prices[d -
31             currentProfits[d] = max(currentProfits[d - 1], maxThusFar + pric
32         }
33     }
```

Solution 1

Solution 2

Solution 3

```
1 #include <vector>
2 using namespace std;
3
4 int maxProfitWithKTransactions(vector<int> prices, int k) {
5     // Write your code here.
6     return -1;
7 }
8
```

Our Tests

Custom Output

Submit Code

Run or submit code when you're ready.