

Solution 1 Solution 2

```

1 // Copyright © 2020 AlgoExpert, LLC. All rights reserved.
2
3 #include <set>
4 #include <unordered_map>
5 #include <algorithm>
6 #include <climits>
7 #include <vector>
8 using namespace std;
9
10 int getMinSpaces(string pi, set<string> numbersTable,
11                 unordered_map<int, int> *cache, int idx);
12
13 // O(n^3 + m) time | O(n + m) space - where n is the number of digits
14 // m is the number of favorite numbers
15 int numbersInPi(string pi, vector<string> numbers) {
16     set<string> numbersTable;
17     for (string number : numbers) {
18         numbersTable.insert(number);
19     }
20     unordered_map<int, int> cache;
21     for (int i = pi.length() - 1; i >= 0; i--) {
22         getMinSpaces(pi, numbersTable, &cache, i);
23     }
24     return cache.at(0) == INT_MAX ? -1 : cache.at(0);
25 }
26
27 int getMinSpaces(string pi, set<string> numbersTable,
28                 unordered_map<int, int> *cache, int idx) {
29     if (idx == pi.length())
30         return -1;
31     if (cache->find(idx) != cache->end())
32         return cache->at(idx);
33     int minSpaces = INT_MAX;

```

Solution 1	Solution 2	Solution 3
------------	------------	------------

```
1 #include <vector>
2 using namespace std;
3
4 int numbersInPi(string pi, vector<string> numbers) {
5     // Write your code here.
6     return -1;
7 }
8
```

```
2. string ID = "XXXXXXXXXXXXXXX";
```
