Our Solution(s) Run Code

Solution 1 Solution 2

```go
// Copyright © 2020 AlgoExpert, LLC. All rights reserved.

package main

// O(log(n)) time | O(log(n)) space
func SearchForRange(array []int, target int) []int {
  finalRange := []int{-1, -1}
  alteredBinarySearch(array, target, 0, len(array)-1, finalRange, tru
  alteredBinarySearch(array, target, 0, len(array)-1, finalRange, fal
  return finalRange
}

func alteredBinarySearch(array []int, target, left, right int, finalR
  if left > right {
    return
  }
  mid := (left + right) / 2
  if array[mid] < target {
    alteredBinarySearch(array, target, mid+1, right, finalRange, goLef
  } else if array[mid] > target {
    alteredBinarySearch(array, target, left, mid-1, finalRange, goLeft
  } else {
    if goLeft {
      if mid == 0 || array[mid-1] != target {
        finalRange[0] = mid
      } else {
        alteredBinarySearch(array, target, left, mid-1, finalRange, go
      }
    } else {
      if mid == len(array)-1 || array[mid+1] != target {
        finalRange[1] = mid
      } else {
        alteredBinarySearch(array, target, mid+1, right, finalRange, g
```

Your Solutions Run Code

Solution 1 Solution 2 Solution 3

```go
package main

func SearchForRange(array []int, target int) []int {
  // Write your code here.
  return nil
}

```

Our Tests

Custom Output Submit Code

Run or submit code when you're ready.