29 } 30

32

33

31 function isInUpperRight(coord1, coord2) {

const [x1, y1] = coord1; const [x2, y2] = coord2; 14рх

Your Solutions

Run Code

Our Solution(s) Run Code

```
Solution 1 Solution 2
                         Solution 3
 1 // Copyright © 2020 AlgoExpert, LLC. All rights reserved.
 3 // O(n^2) time | O(n) space - where n is the number of coordinates
4 function rectangleMania(coords) {
    const coordsTable = getCoordsTable(coords);
     return getRectangleCount(coords, coordsTable);
7 }
9 function getCoordsTable(coords) {
10
    const coordsTable = {};
11
     for (const coord of coords) {
12
      const coordString = coordToString(coord);
13
       coordsTable[coordString] = true;
14
15
     return coordsTable;
16 }
17
18 function getRectangleCount(coords, coordsTable) {
19
     let rectangleCount = 0;
20
     for (const [x1, y1] of coords) \{
21
       for (const [x2, y2] of coords) {
22
         if (!isInUpperRight([x1, y1], [x2, y2])) continue;
         const upperCoordString = coordToString([x1, y2]);
         const rightCoordString = coordToString([x2, y1]);
25
         if (upperCoordString in coordsTable && rightCoordString in coord
26
27
28
     return rectangleCount;
```

```
function rectangleMania(coords) {
   // Write your code here.
}

// Do not edit the line below.
exports.rectangleMania = rectangleMania;
```

 Our Tests
 Custom Output
 Submit Code

Run or submit code when you're ready.

for each program to heightful contract. In this short to

,iii