

```
MariaDB [supplier]> create table SUPPLIERS
-> (
-> sid integer,
-> sname varchar(30),
-> address varchar(30),
-> PRIMARY KEY(sid)
-> );
```

Query OK, 0 rows affected (0.277 sec)

```
MariaDB [supplier]>
MariaDB [supplier]> CREATE TABLE PARTS
-> (
-> pid integer,
-> pname varchar(30),
-> color varchar(30),
-> PRIMARY KEY(pid)
-> );
```

Query OK, 0 rows affected (0.025 sec)

```
MariaDB [supplier]> create table CATALOGUE
-> (
-> sid integer,
-> pid integer,
-> cost VARCHAR(30),
-> FOREIGN KEY (sid) REFERENCES SUPPLIERS(sid),
-> FOREIGN KEY (pid) REFERENCES PARTS(pid)
-> );
```

Query OK, 0 rows affected (0.023 sec)

```
MariaDB [supplier]> insert into SUPPLIERS VALUES(10001,'
Acmewidget','bangalore');
```

Query OK, 1 row affected (0.026 sec)

```
MariaDB [supplier]> insert into SUPPLIERS VALUES(10002,'
jhons','kolkata');
```

Query OK, 1 row affected (0.009 sec)

```
MariaDB [supplier]> insert into SUPPLIERS VALUES(10003,'
vimal','mumbai');
```

Query OK, 1 row affected (0.002 sec)

```

MariaDB [supplier]> insert into SUPPLIERS VALUES(10002,'jhons','kolkata');
Query OK, 1 row affected (0.009 sec)

MariaDB [supplier]> insert into SUPPLIERS VALUES(10003,'vimal','mumbai');
Query OK, 1 row affected (0.002 sec)

MariaDB [supplier]> insert into SUPPLIERS VALUES(10004,'reliance','delhi');
Query OK, 1 row affected (0.008 sec)

MariaDB [supplier]> insert into PARTS VALUES(20001,'book','red');
Query OK, 1 row affected (0.015 sec)

MariaDB [supplier]> insert into PARTS VALUES(20002,'pen','red');
Query OK, 1 row affected (0.006 sec)

MariaDB [supplier]> insert into PARTS VALUES(20003,'pencil','green');
Query OK, 1 row affected (0.003 sec)

MariaDB [supplier]> insert into PARTS VALUES(20004,'mobile','green');
Query OK, 1 row affected (0.002 sec)

MariaDB [supplier]> insert into PARTS VALUES(20005,'charger','black');
Query OK, 1 row affected (0.004 sec)

```

```

Query OK, 1 row affected (0.002 sec)

MariaDB [supplier]> insert into PARTS VALUES(20005,'charger','black');
Query OK, 1 row affected (0.004 sec)

MariaDB [supplier]> insert into CATALOGUE VALUES(10001,20001,10);
Query OK, 1 row affected (0.033 sec)

MariaDB [supplier]> insert into CATALOGUE VALUES(10001,20002,10);
Query OK, 1 row affected (0.025 sec)

MariaDB [supplier]> insert into CATALOGUE VALUES(10001,20003,30);
Query OK, 1 row affected (0.084 sec)

MariaDB [supplier]> insert into CATALOGUE VALUES(10001,20004,10);
Query OK, 1 row affected (0.025 sec)

MariaDB [supplier]> insert into CATALOGUE VALUES(10001,20005,10);
Query OK, 1 row affected (0.037 sec)

MariaDB [supplier]> insert into CATALOGUE VALUES(10002,20001,10);
Query OK, 1 row affected (0.025 sec)

MariaDB [supplier]> insert into CATALOGUE VALUES(10002,20002,20);
Query OK, 1 row affected (0.024 sec)

MariaDB [supplier]> insert into CATALOGUE VALUES(10003,20003,30);
Query OK, 1 row affected (0.024 sec)

MariaDB [supplier]> insert into CATALOGUE VALUES(10004,20003,40);
Query OK, 1 row affected (0.046 sec)

MariaDB [supplier]> select * from SUPPLIERS;
+-----+-----+-----+
| sid  | sname | address |
+-----+-----+-----+
| 10001 | AcmeWidget | bangalore |
| 10002 | jhons   | kolkata   |
| 10003 | vimal   | mumbai    |
| 10004 | reliance | delhi     |
+-----+-----+-----+
4 rows in set (0.002 sec)

MariaDB [supplier]> SELECT * FROM PARTS;
+-----+-----+-----+
| partid | pname | color |
+-----+-----+-----+
| 20001  | book  | red    |
| 20002  | pen   | red    |
| 20003  | pencil | green  |
| 20004  | mobile | green  |
| 20005  | charger | black  |
+-----+-----+-----+
5 rows in set (0.002 sec)

```

```
MariaDB [supplier]> SELECT * FROM PARTS;
```

pid	pname	color
20001	book	red
20002	pen	red
20003	pencil	green
20004	mobile	green
20005	charger	black

```
5 rows in set (0.002 sec)
```

```
MariaDB [supplier]> SELECT * FROM CATALOGUE;
```

sid	pid	cost
10001	20001	10
10001	20002	10
10001	20003	30
10001	20004	10
10001	20005	10
10002	20001	10
10002	20002	20
10003	20003	30
10004	20003	40

```
9 rows in set (0.002 sec)
```

```
MariaDB [supplier]> SELECT pname FROM PARTS,CATALOGUE WHERE CATALOGUE.pid=PARTS.pid AND CATALOGUE.sid IS NOT NULL;
```

```
+-----+
| pname |
+-----+
| book  |
| pen   |
| pencil|
| mobile|
| charger|
| book  |
| pen   |
| pencil|
| pencil|
+-----+
```

```
9 rows in set (0.047 sec)
```

```
MariaDB [supplier]> SELECT S.sname FROM SUPPLIERS S WHERE NOT EXISTS((SELECT P.pid FROM PARTS P ) EXCEPT (SELECT C.pid FROM CATALOGUE C WHERE C.sid = S.sid));
```

```
+-----+
| sname |
+-----+
| AcmeWidget |
+-----+
```

```
1 row in set (0.029 sec)
```

```
MariaDB [supplier]> SELECT S.sname FROM SUPPLIERS S WHERE NOT EXISTS (( SELECT P.pid FROM PARTS P WHERE P.color = 'Red') EXCEPT ( SELECT C.pid FROM CATALOGUE C, PARTS P WHERE C.sid = S.sid AND C.pid = P.pid AND P.color = 'Red' ));
```

```
+-----+
| sname |
+-----+
| AcmeWidget |
| Jhons    |
+-----+
```

```
2 rows in set (0.017 sec)
```

```
MariaDB [supplier]> SELECT P.pname FROM PARTS P, CATALOGUE C, SUPPLIERS S WHERE P.pid = C.pid AND C.sid = S.sid
AND S.sname = 'Acmewidget' AND NOT EXISTS ( SELECT *FROM CATALOGUE C1,SUPPLIERS S1 WHERE P.pid = C1.pid AND C1
.sid = S1.sid AND S1.sname<>'Acmewidget');
```

```
+-----+
| pname |
+-----+
| mobile |
| charger |
+-----+
```

2 rows in set (0.003 sec)

```
MariaDB [supplier]> SELECT DISTINCT C.sid FROM CATALOGUE C WHERE C.cost> ( SELECT AVG (C1.cost) FROM CATALOGUE
C1 WHERE C1.pid = C.pid );
```

```
+-----+
| sid |
+-----+
| 10002 |
| 10004 |
+-----+
```

2 rows in set (0.021 sec)

```
MariaDB [supplier]> SELECT P.pid, S.sname FROM PARTS P, SUPPLIERS S, CATALOGUE C WHERE C.pid = P.pid AND C.sid
= S.sid AND C.cost = (SELECT MAX (C1.cost) FROM CATALOGUE C1 WHERE C1.pid = P.pid);
ERROR 1630 (42000): FUNCTION supplier.MAX does not exist. Check the 'Function Name Parsing and Resolution' sect
ion in the Reference Manual
```

```
MariaDB [supplier]>
```

```
MariaDB [supplier]> SELECT P.pid, S.sname FROM PARTS P, SUPPLIERS S, CATALOGUE C WHERE C.pid = P.pid AND C.sid
= S.sid AND C.cost = (SELECT MAX(C1.cost) FROM CATALOGUE C1 WHERE C1.pid = P.pid);
```

```
+-----+-----+
| pid | sname |
+-----+-----+
| 20001 | Acmewidget |
| 20004 | Acmewidget |
| 20005 | Acmewidget |
| 20001 | jhons |
| 20002 | jhons |
| 20003 | reliance |
+-----+-----+
```

6 rows in set (0.202 sec)

```
MariaDB [supplier]> █
```