| | |
|---|---|
| **Status** | Finished |
| **Started** | Sunday, 18 October 2026, 6:26 PM |
| **Completed** | Sunday, 18 October 2026, 6:30 PM |
| **Duration** | 3 mins 41 secs |
| **Grade** | **15.00** out of 15.00 (**100**%) |

Question **1**

Correct

Mark 1.00 out of 1.00

What will be the output of below Python code?

```
tupl=("python","programming","Computer")
print(tupl[-3:0])
```

a. Computer

b. () ✓

c. (Computer)

d. Error

Question **2**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
True

b. False
False

c. True ✓
True

d. True
False

Question **3**

Correct

Mark 1.00 out of 1.00

Write the Output of the following Code?

t = (15,83,83,52,60,45,52,85,100)

print(min(t)+max(t)+t.count(52))

- a. 2
- b. Error
- c. 100
- d. 117 ✓

Question **4**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t1 = (1,2,3)
t2 = (4,5,6)
x = t1+t2
print(x)
```

- a. Error
- b. (1,2,3,4,5,6) ✓
- c. (1,2,3)(4,5,6)
- d. (1,2,3,3,2,1)

Question **5**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={2,5,3}

set2={3,1}

set3={}

set3=set1&set2

print(set3)
```

a. {2,5,1}

b. {3} ✓

c. {}

d. {2,5,3,1}

Question **6**

Correct

Mark 1.00 out of 1.00

```
What is the output of the following code?
```

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

a. (30, 40, 50)(40, 50, 60, 70, 80)

b. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

c. (10, 20, 30, 40) (40, 50, 60, 70, 80)

d. (30, 40, 50) (10, 20, 30, 40)

Question **7**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
>>>t = (1, 2, 4, 3, 8, 9)
>>>[t[i] for i in range(0, len(t), 2)]
```

- a. (1, 4, 8)
- b. [1, 4, 8] ✓
- c. [2, 3, 9]
- d. [1, 2, 4, 3, 8, 9]

Question **8**

Correct

Mark 1.00 out of 1.00

Select which is true for Python tuple?

- a. We can change the tuple once created
- b. None of these
- c. A tuple is unordered
- d. A tuple maintains the order of items ✓

Question **9**

Correct

Mark 1.00 out of 1.00

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

- a. ['8', '30', '3', '2'] ✓
- b. ['30', '8', '3', '2']
- c. ['2', '3', '8', '30']
- d. ['2', '3', '30', '8']

Question **10**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

t = (58, 47, 36, 25, 14, 3)

x = t[2:-1]

print(x)

a. Error

b. (3,14,25)

c. (36, 25, 14) ✓

d. (58,47,36,25)

Question **11**

Correct

Mark 1.00 out of 1.00

What will be the output of the below Python code?

t1=(55,12,78,64,25)

t1.pop(12)

print(tuple1)

a. Error ✓

b. (55,78,64,25)

c. (12)

d. 12

Question **12**

Correct

Mark 1.00 out of 1.00

What will set1|set2 do?

```
If set1={"a","b",3}
set2={3,7}
```

a. A new set will be created with the unique elements of set1 and set2.

b. Elements of set2 will get appended to set1

c. A new set will be created with the elements of both set1 and set2 ✓

d. Elements of set1 will get appended to set2

Question **13**

Correct

Mark 1.00 out of 1.00

Which of the following options will not result in an error when performed on tuples in Python where tupl=(5,2,7,0,3)?

a. tupl1=tupl+tupl ✓

b. tupl.sort()

c. tupl.append(2)

d. tupl[1]=2

Question **14**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
list1=[1,3,4,2]

x=list1.pop(2)

print(set([x]))
```

a. {2}

b. {1,3,2}

c. {1,3,4}

d. {4} ✓

Question **15**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. False

b. True ✓