routes\main_routes.py

```
from flask import Blueprint, render_template, request, redirect, url_for
from datetime import datetime, timezone, timedelta
import math
from services.orchestrator import data_orchestrator
from utils.filters import FilterService

main_bp = Blueprint('main', __name__)
filter_service = FilterService()

@main_bp.route("/")
def index():
"""Main dashboard route"""
try:
print("[Flask] Loading dashboard...")

year = request.args.get('year', type=int)
month = request.args.get('month', type=int)
day = request.args.get('day', type=int)
severity_filter = request.args.get('severity')
search_query = request.args.get('q')
timeline_years = request.args.get('timeline_years', default=1, type=int)

if timeline_years not in [1, 2, 3, 5]:
timeline_years = 1

print(f"[Flask] Filters: year={year}, month={month}, day={day},
severity={severity_filter}, search={search_query}, timeline_years={timeline_years}")

dashboard_data = data_orchestrator.get_dashboard_data(
year=year,
month=month,
day=day,
severity_filter=severity_filter,
timeline_years=timeline_years,
load_historical=True
)

if search_query:
filtered_cves = filter_service.filter_by_search(dashboard_data['latest_cves'],
search_query)

from collections import Counter
severity_counts = Counter()
for cve in filtered_cves:
severity = cve.get('Severity', 'UNKNOWN').upper()
if severity in ['CRITICAL', 'HIGH', 'MEDIUM', 'LOW']:
severity_counts[severity] += 1
else:
severity_counts['UNKNOWN'] += 1

dashboard_data['metrics'] = {
'CRITICAL': severity_counts.get('CRITICAL', 0),
'HIGH': severity_counts.get('HIGH', 0),
'MEDIUM': severity_counts.get('MEDIUM', 0),
'LOW': severity_counts.get('LOW', 0),
'UNKNOWN': severity_counts.get('UNKNOWN', 0)
}
dashboard_data['total_cves'] = len(filtered_cves)
dashboard_data['latest_cves'] = filtered_cves

total = len(filtered_cves)
if total > 0:
dashboard_data['severity_percentage'] = {}
for key in ['CRITICAL', 'HIGH', 'MEDIUM', 'LOW', 'UNKNOWN']:
percentage = round((severity_counts.get(key, 0) * 100 / total))
dashboard_data['severity_percentage'][key] = f"{percentage}%"
else:
dashboard_data['severity_percentage'] = {k: "0%" for k in ['CRITICAL', 'HIGH', 'MEDIUM',
'LOW', 'UNKNOWN']}

dashboard_data['note_text'] = f"Showing search results for '{search_query}'"
```

```
return render_template(
"pages/dashboard.html",
metrics=dashboard_data['metrics'],
total_cves=dashboard_data['total_cves'],
available_years=dashboard_data['available_years'],
available_months=dashboard_data['available_months'],
timeline_data_days=dashboard_data['timeline_data_days'],
timeline_data_years=dashboard_data['timeline_data_years'],
severity_stats=dashboard_data['metrics'],
severity_percentage=dashboard_data['severity_percentage'],
cwe_radar=dashboard_data['cwe_radar'],
cwe_radar_all=dashboard_data['cwe_radar_all'],
cwe_radar_weighted=dashboard_data['cwe_radar_weighted'],
cwe_radar_descriptions=dashboard_data['cwe_radar_descriptions'],
historical_loaded=dashboard_data.get('historical_loaded', False),
year_filter=year,
month_filter=month,
day_filter=day,
severity_filter=severity_filter,
search_query=search_query,
timeline_years=timeline_years
)

except Exception as e:
print(f"[Flask] Dashboard error: {e}")
import traceback
traceback.print_exc()

return render_template(
"pages/dashboard.html",
metrics={'CRITICAL': 0, 'HIGH': 0, 'MEDIUM': 0, 'LOW': 0, 'UNKNOWN': 0},
total_cves=0,
available_years=list(range(datetime.now().year, 1998, -1)),
available_months=list(range(1, 13)),
timeline_data_days={'labels': [], 'values': []},
timeline_data_years={'labels': [], 'values': []},
severity_stats={'CRITICAL': 0, 'HIGH': 0, 'MEDIUM': 0, 'LOW': 0, 'UNKNOWN': 0},
severity_percentage={'CRITICAL': '0%', 'HIGH': '0%', 'MEDIUM': '0%', 'LOW': '0%',
'UNKNOWN': '0%'},
cwe_radar={'indices': [], 'labels': [], 'values': []},
cwe_radar_all={},
cwe_radar_weighted={'indices': [], 'labels': [], 'values': []},
cwe_radar_descriptions={},
historical_loaded=False,
year_filter=None,
month_filter=None,
day_filter=None,
severity_filter=None,
search_query=None,
timeline_years=1
)


@main_bp.route("/vulnerabilities")
def vulnerabilities():
"""Vulnerabilities listing page"""
try:
year = request.args.get('year', type=int)
month = request.args.get('month', type=int)
day = request.args.get('day', type=int)
severity_filter = request.args.get('severity')
search_query = request.args.get('q')
page = request.args.get('page', default=1, type=int)
per_page = 20

print(f"[Flask] Vulnerabilities filters: year={year}, month={month}, day={day},
severity={severity_filter}, search={search_query}")

all_cves = data_orchestrator.get_filtered_cves(year=year, month=month, day=day)
print(f"[Flask] Got {len(all_cves)} CVEs from orchestrator")

if severity_filter:
all_cves = filter_service.filter_by_severity(all_cves, severity_filter)
print(f"[Flask] After severity filter: {len(all_cves)} CVEs")

if search_query:
all_cves = filter_service.filter_by_search(all_cves, search_query)
```

```
print(f"[Flask] After search filter: {len(all_cves)} CVEs")

all_cves = sorted(all_cves, key=lambda x: x.get('Published', ''), reverse=True)

total_results = len(all_cves)
total_pages = max(1, math.ceil(total_results / per_page))
current_page = max(1, min(page, total_pages))
start_index = (current_page - 1) * per_page
end_index = start_index + per_page
cves_page = all_cves[start_index:end_index]

page_numbers = filter_service.generate_page_numbers(current_page, total_pages)

note_text = filter_service.generate_note_text(year, month, day)
if severity_filter:
note_text += f" (filtered by {severity_filter.lower()} severity)"
if search_query:
note_text += f" (search: '{search_query}')"

print(f"[Flask] Returning {len(cves_page)} CVEs for page {current_page}")

return render_template(
"pages/vulnerabilities.html",
latest_cves=cves_page,
year_filter=year,
month_filter=month,
day_filter=day,
severity_filter=severity_filter,
search_query=search_query,
available_years=list(range(datetime.now().year, 1998, -1)),
available_months=list(range(1, 13)),
current_page=current_page,
total_pages=total_pages,
page_numbers=page_numbers,
total_results=total_results,
note_text=note_text
)

except Exception as e:
print(f"[Flask] Vulnerabilities page error: {e}")
import traceback
traceback.print_exc()

return render_template(
"pages/vulnerabilities.html",
latest_cves=[],
total_results=0,
note_text="Error loading vulnerabilities"
)


@main_bp.route("/cve/<cve_id>")
def cve_detail(cve_id):
"""CVE detail page"""
try:
cve = data_orchestrator.get_cve_detail(cve_id)
return render_template("pages/cve_detail.html", cve=cve)
except Exception as e:
print(f"[Flask] CVE detail error: {e}")
return render_template("pages/cve_detail.html", cve={'ID': cve_id, 'Description': 'Error
loading CVE details'})
```