

# **TAG DESCRIPTION TABLE**

7700H-CV9D0P0

July 2014



# abbrsect

## Abbreviation Section

*Description:* Identifies the paragraph used to define abbreviations/acronyms and the associated list.

*Source paragraph:* 4.3.4 and 4.5.9 (MIL-STD-38784)

*Content Model:* (([title](#), [warning\\*](#), [caution?](#), [note?](#), ([para](#), [note?](#))?, ([step1](#), [step1+](#))?, [subpara1\\*](#))?, ([abbrtitle?](#), [acronymlist](#)))

*Parents:* [intro](#)

*Entities used in this element:* [bodyatt](#), [chgatt](#), [delstat](#), [para0att](#), [parazero](#), [secur](#), [status](#), [verified](#), [wcn](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                          | Default  | Description                                                                                                                                                                                                           |
|-----------|-------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| emergency | NUMBER                        | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                                                                       |
| id        | ID                            | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                                                                                      |
| esds      | NUMBER                        | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the <b>**ESD**</b> symbol by setting this attribute equal to "1". |
| nsp       | NUMBER                        | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the <b>**NSP**</b> symbol by setting this attribute equal to "1".                                                               |
| fcf       | NUMBER                        | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the <b>**FCP**</b> symbol by setting this attribute equal to "1".                                                       |
| hcp       | NUMBER                        | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the <b>**HCP**</b> symbol by setting this attribute equal to "1".                                                           |
| hci       | NUMBER                        | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the <b>**HCI**</b> symbol by setting this attribute equal to "1".                                                                   |
| ocp       | NUMBER                        | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the <b>**OCP**</b> symbol by setting this attribute equal to "1".                                                       |
| oci       | NUMBER                        | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the <b>**OCI**</b> symbol by setting this attribute equal to "1".                                                               |
| applicref | IDREFS                        | #IMPLIED | Allows the author to assign an applicability/effectivity reference to this element.                                                                                                                                   |
| verdate   | CDATA                         | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                                         |
| verrem    | CDATA                         | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                                |
| verstatus | (unver   ver   notapplicable) | unver    | Identifies the verification status of the element.                                                                                                                                                                    |
| security  | (u   c   s   n)               | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.                                                         |
| caveat    | CDATA                         | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                                      |
| fgi       | CDATA                         | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.                                                        |
| label     | CDATA                         | #IMPLIED | Allows the author to label this element manually. The FOSI automatically generates labels, so its use is not necessary unless a label out of the ordinary is desired.                                                 |
| sssn      | CDATA                         | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                                                                   |

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is not currently supported by the FOSI.                                 |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# abbrtitle

## Abbreviation Title

*Description:* Identifies the title for the list of acronyms and abbreviations.

*Source paragraph:* 4.3.4 and 4.5.9 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+) -([figure](#) | [table](#) | [foldout](#) | [objmedia](#))

*Parents:* [abbrsect](#)

*Entities used in this element:* [chgtat](#), [delstat](#), [exclus](#), [secur](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

---

# acronym

## Acronym

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies the first time an acronym or abbreviation is used in a chapter. The def part of the acronym is used to define the acronym/abbreviation, while the term part of the acronym contains the actual acronym/abbreviation. Within the text, the term portion will be surrounded with parenthesis.                                                                                                                                                                                                                                                                                                                                                       |
| <i>Source paragraph:</i>              | 4.3.4 and 4.5.9 (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <i>Content Model:</i>                 | (def, term) -(acronym   figure   table   foldout   objmedia)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <i>Parents:</i>                       | abbrtitle, activity, address, applicabil, apptitle, authnot, change, chgdate, chgnum, chgpara, chgtxt, clink, cogact, contractno, copyright, dataiden, date, dateinc, def, destr, discl, distrib, doctype, ecpno, effdatenot, emphasis, entry, expcont, extapplicabil, figno, ftnote, hazmat, ilink, insertpg, internatlst, item, label, lepchg, leppage, letter, line, maintlvl, mfr, modelno, moveddata, nmlist, nomen, nsn, oadr, pageno, para, param, partno, phrase, pretmidno, pubdate, remarks, removepg, revnum, seqno, serno, sigblock, subject, subtitle, supersed, suppl, symtitle, tabno, term, tfnid, title, tmidno, typedes, typeno, underline |
| <i>Excluded in:</i>                   | acronym, acronymlist                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <i>Entities used in this element:</i> | chgatt, delstat, exclus, status, yesorno                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# acronymlist

## Acronym/Abbreviation List

|                                       |                                                                               |
|---------------------------------------|-------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies the list of acronyms and abbreviations.                            |
| <i>Source paragraph:</i>              | 4.3.4 and 4.5.9 (MIL-STD-38784)                                               |
| <i>Content Model:</i>                 | (acronymrow+   (term, def)+) -(acronym   figure   table   foldout   objmedia) |
| <i>Parents:</i>                       | abbrsect                                                                      |
| <i>Entities used in this element:</i> | chgatt, delstat, exclus, status, yesorno                                      |

### ATTRIBUTE LIST

| Attribute  | Type                                  | Default  | Description                                                                                                                      |
|------------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------|
| rtermwidth | NUTOKEN                               | 2.5in    | Allows the author to define the width of the right column, which typically contains the definitions of the acronym/abbreviation. |
| ltermwidth | NUTOKEN                               | 1in      | Allows the author to define the width of the left column, which typically contains the acronym/abbreviation.                     |
| autobuild  | CDATA                                 | #CONREF  | Set this attribute equal to "1" when the output of this element should be auto-generated.                                        |
| delttype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.    |
| inschlvl   | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                       |
| delchlvl   | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                        |
| status     | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.           |
| revchg     | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                             |

# acronymrow

## Acronym/Abbreviation List Row

*Description:* Identifies a set of term and definition for an acronym/abbreviation list.

*Source paragraph:* 4.3.4 and 4.5.9 (MIL-STD-38784)

*Content Model:* ([term](#), [def](#))

*Parents:* [acronymlist](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# action

## Action

*Description:* Checklist Step Action

*Source paragraph:* N/A

Content Model: ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

Parents: [clitem](#)

Excluded in: [ifstep1](#), [ifstep2](#), [ifstep3](#)

Entities used in this element: [chgatt](#), [delstat](#), [secur](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                 |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated                                                           |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                                                                          |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                           |

# addcond

## Additional Conditions

Description: Used to break the current page to a verso page to place "Other Considerations".

Source paragraph: N/A

Content Model: (([symbs1](#), ([para](#)|([paras](#), [paras](#)+)))<sup>\*</sup>, [endcond](#)?) +([warning](#) | [caution](#))

Included in: [clsection](#), [emergproccl](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

# amplification

## Amplification

*Description:* Provides further clarification of a step.

*Source paragraph:* 3.2.12.1.2 and 3.2.12.1.2.1 (MIL-DTL-7700)

*Content Model:* (((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#)) + | [randlist](#) | [deflist](#) | [seqlist](#)) +)

*Parents:* [clitem](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [list](#), [paracon](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

# applic

## Applicability/Effectivity Definition Entry

*Description:* Defines applicability/effectivity markings.

*Source paragraph:* 4.3f and 4.5.9 (MIL-STD-38784)

*Content Model:* ([term](#), [def](#))

*Parents:* [applicdef](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                           | Default   | Description                                                                                                                   |
|-----------|--------------------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------|
| id        | ID                             | #REQUIRED | Allows the author to generate a unique ID for use when referencing this element.                                              |
| flagnote  | NUMBER                         | 1         | Set this attribute equal to "1" to use flagnotes (TV Screens) to display Effectivity.                                         |
| delttype  | (delete   real   reserve   NA) | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |



| Attribute | Type                                  | Default  | Description                                                                                                            |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------|
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.             |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.              |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element. |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                   |

# applicabil

## Applicability/Effectivity

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies a portion of text as being applicable to a specific model, serial number, part number, etc. Use of this element will cause the applicability/effectivity markings defined in the applicability definition (applicdef) to appear at that point in running text.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <i>Source paragraph:</i>              | 4.3f (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <i>Content Model:</i>                 | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">fnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcp</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> )+) -( <a href="#">applicabil</a>   <a href="#">figure</a>   <a href="#">table</a>   <a href="#">foldout</a>   <a href="#">objmedia</a> )                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <i>Parents:</i>                       | <a href="#">abbrtitle</a> , <a href="#">activity</a> , <a href="#">address</a> , <a href="#">applicabil</a> , <a href="#">apptitle</a> , <a href="#">authnot</a> , <a href="#">change</a> , <a href="#">chgdate</a> , <a href="#">chgnum</a> , <a href="#">chgpara</a> , <a href="#">chgtxt</a> , <a href="#">clink</a> , <a href="#">cogact</a> , <a href="#">contractno</a> , <a href="#">copyright</a> , <a href="#">dataiden</a> , <a href="#">date</a> , <a href="#">dateinc</a> , <a href="#">def</a> , <a href="#">destr</a> , <a href="#">discl</a> , <a href="#">distrib</a> , <a href="#">doctype</a> , <a href="#">ecpno</a> , <a href="#">effdatenot</a> , <a href="#">emphasis</a> , <a href="#">entry</a> , <a href="#">expcont</a> , <a href="#">extapplicabil</a> , <a href="#">figno</a> , <a href="#">fnote</a> , <a href="#">hazmat</a> , <a href="#">ilink</a> , <a href="#">insertpg</a> , <a href="#">internatlstd</a> , <a href="#">item</a> , <a href="#">label</a> , <a href="#">lepchg</a> , <a href="#">leppage</a> , <a href="#">letter</a> , <a href="#">line</a> , <a href="#">maintlvl</a> , <a href="#">mfr</a> , <a href="#">modelno</a> , <a href="#">moveddata</a> , <a href="#">nmlist</a> , <a href="#">nomen</a> , <a href="#">nsn</a> , <a href="#">oadr</a> , <a href="#">pageno</a> , <a href="#">para</a> , <a href="#">param</a> , <a href="#">partno</a> , <a href="#">phrase</a> , <a href="#">pretmidno</a> , <a href="#">pubdate</a> , <a href="#">remarks</a> , <a href="#">removepg</a> , <a href="#">revnum</a> , <a href="#">seqno</a> , <a href="#">serno</a> , <a href="#">sigblock</a> , <a href="#">subject</a> , <a href="#">subtitle</a> , <a href="#">supersed</a> , <a href="#">suppl</a> , <a href="#">symtitle</a> , <a href="#">tabno</a> , <a href="#">term</a> , <a href="#">tfnid</a> , <a href="#">title</a> , <a href="#">tmidno</a> , <a href="#">typesdes</a> , <a href="#">typeno</a> , <a href="#">underline</a> |
| <i>Excluded in:</i>                   | <a href="#">applicabil</a> , <a href="#">extapplicabil</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">exclus</a> , <a href="#">secur</a> , <a href="#">status</a> , <a href="#">text</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

## ATTRIBUTE LIST

| Attribute | Type                                  | Default   | Description                                                                                                                                                    |
|-----------|---------------------------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| applicref | IDREFS                                | #REQUIRED | Allows the author to assign an applicability/effectivity reference to this element.                                                                            |
| security  | (u   c   s   n)                       | n         | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED  | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED  | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0         | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

---

# applicdef

## Applicability/Effectivity Definition

*Description:* Identifies the paragraph used to define applicability/effectivity markings, and the associated list.

*Source paragraph:* 4.3f (MIL-STD-38784)

*Content Model:* (([title](#), [warning\\*](#), [caution?](#), [note?](#), ([para](#), [note?](#))?, ([step1](#), [step1+](#))?, [subpara1\\*](#))?, ([apptitle?](#), [applichd?](#), [applic+](#)))

*Parents:* [foreword](#), [intro](#), [preface](#)

*Entities used in this element:* [bodyatt](#), [chgatt](#), [delstat](#), [para0att](#), [parazero](#), [secur](#), [status](#), [verified](#), [wcn](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute  | Type                          | Default  | Description                                                                                                                                                                                                           |
|------------|-------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| rtermwidth | NUTOKEN                       | 2.5in    | Allows the author to define the width of right column, which typically contains the applicability/effectivity definition. This attribute is not currently supported by the FOSI.                                      |
| ltermwidth | NUTOKEN                       | 1in      | Allows the author to define the width of the left column, which typically contains the applicability/effectivity. This attribute is not currently supported by the FOSI.                                              |
| emergency  | NUMBER                        | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                                                                       |
| id         | ID                            | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                                                                                      |
| esds       | NUMBER                        | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the <b>**ESD**</b> symbol by setting this attribute equal to "1". |
| nsp        | NUMBER                        | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the <b>**NSP**</b> symbol by setting this attribute equal to "1".                                                               |
| fcf        | NUMBER                        | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the <b>**FCP**</b> symbol by setting this attribute equal to "1".                                                       |
| hcp        | NUMBER                        | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the <b>**HCP**</b> symbol by setting this attribute equal to "1".                                                           |
| hci        | NUMBER                        | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the <b>**HCI**</b> symbol by setting this attribute equal to "1".                                                                   |
| ocp        | NUMBER                        | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the <b>**OCP**</b> symbol by setting this attribute equal to "1".                                                       |
| oci        | NUMBER                        | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the <b>**OCI**</b> symbol by setting this attribute equal to "1".                                                               |
| applicref  | IDREFS                        | #IMPLIED | Allows the author to assign an applicability/effectivity reference to this element.                                                                                                                                   |
| verdate    | CDATA                         | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                                         |
| verrem     | CDATA                         | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                                |
| verstatus  | (unver   ver   notapplicable) | unver    | Identifies the verification status of the element.                                                                                                                                                                    |
| security   | (u   c   s   n)               | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.                                                         |
| caveat     | CDATA                         | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                                      |
| fgi        | CDATA                         | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.                                                        |

| Attribute | Type                                  | Default  | Description                                                                                                                                                           |
|-----------|---------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA                                 | #IMPLIED | Allows the author to label this element manually. The FOSI automatically generates labels, so its use is not necessary unless a label out of the ordinary is desired. |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                   |
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is not currently supported by the FOSI.                                                                         |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                         |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                            |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                             |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                  |

## applichd

### Applicability/Effectivity List Column Headings

*Description:* Defines the column headings used for the applicability/effectivity list.

*Source paragraph:* 4.3f (MIL-STD-38784)

*Content Model:* (term, def)

*Parents:* [applicdef](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

## appltile

### Applicability/Effectivity Title

*Description:* Identifies the title for the applicability/effectivity list.

Source paragraph: 4.3f (MIL-STD-38784)

Content Model: ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup> -([figure](#) | [table](#) | [foldout](#) | [objmedia](#))

Parents: [applicdef](#)

Entities used in this element: [chgatt](#), [delstat](#), [exclus](#), [secur](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

# authnot

## Authority Notice

Description: Identifies the authority notice at the bottom of the title page.

Source paragraph: 4.5.1.15 (MIL-STD-38784)

Content Model: ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

Parents: [idinfo](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# bindByCoords

## Bind By Coordinates

|                                       |                                                                                                                               |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies coordinates on a graphic that may be used for referencing. This element is not currently supported by the FOSI.    |
| <i>Source paragraph:</i>              | None                                                                                                                          |
| <i>Content Model:</i>                 | (xref*)                                                                                                                       |
| <i>Parents:</i>                       | <a href="#">graphic</a>                                                                                                       |
| <i>Entities used in this element:</i> | <a href="#">cgmatts</a> , <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">status</a> , <a href="#">yesorno</a> |

### ATTRIBUTE LIST

| Attribute     | Type                                  | Default   | Description                                                                                                                                       |
|---------------|---------------------------------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| coords        | CDATA                                 | #REQUIRED | A list of the coordinates identifying the region on the graphic.                                                                                  |
| id            | ID                                    | #IMPLIED  | Allows the author to generate a unique ID for use when referencing this element.                                                                  |
| title         | CDATA                                 | #IMPLIED  | Label/Screen tip of hot-spot.                                                                                                                     |
| descript      | CDATA                                 | #IMPLIED  | Description of graphical hot-spot.                                                                                                                |
| visibility    | (visible   hidden)                    | visible   | Indicates if an object is visible or not. A non-visible object behaves like a non-interactive object (i.e., it cannot be clicked or highlighted). |
| interactivity | (interactive   none)                  | none      | Indicates if an object may receive mouse events. When this attribute is set to "none", events for this object are disabled.                       |
| delttype      | (delete   real   reserve   NA)        | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                     |
| inschlvl      | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was inserted at the change level indicated.                                        |
| delchlvl      | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was deleted at the change level indicated.                                         |
| status        | (empty   deleted   reserved   notapp) | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the status of this element.                            |
| revchg        | NUMBER                                | 0         | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                              |

---

# bindById

## Bind By ID

|                                       |                                                                                                                                                        |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies by ID a region in a Computer Graphics Metafile (CGM) that may be used for referencing. This element is not currently supported by the FOSI. |
| <i>Source paragraph:</i>              | None                                                                                                                                                   |
| <i>Content Model:</i>                 | (xref*)                                                                                                                                                |
| <i>Parents:</i>                       | <a href="#">graphic</a>                                                                                                                                |
| <i>Entities used in this element:</i> | <a href="#">cgmatts</a> , <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">status</a> , <a href="#">yesorno</a>                          |

## ATTRIBUTE LIST

| Attribute     | Type                                  | Default   | Description                                                                                                                                       |
|---------------|---------------------------------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| objectid      | CDATA                                 | #REQUIRED | The name of the ID identifying the region on the CGM.                                                                                             |
| id            | ID                                    | #IMPLIED  | Allows the author to generate a unique ID for use when referencing this element.                                                                  |
| title         | CDATA                                 | #IMPLIED  | Label/Screen tip of hot-spot.                                                                                                                     |
| descript      | CDATA                                 | #IMPLIED  | Description of graphical hot-spot.                                                                                                                |
| visibility    | (visible   hidden)                    | visible   | Indicates if an object is visible or not. A non-visible object behaves like a non-interactive object (i.e., it cannot be clicked or highlighted). |
| interactivity | (interactive   none)                  | none      | Indicates if an object may receive mouse events. When this attribute is set to "none", events for this object are disabled.                       |
| deltype       | (delete   real   reserve   NA)        | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                     |
| inschlvl      | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was inserted at the change level indicated.                                        |
| delchlvl      | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was deleted at the change level indicated.                                         |
| status        | (empty   deleted   reserved   notapp) | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the status of this element.                            |
| revchg        | NUMBER                                | 0         | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                              |

## bindByName

### Bind By Name

*Description:* Identifies by name a region on a CGM that may be used for referencing. This element is not currently supported by the FOSI.

*Source paragraph:* None

*Content Model:* (xref\*)

*Parents:* [graphic](#)

*Entities used in this element:* [cgmatts](#), [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute     | Type                                  | Default   | Description                                                                                                                                       |
|---------------|---------------------------------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| apstargetname | CDATA                                 | #REQUIRED | The name of the region on the CGM.                                                                                                                |
| id            | ID                                    | #IMPLIED  | Allows the author to generate a unique ID for use when referencing this element.                                                                  |
| title         | CDATA                                 | #IMPLIED  | Label/Screen tip of hot-spot.                                                                                                                     |
| descript      | CDATA                                 | #IMPLIED  | Description of graphical hot-spot.                                                                                                                |
| visibility    | (visible   hidden)                    | visible   | Indicates if an object is visible or not. A non-visible object behaves like a non-interactive object (i.e., it cannot be clicked or highlighted). |
| interactivity | (interactive   none)                  | none      | Indicates if an object may receive mouse events. When this attribute is set to "none", events for this object are disabled.                       |
| deltype       | (delete   real   reserve   NA)        | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                     |
| inschlvl      | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was inserted at the change level indicated.                                        |
| delchlvl      | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was deleted at the change level indicated.                                         |
| status        | (empty   deleted   reserved   notapp) | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the status of this element.                            |

| Attribute | Type   | Default | Description                                                                                          |
|-----------|--------|---------|------------------------------------------------------------------------------------------------------|
| revchg    | NUMBER | 0       | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change. |

# body

## Body

*Description:* Identifies the portion of the manual where sections are used, exclusive of front matter.

*Source paragraph:* 3.2.38 and 4.2.9.3 (MIL-STD-38784), 3.2 (MIL-DTL-7700)

*Content Model:* (([normproccl](#), [emergproccl](#)+, [clsection](#)\*, [performdatacl](#)\*)) +([ftnote](#))

*Parents:* [docfmcl](#)

*Entities used in this element:* [bodyele](#)

### ATTRIBUTE LIST

| Attribute | Type   | Default   | Description                                                                                       |
|-----------|--------|-----------|---------------------------------------------------------------------------------------------------|
| numcols   | (1  2) | #REQUIRED | Allows the author to define the page format as one or two columns for this section of the manual. |

# brk

## Break

*Description:* This element is used to indicate that a column, line, or page break should be forced at that point. This element is included to allow the author flexibility in composing the manual in accordance with this specification.

*Source paragraph:* None

*Content Model:* EMPTY

*Included in:* [doc](#)

### ATTRIBUTE LIST

| Attribute | Type                | Default | Description                                                                                                     |
|-----------|---------------------|---------|-----------------------------------------------------------------------------------------------------------------|
| type      | (col   line   npg ) | line    | Allows the author to define what type of break will occur when the brk element is used - column, line, or page. |

---

## C

### Caution

*Description:* Allows for a boxed 'C' as a symbol in the addcond.

*Source paragraph:* 3.2.1 (MIL-DTL-7700)

*Content Model:* EMPTY

*Parents:* [symsb](#), [symsb1](#)

*Included in:* [docfmcl](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

## caution

### Caution

*Description:* Identifies a CAUTION in the manual.

*Source paragraph:* 4.3.10 (MIL-STD-38784)

*Content Model:* ([para\\*](#)) [-\(randlist | deflist | seqlist | figure | table | foldout | objmedia | warning | caution\)](#)

*Parents:* [abbrsect](#), [applicdef](#), [cmbr1](#), [cmbr2](#), [cmbr3](#), [cmbr4](#), [cmbr5](#), [entry](#), [ifthen](#), [para0](#), [procstep](#), [procstep2](#), [procstep3](#), [procstep4](#), [step1](#), [step2](#), [step3](#), [step4](#), [subpara1](#), [subpara2](#), [subpara3](#), [symsect](#)

*Included in:* [addcond](#), [performdatacl](#), [procedure](#)

*Excluded in:* [caution](#), [note](#), [warning](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [exclus](#), [list](#), [status](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                           | Default  | Description                                                                                                                   |
|-----------|--------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |



| Attribute | Type                                  | Default  | Description                                                                                                            |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------|
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.             |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.              |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element. |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                   |

# change

## Changed Information

**Description:** Identifies material that has been changed. In order to add material, the type attribute should be set to "add", and the change element should surround the added material. In order to delete material where a complete history of all changes to the document are being preserved, the type attribute should be set to "delete" and the change element should surround the deleted material. If all changes are not being preserved, change the material and surround it with a change element, setting the type attribute to "add".

**Source paragraph:** 4.7.3.9 (MIL-STD-38784)

**Content Model:** ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+) -([figure](#) | [table](#) | [foldout](#) | [objmedia](#))

**Parents:** [abbrtitle](#), [action](#), [amplification](#), [applicabil](#), [appltile](#), [authnot](#), [change](#), [chgdate](#), [chgnum](#), [chgtxt](#), [clink](#), [clitem](#), [cogact](#), [condition](#), [contractno](#), [copyright](#), [cpos](#), [crewpos](#), [crewpos1](#), [crewpos2](#), [crewpos3](#), [crewpos4](#), [crewpos5](#), [dataiden](#), [date](#), [def](#), [destr](#), [discl](#), [distrib](#), [doctype](#), [effdatenot](#), [emphasis](#), [entry](#), [etitle](#), [expcont](#), [extapplicabil](#), [fnote](#), [hazmat](#), [ilink](#), [internatlst](#), [item](#), [label](#), [lepchg](#), [leppage](#), [line](#), [maintlvl](#), [mfr](#), [modelno](#), [moveddata](#), [newpos1](#), [newpos2](#), [newpos3](#), [newpos4](#), [newpos5](#), [nmlist](#), [nomen](#), [nsn](#), [oadr](#), [pageno](#), [para](#), [param](#), [parano](#), [paras](#), [paratitle](#), [partno](#), [pgnumber](#), [phrase](#), [pretmidno](#), [pubdate](#), [revnum](#), [sectocstr](#), [seqno](#), [serno](#), [subject](#), [subparano](#), [subtitle](#), [supersd](#), [suppl](#), [symb](#), [symtitle](#), [term](#), [tfmid](#), [title](#), [tmidno](#), [typesdes](#), [underline](#)

**Entities used in this element:** [exclus](#), [secur](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type            | Default   | Description                                                                                                                                                             |
|-----------|-----------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| level     | NMTOKEN         | #REQUIRED | Defines the change level for the modification.                                                                                                                          |
| change    | (add   delete)  | add       | Defines the type of change - addition or deletion of text.                                                                                                              |
| mark      | NUMBER          | 1         | Allows the author to define if a change mark will appear for this change. Setting this attribute to "1" will produce a change bar on the page and "0" will suppress it. |
| revchg    | NUMBER          | 0         | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                    |
| security  | (u   c   s   n) | n         | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.           |
| caveat    | CDATA           | #IMPLIED  | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                        |
| fgi       | CDATA           | #IMPLIED  | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.          |

---

# chgdate

## Change Date

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies the date of the latest change.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <i>Source paragraph:</i>              | 4.5.1.17 (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <i>Content Model:</i>                 | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">ftnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcp</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> ) <sup>+</sup> ) |
| <i>Parents:</i>                       | <a href="#">idinfo</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <i>Entities used in this element:</i> | <a href="#">text</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

---

# chghistory

## Change History

|                          |                                                                                                                                                                   |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>      | Identifies the beginning of the change history dates. The first date in the change history is the original date and subsequent dates are change 1, change 2, etc. |
| <i>Source paragraph:</i> | 4.5.3.1 (MIL-STD-38784)                                                                                                                                           |
| <i>Content Model:</i>    | ( <a href="#">chginfo</a> <sup>*</sup> )                                                                                                                          |
| <i>Parents:</i>          | <a href="#">idinfo</a>                                                                                                                                            |

---

# chginfo

## Change Information

|                          |                                                                                                       |
|--------------------------|-------------------------------------------------------------------------------------------------------|
| <i>Description:</i>      | Container element to identify the change information contained in the change history of the document. |
| <i>Source paragraph:</i> | 4.5.3.1 (MIL-STD-38784)                                                                               |
| <i>Content Model:</i>    | ( <a href="#">chgtxt</a> <sup>?</sup> , <a href="#">date</a> )                                        |
| <i>Parents:</i>          | <a href="#">chghistory</a>                                                                            |

---

# chgnum

## Change Number/Letter

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies the latest change number/letter.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <i>Source paragraph:</i>              | 4.2.1.4.2.3, 4.5.1.17, and 4.7.3.1 (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <i>Content Model:</i>                 | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">ftnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcp</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> ) <sup>+</sup> ) |
| <i>Parents:</i>                       | <a href="#">idinfo</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <i>Entities used in this element:</i> | <a href="#">text</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

---

# chgtxt

## Change Text

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | This element is optional and is used to provide an alpha representation of the current change level. This element will only be used by those branches of the Armed Services that require alpha change levels. For all other users, this element should not be used.                                                                                                                                                                                                                                                                                                                                                                                                        |
| <i>Source paragraph:</i>              | 4.5.3 (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <i>Content Model:</i>                 | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">ftnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcp</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> ) <sup>+</sup> ) |
| <i>Parents:</i>                       | <a href="#">chginfo</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <i>Entities used in this element:</i> | <a href="#">text</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

---

# clink

## Contextual Link

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>      | One of several HyTime elements. Can be used in any situation similar to the xref or extref element. This element will reference any <a href="#">nameloc</a> declared.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <i>Source paragraph:</i> | None                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <i>Content Model:</i>    | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">ftnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcp</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> ) <sup>+</sup> ) |

**Parents:** [abbrtitle](#), [action](#), [amplification](#), [applicabil](#), [appltite](#), [authnot](#), [change](#), [chgdate](#), [chgnum](#), [chgtxt](#), [clink](#), [clitem](#), [cogact](#), [condition](#), [contractno](#), [copyright](#), [cpos](#), [crewpos](#), [crewpos1](#), [crewpos2](#), [crewpos3](#), [crewpos4](#), [crewpos5](#), [dataiden](#), [date](#), [def](#), [destr](#), [discl](#), [distrib](#), [doctype](#), [effdatenot](#), [emphasis](#), [entry](#), [etitle](#), [expcont](#), [extapplicabil](#), [ftnote](#), [hazmat](#), [ilink](#), [internatlst](#), [item](#), [label](#), [lepchg](#), [leppage](#), [line](#), [maintlvl](#), [mfr](#), [modelno](#), [moveddata](#), [newpos1](#), [newpos2](#), [newpos3](#), [newpos4](#), [newpos5](#), [nmlist](#), [nomen](#), [nsn](#), [oadr](#), [pageno](#), [para](#), [param](#), [parano](#), [paras](#), [paratitle](#), [partno](#), [pgnumber](#), [phrase](#), [pretmidno](#), [pubdate](#), [revnum](#), [sectocstr](#), [seqno](#), [serno](#), [subject](#), [subparano](#), [subtitle](#), [supersed](#), [suppl](#), [symb](#), [symtitle](#), [term](#), [tfnid](#), [title](#), [tmidno](#), [typedes](#), [underline](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                               | Default                                    | Description                                                                                                                                                                                                                                  |
|-----------|----------------------------------------------------|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| HyBase    | NAME                                               | #FIXED <code>hylink</code>                 | Used in combination with HyTime to establish a contextual link.                                                                                                                                                                              |
| HyBnames  | CDATA                                              | #FIXED <code>"refsub linkend"</code>       | Used in combination with HyTime to establish a contextual link.                                                                                                                                                                              |
| anchrole  | CDATA                                              | #FIXED <code>"refmark refsub #LIST"</code> | Used in combination with HyTime to establish an anchor role for contextual links.                                                                                                                                                            |
| anchcstr  | NAMES                                              | <code>"self required"</code>               | Used in combination with HyTime to establish the type of anchor string defined for a contextual link.                                                                                                                                        |
| linkend   | CDATA                                              | #IMPLIED                                   | References a linkend declared within a nameloc element. Other attributes are not included at this time as they are not applicable during a period of alpha testing and will be added to the TDT as the options are explored and implemented. |
| delttype  | <code>(delete   real   reserve   NA)</code>        | #IMPLIED                                   | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                                                                                                |
| inschlvl  | NMTOKEN                                            | #IMPLIED                                   | Used during the change package process to indicate the element was inserted at the change level indicated.                                                                                                                                   |
| delchlvl  | NMTOKEN                                            | #IMPLIED                                   | Used during the change package process to indicate the element was deleted at the change level indicated.                                                                                                                                    |
| status    | <code>(empty   deleted   reserved   notapp)</code> | #IMPLIED                                   | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                                                                                       |
| revchg    | NUMBER                                             | 0                                          | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                                                                                         |

# clitem

## checklist item

**Description:** Checklist task item

**Source paragraph:** N/A

**Content Model:** (((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+), [action](#)?, [amplification](#)?)

**Parents:** [clstep1](#), [clstep2](#), [clstep3](#), [clstep4](#), [ifstep1](#), [ifstep2](#), [ifstep3](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [secur](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                         | Default  | Description                                                                                                                                                    |
|-----------|------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | <code>(u   c   s   n)</code> | n        | Identifies security level of the task                                                                                                                          |
| caveat    | CDATA                        | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                        | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

## clsection

### Checklist Section

*Description:* Generic section identifier for flight manual checklists.

*Source paragraph:* 3.2.b (MIL-DTL-7700)

*Content Model:* ((([title](#)), [secttoc](#), [procedure](#)+)) +([sectocstr](#) | [figure](#) | [table](#) | [graphic](#) | [addcond](#) | [etitle](#) | [figtable](#)| [tabmat](#))

*Parents:* [body](#)

*Entities used in this element:* [bodyatt](#), [chapatt](#), [chgatt](#), [delstat](#), [sect](#), [sectatt](#), [secur](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                           |
|-----------|---------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| clsectlr  | CDATA                                 | #IMPLIED | Used to indicate section letter to be paired with the page number for a generic section.                                                                              |
| id        | ID                                    | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                                      |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.         |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                      |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.        |
| label     | CDATA                                 | #IMPLIED | Allows the author to label this element manually. The FOSI automatically generates labels, so its use is not necessary unless a label out of the ordinary is desired. |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                   |
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is This attribute is not currently supported by the FOSI.                                                       |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                        |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                            |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated                                                                  |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                                                                                 |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                  |

| Attribute | Type   | Default  | Description                                                                                                                    |
|-----------|--------|----------|--------------------------------------------------------------------------------------------------------------------------------|
| landscape | NUMBER | #IMPLIED | When set to 1, the procedures should be displayed on the page in a landscape orientation as opposed to a portrait orientation. |

# clstep1

## Checklist First Level Procedural Step

*Description:* Identifies a first level procedural step.

*Source paragraph:* 3.2.12.1 (MIL-DTL-7700)

*Content Model:* (((clitem) | condition?)+, clstep2\*)

*Parents:* [abbrsect](#), [applicdef](#), [para0](#), [procedure](#), [procstep](#), [procstep2](#), [procstep3](#), [procstep4](#), [subpara1](#), [subpara2](#), [subpara3](#), [subproc1](#), [subproc2](#), [subproc3](#), [symsect](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [stepatt](#), [verified](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA                                 | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired.                                           |
| emergency | NUMBER                                | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                                                                |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                                                            |
| id        | ID                                    | #IMPLIED | This allows you to identify each element and later reference it by its id value.                                                                                                                               |
| esds      | NUMBER                                | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the **ESD** symbol by setting this attribute equal to "1". |
| nsp       | NUMBER                                | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the **NSP** symbol by setting this attribute equal to "1".                                                               |
| fcf       | NUMBER                                | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the **FCP** symbol by setting this attribute equal to "1".                                                       |
| hcp       | NUMBER                                | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the **HCP** symbol by setting this attribute equal to "1".                                                           |
| hcl       | NUMBER                                | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the **HCI** symbol by setting this attribute equal to "1".                                                                   |
| ocp       | NUMBER                                | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the **OCP** symbol by setting this attribute equal to "1".                                                       |
| oci       | NUMBER                                | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the **OCI** symbol by setting this attribute equal to "1".                                                               |
| applicref | IDREFS                                | #IMPLIED | Allows you to assign an applicable reference to this element.                                                                                                                                                  |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                                                                 |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Insert Change Level                                                                                                                                                         |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Delete Change Level                                                                                                                                                         |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows you to specify the status of this element.                                                                                                                                                              |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                                                           |
| verdate   | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                                  |
| verrem    | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                         |

| Attribute     | Type                          | Default  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------|-------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| verstatus     | (unver   ver   notapplicable) | unver    | Identifies verification status of the element.                                                                                                                                                                                                                                                                                                                                                                                                                     |
| security      | (u   c   s   n)               | n        | Identifies security level of the element.                                                                                                                                                                                                                                                                                                                                                                                                                          |
| caveat        | CDATA                         | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                                                                                                                                                                                                                                                                                   |
| fgi           | CDATA                         | #IMPLIED | Provides a place for inline FMS portion marking.                                                                                                                                                                                                                                                                                                                                                                                                                   |
| effect        | CDATA                         | #IMPLIED | Used to assign an effectivity to the Step.                                                                                                                                                                                                                                                                                                                                                                                                                         |
| afmem         | NUMBER                        | #IMPLIED | Allows bolding for a step that AF should commit to memory. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                    |
| navmem        | NUMBER                        | #IMPLIED | Allows bolding for a step that Navy should commit to memory. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                  |
| bothmem       | NUMBER                        | #IMPLIED | Allows bolding for a step that both Navy and AF should commit to memory. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                      |
| crewcoordcirc | (0 1)                         | 0        | Allows step number to be circled. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                                             |
| feresponse    | NUMBER                        | 0        | A "through-flight" type of operation, where a crewmember will perform, as a minimum, those steps indicated. One example of this is an ERCC (Engines Running Crew Change) where a crew lands the jet, and only accomplishes enough steps in a shutdown checklist to make the jet safe while leaving the engines running, and a fresh crew gets on board and makes the jet ready for flight again, by accomplishing the "through-flight" items. Only use on clsteps. |
| thruflt       | NUMBER                        | 0        | Preceding any checklist step means the step is contained in section II and that a response is required when the flight engineer reads the item. Only use on clsteps.                                                                                                                                                                                                                                                                                               |
| nomisscrw     | NUMBER                        | 0        | Indicate specific checklist steps the engineer will accomplish when a mission crew is not present. This would only happen when training is being accomplished which does not require the mission crew, such as pattern work, or perhaps air refueling. Only use on clsteps.                                                                                                                                                                                        |
| stepenum      | NUMBER                        | #IMPLIED | Used to restart numbering after an ifthen section of an instance.                                                                                                                                                                                                                                                                                                                                                                                                  |
| manwc         | (W   C   WC)                  | #IMPLIED | Used to indicate whether the flight manual has a warning or caution for that step which did not carry over into the checklist.                                                                                                                                                                                                                                                                                                                                     |

## clstep2

### Checklist Second Level Procedural Step

**Description:** Identifies a second level procedural step.  
**Source paragraph:** 3.2.12.1 (MIL-DTL-7700)  
**Content Model:** (((clitem) | condition?)+, clstep3\*)  
**Parents:** clstep1  
**Entities used in this element:** chgatt, delstat, status, stepatt, verified, yesorno

#### ATTRIBUTE LIST

| Attribute | Type   | Default  | Description                                                                                                                                                          |
|-----------|--------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA  | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired. |
| emergency | NUMBER | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                      |
| sssn      | CDATA  | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                  |
| id        | ID     | #IMPLIED | This allows you to identify each element and later reference it by its id value.                                                                                     |

| Attribute     | Type                                  | Default  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------|---------------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| esds          | NUMBER                                | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the <b>**ESD**</b> symbol by setting this attribute equal to "1".                                                                                                                                                                                                                                              |
| nsp           | NUMBER                                | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the <b>**NSP**</b> symbol by setting this attribute equal to "1".                                                                                                                                                                                                                                                                                                            |
| fcf           | NUMBER                                | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the <b>**FCP**</b> symbol by setting this attribute equal to "1".                                                                                                                                                                                                                                                                                                    |
| hcp           | NUMBER                                | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the <b>**HCP**</b> symbol by setting this attribute equal to "1".                                                                                                                                                                                                                                                                                                        |
| hcl           | NUMBER                                | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the <b>**HCI**</b> symbol by setting this attribute equal to "1".                                                                                                                                                                                                                                                                                                                |
| ocp           | NUMBER                                | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the <b>**OCP**</b> symbol by setting this attribute equal to "1".                                                                                                                                                                                                                                                                                                    |
| oci           | NUMBER                                | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the <b>**OCI**</b> symbol by setting this attribute equal to "1".                                                                                                                                                                                                                                                                                                            |
| applicref     | IDREFS                                | #IMPLIED | Allows you to assign an applicable reference to this element.                                                                                                                                                                                                                                                                                                                                                                                                      |
| deltype       | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                                                                                                                                                                                                                                                                                                                     |
| inschlvl      | NMTOKEN                               | #IMPLIED | Used to generate change packages - Insert Change Level                                                                                                                                                                                                                                                                                                                                                                                                             |
| delchlvl      | NMTOKEN                               | #IMPLIED | Used to generate change packages - Delete Change Level                                                                                                                                                                                                                                                                                                                                                                                                             |
| status        | (empty   deleted   reserved   notapp) | #IMPLIED | Allows you to specify the status of this element.                                                                                                                                                                                                                                                                                                                                                                                                                  |
| revchg        | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                                                                                                                                                                                                                                                                                                               |
| verdate       | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                                                                                                                                                                                                                                                                                      |
| verrem        | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                                                                                                                                                                                                                                                                             |
| verstatus     | (unver   ver   notapplicable)         | unver    | Identifies verification status of the element.                                                                                                                                                                                                                                                                                                                                                                                                                     |
| security      | (u   c   s   n)                       | n        | Identifies security level of the element.                                                                                                                                                                                                                                                                                                                                                                                                                          |
| caveat        | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                                                                                                                                                                                                                                                                                   |
| fgi           | CDATA                                 | #IMPLIED | Provides a place for inline FMS portion marking.                                                                                                                                                                                                                                                                                                                                                                                                                   |
| effect        | CDATA                                 | #IMPLIED | Used to assign an effectivity to the Step.                                                                                                                                                                                                                                                                                                                                                                                                                         |
| afmem         | NUMBER                                | #IMPLIED | Allows bolding for a step that AF should commit to memory. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                    |
| navmem        | NUMBER                                | #IMPLIED | Allows bolding for a step that Navy should commit to memory. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                  |
| bothmem       | NUMBER                                | #IMPLIED | Allows bolding for a step that both Navy and AF should commit to memory. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                      |
| crewcoordcirc | (0 1)                                 | 0        | Allows step number to be circled. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                                             |
| feresponse    | NUMBER                                | 0        | A "through-flight" type of operation, where a crewmember will perform, as a minimum, those steps indicated. One example of this is an ERCC (Engines Running Crew Change) where a crew lands the jet, and only accomplishes enough steps in a shutdown checklist to make the jet safe while leaving the engines running, and a fresh crew gets on board and makes the jet ready for flight again, by accomplishing the "through-flight" items. Only use on clsteps. |
| thruflyt      | NUMBER                                | 0        | Preceding any checklist step means the step is contained in section II and that a response is required when the flight engineer reads the item. Only use on clsteps.                                                                                                                                                                                                                                                                                               |
| nomisscrw     | NUMBER                                | 0        | Indicate specific checklist steps the engineer will accomplish when a mission crew is not present. This would only happen when training is being accomplished which does not require the mission crew, such as pattern work, or perhaps air refueling. Only use on clsteps.                                                                                                                                                                                        |
| stepenum      | NUMBER                                | #IMPLIED | Used to restart numbering after an ifthen section of an instance.                                                                                                                                                                                                                                                                                                                                                                                                  |
| manwc         | (W   C   WC)                          | #IMPLIED | Used to indicate whether the flight manual has a warning or caution for that step which did not carry over into the checklist.                                                                                                                                                                                                                                                                                                                                     |



# clstep3

## Checklist Third Level Procedural Step

**Description:** Identifies a third level procedural step.

**Source paragraph:** 3.2.12.1 (MIL-DTL-7700)

**Content Model:** (((clitem) | condition?)+, clstep4\*)

**Parents:** clstep2

**Entities used in this element:** chgatt, delstat, status, stepatt, verified, yesorno

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA                                 | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired.                                           |
| emergency | NUMBER                                | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                                                                |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                                                            |
| id        | ID                                    | #IMPLIED | This allows you to identify each element and later reference it by its id value.                                                                                                                               |
| esds      | NUMBER                                | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the **ESD** symbol by setting this attribute equal to "1". |
| nsp       | NUMBER                                | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the **NSP** symbol by setting this attribute equal to "1".                                                               |
| fcf       | NUMBER                                | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the **FCP** symbol by setting this attribute equal to "1".                                                       |
| hcp       | NUMBER                                | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the **HCP** symbol by setting this attribute equal to "1".                                                           |
| hcl       | NUMBER                                | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the **HCI** symbol by setting this attribute equal to "1".                                                                   |
| ocp       | NUMBER                                | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the **OCP** symbol by setting this attribute equal to "1".                                                       |
| oci       | NUMBER                                | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the **OCI** symbol by setting this attribute equal to "1".                                                               |
| applicref | IDREFS                                | #IMPLIED | Allows you to assign an applicable reference to this element.                                                                                                                                                  |
| deltpe    | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                                                                 |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Insert Change Level                                                                                                                                                         |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Delete Change Level                                                                                                                                                         |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows you to specify the status of this element.                                                                                                                                                              |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                                                           |
| verdate   | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                                  |
| verrem    | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                         |
| verstatus | (unver   ver   notapplicable)         | unver    | Identifies verification status of the element.                                                                                                                                                                 |
| security  | (u   c   s   n)                       | n        | Identifies security level of the element.                                                                                                                                                                      |

| Attribute     | Type     | Default  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------|----------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| caveat        | CDATA    | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                                                                                                                                                                                                                                                                                   |
| fgi           | CDATA    | #IMPLIED | Provides a place for inline FMS portion marking.                                                                                                                                                                                                                                                                                                                                                                                                                   |
| effect        | CDATA    | #IMPLIED | Used to assign an effectivity to the Step.                                                                                                                                                                                                                                                                                                                                                                                                                         |
| afmem         | NUMBER   | #IMPLIED | Allows bolding for a step that AF should commit to memory. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                    |
| navmem        | NUMBER   | #IMPLIED | Allows bolding for a step that Navy should commit to memory. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                  |
| bothmem       | NUMBER   | #IMPLIED | Allows bolding for a step that both Navy and AF should commit to memory. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                      |
| crewcoordcirc | (0 1)    | 0        | Allows step number to be circled. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                                             |
| feresponse    | NUMBER   | 0        | A "through-flight" type of operation, where a crewmember will perform, as a minimum, those steps indicated. One example of this is an ERCC (Engines Running Crew Change) where a crew lands the jet, and only accomplishes enough steps in a shutdown checklist to make the jet safe while leaving the engines running, and a fresh crew gets on board and makes the jet ready for flight again, by accomplishing the "through-flight" items. Only use on clsteps. |
| thruflt       | NUMBER   | 0        | Preceding any checklist step means the step is contained in section II and that a response is required when the flight engineer reads the item. Only use on clsteps.                                                                                                                                                                                                                                                                                               |
| nomisscrw     | NUMBER   | 0        | Indicate specific checklist steps the engineer will accomplish when a mission crew is not present. This would only happen when training is being accomplished which does not require the mission crew, such as pattern work, or perhaps air refueling. Only use on clsteps.                                                                                                                                                                                        |
| stepenum      | NUMBER   | #IMPLIED | Used to restart numbering after an ifthen section of an instance.                                                                                                                                                                                                                                                                                                                                                                                                  |
| manwc         | (W   C ) | #IMPLIED | Used to indicate whether the flight manual has a warning or caution for that step which did not carry over into the checklist.                                                                                                                                                                                                                                                                                                                                     |

## clstep4

### Checklist Fourth Level Procedural Step

*Description:* Identifies a fourth level procedural step.  
*Source paragraph:* 3.2.12.1 (MIL-DTL-7700)  
*Content Model:* ([clitem](#))  
*Parents:* [clstep3](#)  
*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [stepatt](#), [verified](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type   | Default  | Description                                                                                                                                                                                                    |
|-----------|--------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA  | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired.                                           |
| emergency | NUMBER | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                                                                |
| sssn      | CDATA  | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                                                            |
| id        | ID     | #IMPLIED | This allows you to identify each element and later reference it by its id value.                                                                                                                               |
| esds      | NUMBER | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the **ESD** symbol by setting this attribute equal to "1". |

| Attribute     | Type                                  | Default  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------|---------------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| nsp           | NUMBER                                | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the <b>**NSP**</b> symbol by setting this attribute equal to "1".                                                                                                                                                                                                                                                                                                            |
| fcf           | NUMBER                                | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the <b>**FCP**</b> symbol by setting this attribute equal to "1".                                                                                                                                                                                                                                                                                                    |
| hcp           | NUMBER                                | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the <b>**HCP**</b> symbol by setting this attribute equal to "1".                                                                                                                                                                                                                                                                                                        |
| hcl           | NUMBER                                | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the <b>**HCI**</b> symbol by setting this attribute equal to "1".                                                                                                                                                                                                                                                                                                                |
| ocp           | NUMBER                                | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the <b>**OCP**</b> symbol by setting this attribute equal to "1".                                                                                                                                                                                                                                                                                                    |
| oci           | NUMBER                                | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the <b>**OCI**</b> symbol by setting this attribute equal to "1".                                                                                                                                                                                                                                                                                                            |
| applicref     | IDREFS                                | #IMPLIED | Allows you to assign an applicable reference to this element.                                                                                                                                                                                                                                                                                                                                                                                                      |
| delttype      | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                                                                                                                                                                                                                                                                                                                     |
| inschlvl      | NMTOKEN                               | #IMPLIED | Used to generate change packages - Insert Change Level                                                                                                                                                                                                                                                                                                                                                                                                             |
| delchlvl      | NMTOKEN                               | #IMPLIED | Used to generate change packages - Delete Change Level                                                                                                                                                                                                                                                                                                                                                                                                             |
| status        | (empty   deleted   reserved   notapp) | #IMPLIED | Allows you to specify the status of this element.                                                                                                                                                                                                                                                                                                                                                                                                                  |
| revchg        | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                                                                                                                                                                                                                                                                                                               |
| verdate       | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                                                                                                                                                                                                                                                                                      |
| verrem        | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                                                                                                                                                                                                                                                                             |
| verstatus     | (unver   ver   notapplicable)         | unver    | Identifies verification status of the element.                                                                                                                                                                                                                                                                                                                                                                                                                     |
| security      | (u   c   s   n)                       | n        | Identifies security level of the element.                                                                                                                                                                                                                                                                                                                                                                                                                          |
| caveat        | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                                                                                                                                                                                                                                                                                   |
| fgi           | CDATA                                 | #IMPLIED | Provides a place for inline FMS portion marking.                                                                                                                                                                                                                                                                                                                                                                                                                   |
| effect        | CDATA                                 | #IMPLIED | Used to assign an effectivity to the Step.                                                                                                                                                                                                                                                                                                                                                                                                                         |
| afmem         | NUMBER                                | #IMPLIED | Allows bolding for a step that AF should commit to memory. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                    |
| navmem        | NUMBER                                | #IMPLIED | Allows bolding for a step that Navy should commit to memory. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                  |
| bothmem       | NUMBER                                | #IMPLIED | Allows bolding for a step that both Navy and AF should commit to memory. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                      |
| crewcoordcirc | (0 1)                                 | 0        | Allows step number to be circled. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                                             |
| feresponse    | NUMBER                                | 0        | A "through-flight" type of operation, where a crewmember will perform, as a minimum, those steps indicated. One example of this is an ERCC (Engines Running Crew Change) where a crew lands the jet, and only accomplishes enough steps in a shutdown checklist to make the jet safe while leaving the engines running, and a fresh crew gets on board and makes the jet ready for flight again, by accomplishing the "through-flight" items. Only use on clsteps. |
| thruflt       | NUMBER                                | 0        | Preceding any checklist step means the step is contained in section II and that a response is required when the flight engineer reads the item. Only use on clsteps.                                                                                                                                                                                                                                                                                               |
| nomisscrw     | NUMBER                                | 0        | Indicate specific checklist steps the engineer will accomplish when a mission crew is not present. This would only happen when training is being accomplished which does not require the mission crew, such as pattern work, or perhaps air refueling. Only use on clsteps.                                                                                                                                                                                        |
| stepenum      | NUMBER                                | #IMPLIED | Used to restart numbering after an ifthen section of an instance.                                                                                                                                                                                                                                                                                                                                                                                                  |
| manwc         | (W   C   WC)                          | #IMPLIED | Used to indicate whether the flight manual has a warning or caution for that step which did not carry over into the checklist.                                                                                                                                                                                                                                                                                                                                     |

---

# cmbr1

## Crew Member 1

*Description:* Identifies the Crew Member assigned to column 1 of the Coordinated Action Table

*Source paragraph:* 3.2.12.2.1 (MIL-DTL-7700)

*Content Model:* (([procstep?](#), [procstep2?](#), [procstep3?](#), [procstep4?](#), [warning?](#), [caution?](#), [note?](#)))

*Parents:* [tasks](#)

*Entities used in this element:* [chgatt](#), [cmbr.mdl](#), [delstat](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

# cmbr2

## Crew Member 2

*Description:* Identifies the Crew Member assigned to column 2 of the Coordinated Action Table

*Source paragraph:* 3.2.12.2.1 (MIL-DTL-7700)

*Content Model:* (([procstep?](#), [procstep2?](#), [procstep3?](#), [procstep4?](#), [warning?](#), [caution?](#), [note?](#)))

*Parents:* [tasks](#)

*Entities used in this element:* [chgatt](#), [cmbr.mdl](#), [delstat](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |

| Attribute | Type   | Default | Description                                                                          |
|-----------|--------|---------|--------------------------------------------------------------------------------------|
| revchg    | NUMBER | 0       | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision. |

## cmbr3

### Crew Member 3

*Description:* Identifies the Crew Member assigned to column 3 of the Coordinated Action Table

*Source paragraph:* 3.2.12.2.1 (MIL-DTL-7700)

*Content Model:* (([procstep?](#), [procstep2?](#), [procstep3?](#), [procstep4?](#), [warning?](#), [caution?](#), [note?](#)))

*Parents:* [tasks](#)

*Entities used in this element:* [chgatt](#), [cmbr.mdl](#), [delstat](#), [status](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

## cmbr4

### Crew Member 4

*Description:* Identifies the Crew Member assigned to column 4 of the Coordinated Action Table

*Source paragraph:* 3.2.12.2.1 (MIL-DTL-7700)

*Content Model:* (([procstep?](#), [procstep2?](#), [procstep3?](#), [procstep4?](#), [warning?](#), [caution?](#), [note?](#)))

*Parents:* [tasks](#)

*Entities used in this element:* [chgatt](#), [cmbr.mdl](#), [delstat](#), [status](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                           | Default  | Description                                                                                                |
|-----------|--------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA) | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                        | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |

| Attribute | Type                                  | Default  | Description                                                                                          |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------|
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                 |

## cmb5

### Crew Member 5

*Description:* Identifies the Crew Member assigned to column 5 of the Coordinated Action Table

*Source paragraph:* 3.2.12.2.1 (MIL-DTL-7700)

*Content Model:* (([procstep?](#), [procstep2?](#), [procstep3?](#), [procstep4?](#), [warning?](#), [caution?](#), [note?](#)))

*Parents:* [tasks](#)

*Entities used in this element:* [chgatt](#), [cmb5.mdl](#), [delstat](#), [status](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

## cogact

### Cognizant Field Activity

*Description:* Identifies the Cognizant Field Activity on the title page and is included in the distribution statement. This is a Navy requirement.

*Source paragraph:* 4.5.1.11 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+)

*Parents:* [idinfo](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# colspec

## Column Specification

*Description:* Defines a column in a table. Each column must have a column specification. The column specification defines the width of the column and an optional name used when the column is starting or ending a horizontal span or referenced in a table entry. Column specifications in a table group apply to the table heading (boxheads) and the table body. The table heading can redefine the column specifications if needed, however, the table body must use the column specifications defined in the table group.

*Source paragraph:* 4.2.7 (MIL-STD-38784)

*Content Model:* EMPTY

*Parents:* [entrytbl](#), [tfoot](#), [tgroup](#), [thead](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                     | Default  | Description                                                                                                                                                |
|-----------|------------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| colname   | NMTOKEN                                  | #IMPLIED | Allows the author to define a column name.                                                                                                                 |
| colnum    | NUMBER                                   | #IMPLIED | Allows the author to define a column number.                                                                                                               |
| align     | (left   right   center   justify   char) | #IMPLIED | Defines the horizontal alignment of text within a cell.                                                                                                    |
| charoff   | NUTOKEN                                  | #IMPLIED | Determines the distance the cell content should offset from the horizontal alignment character.                                                            |
| char      | CDATA                                    | #IMPLIED | Defines the alignment character that can be used to align values within a column. This attribute should be used when the align attribute is set to "char". |
| leftmar   | NUTOKEN                                  | #IMPLIED | Defines the left margin for each cell in the column.                                                                                                       |
| rightmar  | NUTOKEN                                  | #IMPLIED | Defines the right margin for each cell in the column.                                                                                                      |
| topmar    | NUTOKEN                                  | #IMPLIED | Defines the top margin for each cell in the column.                                                                                                        |
| botmar    | NUTOKEN                                  | #IMPLIED | Defines the bottom margin for each cell in the column.                                                                                                     |
| mindepth  | NUTOKEN                                  | #IMPLIED | Allows the author to define a minimum depth if desired.                                                                                                    |
| colwidth  | CDATA                                    | #IMPLIED | Allows the author to define the width of the column.                                                                                                       |
| colsep    | NUMBER                                   | #IMPLIED | Allows the author to include a vertical line to separate columns. Setting this attribute equal to "1" will generate column separators.                     |
| rowsep    | NUMBER                                   | #IMPLIED | Allows the author to include a horizontal line to separate rows. Setting this attribute equal to "1" will generate row separators.                         |
| delttype  | (delete   real   reserve   NA)           | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                              |
| inschlvl  | NMTOKEN                                  | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                 |
| delchlvl  | NMTOKEN                                  | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                  |

| Attribute | Type                                  | Default  | Description                                                                                                            |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------|
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element. |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                   |

# condition

## Condition

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies a possible condition under each procedure of an emergency procedure.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <i>Source paragraph:</i>              | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <i>Content Model:</i>                 | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">ftnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcp</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> )+) |
| <i>Parents:</i>                       | <a href="#">clstep1</a> , <a href="#">clstep2</a> , <a href="#">clstep3</a> , <a href="#">EPDecision1</a> , <a href="#">EPDecision2</a> , <a href="#">procedure</a> , <a href="#">procstep</a> , <a href="#">procstep2</a> , <a href="#">procstep3</a> , <a href="#">procstep4</a> , <a href="#">subproc1</a> , <a href="#">subproc2</a> , <a href="#">subproc3</a>                                                                                                                                                                                                                                                                                           |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">secur</a> , <a href="#">status</a> , <a href="#">text</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                 |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated                                                           |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                                                                          |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                           |

# cont

## Continued

|                          |                                      |
|--------------------------|--------------------------------------|
| <i>Description:</i>      | Allows marking for continued column. |
| <i>Source paragraph:</i> | N/A                                  |
| <i>Content Model:</i>    | EMPTY                                |



Included in: [procedure](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

# contractno

## Contract Number

Description: Identifies the contract number on the title page.

Source paragraph: 4.5.1.4 (MIL-STD-38784)

Content Model: ((#PCDATA | [change](#) | [tabmat](#) | [fnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

Parents: [idinfo](#)

Entities used in this element: [secur](#), [text](#)

---

# coordprocs

## Coordinated Action Procedure Checklist

Description: Provides a means of developing coordinated or simultaneous actions in parallel columns among crew members. There are two types: a numbered checklist and a table with unnumbered actions.

Source paragraph: 3.2.12.2, 3.2.12.2.1 (MIL-DTL-7700)

Content Model: ([heading](#), [tasks](#)<sup>+</sup>)

Parents: [procedure](#), [subproc1](#), [subproc2](#), [subproc3](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type   | Default   | Description                                                                       |
|-----------|--------|-----------|-----------------------------------------------------------------------------------|
| label     | CDATA  | #IMPLIED  | Allows you to label this manually.                                                |
| numcols   | NUMBER | #REQUIRED | Allows the author to define the number of columns for the Coordinated Procedures. |

| Attribute | Type                                  | Default  | Description                                                                                                                                               |
|-----------|---------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| orient    | (port   land1)                        | port     | Defines the orientation of the figure, either portrait or landscape. Setting this attribute equal to "land1" will rotate the figure and the figure title. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                            |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                                                                     |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                      |

# copyright

## Copyright Notice

*Description:* Identifies the copyright notice on the title page.

*Source paragraph:* 4.1.2 and 4.5.1.14 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [idinfo](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# cpos

## Crew position

*Description:* Identifies a crew position for coordinated steps.

*Source paragraph:* N/A

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

Included in: [procedure](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                 |
|-----------|---------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------|
| bold      | NUMBER                                | 0        | When the Step item that this element accompanies is bold, setting this attribute to 1 will bold the output of this element. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                              |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                  |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated                        |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                                       |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                        |

---

# crewpos

## Title Page Crew Position

Description: Identifies the crew position on the title page that the checklist applies to.

Source paragraph: 3.7.2.1 (MIL-DTL-7700)

Content Model: ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

Parents: [idinfo](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

# crewpos1

## Crew Position 1

*Description:* Defines the first crew position in the Coordinated Action Table

*Source paragraph:* 3.2.12.2, 3.2.12.2.1 (MIL-DTL-7700)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [heading](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

# crewpos2

## Crew Position 2

*Description:* Defines the first crew position in the Coordinated Action Table

*Source paragraph:* 3.2.12.2, 3.2.12.2.1 (MIL-DTL-7700)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [heading](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                           | Default  | Description                                                                                                |
|-----------|--------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA) | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                        | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                        | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |

| Attribute | Type                                  | Default  | Description                                                                           |
|-----------|---------------------------------------|----------|---------------------------------------------------------------------------------------|
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element. |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.  |

# crewpos3

## Crew Position 3

*Description:* Defines the first crew position in the Coordinated Action Table

*Source paragraph:* 3.2.12.2, 3.2.12.2.1 (MIL-DTL-7700)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hpc](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [heading](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

# crewpos4

## Crew Position 4

*Description:* Defines the first crew position in the Coordinated Action Table

*Source paragraph:* 3.2.12.2, 3.2.12.2.1 (MIL-DTL-7700)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hpc](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [heading](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

## crewpos5

### Crew Position 5

*Description:* Defines the first crew position in the Coordinated Action Table

*Source paragraph:* 3.2.12.2, 3.2.12.2.1 (MIL-DTL-7700)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+)

*Parents:* [heading](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

## dataiden

### Data Identification

*Description:* May be used to identify specific types of data (e.g. hazardous materials, special tools, etc.). Use of this element does not affect the formatted output, but is intended to be used in database functions and data searches.

*Source paragraph:* None

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+) -([dataiden](#) | [figure](#) | [table](#) | [foldout](#) | [objmedia](#))

**Parents:** [abbrtitle](#), [action](#), [amplification](#), [applicabil](#), [applttitle](#), [authnot](#), [change](#), [chgdate](#), [chgnum](#), [chgtxt](#), [clink](#), [clitem](#), [cogact](#), [condition](#), [contractno](#), [copyright](#), [cpos](#), [crewpos](#), [crewpos1](#), [crewpos2](#), [crewpos3](#), [crewpos4](#), [crewpos5](#), [dataiden](#), [date](#), [def](#), [destr](#), [discl](#), [distrib](#), [doctype](#), [effdatenot](#), [emphasis](#), [entry](#), [etitle](#), [expcont](#), [extapplicabil](#), [ftnote](#), [hazmat](#), [ilink](#), [internatlst](#), [item](#), [label](#), [lepchg](#), [leppage](#), [line](#), [maintlvl](#), [mfr](#), [modelno](#), [moveddata](#), [newpos1](#), [newpos2](#), [newpos3](#), [newpos4](#), [newpos5](#), [nmlist](#), [nomen](#), [nsn](#), [oadr](#), [pageno](#), [para](#), [param](#), [parano](#), [paras](#), [paratitle](#), [partno](#), [pgnumber](#), [phrase](#), [pretmidno](#), [pubdate](#), [revnum](#), [sectocstr](#), [seqno](#), [serno](#), [subject](#), [subparano](#), [subtitle](#), [supersed](#), [suppl](#), [symb](#), [symtitle](#), [term](#), [tfnid](#), [title](#), [tmidno](#), [typedes](#), [underline](#)

**Excluded in:** [dataiden](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [exclus](#), [secur](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default   | Description                                                                                                                                                    |
|-----------|---------------------------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| type      | CDATA                                 | #REQUIRED | Defines the type of data being used in the database functions and database searches.                                                                           |
| security  | (u   c   s   n)                       | n         | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED  | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED  | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0         | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

# date

## Date

**Description:** Identifies a date.

**Source paragraph:** 4.5.1.17 and 4.5.9.4b (MIL-STD-38784)

**Content Model:** ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+ -([figure](#) | [table](#) | [foldout](#) | [objmedia](#))

**Parents:** [chginfo](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [exclus](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                           | Default  | Description                                                                                                                   |
|-----------|--------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                        | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |

| Attribute | Type                                  | Default  | Description                                                                                                            |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------|
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.              |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element. |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                   |

## def

### Definition

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies a definition in a list. Each definition has an associated term.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <i>Source paragraph:</i>              | 4.3.4 (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <i>Content Model:</i>                 | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">ftnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcp</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> )+) -( <a href="#">figure</a>   <a href="#">table</a>   <a href="#">foldout</a>   <a href="#">objmedia</a> ) |
| <i>Parents:</i>                       | <a href="#">acronym</a> , <a href="#">acronymlist</a> , <a href="#">acronymrow</a> , <a href="#">applic</a> , <a href="#">applchd</a> , <a href="#">defhd</a> , <a href="#">deflist</a> , <a href="#">symrow</a> , <a href="#">symsect</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">exclus</a> , <a href="#">secur</a> , <a href="#">status</a> , <a href="#">text</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

## defhd

### Definition List Column Headings

|                          |                                                       |
|--------------------------|-------------------------------------------------------|
| <i>Description:</i>      | Identifies the column headings for a definition list. |
| <i>Source paragraph:</i> | 4.3.4 (MIL-STD-38784)                                 |



Content Model: (term, def)

Parents: deflist

Entities used in this element: chgatt, delstat, status, yesorno

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# deflist

## Definition List

Description: Identifies a two-column definition list. This element can be used when a listing is needed to define particular terms.

Source paragraph: 4.3.4 (MIL-STD-38784)

Content Model: (title?, defhd?, (term, def)+)

Parents: amplification, entry, ftnote, para, paras

Excluded in: caution, note, warning

Entities used in this element: chgatt, delstat, secur, status, yesorno

## ATTRIBUTE LIST

| Attribute  | Type                                  | Default  | Description                                                                                                                                                    |
|------------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| rtermwidth | NUTOKEN                               | 1.9in    | Allows the author to set the width of the right column.                                                                                                        |
| ltermwidth | NUTOKEN                               | 0.7in    | Allows the author to set the width of the left column.                                                                                                         |
| delttype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl   | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl   | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status     | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg     | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |
| security   | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat     | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi        | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |

---

# destr

## Destruction Notice

*Description:* Identifies the destruction notice on the title page.

*Source paragraph:* 4.5.1.13 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [idinfo](#)

*Entities used in this element:* [text](#)

---

# discl

## Disclosure Notice

*Description:* Identifies the disclosure notice on the title page.

*Source paragraph:* 4.5.1.10 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [idinfo](#)

*Entities used in this element:* [text](#)

### ATTRIBUTE LIST

| Attribute | Type  | Default  | Description                                                                                                                                                                                  |
|-----------|-------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| disclos1  | CDATA | #IMPLIED | Identifies which type of disclosure notice will appear on the title page. Use of this attribute will generate an alternate disclosure notice as opposed to the notice generated by the FOSI. |

---

# distrib

## Distribution Statement

*Description:* Identifies the distribution statement.

*Source paragraph:* 4.5.1.11 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

Parents: [idinfo](#)

Entities used in this element: [text](#)

## ATTRIBUTE LIST

| Attribute | Type                        | Default   | Description                                                                         |
|-----------|-----------------------------|-----------|-------------------------------------------------------------------------------------|
| type      | (A   B   C   D   E   F   X) | #REQUIRED | Identifies and displays the type of distribution statement per STINFO requirements. |

---

# doc

## Document

Description: Identifies the entire document and is the top level element.

Source paragraph: 4.1.7 (MIL-STD-38784)

Content Model: (docfmcl) +(pgbrk | brk | subjinfo | line | modreq | location | note)

Entities used in this element: [doc](#), [docatt](#), [pubatts](#), [secur](#), [service](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                                                | Default   | Description                                                                                                                                                                                                                                                            |
|-----------|---------------------------------------------------------------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| service   | (AF   NAVAIR   NAVSEA   SPAWARS   ARMY   MC   DLA   CG   DOD   FRN) | #REQUIRED | Identifies which branch of the service. If no branch is suitable, the author should choose "FRN" and manually fill in the appropriate branch using the FRN attribute.                                                                                                  |
| FRN       | CDATA                                                               | #IMPLIED  | Allows the author to manually enter the branch. This will be displayed on the "A" page of the LEP. This should only be used when the service attribute is set to "FRN".                                                                                                |
| docid     | CDATA                                                               | #IMPLIED  | Allows the author to define an identification number for the document.                                                                                                                                                                                                 |
| docstat   | (revision   change   prelim   draft   formal)                       | prelim    | Allows the author to stipulate what form the manual is in.                                                                                                                                                                                                             |
| verstatpg | (ver   unver)                                                       | unver     | Allows the author to stipulate a verified or unverified manual. Use of this attribute will trigger the generation of the verification status page and the temporary file - vsmatter.dat. See the accompanying readme.txt file on verification status for more details. |
| index     | NUMBER                                                              | 0         | Indicates whether an index is included in the manual. This attribute should be set to "1" when an index is present. Use of this attribute will affect the level of detail in the table of contents.                                                                    |
| security  | (u   c   s   n)                                                     | n         | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.                                                                                                          |
| caveat    | CDATA                                                               | #IMPLIED  | Provides a place to set the caveat for the document. For proper formatting on foldout pages, the caveat should be preceded and succeeded with enough "spaces" to occupy the same length as the security classification.                                                |
| fgi       | CDATA                                                               | #IMPLIED  | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.                                                                                                         |
| controlno | CDATA                                                               | 00000000  | System generated attribute value included for compliance with the JCALS menu structure.                                                                                                                                                                                |
| cycle     | CDATA                                                               | new       | System generated attribute value included for compliance with the JCALS menu structure.                                                                                                                                                                                |
| chglevel  | NUMBER                                                              | #IMPLIED  | System generated attribute value included for compliance with the JCALS menu structure.                                                                                                                                                                                |
| initlabel | NUMBER                                                              | #IMPLIED  | System generated attribute value included for compliance with the JCALS menu structure.                                                                                                                                                                                |

| Attribute  | Type   | Default        | Description                                                                                                                                                   |
|------------|--------|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| initpage   | NUMBER | 1              | System generated attribute value included for compliance with the JCALS menu structure.                                                                       |
| docno      | CDATA  | #IMPLIED       | System generated attribute value included for compliance with the JCALS menu structure.                                                                       |
| highguid   | NUMBER | 0              | System generated attribute value included for compliance with the JCALS menu structure.                                                                       |
| labelstyle | CDATA  | FAN            | System generated attribute value included for compliance with the JCALS menu structure.                                                                       |
| HyTime     | NAME   | #FIXED "HyDoc" | Used to alert the processing system that this is a HyTime compliant document. This attribute is only required and/or effective with a HyTime aware processor. |

# docfmcl

## Flight Manual Abbreviated Checklist

**Description:** Second level tag under DOC. JCALS menuing system requires the DOC wrapper tag to be present. All attributes normally found on the document tag are on the DOC tag (see 38784STD-BV9 DTD)

**Source paragraph:** 3.7 (MIL-DTL-7700)

**Content Model:** (front, body) +(w | c)

**Parents:** doc

**Entities used in this element:** docfmcl, presymbol1, presymbol2, presymbol3

### ATTRIBUTE LIST

| Attribute     | Type                                                         | Default   | Description                                                                                                                                                                                                                                           |
|---------------|--------------------------------------------------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pagetype      | (4x7  5x8grad  5x8nograd  5x9grad 5x9nograd  514x11  534x11) | #REQUIRED | Attribute for choosing the page size/type of checklist.                                                                                                                                                                                               |
| paranumbers   | (0   1)                                                      | #REQUIRED | When set to 0, no paranumbers will appear in output, when set to 1 paragraph and procedure numbers will appear.                                                                                                                                       |
| thrfltsym     | (N1 Asterisk1 Plus1 X1  Hash1 Dagger1)                       | N1        | Sets the Through flight symbol to be used throughout the checklist.                                                                                                                                                                                   |
| feresponsesym | (N2 Asterisk2 Plus2 X2  Hash2 Dagger2)                       | N2        | Preceding any checklist step means the step is contained in section II and that a response is required when the flight engineer reads the item.                                                                                                       |
| nomisscrwsym  | (N3 Asterisk3 Plus3 X3  Hash3 Dagger3)                       | N3        | Indicate specific checklist steps the engineer will accomplish when a mission crew is not present. This would only happen when training is being accomplished which does not require the mission crew, such as pattern work, or perhaps air refueling |

# doctype

## Document Type

**Description:** Identifies the type of manual on the title page (e.g. maintenance instructions, illustrated parts breakdown, inspection manual, etc.).

**Source paragraph:** 4.5.1.3.2 (MIL-STD-38784)

Content Model: ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

Parents: [idinfo](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# downgrd

## Downgrade Notice

Description: Identifies the classification downgrade notice on the title page.

Source paragraph: 4.4 (MIL-STD-38784)

Content Model: ([phrase](#) | [oadr](#))

Parents: [idinfo](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# effdatenot

## Effective Date Notice

*Description:* Identifies the effective date notice on the title page.

*Source paragraph:* 4.5.1.8 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [idinfo](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# emergproccl

## Emergency Procedures Checklist

*Description:* Checklists for all emergency procedures from the Flight Manual.

*Source paragraph:* 3.7.6.1 (MIL-DTL-7700)

*Content Model:* (([title](#)), [secttoc](#), [procedure](#)<sup>+</sup>) <sup>+</sup>([sectocstr](#) | [figure](#) | [table](#) | [graphic](#) | [addcond](#) | [etitle](#) | [figtable](#) | [tabmat](#))

*Parents:* [body](#)

*Entities used in this element:* [bodyatt](#), [chapatt](#), [chgatt](#), [delstat](#), [secur](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute   | Type            | Default  | Description                                                                                                                                                   |
|-------------|-----------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| emergsysltr | CDATA           | #IMPLIED | Allows the letter to be entered for emergency procedure section numbering.                                                                                    |
| id          | ID              | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                              |
| security    | (u   c   s   n) | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level. |

| Attribute | Type                                  | Default  | Description                                                                                                                                                          |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                     |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.       |
| label     | CDATA                                 | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired. |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, or Subject Number can be assigned to this element.                                                                                                |
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is This attribute is not currently supported by the FOSI.                                                      |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                       |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Insert Change Level                                                                                                               |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Delete Change Level                                                                                                               |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows you to specify the status of this element.                                                                                                                    |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                 |

# emphasis

## Emphasis

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies portions of text to be highlighted (e.g. italic, bold, etc.). This element is included to allow the author flexibility in composing the manual in accordance with this spec.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <i>Source paragraph:</i>              | None                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <i>Content Model:</i>                 | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">fnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcp</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> +) -(figure   table   foldout   objmedia)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <i>Parents:</i>                       | <a href="#">abbrtitle</a> , <a href="#">action</a> , <a href="#">amplification</a> , <a href="#">applicabil</a> , <a href="#">applttitle</a> , <a href="#">authnot</a> , <a href="#">change</a> , <a href="#">chgdate</a> , <a href="#">chgnum</a> , <a href="#">chgtxt</a> , <a href="#">clink</a> , <a href="#">clitem</a> , <a href="#">cogact</a> , <a href="#">condition</a> , <a href="#">contractno</a> , <a href="#">copyright</a> , <a href="#">cpos</a> , <a href="#">crewpos</a> , <a href="#">crewpos1</a> , <a href="#">crewpos2</a> , <a href="#">crewpos3</a> , <a href="#">crewpos4</a> , <a href="#">crewpos5</a> , <a href="#">dataiden</a> , <a href="#">date</a> , <a href="#">def</a> , <a href="#">destr</a> , <a href="#">discl</a> , <a href="#">distrib</a> , <a href="#">doctype</a> , <a href="#">effdatenot</a> , <a href="#">emphasis</a> , <a href="#">entry</a> , <a href="#">etitle</a> , <a href="#">expcont</a> , <a href="#">extapplicabil</a> , <a href="#">fnote</a> , <a href="#">hazmat</a> , <a href="#">ilink</a> , <a href="#">internatlst</a> , <a href="#">item</a> , <a href="#">label</a> , <a href="#">lepchg</a> , <a href="#">leppage</a> , <a href="#">line</a> , <a href="#">maintlvl</a> , <a href="#">mfr</a> , <a href="#">modelno</a> , <a href="#">moveddata</a> , <a href="#">newpos1</a> , <a href="#">newpos2</a> , <a href="#">newpos3</a> , <a href="#">newpos4</a> , <a href="#">newpos5</a> , <a href="#">nmlist</a> , <a href="#">nomen</a> , <a href="#">nsn</a> , <a href="#">oadr</a> , <a href="#">pageno</a> , <a href="#">para</a> , <a href="#">param</a> , <a href="#">parano</a> , <a href="#">paras</a> , <a href="#">paratitle</a> , <a href="#">partno</a> , <a href="#">pgnumber</a> , <a href="#">phrase</a> , <a href="#">pretmidno</a> , <a href="#">pubdate</a> , <a href="#">revnum</a> , <a href="#">sectocstr</a> , <a href="#">seqno</a> , <a href="#">serno</a> , <a href="#">subject</a> , <a href="#">subparano</a> , <a href="#">subtitle</a> , <a href="#">supersd</a> , <a href="#">suppl</a> , <a href="#">symb</a> , <a href="#">symtitle</a> , <a href="#">term</a> , <a href="#">tfnid</a> , <a href="#">title</a> , <a href="#">tmidno</a> , <a href="#">typedes</a> , <a href="#">underline</a> |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">exclus</a> , <a href="#">status</a> , <a href="#">text</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## ATTRIBUTE LIST

| Attribute | Type                                                                           | Default   | Description                                                                                                                                                                                                                                                                                                                                       |
|-----------|--------------------------------------------------------------------------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| type      | (u b bu i bi q qa x o sup sub ui)                                              | #REQUIRED | Displays different types of emphasis. Set this attribute equal to "u" for underline, "b" for bold, "bu" for bold/underline, "i" for italics, "bi" for bold/italics, "q" for quotes, "qa" for quote alternate (currently unsupported), "x" for box, "o" for overscore, "sup" for superscript, "sub" for subscript, and "ui" for underline/italics. |
| fontsize  | NUTOKEN                                                                        | #IMPLIED  | Allows the author to set the font size which will be applied to the text within the emphasis element.                                                                                                                                                                                                                                             |
| color     | (black   white   red   orange   yellow   green   blue   violet   brown   gray) | #IMPLIED  | Allows the author to set the color which will be applied to the text within the emphasis element.                                                                                                                                                                                                                                                 |
| delttype  | (delete   real   reserve   NA)                                                 | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                                                                                                                                                                                                     |

| Attribute | Type                                  | Default  | Description                                                                                                            |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------|
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.             |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.              |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element. |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                   |

# end

## End

*Description:* Allows marking for end of column.

*Source paragraph:* N/A

*Content Model:* EMPTY

*Included in:* [procedure](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

# endcond

## End condition

*Description:* Allows marking for end of column.

*Source paragraph:* N/A

*Content Model:* EMPTY

*Parents:* [addcond](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST



| Attribute | Type                                                                                                                                                                                | Default  | Description                                                                                                |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| pagetype  | (5x3   5x325   5x35   5x375   5x4   5x425   5x45   5x475   5x5   5x525   5x55   5x575   5x6   5x625   5x65   5x675   5x7   5x725   5x75   5x775   5x8   5x825   5x85   5x875   5x9) | #IMPLIED | Attribute for choosing the page size/type of checklist after the end of the Other Considerations page.     |
| delttype  | (delete   real   reserve   NA)                                                                                                                                                      | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                                                                                                                                                                             | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                                                                                                                                                                             | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp)                                                                                                                                               | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                                                                                                                                                              | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

## entry

### Table Entry

*Description:* Identifies a table entry (cell).

*Source paragraph:* 4.2.7 (MIL-STD-38784)

*Content Model:* (((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+ | [randlist](#) | [deflist](#) | [seqlist](#) | [warning](#) | [caution](#) | [note](#) | (procstep?, procstep2?, procstep3?, procstep4?))+)

*Parents:* [row](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [entry](#), [entryatt](#), [list](#), [secur](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                     | Default  | Description                                                                                                                                                |
|-----------|------------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| colname   | NMTOKEN                                  | #IMPLIED | Allows the author to specify the name of the column to use.                                                                                                |
| spanname  | NMTOKEN                                  | #IMPLIED | Allows the author to define a span name.                                                                                                                   |
| id        | ID                                       | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                           |
| morerows  | NUMBER                                   | 0        | Allows the author to define a vertical span on entries within a table.                                                                                     |
| colsep    | NUMBER                                   | #IMPLIED | Allows the author to include a vertical line to separate columns. Setting this attribute equal to "1" will generate column separators.                     |
| rowsep    | NUMBER                                   | #IMPLIED | Allows the author to include a horizontal line to separate rows. Setting this attribute equal to "1" will generate row separators.                         |
| rotate    | NUMBER                                   | 0        | Set this attribute equal to "1" to rotate the contents of the entry 90 degrees.                                                                            |
| valign    | (top   middle   bottom)                  | #IMPLIED | Defines the vertical alignment of text within a cell.                                                                                                      |
| align     | (left   right   center   justify   char) | #IMPLIED | Defines the horizontal alignment of text within a cell.                                                                                                    |
| charoff   | NUTOKEN                                  | #IMPLIED | Determines the distance the cell content should offset from the horizontal alignment character.                                                            |
| char      | CDATA                                    | #IMPLIED | Defines the alignment character that can be used to align values within a column. This attribute should be used when the align attribute is set to "char". |

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |

# entrytbl

## Entry Table

**Description:** Identifies a table within a table entry. This element allows a table cell to be divided into a sub-table, with its own set of rows, columns, and entries. Use of this element basically allows the author to create a table within a table.

**Source paragraph:** 4.2.7 (MIL-STD-38784)

**Content Model:** (colspec\*, spanspec\*, thead?, tbody) -(entrytbl)

**Parents:** row

**Excluded in:** entrytbl, tfoot, thead

**Entities used in this element:** chgatt, delstat, secur, status, yesorno

## ATTRIBUTE LIST

| Attribute | Type                                     | Default   | Description                                                                                                                                                   |
|-----------|------------------------------------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| cols      | NUMBER                                   | #REQUIRED | Allows the author to define the number of columns.                                                                                                            |
| colname   | NMTOKEN                                  | #IMPLIED  | Allows the author to specify the name of the column to use.                                                                                                   |
| spanname  | NMTOKEN                                  | #IMPLIED  | Allows the author to define a span name.                                                                                                                      |
| colsep    | NUMBER                                   | #IMPLIED  | Allows the author to include a vertical line to separate columns. Setting this attribute equal to "1" will generate column separators.                        |
| rowsep    | NUMBER                                   | #IMPLIED  | Allows the author to include a horizontal line to separate rows. Setting this attribute equal to "1" will generate row separators.                            |
| align     | (left   right   center   justify   char) | #IMPLIED  | Defines the horizontal alignment of text within a cell.                                                                                                       |
| charoff   | NUTOKEN                                  | #IMPLIED  | Determines the distance the cell content should offset from the horizontal alignment character.                                                               |
| char      | CDATA                                    | #IMPLIED  | Defines the alignment character that can be used to align values within a column. This attribute should be used when the align attribute is set to "char".    |
| security  | (u   c   s   n)                          | n         | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level. |
| caveat    | CDATA                                    | #IMPLIED  | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                              |

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

# EPDecision1

## Emergency Procedures Decision One

*Description:* Identifies the first set of steps in an IFTHEN.

*Source paragraph:* N/A

*Content Model:* (condition?, ifstep1\*)

*Parents:* if

*Entities used in this element:* chgatt, delstat, status, yesorno

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

# EPDecision2

## Emergency Procedures Decision Two

*Description:* Identifies the second set of steps in an IFTHEN.

*Source paragraph:* N/A

*Content Model:* (condition?, ifstep1\*)

*Parents:* if

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

# esds

## Electrostatic Discharge Sensitive (ESDS)

**Description:** Identifies ESDS parts. Use of this element will cause the **\*\*ESD\*\*** symbol to appear at that point in the running text. This element should only be used in running text, e.g. to display the **\*\*ESD\*\*** symbol in a paragraph. The esds attribute should be used to place the **\*\*ESD\*\*** symbol between a paragraph/step number and text.

**Source paragraph:** 4.3.10.4 (MIL-STD-38784)

**Content Model:** EMPTY

**Parents:** [abbrtitle](#), [action](#), [amplification](#), [applicabil](#), [appltile](#), [authnot](#), [change](#), [chgdate](#), [chgnum](#), [chgtxt](#), [clink](#), [clitem](#), [cogact](#), [condition](#), [contractno](#), [copyright](#), [cpos](#), [crewpos](#), [crewpos1](#), [crewpos2](#), [crewpos3](#), [crewpos4](#), [crewpos5](#), [dataiden](#), [date](#), [def](#), [destr](#), [discl](#), [distrib](#), [doctype](#), [effdatenot](#), [emphasis](#), [entry](#), [etitle](#), [expcont](#), [extapplicabil](#), [ftnote](#), [hazmat](#), [ilink](#), [internatlstd](#), [item](#), [label](#), [lepchg](#), [leppage](#), [line](#), [maintlvl](#), [mfr](#), [modelno](#), [moveddata](#), [newpos1](#), [newpos2](#), [newpos3](#), [newpos4](#), [newpos5](#), [nmlist](#), [nomen](#), [nsn](#), [oadr](#), [pageno](#), [para](#), [param](#), [parano](#), [paras](#), [paratitle](#), [partno](#), [pgnumber](#), [phrase](#), [pretmidno](#), [pubdate](#), [revnum](#), [sectocstr](#), [seqno](#), [serno](#), [subject](#), [subparano](#), [subtitle](#), [supersed](#), [suppl](#), [symb](#), [symtitle](#), [term](#), [tfnid](#), [title](#), [tmidno](#), [typedes](#), [underline](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# etitle

## Emergency title

*Description:* Allows for a tab title to be added at the bottom of non-graduated recto pages or the bottom of all graduated pages.

*Source paragraph:* 3.7.6.1 (MIL-DTL-7700)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Included in:* [clsection](#), [emergproccl](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

# expcont

## Export Control Notice

*Description:* Identifies the export control notice on the title page. Note that the export control notice entity (&expcontnot;) may be used in place of entering the text manually.

*Source paragraph:* 4.5.1.12 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>) <sup>+</sup>([underline](#))

*Parents:* [idinfo](#)

*Entities used in this element:* [text](#)

# extapplicabil

## External Applicability/Effectivity

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies a portion of text as being applicable to a specific model, serial number, part number, etc. Use of this element will cause the applicability/effectivity markings to appear at that point in running text.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <i>Source paragraph:</i>              | 4.3f (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <i>Content Model:</i>                 | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">ftnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcp</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> )+) -( <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">figure</a>   <a href="#">table</a>   <a href="#">foldout</a>   <a href="#">objmedia</a> )                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <i>Parents:</i>                       | <a href="#">abbrtitle</a> , <a href="#">action</a> , <a href="#">amplification</a> , <a href="#">applicabil</a> , <a href="#">appltile</a> , <a href="#">authnot</a> , <a href="#">change</a> , <a href="#">chgdate</a> , <a href="#">chgnum</a> , <a href="#">chgtxt</a> , <a href="#">clink</a> , <a href="#">clitem</a> , <a href="#">cogact</a> , <a href="#">condition</a> , <a href="#">contractno</a> , <a href="#">copyright</a> , <a href="#">cpos</a> , <a href="#">crewpos</a> , <a href="#">crewpos1</a> , <a href="#">crewpos2</a> , <a href="#">crewpos3</a> , <a href="#">crewpos4</a> , <a href="#">crewpos5</a> , <a href="#">dataiden</a> , <a href="#">date</a> , <a href="#">def</a> , <a href="#">destr</a> , <a href="#">discl</a> , <a href="#">distrib</a> , <a href="#">doctype</a> , <a href="#">effdatenot</a> , <a href="#">emphasis</a> , <a href="#">entry</a> , <a href="#">etitle</a> , <a href="#">expcont</a> , <a href="#">extapplicabil</a> , <a href="#">fnote</a> , <a href="#">hazmat</a> , <a href="#">ilink</a> , <a href="#">internatlstd</a> , <a href="#">item</a> , <a href="#">label</a> , <a href="#">lepchg</a> , <a href="#">leppage</a> , <a href="#">line</a> , <a href="#">maintlvl</a> , <a href="#">mfr</a> , <a href="#">modelno</a> , <a href="#">moveddata</a> , <a href="#">newpos1</a> , <a href="#">newpos2</a> , <a href="#">newpos3</a> , <a href="#">newpos4</a> , <a href="#">newpos5</a> , <a href="#">nmlist</a> , <a href="#">nomen</a> , <a href="#">nsn</a> , <a href="#">oadr</a> , <a href="#">pageno</a> , <a href="#">para</a> , <a href="#">param</a> , <a href="#">parano</a> , <a href="#">paras</a> , <a href="#">paratitle</a> , <a href="#">partno</a> , <a href="#">pgnumber</a> , <a href="#">phrase</a> , <a href="#">pretmidno</a> , <a href="#">pubdate</a> , <a href="#">revnum</a> , <a href="#">sectocstr</a> , <a href="#">seqno</a> , <a href="#">serno</a> , <a href="#">subject</a> , <a href="#">subparano</a> , <a href="#">subtitle</a> , <a href="#">supersed</a> , <a href="#">suppl</a> , <a href="#">symb</a> , <a href="#">symtitle</a> , <a href="#">term</a> , <a href="#">tfnid</a> , <a href="#">title</a> , <a href="#">tmidno</a> , <a href="#">typesdes</a> , <a href="#">underline</a> |
| <i>Excluded in:</i>                   | <a href="#">extapplicabil</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">exclus</a> , <a href="#">secur</a> , <a href="#">status</a> , <a href="#">text</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

### ATTRIBUTE LIST

| Attribute    | Type                                  | Default                 | Description                                                                                                                                                                                                                                                |
|--------------|---------------------------------------|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| targetdoc    | CDATA                                 | #REQUIRED               | Identifies the external document that you are referencing. This value should equal an ID specified in the List of Related Publications. For implementing external references in digital data, this ID must equal the ID of the external document.          |
| targetid     | CDATA                                 | #IMPLIED                | Provides the ID for the element being referenced in the external document. The value of this attribute should equal the ID of an element in the referenced document.                                                                                       |
| displayvalue | CDATA                                 | #IMPLIED                | Allows the author to add additional, unique information for purposes of referencing an external document. This attribute should be used for providing paragraph titles, system numbers, task numbers and for author-generated TO numbers where applicable. |
| HyTime       | NAME                                  | #FIXED "clink"          | Used in combination with HyTime to establish a contextual link.                                                                                                                                                                                            |
| HyNames      | NAMES                                 | #FIXED "linkend xrefid" | Used in combination with HyTime to establish a contextual link.                                                                                                                                                                                            |
| security     | (u   c   s   n)                       | n                       | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.                                                                                              |
| caveat       | CDATA                                 | #IMPLIED                | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                                                                           |
| fgi          | CDATA                                 | #IMPLIED                | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.                                                                                             |
| delttype     | (delete   real   reserve   NA)        | #IMPLIED                | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                                                                                                              |
| inschlvl     | NMTOKEN                               | #IMPLIED                | Used during the change package process to indicate the element was inserted at the change level indicated.                                                                                                                                                 |
| delchlvl     | NMTOKEN                               | #IMPLIED                | Used during the change package process to indicate the element was deleted at the change level indicated.                                                                                                                                                  |
| status       | (empty   deleted   reserved   notapp) | #IMPLIED                | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                                                                                                     |
| revchg       | NUMBER                                | 0                       | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                                                                                                       |

---

# extref

## External Reference

*Description:* Generates a reference to an external document.

*Source paragraph:* 4.3.1m (MIL-STD-38784)

*Content Model:* EMPTY

*Parents:* [abbrtitle](#), [action](#), [amplification](#), [applicabil](#), [appltite](#), [authnot](#), [change](#), [chgdate](#), [chgnum](#), [chgtxt](#), [clink](#), [clitem](#), [cogact](#), [condition](#), [contractno](#), [copyright](#), [cpos](#), [crewpos](#), [crewpos1](#), [crewpos2](#), [crewpos3](#), [crewpos4](#), [crewpos5](#), [dataiden](#), [date](#), [def](#), [destr](#), [discl](#), [distrib](#), [doctype](#), [effdatenot](#), [emphasis](#), [entry](#), [etitle](#), [expcont](#), [extapplicabil](#), [ftnote](#), [hazmat](#), [ilink](#), [internatlst](#), [item](#), [label](#), [lepchg](#), [leppage](#), [line](#), [maintlvl](#), [mfr](#), [modelno](#), [moveddata](#), [newpos1](#), [newpos2](#), [newpos3](#), [newpos4](#), [newpos5](#), [nmlist](#), [nomen](#), [nsn](#), [oadr](#), [pageno](#), [para](#), [param](#), [parano](#), [paras](#), [paratitle](#), [partno](#), [pgnumber](#), [phrase](#), [pretmidno](#), [pubdate](#), [revnum](#), [sectocstr](#), [seqno](#), [serno](#), [subject](#), [subparano](#), [subtitle](#), [supersed](#), [suppl](#), [symb](#), [symtitle](#), [term](#), [tfnid](#), [title](#), [tmidno](#), [typedes](#), [underline](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute    | Type                                  | Default                 | Description                                                                                                                                                                                                                                                |
|--------------|---------------------------------------|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| targetdoc    | CDATA                                 | #REQUIRED               | Identifies the external document that you are referencing. This value should equal an ID specified in the List of Related Publications. For implementing external references in digital data, this ID must equal the ID of the external document.          |
| targetid     | CDATA                                 | #IMPLIED                | Provides the ID for the element being referenced in the external document. The value of this attribute should equal the ID of an element in the referenced document.                                                                                       |
| displayvalue | CDATA                                 | #IMPLIED                | Allows the author to add additional, unique information for purposes of referencing an external document. This attribute should be used for providing paragraph titles, system numbers, task numbers and for author-generated TO numbers where applicable. |
| HyTime       | NAME                                  | #FIXED "clink"          | Used in combination with HyTime to establish a contextual link.                                                                                                                                                                                            |
| HyNames      | NAMES                                 | #FIXED "linkend xrefid" | Used in combination with HyTime to establish a contextual link.                                                                                                                                                                                            |
| delttype     | (delete   real   reserve   NA)        | #IMPLIED                | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                                                                                                              |
| inschlvl     | NMTOKEN                               | #IMPLIED                | Used during the change package process to indicate the element was inserted at the change level indicated.                                                                                                                                                 |
| delchlvl     | NMTOKEN                               | #IMPLIED                | Used during the change package process to indicate the element was deleted at the change level indicated.                                                                                                                                                  |
| status       | (empty   deleted   reserved   notapp) | #IMPLIED                | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                                                                                                     |
| revchg       | NUMBER                                | 0                       | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                                                                                                       |

---

# fcf

## Fracture Critical Parts (FCP)

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies fracture critical parts. Use of this element will cause the <b>FCF</b> symbol to appear at that point in the running text. This element should only be used in running text, e.g. to display the <b>FCF</b> symbol in a paragraph. The fcf attribute should be used to place the <b>FCF</b> symbol between a paragraph/step number and text.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <i>Source paragraph:</i>              | 4.3.10.5 (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <i>Content Model:</i>                 | EMPTY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <i>Parents:</i>                       | <a href="#">abbrtitle</a> , <a href="#">action</a> , <a href="#">amplification</a> , <a href="#">applicabil</a> , <a href="#">apptitle</a> , <a href="#">authnot</a> , <a href="#">change</a> , <a href="#">chgdate</a> , <a href="#">chgnum</a> , <a href="#">chgtxt</a> , <a href="#">clink</a> , <a href="#">clitem</a> , <a href="#">cogact</a> , <a href="#">condition</a> , <a href="#">contractno</a> , <a href="#">copyright</a> , <a href="#">cpos</a> , <a href="#">crewpos</a> , <a href="#">crewpos1</a> , <a href="#">crewpos2</a> , <a href="#">crewpos3</a> , <a href="#">crewpos4</a> , <a href="#">crewpos5</a> , <a href="#">dataiden</a> , <a href="#">date</a> , <a href="#">def</a> , <a href="#">destr</a> , <a href="#">discl</a> , <a href="#">distrib</a> , <a href="#">doctype</a> , <a href="#">effdatenot</a> , <a href="#">emphasis</a> , <a href="#">entry</a> , <a href="#">etitle</a> , <a href="#">expcont</a> , <a href="#">extapplicabil</a> , <a href="#">fnote</a> , <a href="#">hazmat</a> , <a href="#">ilink</a> , <a href="#">internatlst</a> , <a href="#">item</a> , <a href="#">label</a> , <a href="#">lepchg</a> , <a href="#">leppage</a> , <a href="#">line</a> , <a href="#">maintl</a> , <a href="#">mfr</a> , <a href="#">modelno</a> , <a href="#">moveddata</a> , <a href="#">newpos1</a> , <a href="#">newpos2</a> , <a href="#">newpos3</a> , <a href="#">newpos4</a> , <a href="#">newpos5</a> , <a href="#">nmlist</a> , <a href="#">nomen</a> , <a href="#">nsn</a> , <a href="#">oadr</a> , <a href="#">pageno</a> , <a href="#">para</a> , <a href="#">param</a> , <a href="#">parano</a> , <a href="#">paras</a> , <a href="#">paratitle</a> , <a href="#">partno</a> , <a href="#">pgnumber</a> , <a href="#">phrase</a> , <a href="#">pretmidno</a> , <a href="#">pubdate</a> , <a href="#">revnum</a> , <a href="#">sectocstr</a> , <a href="#">seqno</a> , <a href="#">serno</a> , <a href="#">subject</a> , <a href="#">subparano</a> , <a href="#">subtitle</a> , <a href="#">supersd</a> , <a href="#">suppl</a> , <a href="#">syml</a> , <a href="#">symltitle</a> , <a href="#">term</a> , <a href="#">tfnid</a> , <a href="#">title</a> , <a href="#">tmidno</a> , <a href="#">typesdes</a> , <a href="#">underline</a> |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">status</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltpe    | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschl    | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchl    | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# figtable

## Table within a figure

|                                       |                                                                                                                                                                                                                        |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies a table contained within a figure, which does not have a table number or name, and does not appear in the list of tables. An example would be a component table on a schematic diagram.                     |
| <i>Source paragraph:</i>              | 4.3.9.1                                                                                                                                                                                                                |
| <i>Content Model:</i>                 | ( <a href="#">tgroup</a> +) -( <a href="#">figure</a>   <a href="#">table</a>   <a href="#">foldout</a>   <a href="#">objmedia</a> ) +( <a href="#">tfoot</a>   <a href="#">tfnref</a>   <a href="#">tfnidisplay</a> ) |
| <i>Parents:</i>                       | <a href="#">figure</a>                                                                                                                                                                                                 |
| <i>Included in:</i>                   | <a href="#">clsection</a> , <a href="#">emergproccl</a> , <a href="#">normproccl</a>                                                                                                                                   |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">exclus</a> , <a href="#">secur</a> , <a href="#">status</a> , <a href="#">yesorno</a>                                                                   |



## ATTRIBUTE LIST

| Attribute | Type                                         | Default  | Description                                                                                                                                                          |
|-----------|----------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA                                        | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired. |
| frame     | (top   bottom   topbot   all   sides   none) | all      | Defines the frame for the table.                                                                                                                                     |
| colsep    | NUMBER                                       | 1        | Allows you to include a vertical line to separate columns. A value of 1. for this attribute will generate column separators.                                         |
| rowsep    | NUMBER                                       | 0        | Allows you to include a horizontal line to separate rows. A value of 1. for this attribute will generate row separators.                                             |
| tbwidth   | NUTOKEN                                      | #IMPLIED | Defines the width of the table.                                                                                                                                      |
| tbdepth   | NUTOKEN                                      | #IMPLIED | Defines the depth (height) of the table.                                                                                                                             |
| horrefpt  | (left   right)                               | left     | Defines the horizontal reference point for the table.                                                                                                                |
| verrefpt  | (vtop   vbottom)                             | vtop     | Defines the vertical reference point for the table.                                                                                                                  |
| coordst   | CDATA                                        | 0,10000  | Ability to define the coordinates to start the table.                                                                                                                |
| assocfig  | IDREF                                        | #IMPLIED | Provides a means to add the id to an associated figure.                                                                                                              |
| delttype  | (delete   real   reserve   NA)               | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                       |
| inschlvl  | NMTOKEN                                      | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                           |
| delchlvl  | NMTOKEN                                      | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated                                                                 |
| status    | (empty   deleted   reserved   notapp)        | #IMPLIED | Used during the change package process to indicate the current status of the element.                                                                                |
| revchg    | NUMBER                                       | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                 |
| security  | (u   c   s   n)                              | n        | Identifies security level of the document                                                                                                                            |
| caveat    | CDATA                                        | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                     |
| fgi       | CDATA                                        | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.       |
| landscape | NUMBER                                       | #IMPLIED | Allows landscape page                                                                                                                                                |
| newpage   | NUMBER                                       | #IMPLIED | Start the figtable on its own page.                                                                                                                                  |

## figure

### Figure

|                                       |                                                                                                                                                                                                                                                                                    |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies an illustration.                                                                                                                                                                                                                                                        |
| <i>Source paragraph:</i>              | 4.2.8 (MIL-STD-38784)                                                                                                                                                                                                                                                              |
| <i>Content Model:</i>                 | (title, ((subfig, subfig+)   ((graphic, legend?)   figtable   tabdisplay)+)) -(figure   table   foldout   objmedia)                                                                                                                                                                |
| <i>Parents:</i>                       | performdatacl                                                                                                                                                                                                                                                                      |
| <i>Included in:</i>                   | clsection, emergproccl, intro, normproccl                                                                                                                                                                                                                                          |
| <i>Excluded in:</i>                   | abbrtitle, acronym, acronymlist, applicabil, applttitle, caution, change, dataiden, date, def, emphasis, extapplicabil, figtable, figure, ftnote, item, modelno, nomen, note, partno, serno, symtitle, tabdisplay, table, tabmat, term, title, tmidno, typedes, underline, warning |
| <i>Entities used in this element:</i> | bodyatt, chgatt, delstat, exclus, fig, figatts, secur, status, verified, yesorno                                                                                                                                                                                                   |

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                           |
|-----------|---------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pgwide    | NUMBER                                | 1        | Set this attribute equal to "1" to have the figure fill the entire width of the page.                                                                                 |
| orient    | (port   land   land2)                 | port     | Defines the orientation of the figure, either portrait or landscape. Setting this attribute equal to "land2" will rotate the figure and the figure title.             |
| id        | ID                                    | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                                      |
| applicref | IDREFS                                | #IMPLIED | Allows the author to assign an applicability/effectivity reference to this element.                                                                                   |
| legend    | NUMBER                                | 0        | Set this attribute equal to "1" when a legend is tagged as part of the figure.                                                                                        |
| nxtpg     | NUMBER                                | 0        | Set this attribute equal to "1" to indicate the legend should appear on the next page after the graphic.                                                              |
| verdate   | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                                                                         |
| verrem    | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                |
| verstatus | (unver   ver   notapplicable)         | unver    | Identifies the verification status of the element.                                                                                                                    |
| label     | CDATA                                 | #IMPLIED | Allows the author to label this element manually. The FOSI automatically generates labels, so its use is not necessary unless a label out of the ordinary is desired. |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                   |
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is not currently supported by the FOSI.                                                                         |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                         |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                            |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                             |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                  |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.         |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                      |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.        |

# front

## Front

*Description:* Identifies the front matter of the manual.

*Source paragraph:* 4.5 (MIL-STD-38784)

*Content Model:* (([idinfo](#), [lep](#), [verstat?](#), [intro](#))) +([fnote](#))

*Parents:* [docfmcl](#)

*Entities used in this element:* [frnt](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type      | Default   | Description                                                                                       |
|-----------|-----------|-----------|---------------------------------------------------------------------------------------------------|
| t2page    | NUMBER    | 0         | Set this attribute equal to "1" to generate a T-2 page (second title page).                       |
| numcols   | ( 1   2 ) | #REQUIRED | Allows the author to define the page format as one or two columns for this section of the manual. |

# ftnote

## Footnote

**Description:** Identifies footnotes to paragraphs and tables. The footnote appears on the same page that the corresponding footnote reference (<ftnref>) occurs. Only the footnote whose id matches the xrefid specified in the footnote reference will appear. Footnotes to text will be displayed at the bottom of the page where the footnote is referenced.

**Source paragraph:** 4.2.2.2.3 and 4.3.1n (MIL-STD-38784)

**Content Model:** ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#)) + [randlist](#) | [deflist](#) | [seqlist](#)) + -([ftnote](#) | [ftnref](#) | [figure](#) | [table](#) | [foldout](#) | [objmedia](#))

**Included in:** [body](#), [front](#)

**Excluded in:** [ftnote](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [exclus](#), [list](#), [secur](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default   | Description                                                                                                                                                    |
|-----------|---------------------------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| id        | ID                                    | #REQUIRED | Allows the author to generate a unique ID for use when referencing this element.                                                                               |
| security  | (u   c   s   n)                       | n         | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED  | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED  | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0         | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

---

# ftnref

## Footnote Reference

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies a reference to a footnote. This element will cause the footnote number/symbol/letter to appear at the point in the text where used, and will cause the footnote number/symbol/letter and the footnote text to appear at the bottom of the page.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <i>Source paragraph:</i>              | 4.3.1n (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <i>Content Model:</i>                 | EMPTY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <i>Parents:</i>                       | <a href="#">abbrtitle</a> , <a href="#">action</a> , <a href="#">amplification</a> , <a href="#">applicabil</a> , <a href="#">appltile</a> , <a href="#">authnot</a> , <a href="#">change</a> , <a href="#">chgdate</a> , <a href="#">chgnum</a> , <a href="#">chgtxt</a> , <a href="#">clink</a> , <a href="#">clitem</a> , <a href="#">cogact</a> , <a href="#">condition</a> , <a href="#">contractno</a> , <a href="#">copyright</a> , <a href="#">cpos</a> , <a href="#">crewpos</a> , <a href="#">crewpos1</a> , <a href="#">crewpos2</a> , <a href="#">crewpos3</a> , <a href="#">crewpos4</a> , <a href="#">crewpos5</a> , <a href="#">dataiden</a> , <a href="#">date</a> , <a href="#">def</a> , <a href="#">destr</a> , <a href="#">discl</a> , <a href="#">distrib</a> , <a href="#">doctype</a> , <a href="#">effdatenot</a> , <a href="#">emphasis</a> , <a href="#">entry</a> , <a href="#">etitle</a> , <a href="#">expcont</a> , <a href="#">extapplicabil</a> , <a href="#">fnote</a> , <a href="#">hazmat</a> , <a href="#">ilink</a> , <a href="#">internatlst</a> , <a href="#">item</a> , <a href="#">label</a> , <a href="#">lepchg</a> , <a href="#">leppage</a> , <a href="#">line</a> , <a href="#">maintlvl</a> , <a href="#">mfr</a> , <a href="#">modelno</a> , <a href="#">moveddata</a> , <a href="#">newpos1</a> , <a href="#">newpos2</a> , <a href="#">newpos3</a> , <a href="#">newpos4</a> , <a href="#">newpos5</a> , <a href="#">nmlist</a> , <a href="#">nomen</a> , <a href="#">nsn</a> , <a href="#">oadr</a> , <a href="#">pageno</a> , <a href="#">para</a> , <a href="#">param</a> , <a href="#">parano</a> , <a href="#">paras</a> , <a href="#">paratitle</a> , <a href="#">partno</a> , <a href="#">pgnumber</a> , <a href="#">phrase</a> , <a href="#">pretmidno</a> , <a href="#">pubdate</a> , <a href="#">revnum</a> , <a href="#">sectocstr</a> , <a href="#">seqno</a> , <a href="#">serno</a> , <a href="#">subject</a> , <a href="#">subparano</a> , <a href="#">subtitle</a> , <a href="#">supersed</a> , <a href="#">suppl</a> , <a href="#">symb</a> , <a href="#">symtitle</a> , <a href="#">term</a> , <a href="#">tfnid</a> , <a href="#">title</a> , <a href="#">tmidno</a> , <a href="#">typedes</a> , <a href="#">underline</a> |
| <i>Excluded in:</i>                   | <a href="#">fnote</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">status</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

### ATTRIBUTE LIST

| Attribute | Type                                  | Default   | Description                                                                                                                                            |
|-----------|---------------------------------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| xrefid    | IDREF                                 | #REQUIRED | Defines the ID of the element that you are referencing. The value of this attribute should match the value of an ID attribute elsewhere in the manual. |
| mark      | (num   sym   alpha)                   | num       | Indicates the type of symbol or mark used to indicate a footnote.                                                                                      |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                          |
| inschlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was inserted at the change level indicated.                                             |
| delchlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was deleted at the change level indicated.                                              |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the status of this element.                                 |
| revchg    | NUMBER                                | 0         | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                   |

---

# graphic

## Graphic

|                          |                                                                                                                                                             |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>      | Identifies a graphic within a figure, or a graphic within running text or tables. If used within running text, no figure number or title will be generated. |
| <i>Source paragraph:</i> | None                                                                                                                                                        |
| <i>Content Model:</i>    | ( <a href="#">bindById</a>   <a href="#">bindByName</a>   <a href="#">bindByCoords</a> )*                                                                   |

Parents: [abbrtitle](#), [action](#), [amplification](#), [applicabil](#), [appltile](#), [authnot](#), [change](#), [chgdate](#), [chgnum](#), [chgtxt](#), [clink](#), [clitem](#), [cogact](#), [condition](#), [contractno](#), [copyright](#), [cpos](#), [crewpos](#), [crewpos1](#), [crewpos2](#), [crewpos3](#), [crewpos4](#), [crewpos5](#), [dataiden](#), [date](#), [def](#), [destr](#), [discl](#), [distrib](#), [doctype](#), [effdatenot](#), [emphasis](#), [entry](#), [etitle](#), [expcont](#), [extapplicabil](#), [figure](#), [fnote](#), [hazmat](#), [icon](#), [ilink](#), [internatlst](#), [item](#), [label](#), [lepchg](#), [leppage](#), [line](#), [maintlvl](#), [mfr](#), [modelno](#), [moveddata](#), [newpos1](#), [newpos2](#), [newpos3](#), [newpos4](#), [newpos5](#), [nmlist](#), [nomen](#), [nsn](#), [oadr](#), [pageno](#), [para](#), [param](#), [parano](#), [paras](#), [paratitle](#), [partno](#), [pgnumber](#), [phrase](#), [pretmidno](#), [pubdate](#), [revnum](#), [sectocstr](#), [seqno](#), [serno](#), [subfig](#), [subject](#), [subparano](#), [subtitle](#), [supersd](#), [suppl](#), [ymb](#), [symtitle](#), [term](#), [tfnid](#), [title](#), [tmidno](#), [told](#), [typedes](#), [underline](#)

Included in: [clsection](#), [emergproccl](#)

Entities used in this element: [chgatt](#), [delstat](#), [graphatt](#), [secur](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default   | Description                                                                                                                                                                                                                   |
|-----------|---------------------------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| id        | ID                                    | #IMPLIED  | Allows the author to generate a unique ID for use when referencing this element.                                                                                                                                              |
| boardno   | ENTITY                                | #REQUIRED | Allows the author to place the name of the graphic entity here.                                                                                                                                                               |
| graphsty  | NMTOKEN                               | #IMPLIED  | Defines the graphic style.                                                                                                                                                                                                    |
| llcordra  | CDATA                                 | #IMPLIED  | Lower left world coordinates (1,1). If the scalefit attribute is set to "0" and the repropid attribute is not specified, the default is lower left.                                                                           |
| rucordra  | CDATA                                 | #IMPLIED  | Upper right world coordinates (10000,10000). If the scalefit attribute is set to "0" and the reprodep is not specified, the default is upper right.                                                                           |
| repropid  | NUTOKEN                               | #IMPLIED  | Specifies the horizontal dimension (width) of a graphic bounding box.                                                                                                                                                         |
| reprodep  | NUTOKEN                               | #IMPLIED  | Specifies the vertical dimension (depth or height) of a graphic bounding box.                                                                                                                                                 |
| hscale    | NUMBER                                | #IMPLIED  | Allows the author to set the percentage of horizontal scaling for the graphic.                                                                                                                                                |
| vscale    | NUMBER                                | #IMPLIED  | Allows the author to set the percentage of vertical scaling for the graphic.                                                                                                                                                  |
| scalefit  | NUMBER                                | #IMPLIED  | Set this attribute equal to "1" to scale the graphic to fit the graphic bounding box set by the reprodep and repropid attributes. This attribute has no affect if the hscale and vscale attributes are used.                  |
| hplace    | (left   right   center)               | #IMPLIED  | Allows the author to set the horizontal placement of the graphic.                                                                                                                                                             |
| vplace    | (top   middle   bottom)               | #IMPLIED  | Allows the author to set the vertical placement of the graphic. This attribute is not currently supported by the FOSI.                                                                                                        |
| coordst   | CDATA                                 | #IMPLIED  | Specifies the coordinate to start graphic.                                                                                                                                                                                    |
| coordend  | CDATA                                 | #IMPLIED  | Specifies the coordinate to end graphic.                                                                                                                                                                                      |
| color     | NUMBER                                | 0         | Allows the author to choose the graphic color.                                                                                                                                                                                |
| icon      | (yes no)                              | no        | Allows the author to specify whether the graphic is full size or an icon. Setting this attribute equal to "yes" will eliminate the textbrk surrounding the graphic which should make the graphic render inline with the text. |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                                                                                 |
| inschlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was inserted at the change level indicated.                                                                                                                    |
| delchlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was deleted at the change level indicated.                                                                                                                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                                                                        |
| revchg    | NUMBER                                | 0         | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                                                                          |
| security  | (u   c   s   n)                       | n         | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.                                                                 |
| caveat    | CDATA                                 | #IMPLIED  | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                                              |
| fgi       | CDATA                                 | #IMPLIED  | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.                                                                |

---

# hazmat

## Hazardous Material Name

*Description:* Identifies the hazardous material name used with a hazardous material warning icon.

*Source paragraph:* 4.3.10.1 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [icon](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [secur](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

---

# hci

## Hardness Critical Item (HCI)

*Description:* Identifies hardness critical items. Use of this element will cause the **\*\*HCI\*\*** symbol to appear at that point in the running text. This element should only be used in running text, e.g. to display the **\*\*HCI\*\*** symbol in a paragraph. The `hci` attribute should be used to place the **\*\*HCI\*\*** symbol between a paragraph/step number and text.

*Source paragraph:* None

*Content Model:* EMPTY

Parents: [abbrtitle](#), [action](#), [amplification](#), [applicabil](#), [applttitle](#), [authnot](#), [change](#), [chgdate](#), [chgnum](#), [chgtxt](#), [clink](#), [clitem](#), [cogact](#), [condition](#), [contractno](#), [copyright](#), [cpos](#), [crewpos](#), [crewpos1](#), [crewpos2](#), [crewpos3](#), [crewpos4](#), [crewpos5](#), [dataiden](#), [date](#), [def](#), [destr](#), [discl](#), [distrib](#), [doctype](#), [effdatenot](#), [emphasis](#), [entry](#), [etitle](#), [expcont](#), [extapplicabil](#), [ftnote](#), [hazmat](#), [ilink](#), [internatlst](#), [item](#), [label](#), [lepchg](#), [leppage](#), [line](#), [maintlvl](#), [mfr](#), [modelno](#), [moveddata](#), [newpos1](#), [newpos2](#), [newpos3](#), [newpos4](#), [newpos5](#), [nmlist](#), [nomen](#), [nsn](#), [oadr](#), [pageno](#), [para](#), [param](#), [parano](#), [paras](#), [paratitle](#), [partno](#), [pgnumber](#), [phrase](#), [pretmidno](#), [pubdate](#), [revnum](#), [sectocstr](#), [seqno](#), [serno](#), [subject](#), [subparano](#), [subtitle](#), [supersd](#), [suppl](#), [synd](#), [syntitle](#), [term](#), [tfid](#), [title](#), [tmidno](#), [typedes](#), [underline](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# hcp

## Hardness Critical Process (HCP)

Description: Identifies hardness critical processes. Use of this element will cause the **HCP** symbol to appear at that point in the running text. This element should only be used in running text, e.g. to display the **HCP** symbol in a paragraph. The hcp attribute should be used to place the **HCP** symbol between a paragraph/step number and text.

Source paragraph: 4.3.10.3 (MIL-STD-38784)

Content Model: EMPTY

Parents: [abbrtitle](#), [action](#), [amplification](#), [applicabil](#), [applttitle](#), [authnot](#), [change](#), [chgdate](#), [chgnum](#), [chgtxt](#), [clink](#), [clitem](#), [cogact](#), [condition](#), [contractno](#), [copyright](#), [cpos](#), [crewpos](#), [crewpos1](#), [crewpos2](#), [crewpos3](#), [crewpos4](#), [crewpos5](#), [dataiden](#), [date](#), [def](#), [destr](#), [discl](#), [distrib](#), [doctype](#), [effdatenot](#), [emphasis](#), [entry](#), [etitle](#), [expcont](#), [extapplicabil](#), [ftnote](#), [hazmat](#), [ilink](#), [internatlst](#), [item](#), [label](#), [lepchg](#), [leppage](#), [line](#), [maintlvl](#), [mfr](#), [modelno](#), [moveddata](#), [newpos1](#), [newpos2](#), [newpos3](#), [newpos4](#), [newpos5](#), [nmlist](#), [nomen](#), [nsn](#), [oadr](#), [pageno](#), [para](#), [param](#), [parano](#), [paras](#), [paratitle](#), [partno](#), [pgnumber](#), [phrase](#), [pretmidno](#), [pubdate](#), [revnum](#), [sectocstr](#), [seqno](#), [serno](#), [subject](#), [subparano](#), [subtitle](#), [supersd](#), [suppl](#), [synd](#), [syntitle](#), [term](#), [tfid](#), [title](#), [tmidno](#), [typedes](#), [underline](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# heading

## Heading

*Description:* Container element for the crew position headings in the Coordinated Actions Table

*Source paragraph:* N/A

*Content Model:* ([crewpos1](#), [crewpos2](#), [crewpos3?](#), [crewpos4?](#), [crewpos5?](#))

*Parents:* [coordprocs](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

# icon

## Hazardous Material Warning Icon

*Description:* Identifies the hazardous material warnings. The hazardous material warning consists of a graphic(s) (e.g. fire icon, poison icon, etc.), the hazardous material name, and the sequence number which identifies the order in which the hazardous material warnings are included in the safety summary.

*Source paragraph:* 4.3.10.1 and Appendix A (MIL-STD-38784)

*Content Model:* ([graphic+](#), [hazmat+](#), [seqno](#))

*Parents:* [warning](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [icon](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                           | Default  | Description                                                                                                                   |
|-----------|--------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| id        | ID                             | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                              |
| delttype  | (delete   real   reserve   NA) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                        | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |



| Attribute | Type                                  | Default  | Description                                                                                                            |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------|
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.              |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element. |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                   |

# idinfo

## Identification Information (Title Page)

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies the title page and cover (if used) of the manual.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <i>Source paragraph:</i>              | 4.5.1 (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <i>Content Model:</i>                 | ( <a href="#">tmidno</a> +, ( <a href="#">chgnum</a> , <a href="#">chgdate</a> )?, <a href="#">chghistory</a> , <a href="#">pretmidno</a> *, <a href="#">volnum</a> ?, <a href="#">revnum</a> ?, <a href="#">crewpos</a> , <a href="#">doctype</a> , <a href="#">maintlvl</a> ?, <a href="#">prtitle</a> , <a href="#">subtitle</a> ?, ( <a href="#">mfr</a> +, <a href="#">contractno</a> +)?, <a href="#">seal</a> ?, <a href="#">superseded</a> ?, <a href="#">suppl</a> *, <a href="#">effdatenot</a> ?, <a href="#">volnot</a> ?, <a href="#">discl</a> ?, <a href="#">distrib</a> , <a href="#">expcont</a> ?, <a href="#">destr</a> ?, <a href="#">para</a> ?, <a href="#">copyright</a> *, <a href="#">cogact</a> ?, <a href="#">moveddata</a> ?, <a href="#">authnot</a> , <a href="#">downgrd</a> ?, <a href="#">pubdate</a> ) |
| <i>Parents:</i>                       | <a href="#">front</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <i>Entities used in this element:</i> | <a href="#">idinf</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

# if

## IF

|                                       |                                                                                                     |
|---------------------------------------|-----------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Container element for Emergency procedures when a decision point is present.                        |
| <i>Source paragraph:</i>              | N/A                                                                                                 |
| <i>Content Model:</i>                 | ( <a href="#">EPDecision1</a> , <a href="#">EPDecision2</a> )                                       |
| <i>Parents:</i>                       | <a href="#">ifthen</a>                                                                              |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">status</a> , <a href="#">yesorno</a> |

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

# ifstep1

## If Then Step Indenture 1

**Description:** Represents the if-then step indenture 1

**Source paragraph:** N/A

**Content Model:** (clitem, ifstep2\*) -(action)

**Parents:** EPDecision1, EPDecision2

**Excluded in:** normproccl

**Entities used in this element:** chgatt, delstat, status, stepatt, verified, yesorno

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                                                           |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA                                 | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired.                                  |
| emergency | NUMBER                                | 0        | Indicates that the primary paragraph will produce an emergency border on the page when set equal to 1.                                                                                                |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, or Subject Number can be assigned to this element.                                                                                                                                 |
| id        | ID                                    | #IMPLIED | Allows author to designate a unique paragraph ID for use with external and cross references.                                                                                                          |
| esds      | NUMBER                                | 0        | Electrostatic Discharge Sensitive. All paragraphs which address handling or maintenance which could damage *** ESDS *** parts shall be identified by the esds symbol by setting attribute equal to 1. |
| nsp       | NUMBER                                | 0        | Nuclear Surety Procedures. A **NSP** symbol will appear when set equal to 1.                                                                                                                          |
| fcp       | NUMBER                                | 0        | Fracture Critical Process. All paragraphs which address Fracture Critical Process shall be identified by the *** FCP *** symbol by setting attribute equal to 1.                                      |
| hcp       | NUMBER                                | 0        | Hardness Critical Process. All paragraphs which address Hardness Critical Process shall be identified by the *** HCP *** symbol by setting attribute equal to 1.                                      |
| hci       | NUMBER                                | 0        | Hardness Critical Item. All paragraphs which address Hardness Critical Item shall be identified by the *** HCI *** symbol by setting attribute equal to 1.                                            |
| ocp       | NUMBER                                | 0        | Observable Critical Process. All paragraphs which address observable critical processes shall be identified by the *** OCP *** symbol by setting attribute equal to 1.                                |
| oci       | NUMBER                                | 0        | Observable Critical Item. All paragraphs which address observable critical items shall be identified by the *** OCI *** symbol by setting attribute equal to 1.                                       |
| applicref | IDREFS                                | #IMPLIED | Allows you to assign an applicable reference                                                                                                                                                          |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                                                        |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                                                            |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated                                                                                                  |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                                                                                                                 |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                                                  |
| verdate   | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                         |

| Attribute     | Type                          | Default  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------|-------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| verrem        | CDATA                         | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                                                                                                                                                                                                                                                                             |
| verstatus     | (unver   ver   notapplicable) | unver    | Identifies verification status of the element.                                                                                                                                                                                                                                                                                                                                                                                                                     |
| security      | (u   c   s   n)               | n        | Identifies security level of the element.                                                                                                                                                                                                                                                                                                                                                                                                                          |
| caveat        | CDATA                         | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                                                                                                                                                                                                                                                                                   |
| fgi           | CDATA                         | #IMPLIED | Provides a place for inline FMS portion marking.                                                                                                                                                                                                                                                                                                                                                                                                                   |
| effect        | CDATA                         | #IMPLIED | Used to assign an effectivity to the Step.                                                                                                                                                                                                                                                                                                                                                                                                                         |
| afmem         | NUMBER                        | #IMPLIED | Identifies the text as information that must be committed to memory, per Air Force.                                                                                                                                                                                                                                                                                                                                                                                |
| navmem        | NUMBER                        | #IMPLIED | Identifies the text as information that must be committed to memory, per Navy.                                                                                                                                                                                                                                                                                                                                                                                     |
| bothmem       | NUMBER                        | #IMPLIED | Identifies the text as information that must be committed to memory, per Air Force and Navy.                                                                                                                                                                                                                                                                                                                                                                       |
| crewcoordcirc | (0 1)                         | 0        | Allows step number to be circled. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                                             |
| feresponse    | NUMBER                        | 0        | Preceding any checklist step means the step is contained in section II and that a response is required when the flight engineer reads the item. Only use on clsteps.                                                                                                                                                                                                                                                                                               |
| thrufft       | NUMBER                        | 0        | A "through-flight" type of operation, where a crewmember will perform, as a minimum, those steps indicated. One example of this is an ERCC (Engines Running Crew Change) where a crew lands the jet, and only accomplishes enough steps in a shutdown checklist to make the jet safe while leaving the engines running, and a fresh crew gets on board and makes the jet ready for flight again, by accomplishing the "through-flight" items. Only use on clsteps. |
| nomisscrw     | NUMBER                        | 0        | Indicate specific checklist steps the engineer will accomplish when a mission crew is not present. This would only happen when training is being accomplished which does not require the mission crew, such as pattern work, or perhaps air refueling. Only use on clsteps.                                                                                                                                                                                        |
| manwc         | (W   C   WC)                  | #IMPLIED | Used to indicate whether the flight manual has a warning or caution for that step which did not carry over into the checklist.                                                                                                                                                                                                                                                                                                                                     |

## ifstep2

### If Then Step Indenture 2

**Description:** Represents the if-then step indenture 2

**Source paragraph:** N/A

**Content Model:** (clitem, ifstep3\*) -(action)

**Parents:** ifstep1

**Entities used in this element:** chgatt, delstat, status, stepatt, verified, yesorno

### ATTRIBUTE LIST

| Attribute | Type   | Default  | Description                                                                                                                                                          |
|-----------|--------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA  | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired. |
| emergency | NUMBER | 0        | Indicates that the primary paragraph will produce an emergency border on the page when set equal to 1.                                                               |
| sssn      | CDATA  | #IMPLIED | System, Subsystem, or Subject Number can be assigned to this element.                                                                                                |
| id        | ID     | #IMPLIED | Allows author to designate a unique paragraph ID for use with external and cross references.                                                                         |

| Attribute     | Type                                  | Default  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------|---------------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| esds          | NUMBER                                | 0        | Electrostatic Discharge Sensitive. All paragraphs which address handling or maintenance which could damage *** ESDS *** parts shall be identified by the esds symbol by setting attribute equal to 1.                                                                                                                                                                                                                                                              |
| nsp           | NUMBER                                | 0        | Nuclear Surety Procedures. A **NSP** symbol will appear when set equal to 1.                                                                                                                                                                                                                                                                                                                                                                                       |
| fcf           | NUMBER                                | 0        | Fracture Critical Process. All paragraphs which address Fracture Critical Process shall be identified by the *** FCP *** symbol by setting attribute equal to 1.                                                                                                                                                                                                                                                                                                   |
| hcp           | NUMBER                                | 0        | Hardness Critical Process. All paragraphs which address Hardness Critical Process shall be identified by the *** HCP *** symbol by setting attribute equal to 1.                                                                                                                                                                                                                                                                                                   |
| hcl           | NUMBER                                | 0        | Hardness Critical Item. All paragraphs which address Hardness Critical Item shall be identified by the *** HCI *** symbol by setting attribute equal to 1.                                                                                                                                                                                                                                                                                                         |
| ocp           | NUMBER                                | 0        | Observable Critical Process. All paragraphs which address observable critical processes shall be identified by the *** OCP *** symbol by setting attribute equal to 1.                                                                                                                                                                                                                                                                                             |
| oci           | NUMBER                                | 0        | Observable Critical Item. All paragraphs which address observable critical items shall be identified by the *** OCI *** symbol by setting attribute equal to 1.                                                                                                                                                                                                                                                                                                    |
| applicref     | IDREFS                                | #IMPLIED | Allows you to assign an applicable reference                                                                                                                                                                                                                                                                                                                                                                                                                       |
| deltype       | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                                                                                                                                                                                                                                                                                                                     |
| inschlvl      | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                                                                                                                                                                                                                                                                                                                         |
| delchlvl      | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated                                                                                                                                                                                                                                                                                                                                                               |
| status        | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                                                                                                                                                                                                                                                                                                                                                                              |
| revchg        | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                                                                                                                                                                                                                                                                                                               |
| verdate       | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                                                                                                                                                                                                                                                                                      |
| verrem        | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                                                                                                                                                                                                                                                                             |
| verstatus     | (unver   ver   notapplicable)         | unver    | Identifies verification status of the element.                                                                                                                                                                                                                                                                                                                                                                                                                     |
| security      | (u   c   s   n)                       | n        | Identifies security level of the element.                                                                                                                                                                                                                                                                                                                                                                                                                          |
| caveat        | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                                                                                                                                                                                                                                                                                   |
| fgi           | CDATA                                 | #IMPLIED | Provides a place for inline FMS portion marking.                                                                                                                                                                                                                                                                                                                                                                                                                   |
| effect        | CDATA                                 | #IMPLIED | Used to assign an effectivity to the Step.                                                                                                                                                                                                                                                                                                                                                                                                                         |
| afmem         | NUMBER                                | #IMPLIED | Identifies the text as information that must be committed to memory, per Air Force.                                                                                                                                                                                                                                                                                                                                                                                |
| navmem        | NUMBER                                | #IMPLIED | Identifies the text as information that must be committed to memory, per Navy.                                                                                                                                                                                                                                                                                                                                                                                     |
| bothmem       | NUMBER                                | #IMPLIED | Identifies the text as information that must be committed to memory, per Air Force and Navy.                                                                                                                                                                                                                                                                                                                                                                       |
| crewcoordcirc | (0 1)                                 | 0        | Allows step number to be circled. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                                             |
| feresponse    | NUMBER                                | 0        | Preceding any checklist step means the step is contained in section II and that a response is required when the flight engineer reads the item. Only use on clsteps.                                                                                                                                                                                                                                                                                               |
| thruflt       | NUMBER                                | 0        | A "through-flight" type of operation, where a crewmember will perform, as a minimum, those steps indicated. One example of this is an ERCC (Engines Running Crew Change) where a crew lands the jet, and only accomplishes enough steps in a shutdown checklist to make the jet safe while leaving the engines running, and a fresh crew gets on board and makes the jet ready for flight again, by accomplishing the "through-flight" items. Only use on clsteps. |
| nomisscrw     | NUMBER                                | 0        | Indicate specific checklist steps the engineer will accomplish when a mission crew is not present. This would only happen when training is being accomplished which does not require the mission crew, such as pattern work, or perhaps air refueling. Only use on clsteps.                                                                                                                                                                                        |

| Attribute | Type         | Default  | Description                                                                                                                    |
|-----------|--------------|----------|--------------------------------------------------------------------------------------------------------------------------------|
| manwc     | (W   C   WC) | #IMPLIED | Used to indicate whether the flight manual has a warning or caution for that step which did not carry over into the checklist. |

# ifstep3

## If Then Step Indenture 3

*Description:* Represents the if-then step indenture 3  
*Source paragraph:* N/A  
*Content Model:* (clitem) -(action)  
*Parents:* ifstep2  
*Entities used in this element:* chgatt, delstat, status, stepatt, verified, yesorno

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                                                           |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA                                 | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired.                                  |
| emergency | NUMBER                                | 0        | Indicates that the primary paragraph will produce an emergency border on the page when set equal to 1.                                                                                                |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, or Subject Number can be assigned to this element.                                                                                                                                 |
| id        | ID                                    | #IMPLIED | Allows author to designate a unique paragraph ID for use with external and cross references.                                                                                                          |
| esds      | NUMBER                                | 0        | Electrostatic Discharge Sensitive. All paragraphs which address handling or maintenance which could damage *** ESDS *** parts shall be identified by the esds symbol by setting attribute equal to 1. |
| nsp       | NUMBER                                | 0        | Nuclear Surety Procedures. A **NSP** symbol will appear when set equal to 1.                                                                                                                          |
| fcf       | NUMBER                                | 0        | Fracture Critical Process. All paragraphs which address Fracture Critical Process shall be identified by the *** FCP *** symbol by setting attribute equal to 1.                                      |
| hcp       | NUMBER                                | 0        | Hardness Critical Process. All paragraphs which address Hardness Critical Process shall be identified by the *** HCP *** symbol by setting attribute equal to 1.                                      |
| hci       | NUMBER                                | 0        | Hardness Critical Item. All paragraphs which address Hardness Critical Item shall be identified by the *** HCI *** symbol by setting attribute equal to 1.                                            |
| ocp       | NUMBER                                | 0        | Observable Critical Process. All paragraphs which address observable critical processes shall be identified by the *** OCP *** symbol by setting attribute equal to 1.                                |
| oci       | NUMBER                                | 0        | Observable Critical Item. All paragraphs which address observable critical items shall be identified by the *** OCI *** symbol by setting attribute equal to 1.                                       |
| applicref | IDREFS                                | #IMPLIED | Allows you to assign an applicable reference                                                                                                                                                          |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                                                        |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                                                            |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated                                                                                                  |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                                                                                                                 |

| Attribute     | Type                          | Default  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------|-------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| revchg        | NUMBER                        | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                                                                                                                                                                                                                                                                                                               |
| verdate       | CDATA                         | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                                                                                                                                                                                                                                                                                      |
| verrem        | CDATA                         | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                                                                                                                                                                                                                                                                             |
| verstatus     | (unver   ver   notapplicable) | unver    | Identifies verification status of the element.                                                                                                                                                                                                                                                                                                                                                                                                                     |
| security      | (u   c   s   n)               | n        | Identifies security level of the element.                                                                                                                                                                                                                                                                                                                                                                                                                          |
| caveat        | CDATA                         | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                                                                                                                                                                                                                                                                                   |
| fgi           | CDATA                         | #IMPLIED | Provides a place for inline FMS portion marking.                                                                                                                                                                                                                                                                                                                                                                                                                   |
| effect        | CDATA                         | #IMPLIED | Used to assign an effectivity to the Step.                                                                                                                                                                                                                                                                                                                                                                                                                         |
| afmem         | NUMBER                        | #IMPLIED | Identifies the text as information that must be committed to memory, per Air Force.                                                                                                                                                                                                                                                                                                                                                                                |
| navmem        | NUMBER                        | #IMPLIED | Identifies the text as information that must be committed to memory, per Navy.                                                                                                                                                                                                                                                                                                                                                                                     |
| bothmem       | NUMBER                        | #IMPLIED | Identifies the text as information that must be committed to memory, per Air Force and Navy.                                                                                                                                                                                                                                                                                                                                                                       |
| crewcoordcirc | (0 1)                         | 0        | Allows step number to be circled. Only use on clsteps.                                                                                                                                                                                                                                                                                                                                                                                                             |
| feresponse    | NUMBER                        | 0        | Preceding any checklist step means the step is contained in section II and that a response is required when the flight engineer reads the item. Only use on clsteps.                                                                                                                                                                                                                                                                                               |
| thruflt       | NUMBER                        | 0        | A "through-flight" type of operation, where a crewmember will perform, as a minimum, those steps indicated. One example of this is an ERCC (Engines Running Crew Change) where a crew lands the jet, and only accomplishes enough steps in a shutdown checklist to make the jet safe while leaving the engines running, and a fresh crew gets on board and makes the jet ready for flight again, by accomplishing the "through-flight" items. Only use on clsteps. |
| nomisscrw     | NUMBER                        | 0        | Indicate specific checklist steps the engineer will accomplish when a mission crew is not present. This would only happen when training is being accomplished which does not require the mission crew, such as pattern work, or perhaps air refueling. Only use on clsteps.                                                                                                                                                                                        |
| manwc         | (W   C   WC)                  | #IMPLIED | Used to indicate whether the flight manual has a warning or caution for that step which did not carry over into the checklist.                                                                                                                                                                                                                                                                                                                                     |

# ifthen

## If-Then

*Description:* Container element for "parallel" procedures.

*Source paragraph:* N/A

*Content Model:* (if, [warning\\*](#), [caution\\*](#))

*Parents:* [procedure](#), [subproc1](#), [subproc2](#), [subproc3](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                           | Default  | Description                                                                                                |
|-----------|--------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| iflong    | (1   2)                        | 1        | not used                                                                                                   |
| delttype  | (delete   real   reserve   NA) | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                        | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |

| Attribute | Type                                  | Default  | Description                                                                                          |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------|
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                 |

# ilink

## Independent Link

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | One of several HyTime elements. Used in a situation of indirection where a specific ID is not declared in an external document and must be declared using nameloc and nmlist elements.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <i>Source paragraph:</i>              | None                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <i>Content Model:</i>                 | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">ftnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcp</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> ) <sup>+</sup> )                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <i>Parents:</i>                       | <a href="#">abbrtitle</a> , <a href="#">action</a> , <a href="#">amplification</a> , <a href="#">applicabil</a> , <a href="#">appltile</a> , <a href="#">authnot</a> , <a href="#">change</a> , <a href="#">chgdate</a> , <a href="#">chgnum</a> , <a href="#">chgtxt</a> , <a href="#">clink</a> , <a href="#">clitem</a> , <a href="#">cogact</a> , <a href="#">condition</a> , <a href="#">contractno</a> , <a href="#">copyright</a> , <a href="#">cpos</a> , <a href="#">crewpos</a> , <a href="#">crewpos1</a> , <a href="#">crewpos2</a> , <a href="#">crewpos3</a> , <a href="#">crewpos4</a> , <a href="#">crewpos5</a> , <a href="#">dataiden</a> , <a href="#">date</a> , <a href="#">def</a> , <a href="#">destr</a> , <a href="#">discl</a> , <a href="#">distrib</a> , <a href="#">doctype</a> , <a href="#">effdatenot</a> , <a href="#">emphasis</a> , <a href="#">entry</a> , <a href="#">etitle</a> , <a href="#">expcont</a> , <a href="#">extapplicabil</a> , <a href="#">ftnote</a> , <a href="#">hazmat</a> , <a href="#">ilink</a> , <a href="#">internatlst</a> , <a href="#">item</a> , <a href="#">label</a> , <a href="#">lepchg</a> , <a href="#">leppage</a> , <a href="#">line</a> , <a href="#">maintlvl</a> , <a href="#">mfr</a> , <a href="#">modelno</a> , <a href="#">moveddata</a> , <a href="#">newpos1</a> , <a href="#">newpos2</a> , <a href="#">newpos3</a> , <a href="#">newpos4</a> , <a href="#">newpos5</a> , <a href="#">nmlist</a> , <a href="#">nomen</a> , <a href="#">nsn</a> , <a href="#">oadr</a> , <a href="#">pageno</a> , <a href="#">para</a> , <a href="#">param</a> , <a href="#">parano</a> , <a href="#">paras</a> , <a href="#">paratitle</a> , <a href="#">partno</a> , <a href="#">pgnumber</a> , <a href="#">phrase</a> , <a href="#">pretmidno</a> , <a href="#">pubdate</a> , <a href="#">revnum</a> , <a href="#">sectocstr</a> , <a href="#">seqno</a> , <a href="#">serno</a> , <a href="#">subject</a> , <a href="#">subparano</a> , <a href="#">subtitle</a> , <a href="#">supersed</a> , <a href="#">suppl</a> , <a href="#">ymb</a> , <a href="#">symtitle</a> , <a href="#">term</a> , <a href="#">tfmid</a> , <a href="#">title</a> , <a href="#">tmidno</a> , <a href="#">typedes</a> , <a href="#">underline</a> |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">status</a> , <a href="#">text</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

## ATTRIBUTE LIST

| Attribute | Type                                  | Default   | Description                                                                                                                                                                                                                                     |
|-----------|---------------------------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| anchrole  | CDATA                                 | #REQUIRED | Defines the anchor role assumed by the independent link. Used in combination with HyTime.                                                                                                                                                       |
| linkends  | IDREFS                                | #REQUIRED | References the linkends declared within a nameloc element. Other attributes are not included at this time as they are not applicable during a period of alpha testing and will be added to the TDT as the options are explored and implemented. |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                                                                                                   |
| inschlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was inserted at the change level indicated.                                                                                                                                      |
| delchlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was deleted at the change level indicated.                                                                                                                                       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                                                                                          |
| revchg    | NUMBER                                | 0         | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                                                                                            |

---

# internatlst

## International Standardization Agreement Note

**Description:** Identifies the international standardization agreement note. The paragraph number and title, of this note will be automatically generated by the FOSI.

**Source paragraph:** 4.5.9.1 (MIL-STD-38784)

**Content Model:** ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

**Parents:** [intro](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [status](#), [text](#), [verified](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| verdate   | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                                 |
| verrem    | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                        |
| verstatus | (unver   ver   notapplicable)         | unver    | Identifies the verification status of the element.                                                                            |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# intro

## Introduction

**Description:** Identifies the introduction of the manual. This element is identical to the preface and foreword elements, with the exception of the FOSI-generated title for that portion of the manual.

**Source paragraph:** 4.5.9 (MIL-STD-38784)

**Content Model:** ([para0](#), ([para0](#) | [applicdef](#) | [symsect](#) | [abbrsect](#) | [internatlst](#))<sup>\*</sup>) +([figure](#) | [table](#))

**Parents:** [front](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [fpi](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST



| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# item

## Item

*Description:* Identifies an item within a list.

*Source paragraph:* None

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+ -([figure](#) | [table](#) | [foldout](#) | [objmedia](#))

*Parents:* [randlist](#), [seqlist](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [exclus](#), [secur](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                           |
|-----------|---------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA                                 | #IMPLIED | Allows the author to label this element manually. The FOSI automatically generates labels, so its use is not necessary unless a label out of the ordinary is desired. |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.         |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                      |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.        |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                         |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                            |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                             |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                  |

---

# label

## Label

*Description:* Identifies the label for a manually tagged table of contents entry.

*Source paragraph:* 4.5.6 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [cntentry](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# legend

## Legend

*Description:* A tabular listing of an illustration's index numbers/letters and their meanings.

*Source paragraph:* 4.6.17 (MIL-STD-38784)

*Content Model:* ([tabmat](#))

*Parents:* [figure](#), [subfig](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                           | Default  | Description                                                                                                                   |
|-----------|--------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                        | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                        | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |

| Attribute | Type                                  | Default  | Description                                                                                                            |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------|
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element. |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                   |

# lep

## List of Effective Pages (LEP)

*Description:* Identifies the list of effective pages for the manual.

*Source paragraph:* 4.5.3 (MIL-STD-38784)

*Content Model:* ([lepcontents](#)) -([note](#))

*Parents:* [front](#)

### ATTRIBUTE LIST

| Attribute | Type   | Default | Description                                                             |
|-----------|--------|---------|-------------------------------------------------------------------------|
| lepcount  | NUMBER | 0       | Identifies the number of pages in the manual for a manually tagged LEP. |

# lepchg

## List of Effective Pages (LEP) Change

*Description:* Identifies the change number that appears in the change number column in a manually tagged LEP entry.

*Source paragraph:* 4.5.3 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+)

*Parents:* [lepentry](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# lepcontents

## List of Effective Pages (LEP) Contents

*Description:* Contains the entries for the LEP. The FOSI can automatically generate the LEP.

*Source paragraph:* 4.5.3 (MIL-STD-38784)

*Content Model:* ([lepentry+](#))

*Parents:* [lep](#)

*Entities used in this element:* [lepcontents](#)

### ATTRIBUTE LIST

| Attribute | Type  | Default | Description                                                                               |
|-----------|-------|---------|-------------------------------------------------------------------------------------------|
| autobuild | CDATA | #CONREF | Set this attribute equal to "1" when the output of this element should be auto-generated. |

---

# lepentry

## List of Effective Pages (LEP) Entry

*Description:* Identifies an entry for a manually tagged LEP.

*Source paragraph:* 4.5.3 (MIL-STD-38784)

*Content Model:* ([leppage](#), [lepchg](#))

*Parents:* [lepcontents](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# leppage

## List of Effective Pages (LEP) Page

*Description:* Identifies the page numbers that appear in the page number column in a manually tagged LEP entry.

*Source paragraph:* 4.5.3 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [leppentry](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# line

## Line

*Description:* This element is used to indicate that a column or line should be forced at that point.

*Source paragraph:* None

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Included in:* [doc](#), [docfmcl](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [lineatt](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                              | Default  | Description                                                                                                                   |
|-----------|-----------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| prespace  | CDATA                             | #IMPLIED | Allows the author to set the amount of space before/above the line used.                                                      |
| postspace | CDATA                             | #IMPLIED | Allows the author to set the amount of space after/below the line used.                                                       |
| quad      | (left   center   right   justify) | left     | Specifies the quadding option for the line.                                                                                   |
| indent    | CDATA                             | #IMPLIED | Specifies how much indentation is set on the line.                                                                            |
| delttype  | (delete   real   reserve   NA)    | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |

| Attribute | Type                                  | Default  | Description                                                                                                            |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------|
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.             |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.              |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element. |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                   |

---

## maintlvl

### Maintenance Level

*Description:* Identifies the maintenance level of the manual (e.g. organizational, intermediate, depot, etc.) on the title page.

*Source paragraph:* 4.5.1.3.3 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [idinfo](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

## mfr

### Manufacturer

*Description:* Identifies the manufacturer of the equipment on the title page.

*Source paragraph:* 4.5.1.3.6 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [idinfo](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# modelno

## Model Number

*Description:* Identifies the model number of the equipment on the title page and on the difference data sheet.

*Source paragraph:* 4.5.1.3.4 and 4.7.3.3 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+) -([figure](#) | [table](#) | [foldout](#) | [objmedia](#))

*Parents:* [prtitle](#)

*Entities used in this element:* [exclus](#), [secur](#), [text](#)

## ATTRIBUTE LIST

| Attribute | Type            | Default  | Description                                                                                                                                                    |
|-----------|-----------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n) | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA           | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA           | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |

# moveddata

## Moved Data

*Description:* Provides a means to identify the type of information that will appear on the T-2 page when the title page overflows.

*Source paragraph:* 4.5.1 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+)

*Parents:* [idinfo](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# nameloc

## Name Location - HyTime Element

**Description:** One of several elements added to facilitate use of HyTime. This element serves as a locator for external references and contains several nmlist elements. Useful for referencing objects that do not have the traditional SGML id.

**Source paragraph:** None

**Content Model:** ([nmlist](#))\*

**Parents:** [abbrtitle](#), [action](#), [amplification](#), [applicabil](#), [applttitle](#), [authnot](#), [change](#), [chgdate](#), [chgnum](#), [chgtxt](#), [clink](#), [clitem](#), [cogact](#), [condition](#), [contractno](#), [copyright](#), [cpos](#), [crewpos](#), [crewpos1](#), [crewpos2](#), [crewpos3](#), [crewpos4](#), [crewpos5](#), [dataiden](#), [date](#), [def](#), [destr](#), [discl](#), [distrib](#), [doctype](#), [effdatenot](#), [emphasis](#), [entry](#), [etitle](#), [expcont](#), [extapplicabil](#), [ftnote](#), [hazmat](#), [ilink](#), [internatlstid](#), [item](#), [label](#), [lepchg](#), [leppage](#), [line](#), [maintlvl](#), [mfr](#), [modelno](#), [moveddata](#), [newpos1](#), [newpos2](#), [newpos3](#), [newpos4](#), [newpos5](#), [nmlist](#), [nomen](#), [nsn](#), [oadr](#), [pageno](#), [para](#), [param](#), [parano](#), [paras](#), [paratitle](#), [partno](#), [pgnumber](#), [phrase](#), [pretmidno](#), [pubdate](#), [revnum](#), [sectocstr](#), [seqno](#), [serno](#), [subject](#), [subparano](#), [subtitle](#), [supersed](#), [suppl](#), [symp](#), [symtitle](#), [term](#), [tfnid](#), [title](#), [tmidno](#), [typedes](#), [underline](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default                        | Description                                                                                                                   |
|-----------|---------------------------------------|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| HyBase    | NAME                                  | #FIXED <a href="#">nameloc</a> | Assigns <a href="#">nameloc</a> as the HyBase attribute.                                                                      |
| id        | ID                                    | #IMPLIED                       | Allows the author to generate a unique ID for use when referencing this element.                                              |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED                       | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED                       | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED                       | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED                       | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0                              | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |



---

# newpos1

## New Position 1

*Description:* Identifies the new crew position for column 1 of the Coordinated Action Table.

*Source paragraph:* N/A

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [tasks](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

# newpos2

## New Position 2

*Description:* Identifies the new crew position for column 2 of the Coordinated Action Table.

*Source paragraph:* N/A

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [tasks](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                           | Default  | Description                                                                                                |
|-----------|--------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA) | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                        | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                        | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |

| Attribute | Type                                  | Default  | Description                                                                           |
|-----------|---------------------------------------|----------|---------------------------------------------------------------------------------------|
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element. |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.  |

## newpos3

### New Position 3

*Description:* Identifies the new crew position for column 3 of the Coordinated Action Table.

*Source paragraph:* N/A

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [tasks](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

## newpos4

### New Position 4

*Description:* Identifies the new crew position for column 4 of the Coordinated Action Table.

*Source paragraph:* N/A

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [tasks](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

## newpos5

### New Position 5

*Description:* Identifies the new crew position for column 5 of the Coordinated Action Table.

*Source paragraph:* N/A

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+)

*Parents:* [tasks](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

## nmlist

### Name List - HyTime Element

*Description:* One of several elements added to facilitate use of HyTime. This element serves as a description of the location of the entity or element reference in the [nameloc](#) element. Useful for referencing objects that do not have the traditional SGML id and/or entities that reside in external documents.

*Source paragraph:* None

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+)

Parents: [nameloc](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default                                                                                                    | Description                                                                                                                                                                                                                                                                                                 |
|-----------|---------------------------------------|------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| HyBase    | NAME                                  | #FIXED nmsploc                                                                                             | Used in conjunction with HyTime to set up independent and contextual links.                                                                                                                                                                                                                                 |
| impsrc    | NAME                                  | #FIXED grovert                                                                                             | Used in conjunction with HyTime to set up independent and contextual links.                                                                                                                                                                                                                                 |
| HyBnames  | CDATA                                 | #FIXED "locsrc docorsub<br>namespc nametype<br>#MAPTOKEN elements<br>element #MAPTOKEN<br>entities entity" | Used in conjunction with HyTime to set up independent and contextual links.                                                                                                                                                                                                                                 |
| nametype  | (entity element)                      | entity                                                                                                     | Identifies whether the external reference is an element or entity.                                                                                                                                                                                                                                          |
| docorsub  | ENTITY                                | #IMPLIED                                                                                                   | Defines the entity name of the external document as declared in the entity declarations at the top of the tagged instance. Other attributes are not included because at this time as they are not applicable during alpha testing and will be added to the TDT as the options are explored and implemented. |
| notspace  | NAME                                  | ERROR                                                                                                      | Used in conjunction with HyTime to set up independent and contextual links.                                                                                                                                                                                                                                 |
| notname   | NAME                                  | ERROR                                                                                                      | Used in conjunction with HyTime to set up independent and contextual links.                                                                                                                                                                                                                                 |
| notprop   | NAME                                  | ERROR                                                                                                      | Used in conjunction with HyTime to set up independent and contextual links.                                                                                                                                                                                                                                 |
| direct    | (direct indirect)                     | indirect                                                                                                   | Used in conjunction with HyTime to set up independent and contextual links.                                                                                                                                                                                                                                 |
| locsrc    | CDATA                                 | #IMPLIED                                                                                                   | Used in conjunction with HyTime to set up independent and contextual links.                                                                                                                                                                                                                                 |
| cantcnst  | NAME                                  | ERROR                                                                                                      | Used in conjunction with HyTime to set up independent and contextual links.                                                                                                                                                                                                                                 |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED                                                                                                   | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                                                                                                                                                               |
| inschlvl  | NMTOKEN                               | #IMPLIED                                                                                                   | Used during the change package process to indicate the element was inserted at the change level indicated.                                                                                                                                                                                                  |
| delchlvl  | NMTOKEN                               | #IMPLIED                                                                                                   | Used during the change package process to indicate the element was deleted at the change level indicated.                                                                                                                                                                                                   |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED                                                                                                   | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                                                                                                                                                      |
| revchg    | NUMBER                                | 0                                                                                                          | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                                                                                                                                                        |

## nomen

### Nomenclature

Description: Identifies the nomenclature of the equipment on the title page and on the difference data sheet.

Source paragraph: 4.5.1.3.4 and 4.7.3.3 (MIL-STD-38784)

Content Model: ((#PCDATA | [change](#) | [tabmat](#) | [fnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+) -(figure | table | foldout | objmedia)

Parents: [prtitle](#)

Entities used in this element: [chgatt](#), [delstat](#), [exclus](#), [secur](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

# normproccl

## Normal Procedures Checklists

Description: Checklists for all normal procedures from flight manual.

Source paragraph: 3.7, 3.7.1, 3.7.5 (MIL\_DTL-7700)

Content Model: (([title](#)), [sectoc](#), [procedure](#)+, [told?](#)) -([ifstep1](#)) +(figure | [figtable](#) | [table](#))

Parents: [body](#)

Entities used in this element: [bodyatt](#), [chapatt](#), [chgatt](#), [delstat](#), [secur](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type            | Default  | Description                                                                                                                                                          |
|-----------|-----------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| id        | ID              | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                                     |
| security  | (u   c   s   n) | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.        |
| caveat    | CDATA           | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                     |
| fgi       | CDATA           | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.       |
| label     | CDATA           | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired. |
| sssn      | CDATA           | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                  |
| indexid   | CDATA           | #IMPLIED | Provides an index ID for this element. This attribute is This attribute is not currently supported by the FOSI.                                                      |

| Attribute | Type                                  | Default  | Description                                                                          |
|-----------|---------------------------------------|----------|--------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                       |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Insert Change Level                               |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Delete Change Level                               |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows you to specify the status of this element.                                    |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision. |
| landscape | NUMBER                                | #IMPLIED | Allows landscape page                                                                |

## note

### Note

|                                       |                                                                                                                                                                                                                                                                                   |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies a NOTE in the manual.                                                                                                                                                                                                                                                  |
| <i>Source paragraph:</i>              | 4.3.10 (MIL-STD-38784)                                                                                                                                                                                                                                                            |
| <i>Content Model:</i>                 | (para*) -(randlist   deflist   seqlist   figure   table   foldout   objmedia   warning   caution)                                                                                                                                                                                 |
| <i>Parents:</i>                       | abbrsect, abbrsect, applicdef, applicdef, cmbr1, cmbr2, cmbr3, cmbr4, cmbr5, entry, para0, para0, procstep, procstep2, procstep3, procstep4, step1, step1, step2, step2, step3, step3, step4, step4, subpara1, subpara1, subpara2, subpara2, subpara3, subpara3, symsect, symsect |
| <i>Included in:</i>                   | doc, para0, performdatacl, procedure                                                                                                                                                                                                                                              |
| <i>Excluded in:</i>                   | lep, title                                                                                                                                                                                                                                                                        |
| <i>Entities used in this element:</i> | chgatt, delstat, exclus, list, status, yesorno                                                                                                                                                                                                                                    |

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

## nsn

### National Stock Number

|                          |                                                                          |
|--------------------------|--------------------------------------------------------------------------|
| <i>Description:</i>      | Identifies the national stock number of the equipment on the title page. |
| <i>Source paragraph:</i> | 4.5.1.3.4 (MIL-STD-38784)                                                |

Content Model: ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hpc](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

Parents: [prttitle](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# nsp

## Nuclear Surety Procedures

Description: Identifies the nuclear surety procedures. Use of this element will cause the **\*\*NSP\*\*** symbol to appear at that point in the running text. This element should only be used in running text, e.g. to display the **\*\*NSP\*\*** symbol in a paragraph. The nsp attribute should be used to place the **\*\*NSP\*\*** symbol between a paragraph/step number and text.

Source paragraph: 4.3.10.2 (MIL-STD-38784)

Content Model: EMPTY

Parents: [abbrtitle](#), [action](#), [amplification](#), [applicabil](#), [applttitle](#), [authnot](#), [change](#), [chgdate](#), [chgnum](#), [chgtxt](#), [clink](#), [clitem](#), [cogact](#), [condition](#), [contractno](#), [copyright](#), [cpos](#), [crewpos](#), [crewpos1](#), [crewpos2](#), [crewpos3](#), [crewpos4](#), [crewpos5](#), [dataiden](#), [date](#), [def](#), [destr](#), [discl](#), [distrib](#), [doctype](#), [effdatenot](#), [emphasis](#), [entry](#), [etitle](#), [expcont](#), [extapplicabil](#), [ftnote](#), [hazmat](#), [ilink](#), [internatlst](#), [item](#), [label](#), [lepchg](#), [leppage](#), [line](#), [maintlvl](#), [mfr](#), [modelno](#), [moveddata](#), [newpos1](#), [newpos2](#), [newpos3](#), [newpos4](#), [newpos5](#), [nmlist](#), [nomen](#), [nsn](#), [oadr](#), [pageno](#), [para](#), [param](#), [parano](#), [paras](#), [paratitle](#), [partno](#), [pgnumber](#), [phrase](#), [pretmidno](#), [pubdate](#), [revnum](#), [sectocstr](#), [seqno](#), [serno](#), [subject](#), [subparano](#), [subtitle](#), [supersd](#), [suppl](#), [symb](#), [symtitle](#), [term](#), [tfnid](#), [title](#), [tmidno](#), [typedes](#), [underline](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# oadr

## Official Authority Downgrade Review Notice

**Description:** Identifies the official authority downgrade review notice on the title page. This notice is used only on classified manuals.

**Source paragraph:** 4.4 and 4.5.1.10 (MIL-STD-38784)

**Content Model:** ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

**Parents:** [downgrd](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# object

## Multimedia Object

**Description:** Developed for use in interactive manuals to evoke multimedia applications.

**Source paragraph:** None

**Content Model:** ([param](#)<sup>\*</sup>)

**Parents:** [abbrtitle](#), [action](#), [amplification](#), [applicabil](#), [applttitle](#), [authnot](#), [change](#), [chgdate](#), [chgnum](#), [chgtxt](#), [clink](#), [clitem](#), [cogact](#), [condition](#), [contractno](#), [copyright](#), [cpos](#), [crewpos](#), [crewpos1](#), [crewpos2](#), [crewpos3](#), [crewpos4](#), [crewpos5](#), [dataiden](#), [date](#), [def](#), [destr](#), [discl](#), [distrib](#), [doctype](#), [effdatenot](#), [emphasis](#), [entry](#), [etitle](#), [expcont](#), [extapplicabil](#), [fnote](#), [hazmat](#), [ilink](#), [internatistd](#), [item](#), [label](#), [lepchg](#), [leppage](#), [line](#), [maintlvl](#), [mfr](#), [modelno](#), [moveddata](#), [newpos1](#), [newpos2](#), [newpos3](#), [newpos4](#), [newpos5](#), [nmlist](#), [nomen](#), [nsn](#), [oadr](#), [pageno](#), [para](#), [param](#), [parano](#), [paras](#), [paratitle](#), [partno](#), [pgnumber](#), [phrase](#), [pretmidno](#), [pubdate](#), [revnum](#), [sectocstr](#), [seqno](#), [serno](#), [subject](#), [subparano](#), [subtitle](#), [superseded](#), [suppl](#), [symb](#), [symtitle](#), [term](#), [tfnid](#), [title](#), [tmidno](#), [typesdes](#), [underline](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [secur](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type   | Default   | Description                                                       |
|-----------|--------|-----------|-------------------------------------------------------------------|
| objectno  | ENTITY | #REQUIRED | References the object number of the application being referenced. |



| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| reprowid  | NUTOKEN                               | #IMPLIED | Provides the width of the object being invoked, especially if it is a graphic or foldout from an external document.                                            |
| reprodep  | NUTOKEN                               | #IMPLIED | Provides the depth (height) of the object being invoked, especially if it is a graphic or foldout from an external document.                                   |
| type      | CDATA                                 | #IMPLIED | Provides details about the type of applications being referenced.                                                                                              |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

# oci

## Observable Critical Item

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies the observable critical items. Use of this element will cause the <b>**OCI**</b> symbol to appear at that point in the running text. This element should only be used in running text, e.g. to display the <b>**OCI**</b> symbol in a paragraph. The oci attribute should be used to place the <b>**OCI**</b> symbol between a paragraph/step number and text.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <i>Source paragraph:</i>              | 4.3.10.6 (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <i>Content Model:</i>                 | EMPTY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <i>Parents:</i>                       | <a href="#">abbrtitle</a> , <a href="#">action</a> , <a href="#">amplification</a> , <a href="#">applicabil</a> , <a href="#">appltile</a> , <a href="#">authnot</a> , <a href="#">change</a> , <a href="#">chgdate</a> , <a href="#">chgnum</a> , <a href="#">chgtxt</a> , <a href="#">clink</a> , <a href="#">clitem</a> , <a href="#">cogact</a> , <a href="#">condition</a> , <a href="#">contractno</a> , <a href="#">copyright</a> , <a href="#">cpos</a> , <a href="#">crewpos</a> , <a href="#">crewpos1</a> , <a href="#">crewpos2</a> , <a href="#">crewpos3</a> , <a href="#">crewpos4</a> , <a href="#">crewpos5</a> , <a href="#">dataiden</a> , <a href="#">date</a> , <a href="#">def</a> , <a href="#">destr</a> , <a href="#">discl</a> , <a href="#">distrib</a> , <a href="#">doctype</a> , <a href="#">effdatenot</a> , <a href="#">emphasis</a> , <a href="#">entry</a> , <a href="#">etitle</a> , <a href="#">expcont</a> , <a href="#">extapplicabil</a> , <a href="#">fnote</a> , <a href="#">hazmat</a> , <a href="#">ilink</a> , <a href="#">internatlst</a> , <a href="#">item</a> , <a href="#">label</a> , <a href="#">lepchg</a> , <a href="#">leppage</a> , <a href="#">line</a> , <a href="#">maintlvl</a> , <a href="#">mfr</a> , <a href="#">modelno</a> , <a href="#">moveddata</a> , <a href="#">newpos1</a> , <a href="#">newpos2</a> , <a href="#">newpos3</a> , <a href="#">newpos4</a> , <a href="#">newpos5</a> , <a href="#">nmlist</a> , <a href="#">nomen</a> , <a href="#">nsn</a> , <a href="#">oadr</a> , <a href="#">pageno</a> , <a href="#">para</a> , <a href="#">param</a> , <a href="#">parano</a> , <a href="#">paras</a> , <a href="#">paratitle</a> , <a href="#">partno</a> , <a href="#">pgnumber</a> , <a href="#">phrase</a> , <a href="#">pretmidno</a> , <a href="#">pubdate</a> , <a href="#">revnum</a> , <a href="#">sectocstr</a> , <a href="#">seqno</a> , <a href="#">serno</a> , <a href="#">subject</a> , <a href="#">subparano</a> , <a href="#">subtitle</a> , <a href="#">supersd</a> , <a href="#">suppl</a> , <a href="#">symb</a> , <a href="#">symtitle</a> , <a href="#">term</a> , <a href="#">tfnid</a> , <a href="#">title</a> , <a href="#">tmidno</a> , <a href="#">typesdes</a> , <a href="#">underline</a> |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">status</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |

| Attribute | Type   | Default | Description                                                                                          |
|-----------|--------|---------|------------------------------------------------------------------------------------------------------|
| revchg    | NUMBER | 0       | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change. |

# ocp

## Observable Critical Processes

**Description:** Identifies the observable critical processes. Use of this element will cause the **\*\*OCP\*\*** symbol to appear at that point in the running text. This element should only be used in running text, e.g. to display the **\*\*OCP\*\*** symbol in a paragraph. The ocp attribute should be used to place the **\*\*OCP\*\*** symbol between a paragraph/step number and text.

**Source paragraph:** 4.3.10.6 (MIL-STD-38784)

**Content Model:** EMPTY

**Parents:** [abbtitle](#), [action](#), [amplification](#), [applicabil](#), [appltile](#), [authnot](#), [change](#), [chgdate](#), [chgnum](#), [chgtxt](#), [clink](#), [clitem](#), [cogact](#), [condition](#), [contractno](#), [copyright](#), [cpos](#), [crewpos](#), [crewpos1](#), [crewpos2](#), [crewpos3](#), [crewpos4](#), [crewpos5](#), [dataiden](#), [date](#), [def](#), [destr](#), [discl](#), [distrib](#), [doctype](#), [effdatenot](#), [emphasis](#), [entry](#), [etitle](#), [expcont](#), [extapplicabil](#), [ftnote](#), [hazmat](#), [ilink](#), [internatstd](#), [item](#), [label](#), [lepchg](#), [leppage](#), [line](#), [maintlvl](#), [mfr](#), [modelno](#), [moveddata](#), [newpos1](#), [newpos2](#), [newpos3](#), [newpos4](#), [newpos5](#), [nmlist](#), [nomen](#), [nsn](#), [oadr](#), [pageno](#), [para](#), [param](#), [parano](#), [paras](#), [paratitle](#), [partno](#), [pgnumber](#), [phrase](#), [pretmidno](#), [pubdate](#), [revnum](#), [sectocstr](#), [seqno](#), [serno](#), [subject](#), [subparano](#), [subtitle](#), [supersed](#), [suppl](#), [ymb](#), [symtitle](#), [term](#), [tfnid](#), [title](#), [tmidno](#), [typedes](#), [underline](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# para

## Paragraph

**Description:** Identifies text within a paragraph without regard to title, heading, etc. For example, a NOTE consists of a heading and one or more paragraphs.

**Source paragraph:** 4.2.9.5 (MIL-STD-38784)

**Content Model:** (((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+ | [randlist](#) | [deflist](#) | [seqlist](#))+)

Parents: [abbrsect](#), [addcond](#), [applicdef](#), [caution](#), [idinfo](#), [note](#), [para0](#), [procedure](#), [procstep](#), [procstep2](#), [procstep3](#), [procstep4](#), [step1](#), [step2](#), [step3](#), [step4](#), [subpara1](#), [subpara2](#), [subpara3](#), [subproc1](#), [subproc2](#), [subproc3](#), [symsect](#), [warning](#)

Entities used in this element: [chgatt](#), [delstat](#), [list](#), [paracon](#), [secur](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| id        | ID                                    | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                               |
| xrefid    | IDREF                                 | #IMPLIED | Defines the ID of the element that you are referencing. The value of this attribute should match the value of an ID attribute elsewhere in the manual.         |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |

# para0

## Primary Paragraph

Description: Identifies a primary paragraph within the manual.

Source paragraph: 4.2.9.5.1.1 (MIL-STD-38784)

Content Model: (([title](#), [note](#)?, ([para](#), [warning](#)\*, [caution](#)?, [note](#)\*)\*, (([step1](#), [step1](#)+) | ([clstep1](#)\*)?)?, [subpara1](#)\*) + ([note](#))

Parents: [intro](#), [intro](#)

Entities used in this element: [bodyatt](#), [chgatt](#), [delstat](#), [para0att](#), [parazero](#), [secur](#), [status](#), [verified](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type   | Default  | Description                                                                                                                                                                                                    |
|-----------|--------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| emergency | NUMBER | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                                                                |
| id        | ID     | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                                                                               |
| esds      | NUMBER | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the **ESD** symbol by setting this attribute equal to "1". |
| nsp       | NUMBER | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the **NSP** symbol by setting this attribute equal to "1".                                                               |

| Attribute | Type                                  | Default  | Description                                                                                                                                                           |
|-----------|---------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fcf       | NUMBER                                | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the <b>**FCP**</b> symbol by setting this attribute equal to "1".       |
| hcp       | NUMBER                                | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the <b>**HCP**</b> symbol by setting this attribute equal to "1".           |
| hcl       | NUMBER                                | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the <b>**HCI**</b> symbol by setting this attribute equal to "1".                   |
| ocp       | NUMBER                                | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the <b>**OCP**</b> symbol by setting this attribute equal to "1".       |
| oci       | NUMBER                                | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the <b>**OCI**</b> symbol by setting this attribute equal to "1".               |
| applicref | IDREFS                                | #IMPLIED | Allows the author to assign an applicability/effectivity reference to this element.                                                                                   |
| verdate   | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                                                                         |
| verrem    | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                |
| verstatus | (unver   ver   notapplicable)         | unver    | Identifies the verification status of the element.                                                                                                                    |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.         |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                      |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.        |
| label     | CDATA                                 | #IMPLIED | Allows the author to label this element manually. The FOSI automatically generates labels, so its use is not necessary unless a label out of the ordinary is desired. |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                   |
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is not currently supported by the FOSI.                                                                         |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                         |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                            |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                             |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                  |

## param

### Parameter

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Used with Object Media to provide textual information about the application being invoked.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <i>Source paragraph:</i>              | None                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <i>Content Model:</i>                 | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">ftnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcf</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> )+) |
| <i>Parents:</i>                       | <a href="#">object</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">status</a> , <a href="#">text</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

## parano

### Paragraph Number

*Description:* Allows tagging of the para number in the section TOC.

*Source paragraph:* N/A

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+)

*Parents:* [sectoc](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

## paras

### Paragraphs

*Description:* Allows for multiple paragraphs under one symbol group in Other Considerations.

*Source paragraph:* N/A

Content Model: (((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup> | [randlist](#) | [deflist](#) | [seqlist](#))<sup>+</sup>)

Parents: [addcond](#), [addcond](#)

Entities used in this element: [chgatt](#), [delstat](#), [list](#), [paracon](#), [status](#), [text](#), [yesorno](#)

ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

paratitle

Paragraph Title

Description: Allows tagging of the para title in the section TOC.

Source paragraph: N/A

Content Model: ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

Parents: [secttoc](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

# partno

## Part Number

*Description:* Identifies the part number of the equipment on the title page and on the difference data sheet.

*Source paragraph:* 4.5.1.3.4 and 4.7.3.3 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+) -([figure](#) | [table](#) | [foldout](#) | [objmedia](#))

*Parents:* [prtitle](#), [pslist](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [exclus](#), [secur](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

---

# performdataacl

## Performance Data Checklists

*Description:* Checklists for all performance data from the Flight Manual.

*Source paragraph:* 3.7.2.5 (MIL-DTL-7700)

*Content Model:* (([title](#)), [secttoc](#), [figure](#)+) +(warning | caution | note)

*Parents:* [body](#)

*Entities used in this element:* [bodyatt](#), [chapatt](#), [chgatt](#), [delstat](#), [secur](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                          |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| id        | ID                                    | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                                     |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.        |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                     |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.       |
| label     | CDATA                                 | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired. |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                  |
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is This attribute is not currently supported by the FOSI.                                                      |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                       |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Insert Change Level                                                                                                               |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Delete Change Level                                                                                                               |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows you to specify the status of this element.                                                                                                                    |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                 |

## pgbrk

### Page Break

|                                       |                                                                                                                                        |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies where a page will begin. Page breaks can be placed at the top of each logical page to identify where the page should start. |
| <i>Source paragraph:</i>              | 4.2.1.1 (MIL-STD-38784)                                                                                                                |
| <i>Content Model:</i>                 | EMPTY                                                                                                                                  |
| <i>Included in:</i>                   | <a href="#">doc</a>                                                                                                                    |
| <i>Entities used in this element:</i> | <a href="#">status</a> , <a href="#">yesorno</a>                                                                                       |

## ATTRIBUTE LIST

| Attribute | Type  | Default  | Description                                                                                                                                               |
|-----------|-------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| pgnum     | CDATA | #IMPLIED | Page number generated by the FOSI during a recomposition. Provides data for OmniMark and DataLogics Composer in the script and change package processing. |
| pgnumber  | CDATA | #IMPLIED | Allows the author to assign the page number.                                                                                                              |
| pgdesc    | CDATA | #IMPLIED | This attribute is generated and referenced by the JCALS structure and is incorporated into the instance by the JCALS import process.                      |
| nxtpgnum  | CDATA | #IMPLIED | This attribute is generated and referenced by the JCALS structure and is incorporated into the instance by the JCALS import process.                      |
| nxtpgdesc | CDATA | #IMPLIED | This attribute is generated and referenced by the JCALS structure and is incorporated into the instance by the JCALS import process.                      |
| seqnum    | CDATA | #IMPLIED | This attribute is generated and referenced by the JCALS structure and is incorporated into the instance by the JCALS import process.                      |
| prefix    | CDATA | #IMPLIED | This attribute is generated and referenced by the JCALS structure and is incorporated into the instance by the JCALS import process.                      |



| Attribute     | Type                                  | Default  | Description                                                                                                                          |
|---------------|---------------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------|
| paraflag      | NUMBER                                | 0        | Setting this attribute equal to "1" will allow the last paragraph on the page to split.                                              |
| hyphflag      | NUMBER                                | #IMPLIED | Setting this attribute equal to "1" will allow the last word on a page to be hyphenated.                                             |
| shrink        | NUMBER                                | 100      | Used to shrink vertical space so that overflowed text will pull back to the desired page.                                            |
| rectover      | NUMBER                                | #IMPLIED | This attribute is generated and referenced by the JCALS structure and is incorporated into the instance by the JCALS import process. |
| chglevel      | CDATA                                 | #IMPLIED | Specifies the change level of the page.                                                                                              |
| security      | CDATA                                 | #IMPLIED | Identifies the security level of the document                                                                                        |
| empty         | NUMBER                                | 0        | This attribute is generated and referenced by the JCALS structure and is incorporated into the instance by the JCALS import process. |
| ignore        | CDATA                                 | #IMPLIED | This attribute is generated and referenced by the JCALS structure and is incorporated into the instance by the JCALS import process. |
| chgstatus     | CDATA                                 | #IMPLIED | This attribute is generated and referenced by the JCALS structure and is incorporated into the instance by the JCALS import process. |
| prevchgstatus | CDATA                                 | #IMPLIED | This attribute is generated and referenced by the JCALS structure and is incorporated into the instance by the JCALS import process. |
| emergency     | (0   1)                               | #IMPLIED | Indicates that this element will produce an emergency border on the page when set equal to "1".                                      |
| status        | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.               |

# pgnumber

## Page Number

*Description:* Allows tagging of the page number for a section TOC.

*Source paragraph:* N/A

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+)

*Parents:* [secttoc](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

# phrase

## Downgrade Phrase

*Description:* Identifies the text of the downgrade notice on the title page.

*Source paragraph:* 4.4 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [downgrd](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# pretmidno

## Previous Technical Manual Identification Number

*Description:* Identifies the previous technical manual identification number of the manual on the title page. This element is used only when the manual number has been changed. The FOSI will automatically generate the "Formerly" prefix preceding the former manual number.

*Source paragraph:* 4.5.1 and Figure 1 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [idinfo](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [secur](#), [service](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                                                | Default  | Description                         |
|-----------|---------------------------------------------------------------------|----------|-------------------------------------|
| service   | (AF   NAVAIR   NAVSEA   SPAWARS   ARMY   MC   DLA   CG   DOD   FRN) | #IMPLIED | Identifies which branch of service. |

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

# procedure

## Checklist Procedure

*Description:* Names the checklist task.

*Source paragraph:* 3.2.12, 3.2.12.1, 3.2.12.1.2 (MIL-DTL-7700)

*Content Model:* ((([title](#))?, ([para](#) | [condition](#) | [clstep1](#) | [ifthen](#) | [coordprocs](#))<sup>+</sup>), [subproc1](#)<sup>\*</sup>)<sup>+</sup>([warning](#) | [caution](#) | [note](#) | [syms](#) | [end](#) | [cont](#) | [tabmat](#) | [cpos](#))

*Parents:* [clsection](#), [emergproccl](#), [normproccl](#), [normproccl](#)

*Entities used in this element:* [bodyatt](#), [chgatt](#), [delstat](#), [para0att](#), [proced.mdl](#), [secur](#), [status](#), [verified](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute     | Type    | Default  | Description                                                                                                                                                                                           |
|---------------|---------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| applicoboxing | (0   1) | 0        | Allows user to select whether or not the "term" will appear with reverse video or not.                                                                                                                |
| emergency     | NUMBER  | 0        | Indicates that the primary paragraph will produce an emergency border on the page when set equal to 1.                                                                                                |
| id            | ID      | #IMPLIED | Allows author to designate a unique paragraph ID for use with external and cross references.                                                                                                          |
| esds          | NUMBER  | 0        | Electrostatic Discharge Sensitive. All paragraphs which address handling or maintenance which could damage *** ESDS *** parts shall be identified by the esds symbol by setting attribute equal to 1. |
| nsp           | NUMBER  | 0        | Nuclear Surety Procedures. A **NSP** symbol will appear when set equal to 1.                                                                                                                          |
| fcf           | NUMBER  | 0        | Fracture Critical Process. All paragraphs which address Fracture Critical Process shall be identified by the *** FCP *** symbol by setting attribute equal to 1.                                      |
| hcp           | NUMBER  | 0        | Hardness Critical Process. All paragraphs which address Hardness Critical Process shall be identified by the *** HCP *** symbol by setting attribute equal to 1.                                      |
| hci           | NUMBER  | 0        | Hardness Critical Item. All paragraphs which address Hardness Critical Item shall be identified by the *** HCI *** symbol by setting attribute equal to 1.                                            |

| Attribute | Type                                  | Default  | Description                                                                                                                                                            |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ocp       | NUMBER                                | 0        | Observable Critical Process. All paragraphs which address observable critical processes shall be identified by the *** OCP *** symbol by setting attribute equal to 1. |
| oci       | NUMBER                                | 0        | Observable Critical Item. All paragraphs which address observable critical items shall be identified by the *** OCI *** symbol by setting attribute equal to 1.        |
| applicref | IDREFS                                | #IMPLIED | Allows you to assign an applicable reference                                                                                                                           |
| verdate   | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                                                                          |
| verrem    | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                 |
| verstatus | (unver   ver   notapplicable)         | unver    | Identifies verification status of the element.                                                                                                                         |
| security  | (u   c   s   n)                       | n        | Identifies security level of the element.                                                                                                                              |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                       |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.         |
| label     | CDATA                                 | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired.   |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, or Subject Number can be assigned to this element.                                                                                                  |
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. Not currently supported by the FOSI - this attribute is under review.                                                           |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                         |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                             |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated                                                                   |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                                                                                  |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                   |
| newpage   | NUMBER                                | 0        | Allows procedures to start on a new page when set to '1'.                                                                                                              |

# procstep

## Coordinated Procedure Level 1

*Description:* Coordinated procedure for which a checklist step is not applicable. Found in Coordinated Action Table.

*Source paragraph:* 3.2.12.2.1 (MIL-DTL-7700)

*Content Model:* (([para](#), [warning?](#), [caution?](#), [note?](#))\*, ([clstep1](#)+[step1](#)+[condition](#)+)?)

*Parents:* [cmbr1](#), [cmbr2](#), [cmbr3](#), [cmbr4](#), [cmbr5](#), [entry](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [procstep.mdl](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                           | Default  | Description                                                                                                |
|-----------|--------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA) | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                        | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |

| Attribute | Type                                  | Default  | Description                                                                                          |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------|
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                 |

## procstep2

### Coordinated Procedure Level 2

*Description:* Coordinated procedure for which a checklist step is not applicable. Found in Coordinated Action Table.

*Source paragraph:* 3.2.12.2.1 (MIL-DTL-7700)

*Content Model:* (([para](#), [warning?](#), [caution?](#), [note?](#))\*, ([clstep1](#)+|[step1](#)+|[condition](#)+)?)

*Parents:* [cmbr1](#), [cmbr2](#), [cmbr3](#), [cmbr4](#), [cmbr5](#), [entry](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [procstep.mdl](#), [status](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

## procstep3

### Coordinated Procedure Level 3

*Description:* Coordinated procedure for which a checklist step is not applicable. Found in Coordinated Action Table.

*Source paragraph:* 3.2.12.2.1 (MIL-DTL-7700)

*Content Model:* (([para](#), [warning?](#), [caution?](#), [note?](#))\*, ([clstep1](#)+|[step1](#)+|[condition](#)+)?)

*Parents:* [cmbr1](#), [cmbr2](#), [cmbr3](#), [cmbr4](#), [cmbr5](#), [entry](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [procstep.mdl](#), [status](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                          |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA                                 | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired. |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                       |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                           |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated                                                                 |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                                                                                |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                 |

## procstep4

### Coordinated Procedure Level 4

*Description:* Coordinated procedure for which a checklist step is not applicable. Found in Coordinated Action Table.

*Source paragraph:* 3.2.12.2.1 (MIL-DTL-7700)

*Content Model:* (([para](#), [warning?](#), [caution?](#), [note?](#))\*, ([clstep1](#)+[step1](#)+[condition](#)+)?)

*Parents:* [cmbr1](#), [cmbr2](#), [cmbr3](#), [cmbr4](#), [cmbr5](#), [entry](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [procstep.mdl](#), [status](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

## prtitle

### Prime Title

*Description:* Identifies the title of the manual on the title page.

*Source paragraph:* 4.5.1.3.4 (MIL-STD-38784)

*Content Model:* (([nomen](#), ([modelno](#) | [partno](#) | [typedes](#) | [pslist](#) | [nsn](#))+, [serno](#)\*) | [subject](#))

*Parents:* [idinfo](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltpe    | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# pslist

## Part/Serial Number List

*Description:* Identifies a listing on the title page that corresponds a particular part number with associated serial numbers. This element could also be used to correspond model numbers with serial numbers.

*Source paragraph:* 4.5.1.3.4 (MIL-STD-38784)

*Content Model:* ([partno](#), [serno](#))+

*Parents:* [prtitle](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltpe    | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# pubdate

## Publication Date

*Description:* Identifies the basic date of the manual on the title page.

*Source paragraph:* 4.5.1.16 (MIL-STD-38784)

Content Model: ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

Parents: [idinfo](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# randlist

## Random List

Description: Identifies a random list. All items within the random list will appear unnumbered but with bullets, on separate lines, in the order they were entered by the author.

Source paragraph: None

Content Model: ([title?](#), [item](#)<sup>+</sup>)

Parents: [amplification](#), [entry](#), [ftnote](#), [para](#), [paras](#)

Excluded in: [caution](#), [note](#), [warning](#)

Entities used in this element: [chgatt](#), [delstat](#), [secur](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| prefix    | CDATA                                 | #IMPLIED | Used to replace the bullets that are normally created by the FOSI.                                                                                             |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |



---

# revnum

## Revision Number

*Description:* Identifies the revision number of the manual on the title page.

*Source paragraph:* 4.8 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [idinfo](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# row

## Row

*Description:* Identifies a row in a table.

*Source paragraph:* 4.2.7 (MIL-STD-38784)

*Content Model:* ([entry](#) | [entrytbl](#))<sup>+</sup>

*Parents:* [tbody](#), [tfoot](#), [thead](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [secur](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                    | Default  | Description                                                                                                                                                   |
|-----------|-------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| rowsep    | NUMBER                  | #IMPLIED | Allows the author to include a horizontal line to separate rows. Setting this attribute equal to "1" will generate row separators.                            |
| valign    | (top   bottom   middle) | #IMPLIED | Defines the vertical alignment for cell contents.                                                                                                             |
| security  | (u   c   s   n)         | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level. |

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

# seal

## Seal

|                                       |                                                                                                                                 |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies the Department of the Navy Seal, with command identifier, which appears below the contract number on the title page. |
| <i>Source paragraph:</i>              | 4.5.1.5 (MIL-STD-38784)                                                                                                         |
| <i>Content Model:</i>                 | EMPTY                                                                                                                           |
| <i>Parents:</i>                       | <a href="#">idinfo</a>                                                                                                          |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">status</a> , <a href="#">yesorno</a>                             |

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# sectocstr

## Section Table of Contents entry

|                          |                                                                                        |
|--------------------------|----------------------------------------------------------------------------------------|
| <i>Description:</i>      | Does not appear where tagged. Used with scripts to generate section table of contents. |
| <i>Source paragraph:</i> | N/A                                                                                    |

**Content Model:** ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

**Included in:** [clsection](#), [emergproccl](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

# secttoc

## Section Table of Contents

**Description:** Defines the table of contents for each section of the checklist.

**Source paragraph:** 3.7.2.2 (MIL-DTL-7700)

**Content Model:** ((#PCDATA | [cntentry](#)\* | (([parano](#)|[subparano](#))?, [paratitle](#), [pgnumber](#))\*))

**Parents:** [clsection](#), [emergproccl](#), [normproccl](#), [performdatacl](#)

**Entities used in this element:** [chgatt](#), [cntnt](#), [delstat](#), [secur](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| autobuild | (0 1)                                 | 1        | Identifies the secttoc will be autogenerated by the FOSI.                                                                                                      |
| address   | CDATA                                 | #IMPLIED | not used                                                                                                                                                       |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                 |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated                                                           |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                                                                          |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                           |

---

# seqlist

## Sequential List

**Description:** Identifies a sequential list. All items within the sequential list will appear numbered, on separate lines, in the order they were entered by the author.

**Source paragraph:** None

**Content Model:** (title?, item+)

**Parents:** amplification, entry, ftnote, para, paras

**Excluded in:** caution, note, warning

**Entities used in this element:** chgatt, delstat, secur, status, yesorno

### ATTRIBUTE LIST

| Attribute | Type                                             | Default  | Description                                                                                                                                                                                                                                                                                                                                                                              |
|-----------|--------------------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| numstyle  | (alphauc   alphalc   arabic   romanuc   romanlc) | arabic   | Defines the type of enumeration on the sequential list. Set this attribute to "alphauc" for uppercase letters (e.g., A., B., C., etc.), "alphalc" for lowercase letters (e.g., a., b., c., etc.), "arabic" for numbers (e.g., 1., 2., 3., etc.), "romanuc" for uppercase roman numerals (e.g., I., II., III., etc.), "romanlc" for lowercase roman numerals (e.g., i., ii., iii., etc.). |
| deltype   | (delete   real   reserve   NA)                   | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                                                                                                                                                                                                                                            |
| inschlvl  | NMTOKEN                                          | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                                                                                                                                                                                                                                               |
| delchlvl  | NMTOKEN                                          | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                                                                                                                                                                                                                                                |
| status    | (empty   deleted   reserved   notapp)            | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                                                                                                                                                                                                                                   |
| revchg    | NUMBER                                           | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                                                                                                                                                                                                                                     |
| security  | (u   c   s   n)                                  | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.                                                                                                                                                                                                                            |
| caveat    | CDATA                                            | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                                                                                                                                                                                                         |
| fgi       | CDATA                                            | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.                                                                                                                                                                                                                           |

---

# seqno

## Sequence Number

**Description:** Identifies the sequence number for a hazard warning.

**Source paragraph:** 4.3.10.1 (MIL-STD-38784)

**Content Model:** ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

**Parents:** [icon](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# serno

## Serial Number

**Description:** Identifies serial numbers of the equipment on the title page and on the difference data sheet.

**Source paragraph:** 4.5.1.3.4 (MIL-STD-38784)

**Content Model:** ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>) -([figure](#) | [table](#) | [foldout](#) | [objmedia](#))

**Parents:** [prtitle](#), [pslist](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [exclus](#), [secur](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |

---

# spanspec

## Span Specification

**Description:** Used to join two or more columns in a table. Span specifications are similar to column specifications (<colspec>) except that they describe areas of the table that can be spanned (joined) using a table entry (<entry>). For example, a three-column table may have columns named 1, 2, and 3 respectively. A span named 23 may be declared using spanspec. When spanname=23 is used on an entry, that entry would occupy the space in both columns 2 and 3.

**Source paragraph:** 4.2.7 (MIL-STD-38784)

**Content Model:** EMPTY

**Parents:** [entrytbl](#), [tfoot](#), [tgroup](#), [thead](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                     | Default   | Description                                                                                                                                                |
|-----------|------------------------------------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| namest    | NMTOKEN                                  | #REQUIRED | This should be set to the name of the first column of the set of columns that the author wants to span.                                                    |
| nameend   | NMTOKEN                                  | #REQUIRED | This should be set to the name of the last column of the set of columns that the author wants to span.                                                     |
| spanname  | NMTOKEN                                  | #IMPLIED  | Defines a unique name for the span.                                                                                                                        |
| align     | (left   right   center   justify   char) | center    | Defines the horizontal alignment of text within a cell.                                                                                                    |
| charoff   | NUTOKEN                                  | #IMPLIED  | Determines the distance the cell content should offset from the horizontal alignment character.                                                            |
| char      | CDATA                                    | #IMPLIED  | Defines the alignment character that can be used to align values within a column. This attribute should be used when the align attribute is set to "char". |
| colsep    | NUMBER                                   | #IMPLIED  | Allows the author to include a vertical line to separate columns. Setting this attribute equal to "1" will generate column separators.                     |
| rowsep    | NUMBER                                   | #IMPLIED  | Allows the author to include a horizontal line to separate rows. Setting this attribute equal to "1" will generate row separators.                         |
| deltype   | (delete   real   reserve   NA)           | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                              |
| inschlvl  | NMTOKEN                                  | #IMPLIED  | Used during the change package process to indicate the element was inserted at the change level indicated.                                                 |
| delchlvl  | NMTOKEN                                  | #IMPLIED  | Used during the change package process to indicate the element was deleted at the change level indicated.                                                  |
| status    | (empty   deleted   reserved   notapp)    | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the status of this element.                                     |
| revchg    | NUMBER                                   | 0         | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                       |

# step1

## First Level Procedural Step

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies a first level procedural step.                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <i>Source paragraph:</i>              | 4.2.9.5.3 (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <i>Content Model:</i>                 | (( <a href="#">note?</a> , <a href="#">para</a> , <a href="#">warning*</a> , <a href="#">caution?</a> , <a href="#">note?</a> ), ( <a href="#">step2</a> , <a href="#">step2+</a> )?)                                                                                                                                                                                                                                                                                                            |
| <i>Parents:</i>                       | <a href="#">abbrsect</a> , <a href="#">abbrsect</a> , <a href="#">applicdef</a> , <a href="#">applicdef</a> , <a href="#">para0</a> , <a href="#">para0</a> , <a href="#">procstep</a> , <a href="#">procstep2</a> , <a href="#">procstep3</a> , <a href="#">procstep4</a> , <a href="#">subpara1</a> , <a href="#">subpara1</a> , <a href="#">subpara2</a> , <a href="#">subpara2</a> , <a href="#">subpara3</a> , <a href="#">subpara3</a> , <a href="#">symsect</a> , <a href="#">symsect</a> |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">status</a> , <a href="#">step1.mdl</a> , <a href="#">stepatt</a> , <a href="#">stepcon</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                              |

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                                                                           |
|-----------|---------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA                                 | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired.                                                  |
| emergency | NUMBER                                | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                                                                       |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                                                                   |
| id        | ID                                    | #IMPLIED | This allows you to identify each element and later reference it by its id value.                                                                                                                                      |
| esds      | NUMBER                                | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the <b>**ESD**</b> symbol by setting this attribute equal to "1". |
| nsp       | NUMBER                                | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the <b>**NSP**</b> symbol by setting this attribute equal to "1".                                                               |
| fcf       | NUMBER                                | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the <b>**FCP**</b> symbol by setting this attribute equal to "1".                                                       |
| hcp       | NUMBER                                | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the <b>**HCP**</b> symbol by setting this attribute equal to "1".                                                           |
| hcl       | NUMBER                                | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the <b>**HCI**</b> symbol by setting this attribute equal to "1".                                                                   |
| ocp       | NUMBER                                | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the <b>**OCP**</b> symbol by setting this attribute equal to "1".                                                       |
| oci       | NUMBER                                | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the <b>**OCI**</b> symbol by setting this attribute equal to "1".                                                               |
| applicref | IDREFS                                | #IMPLIED | Allows you to assign an applicable reference to this element.                                                                                                                                                         |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                                                                        |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Insert Change Level                                                                                                                                                                |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Delete Change Level                                                                                                                                                                |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows you to specify the status of this element.                                                                                                                                                                     |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                                                                  |
| verdate   | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                                         |
| verrem    | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                                |
| verstatus | (unver   ver   notapplicable)         | unver    | Identifies verification status of the element.                                                                                                                                                                        |
| security  | (u   c   s   n)                       | n        | Identifies security level of the element.                                                                                                                                                                             |

| Attribute | Type  | Default  | Description                                                                                                      |
|-----------|-------|----------|------------------------------------------------------------------------------------------------------------------|
| caveat    | CDATA | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element. |
| fgi       | CDATA | #IMPLIED | Provides a place for inline FMS portion marking.                                                                 |

## step2

### Second Level Procedural Step

*Description:* Identifies a second level procedural step.

*Source paragraph:* 4.2.9.5.3 (MIL-STD-38784)

*Content Model:* (([note?](#), [para](#), [warning\\*](#), [caution?](#), [note?](#)), ([step3](#), [step3+](#))?)

*Parents:* [step1](#), [step1](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [step2.mdl](#), [stepatt](#), [stepcon](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                                                                           |
|-----------|---------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA                                 | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired.                                                  |
| emergency | NUMBER                                | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                                                                       |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                                                                   |
| id        | ID                                    | #IMPLIED | This allows you to identify each element and later reference it by its id value.                                                                                                                                      |
| esds      | NUMBER                                | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the <b>**ESD**</b> symbol by setting this attribute equal to "1". |
| nsp       | NUMBER                                | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the <b>**NSP**</b> symbol by setting this attribute equal to "1".                                                               |
| fcf       | NUMBER                                | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the <b>**FCP**</b> symbol by setting this attribute equal to "1".                                                       |
| hcp       | NUMBER                                | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the <b>**HCP**</b> symbol by setting this attribute equal to "1".                                                           |
| hcl       | NUMBER                                | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the <b>**HCI**</b> symbol by setting this attribute equal to "1".                                                                   |
| ocp       | NUMBER                                | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the <b>**OCP**</b> symbol by setting this attribute equal to "1".                                                       |
| oci       | NUMBER                                | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the <b>**OCI**</b> symbol by setting this attribute equal to "1".                                                               |
| applicref | IDREFS                                | #IMPLIED | Allows you to assign an applicable reference to this element.                                                                                                                                                         |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                                                                        |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Insert Change Level                                                                                                                                                                |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Delete Change Level                                                                                                                                                                |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows you to specify the status of this element.                                                                                                                                                                     |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                                                                  |
| verdate   | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                                         |
| verrem    | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                                |



| Attribute | Type                          | Default  | Description                                                                                                      |
|-----------|-------------------------------|----------|------------------------------------------------------------------------------------------------------------------|
| verstatus | (unver   ver   notapplicable) | unver    | Identifies verification status of the element.                                                                   |
| security  | (u   c   s   n)               | n        | Identifies security level of the element.                                                                        |
| caveat    | CDATA                         | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element. |
| fgi       | CDATA                         | #IMPLIED | Provides a place for inline FMS portion marking.                                                                 |

## step3

### Third Level Procedural Step

**Description:** Identifies a third level procedural step.  
**Source paragraph:** 4.2.9.5.3 (MIL-STD-38784)  
**Content Model:** (([note?](#), [para](#), [warning\\*](#), [caution?](#), [note?](#)), ([step4](#), [step4+](#))?)  
**Parents:** [step2](#), [step2](#)  
**Entities used in this element:** [chgatt](#), [delstat](#), [status](#), [step3.mdl](#), [stepatt](#), [stepcon](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                                                                           |
|-----------|---------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA                                 | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired.                                                  |
| emergency | NUMBER                                | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                                                                       |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                                                                   |
| id        | ID                                    | #IMPLIED | This allows you to identify each element and later reference it by its id value.                                                                                                                                      |
| esds      | NUMBER                                | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the <b>**ESD**</b> symbol by setting this attribute equal to "1". |
| nsp       | NUMBER                                | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the <b>**NSP**</b> symbol by setting this attribute equal to "1".                                                               |
| fcf       | NUMBER                                | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the <b>**FCP**</b> symbol by setting this attribute equal to "1".                                                       |
| hcp       | NUMBER                                | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the <b>**HCP**</b> symbol by setting this attribute equal to "1".                                                           |
| hcl       | NUMBER                                | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the <b>**HCI**</b> symbol by setting this attribute equal to "1".                                                                   |
| ocp       | NUMBER                                | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the <b>**OCP**</b> symbol by setting this attribute equal to "1".                                                       |
| oci       | NUMBER                                | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the <b>**OCI**</b> symbol by setting this attribute equal to "1".                                                               |
| applicref | IDREFS                                | #IMPLIED | Allows you to assign an applicable reference to this element.                                                                                                                                                         |
| deltyp    | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                                                                        |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Insert Change Level                                                                                                                                                                |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Delete Change Level                                                                                                                                                                |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows you to specify the status of this element.                                                                                                                                                                     |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                                                                                                                                  |

| Attribute | Type                          | Default  | Description                                                                                                      |
|-----------|-------------------------------|----------|------------------------------------------------------------------------------------------------------------------|
| verdate   | CDATA                         | #IMPLIED | Identifies the date the element was verified.                                                                    |
| verrem    | CDATA                         | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                           |
| verstatus | (unver   ver   notapplicable) | unver    | Identifies verification status of the element.                                                                   |
| security  | (u   c   s   n)               | n        | Identifies security level of the element.                                                                        |
| caveat    | CDATA                         | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element. |
| fgi       | CDATA                         | #IMPLIED | Provides a place for inline FMS portion marking.                                                                 |

## step4

### Fourth Level Procedural Step

*Description:* Identifies a fourth level procedural step.  
*Source paragraph:* 4.2.9.5.3 (MIL-STD-38784)  
*Content Model:* (([note?](#), [para](#), [warning\\*](#), [caution?](#), [note?](#)))  
*Parents:* [step3](#), [step3](#)  
*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [stepatt](#), [stepcon](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                           | Default  | Description                                                                                                                                                                                                           |
|-----------|--------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA                          | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired.                                                  |
| emergency | NUMBER                         | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                                                                       |
| sssn      | CDATA                          | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                                                                   |
| id        | ID                             | #IMPLIED | This allows you to identify each element and later reference it by its id value.                                                                                                                                      |
| esds      | NUMBER                         | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the <b>**ESD**</b> symbol by setting this attribute equal to "1". |
| nsp       | NUMBER                         | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the <b>**NSP**</b> symbol by setting this attribute equal to "1".                                                               |
| fcf       | NUMBER                         | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the <b>**FCP**</b> symbol by setting this attribute equal to "1".                                                       |
| hcp       | NUMBER                         | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the <b>**HCP**</b> symbol by setting this attribute equal to "1".                                                           |
| hcl       | NUMBER                         | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the <b>**HCI**</b> symbol by setting this attribute equal to "1".                                                                   |
| ocp       | NUMBER                         | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the <b>**OCP**</b> symbol by setting this attribute equal to "1".                                                       |
| oci       | NUMBER                         | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the <b>**OCI**</b> symbol by setting this attribute equal to "1".                                                               |
| applicref | IDREFS                         | #IMPLIED | Allows you to assign an applicable reference to this element.                                                                                                                                                         |
| deltype   | (delete   real   reserve   NA) | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                                                                        |
| inschlvl  | NMTOKEN                        | #IMPLIED | Used to generate change packages - Insert Change Level                                                                                                                                                                |
| delchlvl  | NMTOKEN                        | #IMPLIED | Used to generate change packages - Delete Change Level                                                                                                                                                                |

| Attribute | Type                                  | Default  | Description                                                                                                      |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------|
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows you to specify the status of this element.                                                                |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                             |
| verdate   | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                    |
| verrem    | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                           |
| verstatus | (unver   ver   notapplicable)         | unver    | Identifies verification status of the element.                                                                   |
| security  | (u   c   s   n)                       | n        | Identifies security level of the element.                                                                        |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element. |
| fgi       | CDATA                                 | #IMPLIED | Provides a place for inline FMS portion marking.                                                                 |

## subfig

### Subfigure

|                                       |                                                                                                                                                                                                         |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies a subfigure. This element is used for multi-sheet illustrations with each sheet being a subfigure. The FOSI will automatically generate the sheet count (e.g. Sheet 1 of 10, Sheet 2, etc.). |
| <i>Source paragraph:</i>              | 4.2.4.2 (MIL-STD-38784)                                                                                                                                                                                 |
| <i>Content Model:</i>                 | (( <a href="#">graphic</a> , <a href="#">legend</a> ?)   <a href="#">tabdisplay</a> )                                                                                                                   |
| <i>Parents:</i>                       | <a href="#">figure</a> , <a href="#">figure</a>                                                                                                                                                         |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">secur</a> , <a href="#">status</a> , <a href="#">subfig</a> , <a href="#">yesorno</a>                                                    |

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                           |
|-----------|---------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| orient    | (port   land1 )                       | port     | Defines the orientation of the figure, either portrait or landscape.                                                                                                  |
| id        | ID                                    | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                                      |
| label     | CDATA                                 | #IMPLIED | Allows the author to label this element manually. The FOSI automatically generates labels, so its use is not necessary unless a label out of the ordinary is desired. |
| applicref | IDREFS                                | #IMPLIED | Allows the author to assign an applicability/effectivity reference to this element.                                                                                   |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                         |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                            |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                             |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                  |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.         |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                      |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.        |

---

# subject

## Subject

*Description:* Identifies the prime title of the manual on the title page.

*Source paragraph:* 4.5.1.3.4 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [prtitle](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [secur](#), [status](#), [text](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

---

# subpara1

## First Subordinate Paragraph

*Description:* Identifies a first subordinate paragraph.

*Source paragraph:* 4.2.9.5.1.2 (MIL-STD-38784)

*Content Model:* (([title](#), [note](#)?, ([para](#), [warning](#)\*, [caution](#)?, [note](#)\*)\*, (([step1](#), [step1](#)+) ([clstep1](#)\*)?) ), [subpara2](#)\*)

*Parents:* [abbrsect](#), [applicdef](#), [para0](#), [symsect](#)

*Entities used in this element:* [bodyatt](#), [chgatt](#), [delstat](#), [nparcon](#), [para0att](#), [secur](#), [status](#), [sub1att](#), [verified](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| emergency | NUMBER                                | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                                                                |
| id        | ID                                    | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                                                                               |
| esds      | NUMBER                                | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the **ESD** symbol by setting this attribute equal to "1". |
| nsp       | NUMBER                                | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the **NSP** symbol by setting this attribute equal to "1".                                                               |
| fcp       | NUMBER                                | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the **FCP** symbol by setting this attribute equal to "1".                                                       |
| hcp       | NUMBER                                | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the **HCP** symbol by setting this attribute equal to "1".                                                           |
| hci       | NUMBER                                | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the **HCI** symbol by setting this attribute equal to "1".                                                                   |
| ocp       | NUMBER                                | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the **OCP** symbol by setting this attribute equal to "1".                                                       |
| oci       | NUMBER                                | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the **OCI** symbol by setting this attribute equal to "1".                                                               |
| applicref | IDREFS                                | #IMPLIED | Allows the author to assign an applicability/effectivity reference to this element.                                                                                                                            |
| verdate   | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                                  |
| verrem    | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                         |
| verstatus | (unver   ver   notapplicable)         | unver    | Identifies the verification status of the element.                                                                                                                                                             |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.                                                  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.                                                 |
| label     | CDATA                                 | #IMPLIED | Allows the author to label this element manually. The FOSI automatically generates labels, so its use is not necessary unless a label out of the ordinary is desired.                                          |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                                                            |
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is not currently supported by the FOSI.                                                                                                                  |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                                                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                                                           |

---

# subpara2

## Second Subordinate Paragraph

*Description:* Identifies a second subordinate paragraph.

*Source paragraph:* 4.2.9.5.1.2 (MIL-STD-38784)

*Content Model:* ((title?, note?, (para, warning\*, caution?, note\*)\*,((step1, step1+)|(clstep1\*))?), subpara3\*)

*Parents:* subpara1

*Entities used in this element:* bodyatt, chgatt, delstat, nparcon1, para0att, secur, status, sub2att, verified, yesorno

### ATTRIBUTE LIST

| Attribute | Type                          | Default  | Description                                                                                                                                                                                                    |
|-----------|-------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| emergency | NUMBER                        | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                                                                |
| id        | ID                            | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                                                                               |
| esds      | NUMBER                        | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the **ESD** symbol by setting this attribute equal to "1". |
| nsp       | NUMBER                        | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the **NSP** symbol by setting this attribute equal to "1".                                                               |
| fcf       | NUMBER                        | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the **FCP** symbol by setting this attribute equal to "1".                                                       |
| hcp       | NUMBER                        | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the **HCP** symbol by setting this attribute equal to "1".                                                           |
| hci       | NUMBER                        | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the **HCI** symbol by setting this attribute equal to "1".                                                                   |
| ocp       | NUMBER                        | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the **OCP** symbol by setting this attribute equal to "1".                                                       |
| oci       | NUMBER                        | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the **OCI** symbol by setting this attribute equal to "1".                                                               |
| applicref | IDREFS                        | #IMPLIED | Allows the author to assign an applicability/effectivity reference to this element.                                                                                                                            |
| verdate   | CDATA                         | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                                  |
| verrem    | CDATA                         | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                         |
| verstatus | (unver   ver   notapplicable) | unver    | Identifies the verification status of the element.                                                                                                                                                             |
| security  | (u   c   s   n)               | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.                                                  |
| caveat    | CDATA                         | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                               |
| fgi       | CDATA                         | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.                                                 |
| label     | CDATA                         | #IMPLIED | Allows the author to label this element manually. The FOSI automatically generates labels, so its use is not necessary unless a label out of the ordinary is desired.                                          |
| sssn      | CDATA                         | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                                                            |

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is not currently supported by the FOSI.                                 |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

## subpara3

### Third Subordinate Paragraph

*Description:* Identifies a third subordinate paragraph.

*Source paragraph:* 4.2.9.5.1.2 (MIL-STD-38784)

*Content Model:* ((title?, note?, (para, warning\*, caution?, note\*)\*,((step1, step1+)|(clstep1\*))?)?)

*Parents:* subpara2

*Entities used in this element:* bodyatt, chgatt, delstat, nparcon1, para0att, secur, status, sub3att, subpara3.mdl, verified, yesorno

### ATTRIBUTE LIST

| Attribute | Type                          | Default  | Description                                                                                                                                                                                                    |
|-----------|-------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| emergency | NUMBER                        | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                                                                |
| id        | ID                            | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                                                                               |
| esds      | NUMBER                        | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the **ESD** symbol by setting this attribute equal to "1". |
| nsp       | NUMBER                        | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the **NSP** symbol by setting this attribute equal to "1".                                                               |
| fcf       | NUMBER                        | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the **FCP** symbol by setting this attribute equal to "1".                                                       |
| hcp       | NUMBER                        | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the **HCP** symbol by setting this attribute equal to "1".                                                           |
| hci       | NUMBER                        | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the **HCI** symbol by setting this attribute equal to "1".                                                                   |
| ocp       | NUMBER                        | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the **OCP** symbol by setting this attribute equal to "1".                                                       |
| oci       | NUMBER                        | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the **OCI** symbol by setting this attribute equal to "1".                                                               |
| applicref | IDREFS                        | #IMPLIED | Allows the author to assign an applicability/effectivity reference to this element.                                                                                                                            |
| verdate   | CDATA                         | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                                  |
| verrem    | CDATA                         | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                         |
| verstatus | (unver   ver   notapplicable) | unver    | Identifies the verification status of the element.                                                                                                                                                             |

| Attribute | Type                                  | Default  | Description                                                                                                                                                           |
|-----------|---------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.         |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                      |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.        |
| label     | CDATA                                 | #IMPLIED | Allows the author to label this element manually. The FOSI automatically generates labels, so its use is not necessary unless a label out of the ordinary is desired. |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                   |
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is not currently supported by the FOSI.                                                                         |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                         |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                            |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                             |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                  |

# subparano

## Sub Paragraph Number

*Description:* Allows tagging of the subpara number in the section TOC.

*Source paragraph:* N/A

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hpc](#) | [hcl](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+)

*Parents:* [sectoc](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |



---

# subproc1

## Subprocedure 1

**Description:** Sequence to be accomplished in a procedure.

**Source paragraph:** N/A

**Content Model:** (((title)?, (para | condition | clstep1 | ifthen | coordprocs)+), subproc2\*)

**Parents:** procedure

**Entities used in this element:** bodyatt, chgatt, delstat, para0att, proced.mdl, secur, status, verified, yesorno

### ATTRIBUTE LIST

| Attribute    | Type                          | Default  | Description                                                                                                                                                                                           |
|--------------|-------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| applicboxing | (0   1)                       | 0        | Allows user to select whether or not the "term" will appear with reverse video or not.                                                                                                                |
| emergency    | NUMBER                        | 0        | Indicates that the primary paragraph will produce an emergency border on the page when set equal to 1.                                                                                                |
| id           | ID                            | #IMPLIED | Allows author to designate a unique paragraph ID for use with external and cross references.                                                                                                          |
| esds         | NUMBER                        | 0        | Electrostatic Discharge Sensitive. All paragraphs which address handling or maintenance which could damage *** ESDS *** parts shall be identified by the esds symbol by setting attribute equal to 1. |
| nsp          | NUMBER                        | 0        | Nuclear Surety Procedures. A **NSP** symbol will appear when set equal to 1.                                                                                                                          |
| fcp          | NUMBER                        | 0        | Fracture Critical Process. All paragraphs which address Fracture Critical Process shall be identified by the *** FCP *** symbol by setting attribute equal to 1.                                      |
| hcp          | NUMBER                        | 0        | Hardness Critical Process. All paragraphs which address Hardness Critical Process shall be identified by the *** HCP *** symbol by setting attribute equal to 1.                                      |
| hci          | NUMBER                        | 0        | Hardness Critical Item. All paragraphs which address Hardness Critical Item shall be identified by the *** HCI *** symbol by setting attribute equal to 1.                                            |
| ocp          | NUMBER                        | 0        | Observable Critical Process. All paragraphs which address observable critical processes shall be identified by the *** OCP *** symbol by setting attribute equal to 1.                                |
| oci          | NUMBER                        | 0        | Observable Critical Item. All paragraphs which address observable critical items shall be identified by the *** OCI *** symbol by setting attribute equal to 1.                                       |
| applicref    | IDREFS                        | #IMPLIED | Allows you to assign an applicability/effectivity reference to this element.                                                                                                                          |
| verdate      | CDATA                         | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                         |
| verrem       | CDATA                         | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                |
| verstatus    | (unver   ver   notapplicable) | unver    | Identifies verification status of the element.                                                                                                                                                        |
| security     | (u   c   s   n)               | n        | Identifies security level of the element.                                                                                                                                                             |
| caveat       | CDATA                         | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                      |
| fgi          | CDATA                         | #IMPLIED | Provides a place for inline FMS portion marking.                                                                                                                                                      |
| label        | CDATA                         | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired.                                  |
| sssn         | CDATA                         | #IMPLIED | System, Subsystem, or Subject Number can be assigned to this element.                                                                                                                                 |

| Attribute | Type                                  | Default  | Description                                                                                          |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------|
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is not currently supported by the FOSI.        |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                       |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Insert Change Level                                               |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Delete Change Level                                               |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows you to specify the status of this element.                                                    |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change. |
| clrank    | NUMBER                                | #IMPLIED | not used                                                                                             |

## subproc2

### Subprocedure 2

*Description:* Sequence to be accomplished in a procedure.

*Source paragraph:* N/A

*Content Model:* (((*title*)?, (*para* | *condition* | *clstep1* | *ifthen* | *coordprocs*)+), *subproc3*\*)

*Parents:* [subproc1](#)

*Entities used in this element:* [bodyatt](#), [chgatt](#), [delstat](#), [para0att](#), [proced.mdl](#), [secur](#), [status](#), [verified](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute    | Type    | Default  | Description                                                                                                                                                                                           |
|--------------|---------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| applicboxing | (0   1) | 0        | Allows user to select whether or not the "term" will appear with reverse video or not.                                                                                                                |
| emergency    | NUMBER  | 0        | Indicates that the primary paragraph will produce an emergency border on the page when set equal to 1.                                                                                                |
| id           | ID      | #IMPLIED | Allows author to designate a unique paragraph ID for use with external and cross references.                                                                                                          |
| esds         | NUMBER  | 0        | Electrostatic Discharge Sensitive. All paragraphs which address handling or maintenance which could damage *** ESDS *** parts shall be identified by the esds symbol by setting attribute equal to 1. |
| nsp          | NUMBER  | 0        | Nuclear Surety Procedures. A **NSP** symbol will appear when set equal to 1.                                                                                                                          |
| fcf          | NUMBER  | 0        | Fracture Critical Process. All paragraphs which address Fracture Critical Process shall be identified by the *** FCP *** symbol by setting attribute equal to 1.                                      |
| hcp          | NUMBER  | 0        | Hardness Critical Process. All paragraphs which address Hardness Critical Process shall be identified by the *** HCP *** symbol by setting attribute equal to 1.                                      |
| hci          | NUMBER  | 0        | Hardness Critical Item. All paragraphs which address Hardness Critical Item shall be identified by the *** HCI *** symbol by setting attribute equal to 1.                                            |
| ocp          | NUMBER  | 0        | Observable Critical Process. All paragraphs which address observable critical processes shall be identified by the *** OCP *** symbol by setting attribute equal to 1.                                |
| oci          | NUMBER  | 0        | Observable Critical Item. All paragraphs which address observable critical items shall be identified by the *** OCI *** symbol by setting attribute equal to 1.                                       |
| applicref    | IDREFS  | #IMPLIED | Allows you to assign an applicability/effectivity reference to this element.                                                                                                                          |
| verdate      | CDATA   | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                         |

| Attribute | Type                                  | Default  | Description                                                                                                                                                          |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| verrem    | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                               |
| verstatus | (unver   ver   notapplicable)         | unver    | Identifies verification status of the element.                                                                                                                       |
| security  | (u   c   s   n)                       | n        | Identifies security level of the element.                                                                                                                            |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                     |
| fgi       | CDATA                                 | #IMPLIED | Provides a place for inline FMS portion marking.                                                                                                                     |
| label     | CDATA                                 | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired. |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, or Subject Number can be assigned to this element.                                                                                                |
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is This attribute is not currently supported by the FOSI.                                                      |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                       |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Insert Change Level                                                                                                               |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Delete Change Level                                                                                                               |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows you to specify the status of this element.                                                                                                                    |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                 |
| clrank    | NUMBER                                | #IMPLIED | not used                                                                                                                                                             |

## subproc3

### Subprocedure 3

*Description:* Sequence to be accomplished in a procedure.

*Source paragraph:* N/A

*Content Model:* (([title](#))?, ([para](#) | [condition](#) | [clstep1](#) | [ifthen](#) | [coordprocs](#))+)

*Parents:* [subproc2](#)

*Entities used in this element:* [bodyatt](#), [chgatt](#), [delstat](#), [para0att](#), [proced.mdl](#), [secur](#), [status](#), [verified](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute    | Type    | Default  | Description                                                                                                                                                                                           |
|--------------|---------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| applicboxing | (0   1) | 0        | Allows user to select whether or not the "term" will appear with reverse video or not.                                                                                                                |
| emergency    | NUMBER  | 0        | Indicates that the primary paragraph will produce an emergency border on the page when set equal to 1.                                                                                                |
| id           | ID      | #IMPLIED | Allows author to designate a unique paragraph ID for use with external and cross references.                                                                                                          |
| esds         | NUMBER  | 0        | Electrostatic Discharge Sensitive. All paragraphs which address handling or maintenance which could damage *** ESDS *** parts shall be identified by the esds symbol by setting attribute equal to 1. |
| nsp          | NUMBER  | 0        | Nuclear Surety Procedures. A **NSP** symbol will appear when set equal to 1.                                                                                                                          |
| fcf          | NUMBER  | 0        | Fracture Critical Process. All paragraphs which address Fracture Critical Process shall be identified by the *** FCP *** symbol by setting attribute equal to 1.                                      |
| hcp          | NUMBER  | 0        | Hardness Critical Process. All paragraphs which address Hardness Critical Process shall be identified by the *** HCP *** symbol by setting attribute equal to 1.                                      |

| Attribute | Type                                  | Default  | Description                                                                                                                                                            |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| hci       | NUMBER                                | 0        | Hardness Critical Item. All paragraphs which address Hardness Critical Item shall be identified by the *** HCI *** symbol by setting attribute equal to 1.             |
| ocp       | NUMBER                                | 0        | Observable Critical Process. All paragraphs which address observable critical processes shall be identified by the *** OCP *** symbol by setting attribute equal to 1. |
| oci       | NUMBER                                | 0        | Observable Critical Item. All paragraphs which address observable critical items shall be identified by the *** OCI *** symbol by setting attribute equal to 1.        |
| applicref | IDREFS                                | #IMPLIED | Allows you to assign an applicability/effectivity reference to this element.                                                                                           |
| verdate   | CDATA                                 | #IMPLIED | Identifies the date the element was verified.                                                                                                                          |
| verrem    | CDATA                                 | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                 |
| verstatus | (unver   ver   notapplicable)         | unver    | Identifies verification status of the element.                                                                                                                         |
| security  | (u   c   s   n)                       | n        | Identifies security level of the element.                                                                                                                              |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                       |
| fgi       | CDATA                                 | #IMPLIED | Provides a place for inline FMS portion marking.                                                                                                                       |
| label     | CDATA                                 | #IMPLIED | Allows you to label this paragraph manually. The FOSI will automatically do this for you, so its use is not necessary unless a label out of the ordinary is desired.   |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, or Subject Number can be assigned to this element.                                                                                                  |
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is This attribute is not currently supported by the FOSI.                                                        |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                                                                                         |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Insert Change Level                                                                                                                 |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used to generate change packages - Delete Change Level                                                                                                                 |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows you to specify the status of this element.                                                                                                                      |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                   |
| clrank    | NUMBER                                | #IMPLIED | not used                                                                                                                                                               |

# subtitle

## Subtitle

*Description:* Identifies the subtitle of the manual on the title page. This element is only used with multivolume manuals to indicate the contents of the specific volume as the prime title is shared amongst all the volumes.

*Source paragraph:* 4.5.1.3.5 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+)

*Parents:* [idinfo](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [secur](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type            | Default | Description                                                                                                                                                   |
|-----------|-----------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n) | n       | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level. |

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

---

## supersed

### Supersedure Notice

*Description:* Identifies the supersedure notice on the title page.

*Source paragraph:* 4.5.1.6 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [idinfo](#)

*Entities used in this element:* [text](#)

---

## suppl

### Supplement Notice

*Description:* Identifies the supplement notice on the title page.

*Source paragraph:* 4.5.1.7 (MIL-STD-38784)

*Content Model:* ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))<sup>+</sup>)

*Parents:* [idinfo](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                           | Default  | Description                                                                                                                   |
|-----------|--------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                        | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |

| Attribute | Type                                  | Default  | Description                                                                                                            |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------|
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.              |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element. |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                   |

# symb

## Symbol

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Allows user to enter text as symbol on "Other Considerations".                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <i>Source paragraph:</i>              | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <i>Content Model:</i>                 | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">ftnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcp</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> ) <sup>+</sup> ) |
| <i>Parents:</i>                       | <a href="#">syms</a> , <a href="#">syms1</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">status</a> , <a href="#">text</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

# syms

## Symbols

|                                       |                                                                                                     |
|---------------------------------------|-----------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Allows user to place symbol markings within procedures to coincide with "Other Considerations".     |
| <i>Source paragraph:</i>              | N/A                                                                                                 |
| <i>Content Model:</i>                 | (( <a href="#">w</a>   <a href="#">c</a> )?, <a href="#">ymb</a> )                                  |
| <i>Included in:</i>                   | <a href="#">procedure</a>                                                                           |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">status</a> , <a href="#">yesorno</a> |

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

# syms1

## Symbols

*Description:* Allows user to place symbol groupings in addcond element.

*Source paragraph:* N/A

*Content Model:* ((w | c)?, symb)

*Parents:* [addcond](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

# symrow

## Symbol Row

*Description:* Identifies a row which contains a term and definition for describing symbols used in the manual.

*Source paragraph:* 4.5.9 (MIL-STD-38784)

*Content Model:* (term, def)

*Parents:* [symsect](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

## symsect

### Symbol Paragraph

**Description:** Identifies the paragraph(s) used to define symbols (e.g., ESDS symbol) and the associated list.

**Source paragraph:** 4.5.9 (MIL-STD-38784)

**Content Model:** (((title, note?, (para, warning\*, caution?, note\*)\*, ((step1, step1+)|(clstep1\*)?), subpara1\*)?, (symtitle?, (symrow+ | (term, def)+)))

**Parents:** [intro](#)

**Entities used in this element:** [bodyatt](#), [chgatt](#), [delstat](#), [para0att](#), [parazero](#), [secur](#), [status](#), [symsect](#), [verified](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute  | Type    | Default  | Description                                                                                                                                                                                                    |
|------------|---------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| rtermwidth | NUTOKEN | 2.75in   | Allows the author to define the width of the right column.                                                                                                                                                     |
| ltermwidth | NUTOKEN | 0.75in   | Allows the author to define the width of the left column.                                                                                                                                                      |
| emergency  | NUMBER  | 0        | Indicates that this element will produce an emergency border on the page when set equal to "1".                                                                                                                |
| id         | ID      | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                                                                               |
| esds       | NUMBER  | 0        | Electrostatic Discharge Sensitive (ESDS). All paragraphs which address handling or maintenance which could damage ESDS parts shall be identified by the **ESD** symbol by setting this attribute equal to "1". |
| nsp        | NUMBER  | 0        | Nuclear Surety Procedures (NSP). All nuclear surety procedures shall be identified by the **NSP** symbol by setting this attribute equal to "1".                                                               |
| fcf        | NUMBER  | 0        | Fracture Critical Parts (FCP). All fatigue and fracture critical parts shall be identified by the **FCP** symbol by setting this attribute equal to "1".                                                       |
| hcp        | NUMBER  | 0        | Hardness Critical Processes (HCP). All hardness critical processes shall be identified by the **HCP** symbol by setting this attribute equal to "1".                                                           |
| hcl        | NUMBER  | 0        | Hardness Critical Items (HCI). All hardness critical items shall be identified by the **HCI** symbol by setting this attribute equal to "1".                                                                   |
| ocp        | NUMBER  | 0        | Observable Critical Processes (OCP). All observable critical processes shall be identified by the **OCP** symbol by setting this attribute equal to "1".                                                       |
| oci        | NUMBER  | 0        | Observable Critical Items (OCI). All observable critical items shall be identified by the **OCI** symbol by setting this attribute equal to "1".                                                               |
| applicref  | IDREFS  | #IMPLIED | Allows the author to assign an applicability/effectivity reference to this element.                                                                                                                            |
| verdate    | CDATA   | #IMPLIED | Identifies the date the element was verified.                                                                                                                                                                  |
| verrem     | CDATA   | #IMPLIED | Provides a place for the author to make remarks about the verification of the element.                                                                                                                         |



| Attribute | Type                                  | Default  | Description                                                                                                                                                           |
|-----------|---------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| verstatus | (unver   ver   notapplicable)         | unver    | Identifies the verification status of the element.                                                                                                                    |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.         |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                      |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.        |
| label     | CDATA                                 | #IMPLIED | Allows the author to label this element manually. The FOSI automatically generates labels, so its use is not necessary unless a label out of the ordinary is desired. |
| sssn      | CDATA                                 | #IMPLIED | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                   |
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is not currently supported by the FOSI.                                                                         |
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                         |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                            |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                             |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                  |

# symtitle

## Symbol Paragraph Title

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies the title of the list that is used to define symbols (e.g., ESDS symbol).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <i>Source paragraph:</i>              | 4.5.9 (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <i>Content Model:</i>                 | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">ftnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcp</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> )+) -( <a href="#">figure</a>   <a href="#">table</a>   <a href="#">foldout</a>   <a href="#">objmedia</a> ) |
| <i>Parents:</i>                       | <a href="#">symsect</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">exclus</a> , <a href="#">status</a> , <a href="#">text</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| deltype   | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# tabdisplay

## Table Display

**Description:** Identifies table data contained within an illustration.

**Source paragraph:** 4.3.9 (MIL-STD-38784)

**Content Model:** (tgroup+) -(figure | table | foldout | objmedia) +(tfoot | tfnref | tfndisplay)

**Parents:** figure, subfig

**Entities used in this element:** chgatt, delstat, exclus, secur, status, yesorno

### ATTRIBUTE LIST

| Attribute | Type                                         | Default  | Description                                                                                                                                                           |
|-----------|----------------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label     | CDATA                                        | #IMPLIED | Allows the author to label this element manually. The FOSI automatically generates labels, so its use is not necessary unless a label out of the ordinary is desired. |
| frame     | (top   bottom   topbot   all   sides   none) | all      | Defines the frame for the table.                                                                                                                                      |
| colsep    | NUMBER                                       | 1        | Allows the author to include a vertical line to separate columns. Setting this attribute equal to "1" will generate column separators.                                |
| rowsep    | NUMBER                                       | 0        | Allows the author to include a horizontal line to separate rows. Setting this attribute equal to "1" will generate row separators.                                    |
| tbwidth   | NUTOKEN                                      | #IMPLIED | Defines the width of the table.                                                                                                                                       |
| tbdepth   | NUTOKEN                                      | #IMPLIED | Defines the depth (height) of the table.                                                                                                                              |
| horrefpt  | (left   right)                               | left     | Defines the horizontal reference point for the table.                                                                                                                 |
| verrefpt  | (vtop   vbottom)                             | vtop     | Defines the vertical reference point for the table.                                                                                                                   |
| coordst   | CDATA                                        | 0,10000  | Defines the coordinates to start the table.                                                                                                                           |
| assocfig  | IDREF                                        | #IMPLIED | Used to associate the table with an illustration.                                                                                                                     |
| delttype  | (delete   real   reserve   NA)               | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                         |
| inschlvl  | NMTOKEN                                      | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                            |
| delchlvl  | NMTOKEN                                      | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                             |
| status    | (empty   deleted   reserved   notapp)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                |
| revchg    | NUMBER                                       | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                  |
| security  | (u   c   s   n)                              | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.         |
| caveat    | CDATA                                        | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                      |
| fgi       | CDATA                                        | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.        |

# table

## Table

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies a table.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <i>Source paragraph:</i>              | 4.2.7 (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <i>Content Model:</i>                 | ( <a href="#">title</a> , <a href="#">tgroup</a> +) -( <a href="#">figure</a>   <a href="#">table</a>   <a href="#">foldout</a>   <a href="#">objmedia</a> ) +( <a href="#">tfhref</a>   <a href="#">tfoot</a>   <a href="#">tfndisplay</a>   <a href="#">tfid</a> )                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <i>Included in:</i>                   | <a href="#">clsection</a> , <a href="#">emergproccl</a> , <a href="#">intro</a> , <a href="#">normproccl</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <i>Excluded in:</i>                   | <a href="#">abbrtitle</a> , <a href="#">acronym</a> , <a href="#">acronymlist</a> , <a href="#">applicabil</a> , <a href="#">apptitle</a> , <a href="#">caution</a> , <a href="#">change</a> , <a href="#">dataiden</a> , <a href="#">date</a> , <a href="#">def</a> , <a href="#">emphasis</a> , <a href="#">extapplicabil</a> , <a href="#">figtable</a> , <a href="#">figure</a> , <a href="#">fnote</a> , <a href="#">item</a> , <a href="#">modelno</a> , <a href="#">nomen</a> , <a href="#">note</a> , <a href="#">partno</a> , <a href="#">serno</a> , <a href="#">symtitle</a> , <a href="#">tabdisplay</a> , <a href="#">table</a> , <a href="#">tabmat</a> , <a href="#">term</a> , <a href="#">title</a> , <a href="#">tmidno</a> , <a href="#">typedes</a> , <a href="#">underline</a> , <a href="#">warning</a> |
| <i>Entities used in this element:</i> | <a href="#">bodyatt</a> , <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">exclus</a> , <a href="#">secur</a> , <a href="#">status</a> , <a href="#">tabatts</a> , <a href="#">tabl</a> , <a href="#">verified</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

### ATTRIBUTE LIST

| Attribute | Type                                          | Default   | Description                                                                                                                                                           |
|-----------|-----------------------------------------------|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tabstyle  | NMTOKEN                                       | #IMPLIED  | Describes the type of table.                                                                                                                                          |
| frame     | (top   bottom   topbot   all   sides   none ) | all       | Defines the frame for the table.                                                                                                                                      |
| colsep    | NUMBER                                        | 1         | Allows the author to include a vertical line to separate columns. Setting this attribute equal to "1" will generate column separators.                                |
| rowsep    | NUMBER                                        | 0         | Allows the author to include a horizontal line to separate rows. Setting this attribute equal to "1" will generate row separators.                                    |
| orient    | (port   land1)                                | port      | Defines the orientation of the table on the page, either portrait or landscape.                                                                                       |
| pgwide    | NUMBER                                        | 1         | Set this attribute equal to "1" to have the table fill the entire width of the page.                                                                                  |
| cellcont  | (Continued   Cont)                            | Continued | Specifies whether the table will display "Continued" or "Cont." when it continues on more than one page.                                                              |
| id        | ID                                            | #IMPLIED  | Provides means to specify an ID number for the table.                                                                                                                 |
| footnotes | (page   end)                                  | #IMPLIED  | Allows the author to specify whether table footnotes appear at the end of the table or at the end of the page.                                                        |
| leftind   | CDATA                                         | #IMPLIED  | Specifies the left indent of the table in relationship to the page.                                                                                                   |
| rightind  | CDATA                                         | #IMPLIED  | Specifies the right indent of the table in relationship to the page.                                                                                                  |
| leftmar   | NUTOKEN                                       | #IMPLIED  | Specifies the left margin of the table.                                                                                                                               |
| rightmar  | NUTOKEN                                       | #IMPLIED  | Specifies the right margin of the table.                                                                                                                              |
| topmar    | NUTOKEN                                       | #IMPLIED  | Specifies the top margin of the table.                                                                                                                                |
| botmar    | NUTOKEN                                       | #IMPLIED  | Specifies the bottom margin of the table.                                                                                                                             |
| mindepth  | NUTOKEN                                       | #IMPLIED  | Specifies the minimum depth (height) of the table.                                                                                                                    |
| pgdeep    | NUMBER                                        | 0         | Setting this attribute equal to "1" will set the depth (height) of the table equal to the depth (height) of the page.                                                 |
| applicref | IDREFS                                        | #IMPLIED  | Allows the author to assign an applicability/effectivity reference to this element.                                                                                   |
| verdate   | CDATA                                         | #IMPLIED  | Identifies the date the element was verified.                                                                                                                         |
| verrem    | CDATA                                         | #IMPLIED  | Provides a place for the author to make remarks about the verification of the element.                                                                                |
| verstatus | (unver   ver   notapplicable)                 | unver     | Identifies the verification status of the element.                                                                                                                    |
| label     | CDATA                                         | #IMPLIED  | Allows the author to label this element manually. The FOSI automatically generates labels, so its use is not necessary unless a label out of the ordinary is desired. |
| sssn      | CDATA                                         | #IMPLIED  | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                   |

| Attribute | Type                                  | Default  | Description                                                                                                                                                                                                                                    |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| indexid   | CDATA                                 | #IMPLIED | Provides an index ID for this element. This attribute is not currently supported by the FOSI.                                                                                                                                                  |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                                                                                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                                                                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                                                                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                                                                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                                                                                           |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.                                                                                  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                                                                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.                                                                                 |
| continued | NUMBER                                | 0        | Setting this attribute equal to "1" allows the table to be continued from the previous page. This tag was only added to allow for proper formatting of table footnotes. It is to be used in conjunction with the 38784 Table Footnotes script. |

# tabmat

## Tabular Material

**Description:** Identifies tabular material that is to be displayed without the table title or headers.

**Source paragraph:** 4.3.9.1 (MIL-STD-38784)

**Content Model:** (tgroup+) -(figure | table | foldout | objmedia)

**Parents:** abbrtitle, action, amplification, applicabil, appltile, authnot, change, chgdate, chgnum, chgtxt, clink, clitem, cogact, condition, contractno, copyright, cpos, crewpos, crewpos1, crewpos2, crewpos3, crewpos4, crewpos5, dataiden, date, def, destr, discl, distrib, doctype, effdatenot, emphasis, entry, etitle, expcont, extapplicabil, ftnote, hazmat, ilink, internatlst, item, label, legend, lepchg, leppage, line, maintl, mfr, modelno, moveddata, newpos1, newpos2, newpos3, newpos4, newpos5, nmlist, nomen, nsn, oadr, pageno, para, param, parano, paras, paratitle, partno, pnumber, phrase, pretmidno, pubdate, revnum, sectocstr, seqno, serno, subject, subparano, subtitle, supersed, suppl, symb, symtitle, term, tfnid, title, tmidno, typedes, underline, verstat

**Included in:** clsection, emergproccl, procedure

**Entities used in this element:** bodyatt, chgatt, delstat, exclus, secur, status, tabatts, verified, yesorno

## ATTRIBUTE LIST

| Attribute | Type                                          | Default  | Description                                                                                                                            |
|-----------|-----------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------|
| tabstyle  | NMTOKEN                                       | #IMPLIED | Describes the type of table.                                                                                                           |
| frame     | (top   bottom   topbot   all   sides   none ) | all      | Defines the frame for the table.                                                                                                       |
| colsep    | NUMBER                                        | 1        | Allows the author to include a vertical line to separate columns. Setting this attribute equal to "1" will generate column separators. |
| rowsep    | NUMBER                                        | 0        | Allows the author to include a horizontal line to separate rows. Setting this attribute equal to "1" will generate row separators.     |
| orient    | (port   land1)                                | port     | Defines the orientation of the table on the page, either portrait or landscape.                                                        |

| Attribute | Type                                  | Default   | Description                                                                                                                                                           |
|-----------|---------------------------------------|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pgwide    | NUMBER                                | 1         | Set this attribute equal to "1" to have the table fill the entire width of the page.                                                                                  |
| cellcont  | (Continued   Cont)                    | Continued | Specifies whether the table will display "Continued" or "Cont." when it continues on more than one page.                                                              |
| id        | ID                                    | #IMPLIED  | Provides means to specify an ID number for the table.                                                                                                                 |
| footnotes | (page   end)                          | #IMPLIED  | Allows the author to specify whether table footnotes appear at the end of the table or at the end of the page.                                                        |
| leftind   | CDATA                                 | #IMPLIED  | Specifies the left indent of the table in relationship to the page.                                                                                                   |
| rightind  | CDATA                                 | #IMPLIED  | Specifies the right indent of the table in relationship to the page.                                                                                                  |
| leftmar   | NUTOKEN                               | #IMPLIED  | Specifies the left margin of the table.                                                                                                                               |
| rightmar  | NUTOKEN                               | #IMPLIED  | Specifies the right margin of the table.                                                                                                                              |
| topmar    | NUTOKEN                               | #IMPLIED  | Specifies the top margin of the table.                                                                                                                                |
| botmar    | NUTOKEN                               | #IMPLIED  | Specifies the bottom margin of the table.                                                                                                                             |
| mindepth  | NUTOKEN                               | #IMPLIED  | Specifies the minimum depth (height) of the table.                                                                                                                    |
| pgdeep    | NUMBER                                | 0         | Setting this attribute equal to "1" will set the depth (height) of the table equal to the depth (height) of the page.                                                 |
| applicref | IDREFS                                | #IMPLIED  | Allows the author to assign an applicability/effectivity reference to this element.                                                                                   |
| verdate   | CDATA                                 | #IMPLIED  | Identifies the date the element was verified.                                                                                                                         |
| verrem    | CDATA                                 | #IMPLIED  | Provides a place for the author to make remarks about the verification of the element.                                                                                |
| verstatus | (unver   ver   notapplicable)         | unver     | Identifies the verification status of the element.                                                                                                                    |
| label     | CDATA                                 | #IMPLIED  | Allows the author to label this element manually. The FOSI automatically generates labels, so its use is not necessary unless a label out of the ordinary is desired. |
| sssn      | CDATA                                 | #IMPLIED  | System, Subsystem, Sub-subsystem Number (SSSN). Allows the author to assign a SSSN to this element.                                                                   |
| indexid   | CDATA                                 | #IMPLIED  | Provides an index ID for this element. This attribute is not currently supported by the FOSI.                                                                         |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                         |
| inschlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was inserted at the change level indicated.                                                            |
| delchlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was deleted at the change level indicated.                                                             |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                |
| revchg    | NUMBER                                | 0         | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                  |
| security  | (u   c   s   n)                       | n         | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.         |
| caveat    | CDATA                                 | #IMPLIED  | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                                      |
| fgi       | CDATA                                 | #IMPLIED  | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals.        |

# tasks

## Tasks

*Description:* Identifies the tasks for each crew member listed in the Coordinated Action Table.

*Source paragraph:* 3.2.12.2, 3.2.12.2.1 (MIL-DTL-7700)

Content Model: ((newpos1?, newpos2?, newpos3?, newpos4?, newpos5?) | (cmbr1?, cmbr2?, cmbr3?, cmbr4?, cmbr5?))

Parents: coordprocs

Entities used in this element: chgatt, delstat, status, yesorno

ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

tbody

Table Body

Description: Identifies the body of a table (e.g., material below the boxheads).

Source paragraph: 4.2.7 (MIL-STD-38784)

Content Model: (row+)

Parents: entrytbl, tgroup

Entities used in this element: chgatt, delstat, status, yesorno

ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| valign    | (top   middle   bottom)               | top      | Defines the vertical alignment of text within the cells of the table body.                                                    |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# term

## Term

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Identifies an entry in the term portion of a list. Each term has an associated definition.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <i>Source paragraph:</i>              | 4.3.4 (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <i>Content Model:</i>                 | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">ftnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcp</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> )+) -( <a href="#">figure</a>   <a href="#">table</a>   <a href="#">foldout</a>   <a href="#">objmedia</a> ) |
| <i>Parents:</i>                       | <a href="#">acronym</a> , <a href="#">acronymlist</a> , <a href="#">acronymrow</a> , <a href="#">applic</a> , <a href="#">applchd</a> , <a href="#">defhd</a> , <a href="#">deflist</a> , <a href="#">symrow</a> , <a href="#">symsect</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <i>Entities used in this element:</i> | <a href="#">chgatt</a> , <a href="#">delstat</a> , <a href="#">exclus</a> , <a href="#">secur</a> , <a href="#">status</a> , <a href="#">text</a> , <a href="#">yesorno</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| id        | ID                                    | #IMPLIED | Allows the author to generate a unique ID for use when referencing this element.                                                                               |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

---

# tfndisplay

## Table Footnote Display

|                          |                                                                                                                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>      | This element is for displaying footnotes in a table. Footnotes to tables will be displayed at the end of the table. This element should be placed in a span in the last row of the table. |
| <i>Source paragraph:</i> | 4.2.7.5 (MIL-STD-38784)                                                                                                                                                                   |
| <i>Content Model:</i>    | EMPTY                                                                                                                                                                                     |
| <i>Included in:</i>      | <a href="#">figtable</a> , <a href="#">tabdisplay</a> , <a href="#">table</a>                                                                                                             |

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

# tfnid

## Table Footnote ID

**Description:** This element is for placing a footnote in a table. A superscript character will be placed at this point in the table and the footnote value will be placed at the bottom of the table if a table footnote display element is used.

**Source paragraph:** 4.2.7.5 (MIL-STD-38784)

**Content Model:** ((#PCDATA | [change](#) | [tabmat](#) | [fnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+)

**Parents:** [tfoot](#)

**Included in:** [table](#)

Entities used in this element: [chgatt](#), [delstat](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default   | Description                                                                                                                               |
|-----------|---------------------------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------|
| id        | ID                                    | #REQUIRED | Allows the author to generate a unique ID for use when referencing this element.                                                          |
| tfntype   | (num   alpha   sym)                   | num       | Defines the type of symbol used to indicate a table footnote.                                                                             |
| tfnsymbol | CDATA                                 | #IMPLIED  | Allows the author to define the actual symbol to serve as a table footnote reference.                                                     |
| tfnval    | CDATA                                 | #IMPLIED  | Defines the text value of the reference. The actual data to be generated at the bottom of the table should be placed with this attribute. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.             |
| inschlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was inserted at the change level indicated.                                |
| delchlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was deleted at the change level indicated.                                 |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the status of this element.                    |
| revchg    | NUMBER                                | 0         | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                      |



---

# tfnref

## Table Footnote Reference

**Description:** This element is for referencing a footnote in a table that was created with a table footnote ID. The superscript character that was generated from the table footnote ID will be placed at this point in the table and the footnote value will be placed at the bottom of the table if a table footnote display element is used.

**Source paragraph:** 4.2.7.5 (MIL-STD-38784)

**Content Model:** EMPTY

**Included in:** [figtable](#), [tabdisplay](#), [table](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                                  | Default   | Description                                                                                                                                            |
|-----------|---------------------------------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| xrefid    | IDREF                                 | #REQUIRED | Defines the ID of the element that you are referencing. The value of this attribute should match the value of an ID attribute elsewhere in the manual. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                          |
| inschlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was inserted at the change level indicated.                                             |
| delchlvl  | NMTOKEN                               | #IMPLIED  | Used during the change package process to indicate the element was deleted at the change level indicated.                                              |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the status of this element.                                 |
| revchg    | NUMBER                                | 0         | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                   |

---

# tfoot

## Table Footer

**Description:** The footer of the table.

**Source paragraph:** 4.2.7.5 (MIL-STD-38784)

**Content Model:** (([colspec](#)\*, [spanspec](#)\*, [row](#)+) | [tfnid](#)+) -([entrytbl](#))

**Parents:** [tgroup](#)

**Included in:** [figtable](#), [tabdisplay](#), [table](#)

**Entities used in this element:** [chgatt](#), [delstat](#), [status](#), [yesorno](#)

### ATTRIBUTE LIST

| Attribute | Type                           | Default  | Description                                                                                                                   |
|-----------|--------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |

| Attribute | Type                                  | Default  | Description                                                                                                            |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------|
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.             |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.              |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element. |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                   |

## tggroup

### Table Group

*Description:* Identifies a table group which consists of a table heading (boxheads) and a table body.

*Source paragraph:* 4.2.7 (MIL-STD-38784)

*Content Model:* (colspec\*, spanspec\*, (thead?, tfoot?, tbody))

*Parents:* figtable, tabdisplay, table, tabmat

*Entities used in this element:* chgatt, delstat, status, yesorno

### ATTRIBUTE LIST

| Attribute | Type                                     | Default   | Description                                                                                                                                                |
|-----------|------------------------------------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| cols      | NUMBER                                   | #REQUIRED | Defines the number of columns within the table.                                                                                                            |
| colsep    | NUMBER                                   | #IMPLIED  | Allows the author to include a vertical line to separate columns. Setting this attribute equal to "1" will generate column separators.                     |
| rowsep    | NUMBER                                   | #IMPLIED  | Allows the author to include a horizontal line to separate rows. Setting this attribute equal to "1" will generate row separators.                         |
| align     | (left   right   center   justify   char) | left      | Defines the horizontal alignment of text within a cell.                                                                                                    |
| leftind   | CDATA                                    | #IMPLIED  | Defines the left indent of text within the cell.                                                                                                           |
| rightind  | CDATA                                    | #IMPLIED  | Defines the right indent of the text within the cell.                                                                                                      |
| leftmar   | NUTOKEN                                  | #IMPLIED  | Defines the left margin of the cell.                                                                                                                       |
| rightmar  | NUTOKEN                                  | #IMPLIED  | Defines the right margin of the cell.                                                                                                                      |
| topmar    | NUTOKEN                                  | #IMPLIED  | Defines the top margin of the cell.                                                                                                                        |
| botmar    | NUTOKEN                                  | #IMPLIED  | Defines the bottom margin of the cell.                                                                                                                     |
| mindepth  | NUTOKEN                                  | #IMPLIED  | Defines the minimum depth (height) of the table.                                                                                                           |
| charoff   | NUTOKEN                                  | #IMPLIED  | Determines the distance the cell content should offset from the horizontal alignment character.                                                            |
| char      | CDATA                                    | #IMPLIED  | Defines the alignment character that can be used to align values within a column. This attribute should be used when the align attribute is set to "char". |
| delttype  | (delete   real   reserve   NA)           | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                              |
| inschlvl  | NMTOKEN                                  | #IMPLIED  | Used during the change package process to indicate the element was inserted at the change level indicated.                                                 |
| delchlvl  | NMTOKEN                                  | #IMPLIED  | Used during the change package process to indicate the element was deleted at the change level indicated.                                                  |
| status    | (empty   deleted   reserved   notapp)    | #IMPLIED  | Allows for additional processing during the change package process and is used to indicate the status of this element.                                     |
| revchg    | NUMBER                                   | 0         | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                       |

---

# thead

## Table Heading (Boxheads)

*Description:* Identifies a table heading (boxheads). The table heading (boxheads) repeat when the table breaks across a column or page.

*Source paragraph:* 4.2.7.3 (MIL-STD-38784)

*Content Model:* (colspec\*, spanspec\*, row+) -(entrytbl)

*Parents:* entrytbl, tgroup

*Entities used in this element:* chgatt, delstat, status, yesorno

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| valign    | (top   middle   bottom)               | bottom   | Defines the vertical alignment of text within a cell.                                                                         |
| deltypes  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

# title

## Title

*Description:* Identifies a title (e.g., chapter, paragraph, table, etc.). The title should be tagged exactly as it is to appear in the table of contents. Titles that are placed on tables will appear in the List of Tables, and titles that are placed on figures and figure tables will be placed in the List of Illustrations.

*Source paragraph:* 4.2.7.2, 4.2.8.2, 4.2.9.3, 4.2.9.4, 4.2.9.5.1, and 4.2.9.5.1.1 (MIL-STD-38784)

*Content Model:* ((#PCDATA | change | tabmat | fnref | xref | verbatim | emphasis | applicabil | extapplicabil | graphic | extref | dataiden | hcp | hci | esds | nsp | oci | ocp | fcp | acronym | prindex | secindex | nameloc | clink | ilink | object)+) -(figure | table | foldout | objmedia | note)

*Parents:* abbrsect, applicdef, clsection, cntentry, deflist, emergproccl, figure, normproccl, para0, performdatacl, procedure, randlist, seqlist, subpara1, subpara2, subpara3, subproc1, subproc2, subproc3, symsect, table

*Entities used in this element:* chgatt, delstat, exclus, secur, status, text, yesorno

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

# tmidno

## Technical Manual Identification Number

**Description:** Identifies the technical manual identification number. When used on the title page (<idinfo>), it will cause the technical manual number to appear on the title page and at the top of each page in the manual. When used in the list of related publications (<lrp>), it will cause the technical manual number to be placed in the Publication Number column.

**Source paragraph:** 4.2.1.5 and 4.5.9.2 (MIL-STD-38784)

**Content Model:** ((#PCDATA | [change](#) | [tabmat](#) | [ftnref](#) | [xref](#) | [verbatim](#) | [emphasis](#) | [applicabil](#) | [extapplicabil](#) | [graphic](#) | [extref](#) | [dataiden](#) | [hcp](#) | [hci](#) | [esds](#) | [nsp](#) | [oci](#) | [ocp](#) | [fcp](#) | [acronym](#) | [prindex](#) | [secindex](#) | [nameloc](#) | [clink](#) | [ilink](#) | [object](#))+) -([figure](#) | [table](#) | [foldout](#) | [objmedia](#))

**Parents:** [idinfo](#)

**Entities used in this element:** [chgtatt](#), [delstat](#), [exclus](#), [secur](#), [service](#), [status](#), [text](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                                                | Default  | Description                                                                                                                                                   |
|-----------|---------------------------------------------------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| service   | (AF   NAVAIR   NAVSEA   SPAWARS   ARMY   MC   DLA   CG   DOD   FRN) | #IMPLIED | Defines the branch of service.                                                                                                                                |
| delttype  | (delete   real   reserve   NA)                                      | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                 |
| inschlvl  | NMTOKEN                                                             | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                    |
| delchlvl  | NMTOKEN                                                             | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                     |
| status    | (empty   deleted   reserved   notapp)                               | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                        |
| revchg    | NUMBER                                                              | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                          |
| security  | (u   c   s   n)                                                     | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level. |
| caveat    | CDATA                                                               | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                              |

| Attribute | Type  | Default  | Description                                                                                                                                                    |
|-----------|-------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fgi       | CDATA | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |

# told

## Takeoff and Landing Data Card

*Description:* Defines the takeoff and data landing card used in the normal procedures checklist.

*Source paragraph:* 3.7.4 (MIL-DTL-7700)

*Content Model:* (graphic)

*Parents:* normproccl

*Entities used in this element:* chgatt, delstat, status, yesorno

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

# typedes

## Type Designation

*Description:* Identifies a type designation on the title page and on the difference data sheet.

*Source paragraph:* 4.5.1.3.4 and 4.7.3.3.1b (MIL-STD-38784)

*Content Model:* ((#PCDATA | change | tabmat | ftref | xref | verbatim | emphasis | applicabil | extapplicabil | graphic | extref | dataiden | hcp | hci | esds | nsp | oci | ocp | fcp | acronym | prindex | secindex | nameloc | clink | ilink | object)+) -(figure | table | foldout | objmedia)

*Parents:* prtitle

*Entities used in this element:* chgatt, delstat, exclus, secur, status, text, yesorno

### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

# underline

## Underline

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>                   | Allows for the underlining of certain parts of the export control notice.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <i>Source paragraph:</i>              | 4.5.1.12 (MIL-STD-38784)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <i>Content Model:</i>                 | ((#PCDATA   <a href="#">change</a>   <a href="#">tabmat</a>   <a href="#">ftnref</a>   <a href="#">xref</a>   <a href="#">verbatim</a>   <a href="#">emphasis</a>   <a href="#">applicabil</a>   <a href="#">extapplicabil</a>   <a href="#">graphic</a>   <a href="#">extref</a>   <a href="#">dataiden</a>   <a href="#">hcp</a>   <a href="#">hci</a>   <a href="#">esds</a>   <a href="#">nsp</a>   <a href="#">oci</a>   <a href="#">ocp</a>   <a href="#">fcp</a>   <a href="#">acronym</a>   <a href="#">prindex</a>   <a href="#">secindex</a>   <a href="#">nameloc</a>   <a href="#">clink</a>   <a href="#">ilink</a>   <a href="#">object</a> )+) -(figure   table   foldout   objmedia) |
| <i>Included in:</i>                   | <a href="#">expcont</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <i>Entities used in this element:</i> | <a href="#">exclus</a> , <a href="#">text</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

# verbatim

## Verbatim Text

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Description:</i>      | A verbatim element is used to format computer examples or similar text in a typewritten emulation mode. Formatting follows "asis" quadding with monospaced font.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <i>Source paragraph:</i> | None                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <i>Content Model:</i>    | (#PCDATA)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <i>Parents:</i>          | <a href="#">abbrtitle</a> , <a href="#">action</a> , <a href="#">amplification</a> , <a href="#">applicabil</a> , <a href="#">appltile</a> , <a href="#">authnot</a> , <a href="#">change</a> , <a href="#">chgdate</a> , <a href="#">chgnum</a> , <a href="#">chgtxt</a> , <a href="#">clink</a> , <a href="#">clitem</a> , <a href="#">cogact</a> , <a href="#">condition</a> , <a href="#">contractno</a> , <a href="#">copyright</a> , <a href="#">cpos</a> , <a href="#">crewpos</a> , <a href="#">crewpos1</a> , <a href="#">crewpos2</a> , <a href="#">crewpos3</a> , <a href="#">crewpos4</a> , <a href="#">crewpos5</a> , <a href="#">dataiden</a> , <a href="#">date</a> , <a href="#">def</a> , <a href="#">destr</a> , <a href="#">discl</a> , <a href="#">distrib</a> , <a href="#">doctype</a> , <a href="#">effdatenot</a> , <a href="#">emphasis</a> , <a href="#">entry</a> , <a href="#">etitle</a> , <a href="#">expcont</a> , <a href="#">extapplicabil</a> , <a href="#">fnote</a> , <a href="#">hazmat</a> , <a href="#">ilink</a> , <a href="#">internatlst</a> , <a href="#">item</a> , <a href="#">label</a> , <a href="#">lepchg</a> , <a href="#">leppage</a> , <a href="#">line</a> , <a href="#">maintlvl</a> , <a href="#">mfr</a> , <a href="#">modelno</a> , <a href="#">moveddata</a> , <a href="#">newpos1</a> , <a href="#">newpos2</a> , <a href="#">newpos3</a> , <a href="#">newpos4</a> , <a href="#">newpos5</a> , <a href="#">nmlist</a> , <a href="#">nomen</a> , <a href="#">nsn</a> , <a href="#">oadr</a> , <a href="#">pageno</a> , <a href="#">para</a> , <a href="#">param</a> , <a href="#">parano</a> , <a href="#">paras</a> , <a href="#">paratitle</a> , <a href="#">partno</a> , <a href="#">pgnumber</a> , <a href="#">phrase</a> , <a href="#">pretmidno</a> , <a href="#">pubdate</a> , <a href="#">revnum</a> , <a href="#">sectocstr</a> , <a href="#">seqno</a> , <a href="#">serno</a> , <a href="#">subject</a> , <a href="#">subparano</a> , <a href="#">subtitle</a> , <a href="#">supersed</a> , <a href="#">suppl</a> , <a href="#">symb</a> , <a href="#">symtitle</a> , <a href="#">term</a> , <a href="#">tfnid</a> , <a href="#">title</a> , <a href="#">tmidno</a> , <a href="#">typedes</a> , <a href="#">underline</a> |

Entities used in this element: [chgatt](#), [delstat](#), [secur](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                                                    |
|-----------|---------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| allowbrk  | NUMBER                                | 1        | Setting this attribute equal to "1" allows breaks to be inserted into verbatim text.                                                                           |
| security  | (u   c   s   n)                       | n        | Identifies the security level of the element. Set this attribute to "u" for UNCLASSIFIED, "c" for CONFIDENTIAL, "s" for SECRET, or "n" for no security level.  |
| caveat    | CDATA                                 | #IMPLIED | Provides a place to set the caveat for the document. This attribute should be ignored unless on the doc element.                                               |
| fgi       | CDATA                                 | #IMPLIED | Foreign Government Identification (FGI). Provides a place for inline FGI portion marking. This is typically only used in Foreign Military Sales (FMS) manuals. |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                  |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                                                     |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                                                      |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.                                         |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                           |

---

# verstat

## Verification Status Page

*Description:* Identifies the verification status page in the manual. This information is automatically generated by the FOSI. This element should not be used if a verification status page is not desired.

*Source paragraph:* 4.5.4 (MIL-STD-38784)

*Content Model:* ([tabmat?](#))

*Parents:* [front](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                                   |
|-----------|---------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| autobuild | NUMBER                                | 1        | Set this attribute equal to "1" when the output of this element should be auto-generated.                                     |
| agency    | CDATA                                 | #IMPLIED | Identifies the technical order management agency.                                                                             |
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.                    |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.                     |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element.        |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                          |

---

## W

### Warning

*Description:* Allows for a boxed 'W' as a symbol in the addcond.

*Source paragraph:* 3.2.1(MIL-DTL-7700)

*Content Model:* EMPTY

*Parents:* [symsb](#), [symsb1](#)

*Included in:* [docfmcl](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                                  | Default  | Description                                                                                                |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA)        | #IMPLIED | Used to generate change packages - Delete Type                                                             |
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated. |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during change package process to indicate the element was deleted at the change level indicated       |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Used during the change package process to indicate the current status of the element.                      |
| revchg    | NUMBER                                | 0        | Toggle between a revision or a change. Attribute is set to 1 to indicate a revision.                       |

---

## warning

### Warning

*Description:* Identifies a WARNING in the manual. Multiple warning tags may be used only when it is desired to change the warning icon (standard or hazardous warning graphic).

*Source paragraph:* 4.3.10 (MIL-STD-38784)

*Content Model:* ([icon?](#), [para\\*](#)) -([randlist](#) | [deflist](#) | [seqlist](#) | [figure](#) | [table](#) | [foldout](#) | [objmedia](#) | [warning](#) | [caution](#))

*Parents:* [abbrsect](#), [applicdef](#), [cmbr1](#), [cmbr2](#), [cmbr3](#), [cmbr4](#), [cmbr5](#), [entry](#), [ifthen](#), [para0](#), [procstep](#), [procstep2](#), [procstep3](#), [procstep4](#), [step1](#), [step2](#), [step3](#), [step4](#), [subpara1](#), [subpara2](#), [subpara3](#), [symsect](#)

*Included in:* [addcond](#), [performdatacl](#), [procedure](#)

*Excluded in:* [caution](#), [note](#), [warning](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [exclus](#), [list](#), [status](#), [yesorno](#)

#### ATTRIBUTE LIST

| Attribute | Type                           | Default  | Description                                                                                                                   |
|-----------|--------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| delttype  | (delete   real   reserve   NA) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the deletion type of this element. |



| Attribute | Type                                  | Default  | Description                                                                                                            |
|-----------|---------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------|
| inschlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was inserted at the change level indicated.             |
| delchlvl  | NMTOKEN                               | #IMPLIED | Used during the change package process to indicate the element was deleted at the change level indicated.              |
| status    | (empty   deleted   reserved   notapp) | #IMPLIED | Allows for additional processing during the change package process and is used to indicate the status of this element. |
| revchg    | NUMBER                                | 0        | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                   |

# xref

## Cross-reference

*Description:* Identifies a cross-reference to a paragraph, figure, table, etc.

*Source paragraph:* 4.3.1 (MIL-STD-38784)

*Content Model:* EMPTY

*Parents:* [abbrtitle](#), [action](#), [amplification](#), [applicabil](#), [appltile](#), [authnot](#), [bindByCoords](#), [bindByd](#), [bindByName](#), [change](#), [chgdate](#), [chgnum](#), [chgtxt](#), [clink](#), [clitem](#), [cogact](#), [condition](#), [contractno](#), [copyright](#), [cpos](#), [crewpos](#), [crewpos1](#), [crewpos2](#), [crewpos3](#), [crewpos4](#), [crewpos5](#), [dataiden](#), [date](#), [def](#), [destr](#), [discl](#), [distrib](#), [doctype](#), [effdatenot](#), [emphasis](#), [entry](#), [etitle](#), [expcont](#), [extapplicabil](#), [fnote](#), [hazmat](#), [ilink](#), [internatlstd](#), [item](#), [label](#), [lepchg](#), [leppage](#), [line](#), [maintlvl](#), [mfr](#), [modelno](#), [moveddata](#), [newpos1](#), [newpos2](#), [newpos3](#), [newpos4](#), [newpos5](#), [nmlist](#), [nomen](#), [nsn](#), [oadr](#), [pageno](#), [para](#), [param](#), [parano](#), [paras](#), [paratitle](#), [partno](#), [pgnumber](#), [phrase](#), [pretmidno](#), [pubdate](#), [revnum](#), [sectocstr](#), [seqno](#), [serno](#), [subject](#), [subparano](#), [subtitle](#), [supersd](#), [suppl](#), [symb](#), [symtitle](#), [term](#), [tfnid](#), [title](#), [tmidno](#), [typedes](#), [underline](#)

*Entities used in this element:* [chgatt](#), [delstat](#), [status](#), [yesorno](#)

## ATTRIBUTE LIST

| Attribute    | Type                                  | Default                 | Description                                                                                                                                                                                                                                                |
|--------------|---------------------------------------|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| xrefid       | IDREF                                 | #IMPLIED                | Defines the ID of the element that you are referencing. The value of this attribute should match the value of an ID attribute elsewhere in the manual.                                                                                                     |
| displayvalue | CDATA                                 | #IMPLIED                | Allows the author to add additional, unique information for purposes of referencing an external document. This attribute should be used for providing paragraph titles, system numbers, task numbers and for author-generated TO numbers where applicable. |
| HyTime       | NAME                                  | #FIXED "clink"          | Used in combination with HyTime to establish a contextual link.                                                                                                                                                                                            |
| HyNames      | NAMES                                 | #FIXED "linkend xrefid" | Used in combination with HyTime to establish a contextual link.                                                                                                                                                                                            |
| delttype     | (delete   real   reserve   NA)        | #IMPLIED                | Allows for additional processing during the change package process and is used to indicate the deletion type of this element.                                                                                                                              |
| inschlvl     | NMTOKEN                               | #IMPLIED                | Used during the change package process to indicate the element was inserted at the change level indicated.                                                                                                                                                 |
| delchlvl     | NMTOKEN                               | #IMPLIED                | Used during the change package process to indicate the element was deleted at the change level indicated.                                                                                                                                                  |
| status       | (empty   deleted   reserved   notapp) | #IMPLIED                | Allows for additional processing during the change package process and is used to indicate the status of this element.                                                                                                                                     |
| revchg       | NUMBER                                | 0                       | Used to mark changes in a revision. Setting this attribute equal to "1" indicates a revision change.                                                                                                                                                       |

