
# RAJALAKSHMI ENGINEERING COLLEGE RAJALAKSHMI NAGAR, THANDALAM – 602 105



# CS23331 DESIGN AND ANALYSIS OF ALGORITHM LAB

# **Laboratory Observation Note Book**

Name : DEJASWINJ BG.
Year / Branch / Section : 2 <sup>nd</sup> Year / AIML / A
Register No. : 231501032
Semester : 3 <sup>rd</sup> Şemeşter
Academic Year : 2024-2025



1) Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

**Input Format:** 

**First Line - Number of elements** 

n Lines - n Elements

**Output Format:** 

**Element x - That is repeated** 

#### For example:

Input	Result
5	1
11234	

#### CODE:

```
#include<stdio.h>
int main()
{
   int n,i,j;
   scanf("%d",&n);
   int a[n];
   for(i=0;i<n;i++)
      scanf("%d",&a[i]);</pre>
```

```
for(i=0;i<n;i++)
{
    for(j=i+1;j<n;j++)
    {
        if(a[i]==a[j])
        printf("%d",a[i]);
    }
}</pre>
```

# OUTPUT:

10 9 7 6 5 1 2 3 8 4 7 5 1 2 3 4 4	7 •
1 2 3 4 4	4
F 1 1	
5 1 1 2 3 4 1 1 1	1 🗸
ssed all tests! 🗸	

2) Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

#### **Input Format**

- The first line contains T, the number of test cases. Following T lines contain:
- 1. Line 1 contains N1, followed by N1 integers of the first array
- 2. Line 2 contains N2, followed by N2 integers of the second array

#### **Output Format**

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

**Output:** 

10 57

Input:

1

6123456

216

**Output:** 

16

# For example:

Input	Result
1	10 57
3 10 17 57	
6	
2 7 10 15 57 246	

## CODE:

```
#include <stdio.h>
int main() {
  int t, n1, n2, i, j;
  scanf("%d", &t);
  while (t--) {
    scanf("%d", &n1);
    int a[n1];
  for (i = 0; i < n1; i++)
      scanf("%d", &a[i]);
  scanf("%d", &n2);
  int b[n2];
  for (j = 0; j < n2; j++) {</pre>
```

```
scanf("%d", &b[j]);
    }
    i=0;
    j=0;
    while(i<n1 &&j<n2)
    {
      if(a[i]==b[j])
      {
         printf("%d ",a[i]);
         i++;
        j++;
      }
      else if(a[i]<b[j])
         i++;
      else
         j++;
    }}
OUTPUT:
```

	Input	Expected	Got		
~	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	*	
~	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	*	
Passed all tests! ✓					
-	for this submission: 1.00	0/1.00.			

3) Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

## **Input Format:**

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

**Output Format:** 

1 - If pair exists

0 - If no pair exists

**Explanation for the given Sample Testcase:** 

YES as 5 - 1 = 4

So Return 1.

#### For example:

Input	Result
3	1
135	
4	

# CODE:

```
#include <stdio.h>
int main() {
  int n, k, i, j;
  scanf("%d", &n);
  int a[n];
  for(i = 0; i < n; i++)
  {
    scanf("%d", &a[i]);
  scanf("%d", &k);
  for(i = 0; i < n; i++) {
    for(j = i + 1; j < n; j++)
       if(a[j] - a[i] == k)
       {
          printf("1\n");
          return 0;
       }
  printf("0\n");
```

# **OUTPUT:**

	Input	Expected	Got	
~	3 1 3 5 4	1	1	<b>~</b>
*	10 1 4 6 8 12 14 15 20 21 25 1	1	1	<b>~</b>
~	10 1 2 3 5 11 14 16 24 28 29 0	0	0	<b>~</b>
~	10 0 2 3 7 13 14 15 20 24 25 10	1	1	<b>~</b>

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.