



## Bit Soccer

Time limit: 500 ms

Memory limit: 256 MB

Peredo is a computer scientist who loves soccer. His favorite soccer player is Paolo Guerrero, one of the best Peruvian players, and his favorite team is the Brazilian national team.

He has a very large database of players with videos, photos, and many statistics related to their performance in hundreds of games. He uses his database to compute a binary **performance index** that tracks the players' abilities across 40 possible game metrics.

The **performance index** represents all possible soccer abilities of each player with a 0 for a lack of ability in a given game metric and a 1 for perfect ability, with no fractions in between 0 and 1.

Based on these numbers, Peredo created a simulation game that takes the **performance indices** and combines multiple players to form a **team performance index**.

The **team performance index** is such that if a single player has a 1 in a given metric then the **team performance index** also has a 1 in that metric.

You are given a list of players in your **roster** represented by their **performance indices** in decimal format and your task is to combine a subset from your **roster** to form your **starting team** and to obtain a specific **team performance index**. There is no limit to the number of players that can form the **starting team**.

As an example, simplifying with just 4 game metrics, if we have two players on our **starting team** with **performance indices** 5 (0101) and 3 (0011) the resulting **team performance index** will be 7 (0111).

## Standard input

The first line of the input contains an integer  $N$  denoting the number of player available in your **roster**. The second line contains  $N$  integers  $P_i$ , denoting the **performance indices** of each player. The third line contains an integer  $Q$ , denoting the number of queries, and each of the next  $Q$  lines contains an integer  $G$  that represents the goal **team performance index**.

## Standard output

For each query, print **YES** if it is possible to select a **starting team** from the **roster** and obtain the **team performance index**  $G$ , otherwise print **NO**.

## Constraints and notes

- $1 \leq N \leq 10^5$
- $1 \leq Q \leq 20$
- $1 \leq P_i, G \leq 2^{40} - 1$

Input	Output	Explanation
5 10 3 5 8 6 2 7 4	YES NO	<p>In the first query, we can obtain 7 by selecting the players with <b>performance indices</b> 3 and 6.</p> <p>There is no way to obtain a <b>team performance index</b> of 4.</p>