# tbl_appointment

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| char_appointstatus | char(20) | No | | | | |
| int_userID | int(10) | No | | tbl_user -> int_userID | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| int_userID | BTREE | No | No | int_userID | 0 | A | No | |

# tbl_baptism

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_eventinfoID | int(10) | No | | tbl_eventinfo -> int_eventinfoID | | |
| var_parentmarriageadd | varchar(100) | No | | | | |
| var_fatherbplace | varchar(100) | No | | | | |
| var_motherbplace | varchar(100) | No | | | | |
| var_fathername | varchar(100) | No | | | | |
| var_mothername | varchar(100) | No | | | | |
| var_contactnum | varchar(13) | No | | | | |
| date_desireddate | date | No | | | | |
| time_desiredtime | time | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| int_eventinfoID | BTREE | Yes | No | int_eventinfoID | 7 | A | No | |

# tbl_blessing

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_eventinfoID | int(11) | No | | tbl_eventinfo -> int_eventinfoID | | |
| var_blessingaddress | varchar(100) | No | | | | |
| var_blessingdetails | varchar(100) | No | | | | |
| date_desireddate | date | No | | | | |
| time_desiredtime | time | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| int_eventinfoID | BTREE | Yes | No | int_eventinfoID | 0 | A | No | |

# tbl_defaulttime

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_defaulttimeID *(Primary)* | int(11) | No | | | | |
| time_defaulttime | time | No | | | | |
| int_eventID | int(11) | No | | tbl_services -> int_eventID | | |

### Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_defaulttimeID | 2 | A | No | |
| tbl_ibfk_1_idx | BTREE | No | No | int_eventID | 2 | A | No | |

## tbl_document

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_documentID *(Primary)* | int(11) | No | | | | |
| var_documenttype | varchar(50) | No | | | | |
| var_doctemplatepath | varchar(45) | No | | | | |
| dbl_docuprice | double | No | | | | |

### Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_documentID | 3 | A | No | |

## tbl_documentrequest

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_requestID *(Primary)* | int(11) | No | | | | |
| int_userID | int(11) | No | | tbl_user -> int_userID | | |
| int_documentID | int(11) | No | | tbl_document -> int_documentID | | |
| var_doclastname | varchar(50) | No | | | | |
| var_docfirstname | varchar(50) | No | | | | |
| text_purpose | text | No | | | | |
| date_docurequested | date | No | | | | |
| date_docureleased | date | Yes | *NULL* | | | |
| date_docureceived | int(11) | Yes | *NULL* | | | |
| char_docustatus | varchar(20) | No | | | | |
| date_doceventdate | date | No | | | | |
| int_paymentID | int(11) | Yes | *NULL* | tbl_payment -> int_paymentID | | |

### Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_requestID | 4 | A | No | |
| int_documentID | BTREE | No | No | int_documentID | 2 | A | No | |
| int_userID | BTREE | No | No | int_userID | 2 | A | No | |

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| tbl_documentrequest_ibfk_4_idx | BTREE | No | No | int_paymentID | 4 | A | Yes | |

## tbl_documentsevents

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_docu_eventID *(Primary)* | int(11) | No | | | | |
| int_eventID | int(11) | No | | tbl_services -> int_eventID | | |
| int_documentID | int(11) | No | | tbl_document -> int_documentID | | |

### Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_docu_eventID | 2 | A | No | |
| tbl_id_event_idx | BTREE | No | No | int_eventID | 2 | A | No | |
| tbl_id_docu_idx | BTREE | No | No | int_documentID | 2 | A | No | |

## tbl_docureqtype

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_docureqtypeID *(Primary)* | int(11) | No | | | | |
| var_reqname | varchar(45) | No | | | | |
| var_reqdesc | varchar(100) | No | | | | |

### Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_docureqtypeID | 0 | A | No | |

## tbl_eventapplication

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_eventapplicationID *(Primary)* | int(10) | No | | | | |
| int_eventinfoID | int(10) | No | | tbl_eventinfo -> int_eventinfoID | | |
| char_approvalstatus | char(20) | No | | | | |
| var_remarks | varchar(20) | Yes | *NULL* | | | |
| int_paymentID | int(11) | Yes | *NULL* | tbl_payment -> int_paymentID | | |

### Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_eventapplicationID | 10 | A | No | |
| int_eventinfoID | BTREE | No | No | int_eventinfoID | 10 | A | No | |
| tbl_eventapplication_ibfk_1_idx | BTREE | No | No | int_paymentID | 10 | A | Yes | |

## tbl_eventinfo

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_eventinfoID *(Primary)* | int(10) | No | | | | |
| int_userID | int(10) | No | | tbl_user -> int_userID | | |
| int_eventID | int(10) | No | | tbl_services -> int_eventID | | |
| date_approveddate | date | Yes | *NULL* | | | |
| time_approvedstart | time | Yes | *NULL* | | | |
| time_approvedend | time | Yes | *NULL* | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_eventinfoID | 10 | A | No | |
| int_userID | BTREE | No | No | int_userID | 2 | A | No | |
| tbl_eventinfo_ibfk_2_idx | BTREE | No | No | int_eventID | 5 | A | No | |

# tbl_grd3students

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_studentID *(Primary)* | int(10) | No | | | | |
| int_relationID | int(10) | No | | tbl_relation -> int_relationID | | |
| var_school | varchar(100) | No | | | | |
| var_batch | varchar(20) | No | | | | |
| var_section | varchar(20) | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_studentID | 0 | A | No | |
| int_relationID | BTREE | No | No | int_relationID | 0 | A | No | |

# tbl_houseblessing

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_eventinfoID | int(11) | No | | tbl_eventinfo -> int_eventinfoID | | |
| var_owner | varchar(100) | No | | | | |
| var_estloc | varchar(100) | No | | | | |
| var_ownercontactnum | varchar(13) | No | | | | |
| var_owneremailadd | varchar(50) | No | | | | |
| date_desireddate | date | No | | | | |
| time_desiredtime | time | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| int_eventinfoID | BTREE | Yes | No | int_eventinfoID | 0 | A | No | |

# tbl_members

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_membersID *(Primary)* | int(11) | No | | | | |
| int_userID | int(11) | No | | tbl_user -> int_userID | | |
| int_ministryID | int(11) | No | | tbl_ministry -> int_ministryID | | |
| var_position | varchar(45) | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_membersID | 0 | A | No | |
| tbl_ibfk_1_idx | BTREE | No | No | int_userID | 0 | A | No | |
| tbl_ibfk_w_idx | BTREE | No | No | int_ministryID | 0 | A | No | |

# tbl_message

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_messageID *(Primary)* | int(10) | No | | | | |
| int_senderID | int(10) | No | | tbl_user -> int_userID | | |
| int_receiverID | int(10) | No | | tbl_user -> int_userID | | |
| text_message | text | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_messageID | 0 | A | No | |
| int_senderID | BTREE | No | No | int_senderID | 0 | A | No | |
| int_receiverID | BTREE | No | No | int_receiverID | 0 | A | No | |

# tbl_ministry

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_ministryID *(Primary)* | int(11) | No | | | | |
| var_ministryname | varchar(45) | No | | | | |
| var_ministrydesc | varchar(45) | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_ministryID | 5 | A | No | |

# tbl_notification

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_notifID *(Primary)* | int(10) | No | | | | |

| int_userID | int(10) | No | | tbl_user -> int_userID | | |
| var_notifdesc | varchar(55) | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_notifID | 2 | A | No | |
| int_userID | BTREE | No | No | int_userID | 2 | A | No | |

# tbl_payment

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_paymentID *(Primary)* | int(10) | No | | | | |
| dbl_amount | double | No | | | | |
| char_paymentstatus | char(10) | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_paymentID | 50 | A | No | |

# tbl_relation

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_relationID *(Primary)* | int(10) | No | | | | |
| int_eventinfoID | int(10) | No | | tbl_eventinfo -> int_eventinfoID | | |
| var_relation | varchar(20) | Yes | *NULL* | | | |
| var_lname | varchar(50) | No | | | | |
| var_fname | varchar(50) | No | | | | |
| var_mname | varchar(50) | Yes | *NULL* | | | |
| char_gender | varchar(10) | No | | | | |
| var_address | varchar(100) | No | | | | |
| date_birthday | date | No | | | | |
| var_birthplace | varchar(100) | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_relationID | 10 | A | No | |
| int_eventinfoID | BTREE | No | No | int_eventinfoID | 10 | A | No | |

# tbl_requirements

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_requirementID *(Primary)* | int(10) | No | | | | |
| var_reqpath | varchar(300) | Yes | *NULL* | | | |

| var_reqloc | varchar(100) | Yes | NULL | | | |
|---|---|---|---|---|---|---|
| date_reqreceived | date | No | | | | |
| int_reqtypeID | int(11) | No | | tbl_requirementtype -> int_reqtypeID | | |
| var_reqstatus | varchar(45) | No | | | | |

### Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_requirementID | 10 | A | No | |
| int_reqtypeID | BTREE | No | No | int_reqtypeID | 5 | A | No | |

## tbl_requirementsdocument

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_requirementdocumentID *(Primary)* | int(11) | No | | | | |
| var_reqpath | varchar(45) | No | | | | |
| date_reqreceived | date | No | | | | |
| bool_reqstatus | char(10) | No | | | | |
| int_requestID | int(11) | No | | tbl_documentrequest -> int_requestID | | |
| int_docureqtypeID | int(11) | Yes | NULL | tbl_docureqtype -> int_docureqtypeID | | |

### Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_requirementdocumentID | 4 | A | No | |
| tbl_fk_2_idx | BTREE | No | No | int_requestID | 4 | A | No | |
| tbl_fk_3_idx | BTREE | No | No | int_docureqtypeID | 2 | A | Yes | |

## tbl_requirementsinevents

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_requirementsineventsID *(Primary)* | int(11) | No | | | | |
| int_requirementID | int(11) | No | | | | |
| int_eventinfoID | int(11) | No | | tbl_eventinfo -> int_eventinfoID | | |

### Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_requirementsineventsID | 6 | A | No | |
| tbl_event_idx | BTREE | No | No | int_eventinfoID | 6 | A | No | |

## tbl_requirementtype

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|

| int_reqtypeID *(Primary)* | int(11) | No | | | | |
|---|---|---|---|---|---|---|
| int_eventID | int(11) | No | | tbl_services -> int_eventID | | |
| var_reqname | varchar(100) | No | | | | |
| var_reqdesc | varchar(100) | No | | | | |
| char_reqmode | char(25) | No | | | | |
| char_reqtype | varchar(25) | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_reqtypeID | 35 | A | No | |
| int_eventID | BTREE | No | No | int_eventID | 35 | A | No | |

# tbl_schedule

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_scheduleID *(Primary)* | int(10) | No | | | | |
| int_userID | int(10) | No | | tbl_user -> int_userID | | |
| int_eventinfoID | int(10) | No | | tbl_eventinfo -> int_eventinfoID | | |
| text_schedulenote | text | No | | | | |
| var_venue | varchar(100) | No | | | | |
| time_schedstart | time | No | | | | |
| time_schedend | time | No | | | | |
| date_schedule | date | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_scheduleID | 0 | A | No | |
| int_userID | BTREE | No | No | int_userID | 0 | A | No | |
| int_eventID | BTREE | No | No | int_eventinfoID | 0 | A | No | |

# tbl_services

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_eventID *(Primary)* | int(10) | No | | | | |
| var_eventname | varchar(50) | No | | | | |
| var_eventdesc | text | No | | | | |
| char_type | char(15) | No | | | | |
| char_status | varchar(45) | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_eventID | 12 | A | No | |

# tbl_serviceutilities

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_serviceutilitiesID *(Primary)* | int(11) | No | | | | |
| var_servicename | varchar(45) | No | | | | |
| char_status | char(10) | No | | | | |
| var_servicedesc | text | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_serviceutilitiesID | 0 | A | No | |

# tbl_specialevent

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_specialeventID *(Primary)* | int(11) | No | | | | |
| int_userID | int(11) | No | | tbl_user -> int_userID | | |
| var_spceventname | varchar(50) | No | | | | |
| text_eventdesc | text | No | | | | |
| time_eventstart | timestamp | No | 0000-00-00 00:00:00 | | | |
| time_eventend | timestamp | No | 0000-00-00 00:00:00 | | | |
| var_eventvenue | varchar(200) | No | | | | |
| char_eventtype | char(25) | No | | | | |
| var_approvalstatus | varchar(25) | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_specialeventID | 0 | A | No | |
| int_userID | BTREE | No | No | int_userID | 0 | A | No | |

# tbl_sponsors

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_sponsorID *(Primary)* | int(10) | No | | | | |
| int_eventinfoID | int(10) | No | | tbl_eventinfo -> int_eventinfoID | | |
| var_sponsorname | varchar(50) | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_sponsorID | 14 | A | No | |
| int_eventinfoID | BTREE | No | No | int_eventinfoID | 14 | A | No | |

# tbl_user

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_userID *(Primary)* | int(10) | No | | | | |
| var_userlname | varchar(55) | No | | | | |
| var_userfname | varchar(55) | No | | | | |
| var_usermname | varchar(55) | No | | | | |
| char_usergender | char(10) | No | | | | |
| var_useraddress | varchar(100) | No | | | | |
| var_usercontactnum | varchar(13) | No | | | | |
| var_username | varchar(55) | No | | | | |
| var_useremail | varchar(55) | No | | | | |
| var_password | varchar(80) | No | | | | |
| char_usertype | char(20) | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_userID | 10 | A | No | |

# tbl_utilities

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_utilitiesID *(Primary)* | int(11) | No | | | | |
| int_eventID | int(11) | No | | | | |
| int_reservationmindays | int(11) | No | | | | |
| int_reservationmaxdays | int(11) | No | | | | |
| int_downpaymentdays | int(11) | Yes | *NULL* | | | |
| int_fullpaymentdays | int(11) | Yes | *NULL* | | | |
| int_requirementsdays | int(11) | No | | | | |
| bool_refundable | tinyint(1) | Yes | *NULL* | | | |
| int_refundpercentdays | int(11) | Yes | *NULL* | | | |
| double_refundpercent | double | Yes | *NULL* | | | |
| int_agemin | int(11) | Yes | *NULL* | | | |
| int_agemax | int(11) | Yes | *NULL* | | | |
| double_fee | double | Yes | *NULL* | | | |
| time_duration | time | No | | | | |
| double_addrate | double | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_utilitiesID | 11 | A | No | |
| tbl_ibfk1_idx | BTREE | No | No | int_eventID | 11 | A | No | |

# tbl_utilities_availabletime

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_utilitiesavailabletimeID *(Primary)* | int(11) | No | | | | |
| time_availabletime | time | No | | | | |
| int_serviceID | int(11) | No | | tbl_services -> int_eventID | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_utilitiesavailabletimeID | 4 | A | No | |
| tbl_ibfk_service_idx | BTREE | No | No | int_serviceID | 4 | A | No | |

# tbl_voucher

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_voucherID *(Primary)* | int(11) | No | | | | |
| int_notifID | int(11) | No | | tbl_notification -> int_notifID | | |
| int_requestID | int(11) | No | | tbl_documentrequest -> int_requestID | | |
| date_issued | date | No | | | | |
| date_due | date | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_voucherID | 2 | A | No | |
| int_notifID_idx | BTREE | No | No | int_notifID | 2 | A | No | |
| int_requestID_idx | BTREE | No | No | int_requestID | 2 | A | No | |

# tbl_wedbride

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_eventinfoID | int(10) | No | | tbl_eventinfo -> int_eventinfoID | | |
| var_blname | varchar(30) | No | | | | |
| var_bfname | varchar(30) | No | | | | |
| var_bmname | varchar(30) | Yes | *NULL* | | | |
| char_bgender | char(10) | No | | | | |
| var_baddress | varchar(100) | No | | | | |
| date_bbirthday | date | No | | | | |
| var_bbirthplace | varchar(100) | No | | | | |
| var_bnationality | varchar(20) | No | | | | |
| var_bcivilstatus | varchar(50) | No | | | | |
| var_breligion | varchar(20) | No | | | | |
| var_boccupation | varchar(50) | No | | | | |
| bool_bpregnant | tinyint(1) | No | | | | |
| var_bfathername | varchar(100) | No | | | | |
| var_bfatherbplace | varchar(100) | No | | | | |

| var_bfatherreligion | varchar(20) | No | | | | |
| var_bmothername | varchar(100) | No | | | | |
| var_bmotherbplace | varchar(100) | No | | | | |
| var_bmotherreligion | varchar(20) | No | | | | |
| var_bcurrparish | varchar(100) | No | | | | |
| bool_bbaptized | tinyint(1) | No | | | | |
| date_bbapdate | date | Yes | *NULL* | | | |
| var_bbapplace | varchar(100) | Yes | *NULL* | | | |
| bool_bconfirmed | tinyint(1) | No | | | | |
| date_bcondate | date | Yes | *NULL* | | | |
| var_bconplace | varchar(100) | Yes | *NULL* | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| int_eventinfoID | BTREE | Yes | No | int_eventinfoID | 0 | A | No | |

# tbl_wedcouple

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_eventinfoID | int(20) | No | | tbl_eventinfo -> int_eventinfoID | | |
| bool_livingin | tinyint(1) | No | | | | |
| bool_married | tinyint(1) | No | | | | |
| date_cprevweddate | date | Yes | *NULL* | | | |
| var_cprevwedplace | varchar(100) | Yes | *NULL* | | | |
| date_desireddate | date | No | | | | |
| time_desiredtime | time | No | | | | |
| char_weddingtype | char(15) | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| int_eventinfoID | BTREE | Yes | No | int_eventinfoID | 0 | A | No | |

# tbl_weddingcases

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_weddingcaseID *(Primary)* | int(11) | No | | | | |
| var_casename | varchar(45) | No | | | | |
| var_casedesc | varchar(100) | No | | | | |
| var_caseprocess | varchar(100) | No | | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_weddingcaseID | 0 | A | No | |

# tbl_wedgroom

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_eventinfoID | int(10) | No | | tbl_eventinfo -> int_eventinfoID | | |
| var_gnationality | varchar(20) | No | | | | |
| var_gcivilstatus | varchar(50) | No | | | | |
| var_greligion | varchar(20) | No | | | | |
| var_goccupation | varchar(50) | No | | | | |
| var_gfathername | varchar(100) | No | | | | |
| var_gfatherreligion | varchar(20) | No | | | | |
| var_gfatherbplace | varchar(100) | No | | | | |
| var_gmothername | varchar(100) | No | | | | |
| var_gmotherreligion | varchar(20) | No | | | | |
| var_gmotherbplace | varchar(100) | No | | | | |
| var_gcurrparish | varchar(100) | No | | | | |
| bool_gbaptized | tinyint(1) | No | | | | |
| date_gbapdate | date | Yes | *NULL* | | | |
| var_gbapplace | varchar(100) | Yes | *NULL* | | | |
| bool_gconfirmed | tinyint(1) | No | | | | |
| date_gcondate | date | Yes | *NULL* | | | |
| var_gconplace | varchar(100) | Yes | *NULL* | | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| int_eventinfoID_2 | BTREE | Yes | No | int_eventinfoID | 0 | A | No | |
| int_eventinfoID | BTREE | No | No | int_eventinfoID | 0 | A | No | |

# tbl_wedsteps

| Column | Type | Null | Default | Links to | Comments | MIME |
|---|---|---|---|---|---|---|
| int_weddingsteps *(Primary)* | int(11) | No | | | | |
| var_weddingstepname | varchar(45) | No | | | | |
| int_wedcaseID | int(11) | No | | tbl_weddingcases -> int_weddingcaseID | | |

## Indexes

| Keyname | Type | Unique | Packed | Column | Cardinality | Collation | Null | Comment |
|---|---|---|---|---|---|---|---|---|
| PRIMARY | BTREE | Yes | No | int_weddingsteps | 0 | A | No | |
| tbl_D_idx | BTREE | No | No | int_wedcaseID | 0 | A | No | |