

jQuery Quiz II

December 2016

1. Which, if any, of the following 3 code fragments are equivalent? Explain why they are different, if they are. Explain why they can have different parameters and be equivalent, if they are equivalent.

```
//code fragment 1
$("li").each(function(idx, e) {
    $(e).css("color", "yellow"); });
```

```
//code fragment 2
$("li").each(function() {
    $(this).css("color", "yellow"); });
```

```
//code fragment 3
$("li").each(function(idx) {
    $(this).css("color", "yellow"); });
```

Answer : all code same. Index or element are optional. We can use this instead.

2. Write a jQuery expression to find all *divs* on a page that include an unordered list in them, and make their text color be blue.

```
<div>no ul here </div>
<div>
  This does contain a ul.
  <ul>
    <li>the first item</li>
    <li>the second item</li>
  </ul>
</div>
<script>

    $(document).ready(function() {
        $("div").has("ul").css("background-color", "blue");
    });

</script>
</body>
```

3. Write jQuery code to append the following *div* element (and all of its contents) dynamically to the *body* element.

```
<div><h1>jQuery Core</h1></div>
```

HTML:

```
<!DOCTYPE html>
<html>
<head>
  <meta charset="utf-8">
  <title>JS Bin</title>
</head>
<body>

</body>
</html>
```

```
<script>
$(document).ready(function() {
  $( "body" ).append( "<div><h1>jQuery Core</h1></div>"
);
});
</script>
```