

Name: P. Delhi Ganesht

Reg No: 1925211211

Course: Ethical

Hacking

Date: 18.08.2026

14 OSINT - Reconnaissance: using the Harvester against tesla.com.

METHODOLOGY:

The Harvester - d tesla.com - b all - 1500 - F tella - all, HTML.

The Harvester - d tesla.com - b catch

The Harvester - d tesla.com - b bing

The Harvester - d tesla.com - b limit in

The Harvester - d tesla.com - b shodan

Sample - output

The Harvester H.H.H

[*] Target: tesla.com

[*] Searching catch...

[*] searching bing...

[*] searching linkedin...

[*] searching shodan...

press@tesla.com
media@tesla.com
career@tesla.com

[*] hosts.txt: 8

shop.tesla.com: 32.238 X

ir.tesla.com: 104.16.85 X

digital.sks.tesla.com: 151.101.2 X

api.tesla.com: 101.16.85 X

[x] linked in people found: 6

Recruiter - talent Acquisition

like Reliability Engineer

Security Engineer

24 Niko - web scan on test.php.vuln.web.com.

steps:

1. Run Niko against the target web

search.

2. Review flagged files methods, and

headers.

Input: curl -H "Host: 11-test.php.vulnweb.com"

Output:

+ Server: nginx/1.19.0

+ /: Returned x-powered-by header:

PHP/5.6.40

+ /login.php: admin login page location found.

+ /css/ Entries: CSS entries files is aside.

Revealing directory listings:

+ /admin/: This might be interesting

+ Options: Allowed HTTP methods: GET, HEAD, POST, OPTIONS, TRACE

+ TRACE: Server allows TRACE, indicating XST is possible.

+ image/: Directory including found.

+ 7530 request: 8 items {0} reported.

2. Pig - Dns Enumeration On 3 one hanster.com

Steps:-

1. Query standard Dns records
2. Identify authoritative name servers
3. Attempt a zone transfer (AXFR)

Input :-

```
dig zone hanster.me A
dig zone hanster.me MX
dig zone hanster.me NS
dig zone hanster.me +short
dig zone hanster.me @ns2.mt.digi.ninja
```

Output :

```
2 onehanster.me. 7200 IN A 5.196.105.14
2 onehanster.me. 300 IN MX 0 ASPMX.L.GOOGLE
2 onehanster.me. 300 IN NS ns2.mt.digi.ninja
2 onehanster.me. 300 IN NS ns2.mt.digi.ninja.
```

44 Enum4 linux - SMB Enumeration on 192.168.1.100

Steps :-

1. Run Enum4 linux in full mode against the target.
2. Check for null session, user, shares, password policy.

3.

Input :

Enum4 linux - o 192.168.1.100

Output :

Users :-

Index : 0x2e8 RID : 0x2e8 Account : administrator

Index : 0x2e9 RID : 0x2e9 Account : guest

Index : 0x2ea RID : 0x2ea Account : Idoe

Index : 0x2eb RID : 0x2eb Account : svc - backup

Shares :-

Admins	Disk	Remote	Admin
asl	Disk	Default	share
Public	Disk	Company - wide	Fileshare

1. Netcat - Banner running on scanner.

nc -v - scanner.nmap.org 22

steps.

1. connect to open TCP ports
2. Record Service, Banner / header, returned

Input :

nc -v - scanner.nmap.org 22
Point F, Head / HTTP / 1.0.1.1 in host: scanned
- nmap.org 80
- nmap.org 80

Output :

connections to scanner.nmap.org.22
Port, [tcp] set [succeeded]
set - 2.0 opens! HTTP/1.0.1.1. Port, banner -
20 banner 2.1.2
connections of scanner.nmap.org 80
Port (np) HTTP [succeeded]
HTTP/1.1 200 OK