





STB10NK60ZT4, STP10NK60Z STP10NK60ZFP, STW10NK60Z

Datasheet

N-channel 600 V, 0.68 Ω typ., 10 A SuperMESH Power MOSFETs in D²PAK, TO-220, TO-220FP and TO-247 packages

Features



AM01476v1_tab

Order code	V_{DS}	$R_{DS(on)}$ max.	I_D
STB10NK60ZT4	600 V	0.75 Ω	10 A
STP10NK60Z			
STP10NK60ZFP			
STW10NK60Z			

- 100% avalanche tested
- Extremely high dv/dt capability
- Gate charge minimized
- Zener-protected

Applications

- Switching applications

Description

These high-voltage devices are Zener-protected N-channel Power MOSFETs developed using the SuperMESH technology by STMicroelectronics, an optimization of the well-established PowerMESH. In addition to a significant reduction in on-resistance, these devices are designed to ensure a high level of dv/dt capability for the most demanding applications.



Product status links

[STB10NK60ZT4](#)

[STP10NK60Z](#)

[STP10NK60ZFP](#)

[STW10NK60Z](#)

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value			Unit
		D ² PAK TO-220	TO-220FP	TO-247	
V _{DS}	Drain-source voltage	600			V
V _{GS}	Gate-source voltage	±30			V
I _D	Drain current (continuous) at T _C = 25 °C	10	10 ⁽¹⁾	10	A
	Drain current (continuous) at T _C = 100 °C	5.7	5.7 ⁽¹⁾	5.7	
I _{DM} ⁽²⁾	Drain current (pulsed)	36	36 ⁽¹⁾	36	A
P _{TOT}	Total power dissipation at T _C = 25 °C	115	35	156	W
ESD	Gate-source human body model (C = 100 pF, R = 1.5 kΩ)	4			kV
dv/dt ⁽³⁾	Peak diode recovery voltage slope	4.5			V/ns
V _{ISO}	Insulation withstand voltage (RMS) from all three leads to external heat sink (t = 1 s, T _C = 25 °C)	-	2.5	-	kV
T _{stg}	Storage temperature range	-55 to 150			°C
T _J	Operating junction temperature range				

1. Limited by maximum junction temperature.
2. Pulse width is limited by safe operating area.
3. I_{SD} ≤ 10 A, di/dt ≤ 200 A/μs, V_{DD} = 480 V.

Table 2. Thermal data

Symbol	Parameter	Value				Unit
		D ² PAK	TO-220	TO-220FP	TO-247	
R _{thJC}	Thermal resistance, junction-to-case	1.09		3.6	0.8	°C/W
R _{thJA}	Thermal resistance, junction-to-ambient	35 ⁽¹⁾	62.5		50	°C/W

1. When mounted on a standard 1 inch² area of FR-4 PCB with 2-oz copper.

Table 3. Avalanche characteristics

Symbol	Parameter	Value	Unit
I _{AR}	Avalanche current, repetitive or not repetitive (pulse width is limited by T _J max.)	10	A
E _{AS}	Single pulse avalanche energy (starting T _J = 25 °C, I _D = I _{AR} , V _{DD} = 50 V)	300	mJ
E _{AR}	Repetitive avalanche energy (pulse width limited by T _J max.)	3.5	mJ

2 Electrical characteristics

$T_C = 25\text{ }^{\circ}\text{C}$ unless otherwise specified.

Table 4. On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	$I_D = 250\text{ }\mu\text{A}$, $V_{GS} = 0\text{ V}$	600	-	-	V
I_{DSS}	Zero gate voltage drain current	$V_{GS} = 0\text{ V}$, $V_{DS} = 600\text{ V}$	-	-	1	μA
		$V_{GS} = 0\text{ V}$, $V_{DS} = 600\text{ V}$, $T_C = 125\text{ }^{\circ}\text{C}^{(1)}$	-	-	50	
I_{GSS}	Gate body leakage current	$V_{GS} = \pm 20\text{ V}$, $V_{DS} = 0\text{ V}$	-	-	± 10	μA
$V_{GS(th)}$	Gate threshold voltage	$V_{DS} = V_{GS}$, $I_D = 250\text{ }\mu\text{A}$	3.00	3.75	4.50	V
$R_{DS(on)}$	Static drain-source on-resistance	$V_{GS} = 10\text{ V}$, $I_D = 4.5\text{ A}$	-	0.68	0.75	Ω

1. Specified by design, not tested in production.

Table 5. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$g_{fs}^{(1)}$	Forward transconductance	$V_{DS} = 25\text{ V}$, $I_D = 4.5\text{ A}$	-	7.8	-	S
C_{iss}	Input capacitance	$V_{DS} = 25\text{ V}$, $f = 1\text{ MHz}$, $V_{GS} = 0\text{ V}$	-	1370	-	pF
C_{oss}	Output capacitance		-	156	-	pF
C_{rss}	Reverse transfer capacitance		-	37	-	pF
$C_{oss\text{ eq.}}^{(2)}$	Equivalent output capacitance	$V_{GS} = 0\text{ V}$, $V_{DS} = 0\text{ to }480\text{ V}$	-	93	-	pF
Q_g	Total gate charge	$V_{DD} = 480\text{ V}$, $I_D = 8\text{ A}$, $V_{GS} = 0\text{ to }10\text{ V}$ (see the Figure 18. Test circuit for gate charge behavior)	-	48	70 ⁽³⁾	nC
Q_{gs}	Gate-source charge		-	10	-	nC
Q_{gd}	Gate-drain charge		-	25	-	nC

1. Pulsed: pulse duration = 300 μs , duty cycle 1.5%.

2. $C_{oss\text{ eq.}}$ is defined as the constant equivalent capacitance giving the same charging time as C_{oss} when V_{DS} increases from 0 to 80% V_{DSS} .

3. Specified by design, not tested in production.

Table 6. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 300\text{ V}$, $I_D = 4\text{ A}$, $R_G = 4.7\text{ }\Omega$, $V_{GS} = 10\text{ V}$	-	20	-	ns
t_r	Rise time		-	20	-	ns
$t_{d(off)}$	Turn-off delay time	(see the Figure 17. Test circuit for resistive load switching times and Figure 22. Switching time waveform)	-	55	-	ns
t_f	Fall time		-	30	-	ns

Table 7. Source-drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}	Source-drain current		-	-	10	A
$I_{SDM}^{(1)}$	Source-drain current (pulsed)		-	-	36	A
$V_{SD}^{(2)}$	Forward on voltage	$I_{SD} = 10\text{ A}$, $V_{GS} = 0\text{ V}$	-	-	1.6	V
t_{rr}	Reverse recovery time	$I_{SD} = 8\text{ A}$, $di/dt = 100\text{ A}/\mu\text{s}$, $V_{DD} = 40\text{ V}$, $T_J = 150\text{ }^\circ\text{C}$ (see the Figure 19. Test circuit for inductive load switching and diode recovery times)	-	570	-	ns
Q_{rr}	Reverse recovery charge		-	4.3	-	μC
I_{RRM}	Reverse recovery current		-	15	-	A

1. Pulse width is limited by safe operating area.

2. Pulsed: pulse duration = 300 μs , duty cycle 1.5%.

2.1 Electrical characteristics (curves)







Figure 1. Safe operating area for D²PAK and TO-220

Figure 2. Normalized transient thermal impedance for D²PAK and TO-220

Figure 3. Safe operating area for TO-220FP

Figure 4. Normalized transient thermal impedance for TO-220FP

Figure 5. Safe operating area for TO-247

Figure 6. Normalized transient thermal impedance for TO-247














Figure 7. Typical output characteristics

Figure 8. Typical transconductance characteristics

Figure 9. Typical drain-source on-resistance

Figure 10. Typical gate charge characteristics

Figure 11. Typical capacitance characteristics

Figure 12. Normalized gate threshold vs temperature


Figure 13. Normalized on-resistance vs temperature

Figure 14. Typical reverse diode forward characteristics

Figure 15. Maximum avalanche energy vs temperature

Figure 16. Normalized breakdown voltage vs temperature



3 Test circuits

Figure 17. Test circuit for resistive load switching times



AM01468v1

Figure 18. Test circuit for gate charge behavior



AM01469v1

Figure 19. Test circuit for inductive load switching and diode recovery times



AM01470v1

Figure 20. Unclamped inductive load test circuit


AM01471v1

Figure 21. Unclamped inductive waveform


AM01472v1

Figure 22. Switching time waveform


AM05540v2




4 Package information

To meet environmental requirements, ST offers these devices in different grades of **ECOPACK** packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: www.st.com. ECOPACK is an ST trademark.

4.1 D²PAK (TO-263) type A package information

Figure 23. D²PAK (TO-263) type A package outline




0079457_27

Table 8. D²PAK (TO-263) type A package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.40		4.60
A1	0.03		0.23
b	0.70		0.93
b2	1.14		1.70
c	0.45		0.60
c2	1.23		1.36
D	8.95		9.35
D1	7.50	7.75	8.00
D2	1.10	1.30	1.50
E	10.00		10.40
E1	8.30	8.50	8.70
E2	6.85	7.05	7.25
e		2.54	
e1	4.88		5.28
H	15.00		15.85
J1	2.49		2.69
L	2.29		2.79
L1	1.27		1.40
L2	1.30		1.75
R		0.40	
V2	0°		8°

4.2 D²PAK (TO-263) type B package information


Figure 24. D²PAK (TO-263) type B package outline



0079457_27_B

Table 9. D²PAK (TO-263) type B mechanical data


Dim.	mm		
	Min.	Typ.	Max.
A	4.36		4.56
A1	0.00		0.25
b	0.70		0.90
b1	0.51		0.89
b2	1.17		1.37
c	0.38		0.694
c1	0.38		0.534
c2	1.19		1.34
D	8.60		9.00
D1	6.90		7.50
E	10.15		10.55
E1	8.10		8.70
e	2.54 BSC		
H	15.00		15.60
L	1.90		2.50
L1			1.65
L2			1.78
L3		0.25	
L4	4.78		5.28

Figure 25. D²PAK (TO-263) recommended footprint (dimensions are in mm)


0079457_Rev27_footprint

4.3 TO-220 type A package information

Figure 26. TO-220 type A package outline




0015988_typeA_Rev_24

Table 10. TO-220 type A package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.40		4.60
b	0.61		0.88
b1	1.14		1.55
c	0.48		0.70
D	15.25		15.75
D1		1.27	
E	10.00		10.40
e	2.40		2.70
e1	4.95		5.15
F	1.23		1.32
H1	6.20		6.60
J1	2.40		2.72
L	13.00		14.00
L1	3.50		3.93
L20		16.40	
L30		28.90	
øP	3.75		3.85
Q	2.65		2.95
Slug flatness		0.03	0.10

4.4 TO-220FP type B package information

Figure 27. TO-220FP type B package outline




7012510_B_rev.14

Table 11. TO-220FP type B package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.40		4.60
B	2.50		2.70
D	2.50		2.75
E	0.45		0.70
F	0.75		1.00
F1	1.15		1.70
F2	1.15		1.70
G	4.95		5.20
G1	2.40		2.70
H	10.00		10.40
L2		16.00	
L3	28.60		30.60
L4	9.80		10.60
L5	2.90		3.60
L6	15.90		16.40
L7	9.00		9.30
Dia	3.00		3.20

4.5 TO-247 package information

Figure 28. TO-247 package outline




0075325_10

Table 12. TO-247 package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.85		5.15
A1	2.20		2.60
b	1.0		1.40
b1	2.0		2.40
b2	3.0		3.40
c	0.40		0.80
D	19.85		20.15
E	15.45		15.75
e	5.30	5.45	5.60
L	14.20		14.80
L1	3.70		4.30
L2		18.50	
ØP	3.55		3.65
ØR	4.50		5.50
S	5.30	5.50	5.70
aaa		0.04	0.10

4.6 D²PAK packing information

Figure 29. D²PAK tape drawing (dimensions are in mm)



DM01095771 2



5 Ordering information

Table 13. Order codes

Order codes	Marking	Package	Packing
STB10NK60ZT4	B10NK60Z	D ² PAK	Tape and reel
STP10NK60Z	P10NK60Z	TO-220	Tube
STP10NK60ZFP	P10NK60ZFP	TO-220FP	
STW10NK60Z	W10NK60Z	TO-247	

Revision history

Table 14. Document revision history

Date	Revision	Changes
29-Sep-2005	6	Inserted ecopack indication.
29-Oct-2005	7	New value inserted in <i>Table 6</i> .
11-Apr-2006	8	New template.
19-Sep-2006	9	Unit changed in <i>Table 5</i> .
17-Nov-2008	10	Updated <i>Section 4: Package mechanical data</i> .
15-Nov-2012	11	Updated <i>Table 2: Absolute maximum ratings</i> , <i>Table 3: Thermal data</i> , <i>Table 5: On /off states</i> and <i>Table 9: Gate-source Zener diode</i> . Updated <i>Section 4: Package mechanical data</i> and <i>Section 5: Packaging mechanical data</i> . Minor text changes.
14-Jul-2025	12	Removed order code STB10NK60Z-1. Updated Section 4: Package information .



Contents

1	Electrical ratings	2
2	Electrical characteristics.....	3
2.1	Electrical characteristics (curves)	5
3	Test circuits	8
4	Package information.....	9
4.1	D ² PAK (TO-263) type A package information	10
4.2	D ² PAK (TO-263) type B package information	12
4.3	TO-220 type A package information	14
4.4	TO-220FP type B package information	16
4.5	TO-247 package information	18
4.6	D ² PAK packing information	20
5	Ordering information	21
	Revision history	22



IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice.

In the event of any conflict between the provisions of this document and the provisions of any contractual arrangement in force between the purchasers and ST, the provisions of such contractual arrangement shall prevail.

The purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgment.

The purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of the purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

If the purchasers identify an ST product that meets their functional and performance requirements but that is not designated for the purchasers' market segment, the purchasers shall contact ST for more information.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2025 STMicroelectronics – All rights reserved