

RESTful Web Services



A brief introduction.

Lecturer: Prof. Dr. Michael Eichberg
Contact: michael.eichberg@dhbw.de , Room 149B
Version: 1.0.0.1
Source: RESTful Web Services; Leonard Richardson & Sam Ruby; O'Reilly

Slides/Script: https://delors.github.io/ds-introduction_to_rest/folien.en.md.html
https://delors.github.io/ds-introduction_to_rest/folien.en.md.html.pdf

Reporting errors: <https://github.com/Delors/delors.github.io/issues>

AI Usage: AI assistants (in particular Claude, but also ChatGPT, Ollama with Gemma/LLama/Qwen, OpenCode with Kimi, etc.) were used to assist in the creation of the slides. This was done, for example, to efficiently generate graphics (i.e. SVG files), or to generate summary tables. Furthermore, AI was used for general quality assurance. Content that may have been suggested by an AI was explicitly validated and adapted whenever it was incorporated.

What is a *Web Service* in the context of RESTful Web Services?

Traditional view

A *Web Service* is simply a web page that can be requested and processed by a computer.

A *Web Service* is a "web page" that is to be consumed by an *autonomous program* - as opposed to a web browser or similar UI tool.



REST^[1]

- REST = Representational State Transfer

(Essentially a set of design principles for judging architecture; **an architectural style**).

- Resources are identified by uniform resource identifiers (URIs)
- Resources are manipulated by their representations
- Messages are self-describing and stateless

Of secondary importance:

- Multiple representations are accepted or sent
 - "Hypertext" represents the application state
-

^[1] REST was described by Roy Fielding in his dissertation.

A possible architecture for RESTful web services

Resource-oriented Architecture (ROA)

- Information about the method is included in the HTTP method.
- Scoping information is included in the URI.
(I. e. which data is affected.)

REST-Style

- Client-server
- stateless
- Cached
- Uniform Interface (HTTP Methods)
- Multi-layered system

RESTful Web Services - Foundations

HTTP: the underlying stateless transport protocol:
Essential methods:

GET: sideeffect-free requests for information

POST: adding new information (without specifying the target URI)

PUT: idempotent update or creation of new information at the given URI

DELETE: idempotent deletion of information

URI: used to find resources

Representation: **JSON**, XML, SVG, WebP, XML, ...

Two Types of State

Application State / Session State

1

- "State" refers to Application-/Session State

The application state is the information necessary to understand the context of an interaction
Authorization and authentication information are examples of application state.

- Maintained as part of the content transmitted from the client to the server and back to the client.
I. e. the client manages the application state.
- Thus, any server can potentially resume the transaction at the point where it was interrupted.

Resource State

2

- The resource state is the type of state that the *S* in *REST* refers to.
- The *stateless* restriction means that all messages must contain the entire application state (i. e. we effectively have no sessions).

Multiple representations

- Most resources only have a single representation.
- REST can support any media type; JSON is the standard.
(HTTP supports content negotiation.)
- Links can be embedded and reflect the structure with which a user can navigate through an application.

Simple/first tests for RESTfulness

- Can I use a GET to retrieve the URLs I have POSTed to?
- Would the client notice if the server...
 - is restarted at any point between requests
 - is reinitialized when the client makes the next request.

Resource modeling

- organize the application into URI-addressable resources (discrete resources should have their own stable URIs).
 - use only the standard HTTP messages - GET, PUT, POST, DELETE and PATCH - to provide the full capabilities of the application
-

HTTP methods

GET is used to query resources.

PUT is used to create a resource or update it if you know the URI.

POST is used to create a new resource. The response should then contain the URI of the created resource.

DELETE deletes the specified resource.

The difference between **PUT** and **POST** is that **PUT** is idempotent: a single or repeated calls have the same effect (i. e. a repeated call has no side effect), while successive identical **POST** calls can have additional effects, such as the repeated transfer of an order/the repeated creation of a message.

A **PATCH** request is regarded as a set of instructions for changing a resource. In contrast, a PUT request is a complete representation of a resource.

Example Application del.icio.us

Source: <https://www.peej.co.uk/articles/restfully-delicious.html>

del.icio.us enables us:

- to get a list of all our bookmarks and filter this list by tags or date and to limit the number of retrieved bookmarks
- to retrieve the number of bookmarks created on different days
- to retrieve when we last updated our bookmarks
- to retrieve a list of all our markers
- to add a bookmark
- to edit a bookmark
- to delete a bookmark
- to rename a bookmark

Example Application del.icio.us: Resources

Bookmarks: `http://del.icio.us/api/[username]/bookmarks`

Tags: `http://del.icio.us/api/[username]/tags`

[username]: is the username of the user whose bookmarks we are interested in

Example Application del.icio.us: Representation of Resources

We define (in this example) some XML document formats and media types to identify them:

Mediatype	Description
delicious/bookmarks+xml	list of bookmarks
delicious/bookmark+xml	one bookmark
delicious/bookmarkcount+xml	number of bookmarks per tag
delicious/update+xml	time at which the bookmarks were last updated
delicious/tags+xml	list of tags
delicious/tag+xml	a tag

Example Application del.icio.us: Query Bookmarks

URL: `http://del.icio.us/api/[username]/bookmarks/`

Method: GET

Querystring: tag = Filter by tag
dt = Filter by date

start = The number of the first returned bookmark

end = The number of the last returned bookmark

Return value: 200 OK & XML (delicious/bookmarks+xml)
401 Unauthorized
404 Not Found

Example application del.icio.us: Query bookmarks - example response

GET <http://del.icio.us/api/peej/bookmarks/?start=1&end=2>

```
1 <?xml version="1.0"?>
2 <bookmarks start="1" end="2"
3   next="http://del.icio.us/api/peej/bookmarks?start=3&end=4">
4   <bookmark url="http://www.example.org/one" tags="example,test"
5     href="http://del.icio.us/api/peej/bookmarks/a211528fb5108cddaa4b0d3aecdbdcf"
6     time="2005-10-21T19:07:30Z">
7     Example of a Delicious bookmark
8   </bookmark>
9   <bookmark url="http://www.example.org/two" tags="example,test"
10    href="http://del.icio.us/api/peej/bookmarks/e47d06a59309774edab56813438bd3ce"
11    time="2005-10-21T19:34:16Z">
12    Another example of a Delicious bookmark
13  </bookmark>
14 </bookmarks>
```

Example application del.icio.us: Information about a bookmark

URL: `http://del.icio.us/api/[username]/bookmarks/[hash]`
Method: `GET`
Return value: 200 OK & XML (delicious/bookmark+xml)
401 Unauthorized
404 Not Found

Example application del.icio.us: Information about a bookmark - Example response

GET <http://del.icio.us/api/peej/bookmarks/a211528fb5108cdd>

```
1 <?xml version="1.0"?>
2 <bookmark url="http://www.example.org/one" time="2005-10-21T19:07:30Z">
3   <description>
4     Example of a Delicious bookmark
5   </description>
6   <tags count="2">
7     <tag name="example" href="http://del.icio.us/api/peej/tags/example"/>
8     <tag name="test" href="http://del.icio.us/api/peej/tags/test"/>
9   </tags>
10 </bookmark>
```

Example application del.icio.us: Query the number of bookmarks

URL: `http://del.icio.us/api/[username]/bookmarks/count`

Method: GET

Query parameter: tag = Filter by tag

Return value: 200 OK & XML (delicious/bookmark+xml)

401 Unauthorized

404 Not Found

Example application del.icio.us: Query when the last change was made

URL: `http://del.icio.us/api/[username]/bookmarks/update`

Method: GET

Return value: 200 OK & XML (delicious/bookmark+xml) 401 Unauthorized 404 Not Found

Example application del.icio.us: Adding a bookmark

URL: `http://del.icio.us/api/[username]/bookmarks/`
Method: POST
Query document: XML (delicious/bookmark+xml)
Return value: 201 Created & Location
401 Unauthorized
415 Unsupported Media Type(if the send document is not valid)

Example application del.icio.us: Adding a bookmark - example document

POST <http://del.icio.us/api/peej/bookmarks/>

```
1 <?xml version="1.0"?>
2 <bookmark url="http://www.example.org/one"
3   time="2005-10-21T19:07:30Z">
4   <description>Example of a Delicious bookmark</description>
5   <tags>
6     <tag name="example" />
7     <tag name="test" />
8   </tags>
9 </bookmark>
```

Example application del.icio.us: Update a bookmark

URL: `http://del.icio.us/api/[username]/bookmarks/[hash]`
Method: PUT
Query document: XML (delicious/bookmark+xml)
Return value: 201 Created & Location
401 Unauthorized
404 Not Found (new bookmarks cannot be created using put!)
415 Unsupported Media Type (if the send document is not valid)

Example application del.icio.us: Delete a bookmark

URL: `http://del.icio.us/api/[username]/bookmarks/[hash]`
Method: DELETE
Return value: 204 No Content
401 Unauthorized
404 Not Found