
Layout Directives

Grid & Cell

```
.. grid:: <classes>
```

```
.. cell:: <classes>
```

:align:	auto (default), center, start, end
:theme:	Any theme name (emitted as data-theme)

```
.. grid::
```

```
.. cell:: width-50  
    :align: center  
    :theme: muted
```

Cell content.

```
.. cell:: width-50
```

Another cell.

Deck & Card

```
.. deck:: <classes>
```

```
.. card:: <classes>
```

:theme: (deck)	Any theme name (emitted as data-theme on <ld-deck>)
:theme: (card)	Any theme name (emitted as data-theme on <ld-card>)
:not-incremental: (card)	Flag; prevents the card from being shown incrementally

```
.. deck::  
    :theme: dark
```

```
.. card::  
    :theme: light
```

First card content.

```
.. card::  
    :not-incremental:
```

This card is not incremental.

Compound

```
.. compound:: — Standard docutils directive, extended with:
```

:theme:	Any theme name (emitted as data-theme)
---------	--

```
.. compound::  
    :theme: muted
```

Content inside a compound container.

Information Directives

Global Information

.. global-information:: <title>

:formatted-title:	Inline markup supported (e.g. bold)
:symbol:	Single character symbol (e.g. λ)
:type:	cheat-sheet (default) or slide
:embed:	Flag; embed in document flow
:class:	CSS class(es)
:name:	Reference name

.. *global-information*:: Functional Programming
:symbol: λ
:type: cheat-sheet
:embed:

Background information.

Supplemental

.. supplemental:: <classes>

:embed-in-document-flow:	Flag; makes content indistinguishable from main content in document view
--------------------------	--

.. *supplemental*::
:embed-in-document-flow:

This appears inline in the document.

Presenter Note

.. presenter-note:: <classes>

:name:	Reference name
--------	----------------

.. *presenter-note*::

Notes for the presenter.

Module

.. module:: <name>

:class:	CSS class(es)
:scope:	slide, document, or all (default)

.. *module*:: My Module
:scope: slide

Module content.

Source

.. source:: <filename>

:prefix:	Text to prepend to the resolved path
:suffix:	Text to append to the resolved path
:path:	relative (default) or absolute

.. *source*:: my_file.rst
:prefix: https://example.com/
:path: absolute

Exercise Directives

Exercise

```
.. exercise:: <title>
```

:formatted-title:	Inline markup supported
:name:	Reference name
:class:	CSS class(es)

```
.. exercise:: My Exercise
```

Exercise description.

Solution

```
.. solution:: <title> (must be nested inside exercise)
```

:pwd:	Password (min. 3 chars); auto-generated if omitted
:class:	CSS class(es)

```
.. exercise:: My Exercise
```

```
.. solution::
  :pwd: 1234
```

Solution content.

Admonition Directives

All custom admonitions support an optional title argument and the standard options:

:class:	CSS class(es)
:name:	Reference name

Custom Admonitions

```
.. background::... definition::... proof::... theorem::... lemma::... conclusion::...
observation::... remark::... summary::... legend::... repetition::... question::...
answer::... remember::... deprecated::... assessment::... example::... discussion::
```

```
.. theorem:: The Theorem Title
  :class: important
```

The theorem statement.

Content Directives

Story

```
.. story:: <classes>
```

No custom options.

```
.. story::
```

A story block.

Scrollable

```
.. scrollable:: <classes>
```

:height:	CSS height value (e.g. 300px, 10em)
----------	-------------------------------------

```
.. scrollable::
  :height: 300px
```

Long content that scrolls.

Popover

```
.. popover:: <title>
```

--	--

`:class:` CSS class(es) for the trigger button

```
.. popover:: Click me
   :class: my-button
```

Hidden popover content.

Code Directive Extension

.. `code`:: <language> — Standard docutils directive, extended with:

`:line-number-digits:` Integer 1–4; minimum padding width for line numbers

Implicitly enables `:number-lines:` when set.

```
.. code:: java
   :line-number-digits: 2

   public static void main(...) { }
```
