



Assessment of nutrients and water-quality constituents in the North Delta during Yolo Bypass inundation: March 2017

Methods

The study is based on the assessment and comparison of two broad-area high-resolution water quality mapping surveys of the North Delta conducted in March 2017, during Yolo Bypass inundation. Each survey consists of one day of high-resolution mapping, with each day covering a similar spatial extent; transects began and ended on the Sacramento River at Rio Vista and include measurements in the Cache Slough Complex and upstream along the Toe Drain into the Yolo Bypass when water depth permitted. Data were collected at high speed to minimize to the extent to which tidal currents obscure nutrient and phytoplankton distributions.

Sampling and analysis

Underway water sampling and onboard analyses:

Surveys were conducted using the USGS R/V Dora Henry on March 8 and March 15, 2017. On each day data were collected during daylight hours beginning at approximately 7:30 am. For analysis, sample water was continuously pumped onto the boat while underway at speeds up to 30 mph (13 m/s) using a pick-up tube mounted at a fixed depth of approximately 1 m below the surface, routed through a screen to remove large debris and into a pressure-compensated manifold that maintained system pressure at a proscribed level irrespective of boat speed (Downing et al., 2016). A 2-stage debubbler was used to remove bubbles that can interfere with optical measurements. Sample water was split into separate flow paths for each analytical flow path, with constant flow rates maintained by metering the discharge line. Flows were continuously monitored using a sight gauge for each flow path.

The manifold delivered water to the following flowpaths: (1) A flow-through system consisting of a thermosalinograph that recorded temperature and conductance (Sea-Bird Scientific SB45 (TSG), Bellevue, WA); fluorometers that measured fluorescence of chlorophyll (fchl) and fluorescence of dissolved organic matter (fDOM, WETLabs WETstar (WS), Philomath, OR); a beam transmissometer that recorded transmittance and attenuation (WETLabs model C-Star transmissometer (CStar), Philomath, OR), a nitrate (NO₃) analyzer (ISUS V3; Satlantic, Halifax, Nova Scotia) and a second NO₃ analyzer (SUNA V1; Sea-Bird Scientific, Bellevue, WA). (2) A flow chamber for a multiparameter water quality sonde (YSI EXO2; Xylem Inc. (EXO), Rye Brook, New York) equipped with sensors to measure temperature, specific conductance (SpC), turbidity, pH, dissolved oxygen (DO), fDOM and fchl.

All instrumentation was cleaned, and calibrations were checked prior to each use following the manufacturer's recommendation or as described below. Data for most instruments was recorded at 1-second frequency on a single data logger (CR6, Campbell Scientific, Logan, Utah, United States) together with a timestamp and boat position obtained from a high-resolution global positioning system receiver (16X-HVS, Garmin, Olathe, Kansas). All data were displayed in real time, so scientists on board could respond when they observed changes relevant to study objectives, or if issues with flow or instrument performance were noted.

Discrete water sampling and laboratory analyses:

Discrete water samples were collected either underway or—in the case of more extensive sample requirements—while stopped on station. Discrete samples were collected while underway either using a fourth flow path on the sampling manifold or using a separate system with a separate pick-up tube mounted adjacent to the main sampling pick-up and pumping sample through a 0.45-micron filter into a sample bottle. At designated sampling stations (approximately 10 per day) samples for determination of NH_4 , NO_3 , PO_4 , dissolved organic carbon (DOC), and total dissolved nitrogen (TDN) concentrations were collected using this system. Additionally, unfiltered samples were collected approximately from 1 m depth using a submersible pump for analysis of chlorophyll-a (Chl-a), pheophytin, phycocyanin, allophycocyanin, and phycoerythrin pigments, and stable water isotopes.

All samples were stored on ice in the dark during transit to the laboratory where they were stored at 2°C. Dissolved organic carbon samples were preserved to <2 pH with high-purity sulphuric acid the day following collection and stored at 2°C. Samples for pigment analysis were filtered <24 hours after collection and immediately frozen (-90°C). Total Chl-a, pheophytin, phycocyanin, allophycocyanin, and phycoerythrin pigment analysis samples were filtered through a 0.3 μm nominal pore size glass fiber filter (Advantec MFS, Inc, Dublin, CA). Frozen Chl-a filters and chilled nutrient samples were shipped to the USGS National Water Quality Laboratory (Denver, CO). Frozen filters for analysis of phycocyanin, allophycocyanin, and phycoerythrin were shipped to BSA Environmental Services, Inc. (Beachwood, OH).

Concentrations of nutrients were determined colorimetrically using an automated-segmented flow analyzer. Concentrations of nitrogen as nitrite ($\text{NO}_2\text{-N}$) and as nitrate plus nitrite ($\text{NO}_3\text{-N} + \text{NO}_2\text{-N}$) were determined by colorimetric analysis (Fishman, 1993; Patton and Kryskalla, 2011), ammonium as nitrogen ($\text{NH}_4\text{-N}$) was determined by colorimetric analysis after reaction with salicylate-hypochlorite (Fishman, 1993), and total dissolved nitrogen (TDN) was determined by alkaline persulfate digestion (Patton and Kryskalla 2003). Orthophosphate as phosphorous ($\text{PO}_4\text{-P}$; also referred to as soluble reactive phosphate) was determined by colorimetric analysis after reaction with NH_4 molybdate and reduction with ascorbic acid (Patton and Truitt, 1992). Chlorophyll-a and pheophytin concentrations were determined according to EPA Method 445.0 (Arar and Collins, 1997) using sonication extraction. Dissolved organic carbon concentrations were measured using a total organic carbon analyzer (TOC-VCSH, Shimadzu Scientific Instruments, Columbia, Maryland) using high-temperature catalytic combustion according to a modified version of USEPA method 415.3 (Potter and Wimsatt, 2005).

Dissolved organic carbon concentrations were measured using a total organic carbon analyzer (TOC-VCSH, Shimadzu Scientific Instruments, Columbia, Maryland) using high-temperature catalytic combustion according to a modified version of USEPA method 415.3 (Potter and Wimsatt, 2005). Absorbance spectra and fluorescence EEMs were simultaneously measured using an Aqualog[®] equipped with a photodiode and charge-coupled device (CCD) (Horiba Instruments, NJ, USA) according to the method described by Hansen et al. (2018). Briefly, excitation and absorbance spectra were measured

using a 150 W xenon lamp, a 5 nm bandpass, and a 1 s integration time at wavelengths of 240–600 nm. Emission spectra were collected with a CCD at approximately 1.64 nm (4 pixel) intervals at wavelengths of 250–600 nm. To reduce ultraviolet light exposure of the sample and limit the effects of photobleaching, excitation and absorbance wavelengths were scanned from low to high energy (i.e., visible to ultraviolet range) during analysis. Peaks, ratios, and slopes reported in the data were calculated as described by Hansen et al. (2016).

Data processing

All data directly logged to the flow-through data collection system was processed using pandas software library (0.220) in Python (3.7.3) to remove periods of compromised data (e.g. flow blockages, bubbles), to apply instrument corrections and unit conversions, and to apply a centered 20 second median filter to the time series. Final NO₃ values were obtained by regressing instrument response against NO₃ concentrations obtained from laboratory measurements of discrete samples collected through the course of the day. Individual sample results with more than three standard deviations from the regression were judged to be outliers and removed from the regression.

Larger differences between SUNA or ISUS and laboratory NO₃ concentration data are assumed to arise from 1) actual spatial heterogeneity in environmental NO₃ concentrations between water entering the flow through system and that captured in the sample bottle, 2) interferences of turbidity and dissolved organic matter using the UV absorption method for nitrate, or 3) errors in sample handling and laboratory analysis. Excepting these potential sources of error, the field and laboratory NO₃ measurements are typically well correlated with a linear fit. For the simple linear regressions, the SUNA or ISUS NO₃ concentration data was the explanatory variable to compute the response variable of the laboratory NO₃ concentration. P-values were <0.0001 for all regressions. Summary statistics and the regression used for the 2 mapping dates are identified in Table 1 for SUNA measurements. The summary statistics and regression applied for ISUS measurements are generated from several mapping datasets in the region and are identified in Table 2. The NO₃ regressions were developed according to methods in and Bergamaschi et al. (in press).

Dissolved inorganic nitrogen (DIN) concentration was calculated as the sum of NO₃, NO₂ and NH₄ for the discrete sample data. Laboratory DON concentration was calculated by subtracting NH₄, NO₃, and NO₂ data from the TDN data (i.e. $DON = TDN - DIN$). Individual sample results with more than three standard deviations from the regression were judged to be outliers and removed. The regression equation for estimated DON = $0.357 \cdot (fDOM\ WS) + 0.1563$ with $R^2 = 0.8257$. Estimated DOC values were obtained by regressing fDOM sensor (WS) response against DOC concentrations obtained from laboratory measurements of discrete samples collected across all mapping dates. Individual sample results with more than three standard deviations from the regression were judged to be outliers and removed. The regression equation for estimated DOC = $0.057 \cdot (fDOM\ WS) + 0.8974$ with $R^2 = 0.7229$. Both DOC and DON regressions were developed according to modified methods by Snyder et al. (2018).

Data was spatially aligned (SA) to a common spatial framework to facilitate comparisons between dates and to minimize the effects of differential data density on the spatial interpolation calculations by assigning median-filtered data by proximity to a centerline vector comprising points located at the centerline of all channels navigated, spaced at approximately 150 m intervals. The raster output was

moothed with the Focal Statistics tool, and interpolated values were extracted to the spatially aligned points to create continuous spatially aligned data across the mapping domain.

Table 1. Summary statistics and linear regressions for nitrate (NO₃) concentration data obtained from high-resolution SUNA instrument and discrete samples analyzed using standard laboratory methods [n, number of observations; μ M, micromolar; mean, mean high-resolution nitrate concentration; median, median high-resolution nitrate concentration; min, minimum high-resolution nitrate concentration; max, maximum high-resolution nitrate concentration; SS, sum of squared error; SSE, sum of squared estimate of error; MSE, mean square error; RMSE, root mean square error; %, percent; MSPE, model standard percentage error; R², coefficient of determination; *, asterisk indicates adjusted R²].

Parameter	n	min (μ M)	max (μ M)	median (μ M)	mean (μ M)	SS (μ M)	SSE (μ M)	MSE (μ M)	RMSE (μ M)	MSPE (%)	regression equation	p-value	R ²
NO ₃ (SUNA)	12	7.1	183.0	8.8	25.3	19273	25.2	2.8	2.1	0.09	$y = 1.2225x - 8.2154$	<0.0001	0.998*

Table 2. Summary statistics and linear regressions for nitrate (NO₃) concentration data obtained from high-resolution ISUS instrument and discrete samples analyzed using standard laboratory methods [n, number of observations; μ M, micromolar; mean, mean high-resolution nitrate concentration; median, median high-resolution nitrate concentration; min, minimum high-resolution nitrate concentration; max, maximum high-resolution nitrate concentration; SS, sum of squared error; SSE, sum of squared estimate of error; MSE, mean square error; RMSE, root mean square error; %, percent; MSPE, model standard percentage error; R², coefficient of determination; *, asterisk indicates adjusted R²].

Parameter	n	min (μ M)	max (μ M)	median (μ M)	mean (μ M)	SS (μ M)	SSE (μ M)	MSE (μ M)	RMSE (μ M)	MSPE (%)	regression equation	p-value	R ²
NO ₃ (ISUS)	177	0.2	196.8	17.6	21.4	87608	942	5.5	16.5	1.0	$y = 0.92x - 1.7651$	<0.0001	0.961*

References

Arar, E.J. and Collins, G.B. (1997) Method 445.0: In vitro determination of chlorophyll a and pheophytin a in marine and freshwater algae by fluorescence. United States Environmental Protection Agency, Office of Research and Development, National Exposure Research Laboratory.

- Bennett, A. and Bogorad, L. (1973) Complementary chromatic adaptation in a filamentous blue-green alga. *The Journal of cell biology* 58, 419-435.
- Bergamaschi, B.A., T.E.C. Kraus, B.D. Downing, E.B. Stumpner, K. O'Donnell, J. Hansen, J. Soto Perez, A. Hansen, and A. Gelber (in press). Assessing Spatial Variability of Nutrients, Phytoplankton and Related Water Quality Constituents in the California Sacramento-San Joaquin Delta at the Landscape Scale: 2018 High Resolution Mapping Surveys. U.S. Geological Survey Scientific Investigation Report.
- Carlson, R.M. (1986). Continuous flow of reduction of nitrate to ammonia with granular zinc. *Analytical Chemistry* 58, 7, 1590-1591.
- Downing, B.D., Bergamaschi, B.A., Kendall, C., Kraus, T.E.C., Dennis, K.J., Carter, J.A. and Von Dessenneck, T.S. (2016) Using Continuous Underway Isotope Measurements to Map Water Residence Time in Hydrodynamically Complex Tidal Environments. *Environmental Science & Technology* 50, 13387-13396.
- Fishman, M.J. (1993) Methods of analysis by the US Geological Survey National Water Quality Laboratory: Determination of inorganic and organic constituents in water and fluvial sediments. US Geological Survey open-file report (USA).
- Grenier, L., Grossinger, R. (2016) Tools for landscape-scale restoration planning in the Delta. Presentation to the Delta Independent Science Board, January 16, 2013, 2nd Floor Conference Center, Sacramento, CA.
- Hansen, A.M., Kraus, T.E., Pellerin, B.A., Fleck, J.A., Downing, B.D. and Bergamaschi, B.A., 2016. Optical properties of dissolved organic matter (DOM): Effects of biological and photolytic degradation. *Limnology and oceanography*, 61(3), pp.1015-1032.
- Jabusch, T., Bresnahan, P., Trowbridge, P., Novick, E., Wong, A., Salomon, M. and Senn, D. (2016) Summary and evaluation of Delta subregions for nutrient monitoring and assessment Technical report. San Francisco Estuary Institute, Richmond, CA. [Google Scholar].
- Patton, C.J. and Kryskalla, J.R. (2011) Colorimetric determination of nitrate plus nitrite in water by enzymatic reduction, automated discrete analyzer methods. *US Geological Survey Techniques and Methods* 34.
- Patton, C.J. and Truitt, E.P. (1992) Methods of Analysis by the US Geological Survey National Water Quality Laboratory: Determination of the Total Phosphorus by a Kjeldahl Digestion Method and an Automated Colorimetric Finish that Includes Dialysis. US Geological Survey.
- Potter, B. and Wimsatt, J. (2005) Determination of total organic carbon and specific UV absorbance at 254 nm in source water and drinking water. EPA Document: EPA.
- Snyder, L., Potter, J.D. and McDowell, W.H., 2018. An evaluation of nitrate, fDOM, and turbidity sensors in New Hampshire streams. *Water Resources Research*, 54(3), pp.2466-2479.
- Zimba, P.V. (2012) An improved phycobilin extraction method. *Harmful Algae* 17, 35-39.