

Dikes Overtopping Kernel - Technical documentation

Generated by Doxygen 1.8.9.1

Tue Oct 31 2017 14:59:06

Contents

1	Modules Index	1
1.1	Modules List	1
2	Data Type Index	3
2.1	Class List	3
3	File Index	5
3.1	File List	5
4	Module Documentation	7
4.1	dllovertopping Module Reference	7
4.1.1	Detailed Description	8
4.1.2	Function/Subroutine Documentation	8
4.1.2.1	calculateqo	8
4.1.2.2	calculateqof	9
4.1.2.3	calculateqoj	10
4.1.2.4	calczvalue	11
4.1.2.5	geometry_c_f	12
4.1.2.6	getlanguage	13
4.1.2.7	input_j_f	13
4.1.2.8	omkeervariantf	14
4.1.2.9	omkeervariantj	15
4.1.2.10	setlanguage	16
4.1.2.11	validateinputc	16
4.1.2.12	validateinputf	17
4.1.2.13	validateinputj	18
4.1.2.14	versionnumber	18
4.1.3	Variable Documentation	19
4.1.3.1	separationchar	19
4.2	factormoduleovertopping Module Reference	19
4.2.1	Detailed Description	19
4.2.2	Function/Subroutine Documentation	19

4.2.2.1	calculategammab	19
4.2.2.2	calculategammabeta	20
4.2.2.3	calculategammaf	20
4.2.2.4	calculatetanalpha	21
4.3	formulamoduleovertopping Module Reference	22
4.3.1	Detailed Description	23
4.3.2	Function/Subroutine Documentation	23
4.3.2.1	adjustinfluencefactors	23
4.3.2.2	calculateanglewaveattack	24
4.3.2.3	calculatebreakerlimit	24
4.3.2.4	calculatebreakerparameter	24
4.3.2.5	calculatewavelength	25
4.3.2.6	calculatewaveovertoppingdischarge	25
4.3.2.7	calculatewaverunup	26
4.3.2.8	calculatewavesteepness	27
4.3.2.9	cubicroots	28
4.3.2.10	isequalreal	28
4.3.2.11	isequalzero	28
4.3.2.12	realrootscubicfunction	29
4.3.2.13	rootsdepressedcubic	29
4.3.2.14	rootsgeneralcubic	30
4.4	geometrymoduleovertopping Module Reference	31
4.4.1	Detailed Description	31
4.4.2	Function/Subroutine Documentation	31
4.4.2.1	adjustnonhorizontalberms	31
4.4.2.2	allocatevectorsgeometry	32
4.4.2.3	basicgeometrytest	33
4.4.2.4	calculatehorzdistance	33
4.4.2.5	calculatehorzlengths	34
4.4.2.6	calculatesegmentslopes	35
4.4.2.7	checkcrosssection	35
4.4.2.8	copygeometry	36
4.4.2.9	deallocategeometry	37
4.4.2.10	determinesegmenttypes	38
4.4.2.11	initializegeometry	39
4.4.2.12	mergesequentialberms	40
4.4.2.13	removeberms	41
4.4.2.14	removedikessegments	42
4.4.2.15	splitcrosssection	42
4.5	mainmoduleovertopping Module Reference	43

4.5.1	Detailed Description	44
4.5.2	Function/Subroutine Documentation	44
4.5.2.1	calculateovertopping	44
4.5.2.2	calculateovertoppingnegativefreeboard	45
4.5.2.3	calculateovertoppingsection	45
4.5.2.4	calculatewaveovertopping	46
4.5.2.5	checkinputdata	47
4.5.2.6	checkmodelfactors	48
4.5.2.7	interpolateresultssections	49
4.6	modulelogging Module Reference	49
4.6.1	Detailed Description	50
4.6.2	Variable Documentation	50
4.6.2.1	maxfilenamelength	50
4.7	omkeervariantmodule Module Reference	50
4.7.1	Detailed Description	50
4.7.2	Function/Subroutine Documentation	51
4.7.2.1	checkifonberm	51
4.7.2.2	iteratetogivendischarge	53
4.7.2.3	iteratetogivendischargevalidprofile	54
4.7.3	Variable Documentation	55
4.7.3.1	minzberm	55
4.7.3.2	toldikeheight	55
4.7.3.3	toldischarge	55
4.8	overtoppinginterface Module Reference	56
4.8.1	Detailed Description	56
4.8.2	Variable Documentation	56
4.8.2.1	varmodelfactorcriticalovertopping	56
4.9	overtoppingmessages Module Reference	56
4.9.1	Detailed Description	57
4.9.2	Function/Subroutine Documentation	57
4.9.2.1	getformattoomanyberms	57
4.9.2.2	getlanguage	57
4.9.2.3	getmsg_calc_influence_roughness	57
4.9.2.4	getmsg_calculategammaftohigh	57
4.9.2.5	getmsg_calculategammaftolow	58
4.9.2.6	getmsg_first_segment_berm	58
4.9.2.7	getmsg_last_segment_berm	58
4.9.2.8	getmsgremovenonhorizontalberm	58
4.9.2.9	getovertoppingformat	58
4.9.2.10	getovertoppingmessage	59

4.9.2.11	getovertoppingparameter	59
4.9.2.12	setlanguage	60
4.9.3	Variable Documentation	60
4.9.3.1	language	60
4.9.3.2	maxmsg	60
4.9.3.3	maxpar	60
4.10	typedefinitionsovertopping Module Reference	60
4.10.1	Detailed Description	61
4.10.2	Variable Documentation	61
4.10.2.1	berm_max	61
4.10.2.2	berm_min	62
4.10.2.3	fb_max	62
4.10.2.4	fb_min	62
4.10.2.5	fn_max	62
4.10.2.6	fn_min	62
4.10.2.7	foreshore_max	62
4.10.2.8	foreshore_min	62
4.10.2.9	frunup1	62
4.10.2.10	frunup2	62
4.10.2.11	frunup3	62
4.10.2.12	fs_max	63
4.10.2.13	fs_min	63
4.10.2.14	margindiff	63
4.10.2.15	margingrad	63
4.10.2.16	mz2_max	63
4.10.2.17	mz2_min	63
4.10.2.18	rfactor_max	63
4.10.2.19	rfactor_min	63
4.10.2.20	slope_max	63
4.10.2.21	slope_min	64
4.10.2.22	xdiff_min	64
4.10.2.23	z2_iter_max1	64
4.10.2.24	z2_iter_max2	64
4.10.2.25	z2_margin	64
4.11	waverunup Module Reference	64
4.11.1	Detailed Description	64
4.11.2	Function/Subroutine Documentation	65
4.11.2.1	convergedwithresidu	65
4.11.2.2	determinestartingvalue	65
4.11.2.3	findsmallestresidu	66

4.11.2.4	innercalculation	66
4.11.2.5	iterationwaverunup	67
4.12	zfunctionsovertopping Module Reference	68
4.12.1	Detailed Description	69
4.12.2	Function/Subroutine Documentation	69
4.12.2.1	adjustprofile	69
4.12.2.2	calculateqorto	70
4.12.2.3	profileinstructure	71
4.12.2.4	zfunclogratios	72
5	Data Type Documentation	75
5.1	overtoppinginterface::overtoppinggeometrytype Type Reference	75
5.1.1	Detailed Description	76
5.1.2	Member Data Documentation	76
5.1.2.1	normal	76
5.1.2.2	npoints	76
5.1.2.3	roughness	76
5.1.2.4	xcoords	76
5.1.2.5	ycoords	76
5.2	overtoppinginterface::overtoppinggeometrytypef Type Reference	77
5.2.1	Detailed Description	77
5.2.2	Member Data Documentation	77
5.2.2.1	normal	77
5.2.2.2	npoints	77
5.2.2.3	roughness	78
5.2.2.4	xcoords	78
5.2.2.5	ycoords	78
5.3	modulelogging::tlogging Type Reference	78
5.3.1	Detailed Description	78
5.3.2	Member Data Documentation	79
5.3.2.1	filename	79
5.3.2.2	verbosity	79
5.4	omkeervariantmodule::tomkeer Type Reference	79
5.4.1	Detailed Description	80
5.4.2	Member Data Documentation	80
5.4.2.1	dischargeprofile	80
5.4.2.2	isberm	80
5.4.2.3	isvalidz	80
5.4.2.4	zprofile	80
5.5	typedefinitionsovertopping::tpgeometry Type Reference	80

5.5.1	Detailed Description	82
5.5.2	Member Data Documentation	82
5.5.2.1	nbermsements	82
5.5.2.2	ncoordinates	82
5.5.2.3	psi	82
5.5.2.4	roughnessfactors	82
5.5.2.5	segmentslopes	82
5.5.2.6	segmenttypes	82
5.5.2.7	xcoorddiff	82
5.5.2.8	xcoordinates	83
5.5.2.9	ycoorddiff	83
5.5.2.10	ycoordinates	83
5.6	typedefinitionsovertopping::tpload Type Reference	83
5.6.1	Detailed Description	84
5.6.2	Member Data Documentation	84
5.6.2.1	h	84
5.6.2.2	hm0	84
5.6.2.3	phi	84
5.6.2.4	tm_10	84
5.7	typedefinitionsovertopping::tpovertopping Type Reference	84
5.7.1	Detailed Description	85
5.7.2	Member Data Documentation	85
5.7.2.1	qo	85
5.7.2.2	z2	85
5.8	typedefinitionsovertopping::tpovertoppinginput Type Reference	86
5.8.1	Detailed Description	87
5.8.2	Member Data Documentation	87
5.8.2.1	computedovertopping	87
5.8.2.2	criticalovertopping	87
5.8.2.3	factordeterminationq_b_f_b	87
5.8.2.4	factordeterminationq_b_f_n	87
5.8.2.5	fshallow	87
5.8.2.6	m_z2	87
5.8.2.7	reductionfactorforeshore	87
5.8.2.8	relaxationfactor	88
5.9	overtoppinginterface::tpprofilecoordinate Type Reference	88
5.9.1	Detailed Description	88
5.9.2	Member Data Documentation	88
5.9.2.1	roughness	89
5.9.2.2	xcoordinate	89

5.9.2.3	zcoordinate	89
6	File Documentation	91
6.1	dllOvertopping.f90 File Reference	91
6.1.1	Detailed Description	92
6.2	factorModuleOvertopping.f90 File Reference	92
6.2.1	Detailed Description	93
6.3	formulaModuleOvertopping.f90 File Reference	93
6.3.1	Detailed Description	94
6.4	geometryModuleOvertopping.f90 File Reference	94
6.4.1	Detailed Description	95
6.5	mainModuleOvertopping.f90 File Reference	95
6.5.1	Detailed Description	96
6.6	ModuleLogging.f90 File Reference	96
6.6.1	Detailed Description	96
6.7	omkeerVariantModule.f90 File Reference	96
6.7.1	Detailed Description	97
6.8	overtoppingInterface.f90 File Reference	97
6.8.1	Detailed Description	97
6.9	OvertoppingMessages.f90 File Reference	97
6.9.1	Detailed Description	98
6.10	typeDefinitionsOvertopping.f90 File Reference	98
6.10.1	Detailed Description	100
6.11	waveRunup.f90 File Reference	100
6.11.1	Detailed Description	100
6.12	zFunctionsOvertopping.f90 File Reference	100
6.12.1	Detailed Description	101
Index		103

Chapter 1

Modules Index

1.1 Modules List

Here is a list of all modules with brief descriptions:

dllovertopping	Main entry for the dll DikesOvertopping	7
factormoduleovertopping	Functions for the slope angle and influence factors	19
formulamoduleovertopping	Core computations for Dikes Overtopping	22
geometrymoduleovertopping	Core computations related to the geometry	31
mainmoduleovertopping	Core computations for Dikes Overtopping	43
modulelogging	Steering the extra logging	49
omkeervariantmodule	Module for the 'omkeerVariant'	50
overtoppinginterface	Module for the interface of dllOvertopping	56
overtoppingmessages	Module for the messages in the overtopping dll, in Dutch or English	56
typedefinitionsovertopping	Type definitions for Dikes Overtopping	60
waverunup	Iteration procedure for 2% wave runup	64
zfunctionsovertopping	Module for the Limit State Functions (Z-functions) for wave overtopping	68

Chapter 2

Data Type Index

2.1 Class List

Here are the data types with brief descriptions:

overtoppinginterface::overtoppinggeometrytype	75
overtoppinginterface::overtoppinggeometrytypef	77
modulelogging::tlogging	
TLogging: structure for steering the logging	78
omkeervariantmodule::tomkeer	79
typedefinitionsovertopping::tpgeometry	
TpGeometry: structure with geometry data	80
typedefinitionsovertopping::tpload	
TpLoad: structure with load parameters	83
typedefinitionsovertopping::tpovertopping	
TpOvertopping: structure with overtopping results	84
typedefinitionsovertopping::tpovertoppinginput	
OvertoppingModelFactors: C-structure with model factors	86
overtoppinginterface::tpprofilecoordinate	88

Chapter 3

File Index

3.1 File List

Here is a list of all files with brief descriptions:

dllOvertopping.f90	Main entry for the dll DikesOvertopping FUNCTIONS/SUBROUTINES exported from dll↔ Overtopping.dll:	91
factorModuleOvertopping.f90	This file contains a module with functions for the slope angle and influence factors	92
formulaModuleOvertopping.f90	This file contains a module with the core computations for Dikes Overtopping	93
geometryModuleOvertopping.f90	This file contains a module with the core computations for Dikes Overtopping related to the geometry	94
mainModuleOvertopping.f90	This file contains a module with the core computations for Dikes Overtopping	95
ModuleLogging.f90	Module for steering the extra logging	96
omkeerVariantModule.f90	This file contains the omkeerVariant	96
overtoppingInterface.f90	This file contains the parameters and types (structs) as part of the interface to and from dll↔ Overtopping	97
OvertoppingMessages.f90	This file contains the messages in the overtopping dll, in Dutch or English	97
typeDefinitionsOvertopping.f90	This file contains a module with the type definitions for Dikes Overtopping	98
waveRunup.f90	This file contains a module with the iteration procedure for 2% wave runup	100
zFunctionsOvertopping.f90	This file contains the limit state functions for wave overtopping within VTV	100

Chapter 4

Module Documentation

4.1 dllovertopping Module Reference

Main entry for the dll DikesOvertopping.

Functions/Subroutines

- subroutine, public [calculateqo](#) (load, geometryInput, dikeHeight, modelFactors, overtopping, success, error↵
Text, verbosity, logFile)
*Subroutine that calculates the discharge needed for the Z-function DikesOvertopping Wrapper for calculateQoF↵
: convert C-like input structures to Fortran input structures.*
- subroutine, public [calculateqoj](#) (load, xcoords, ycoords, roughness, normal, npoints, dikeHeight, model↵
Factors, output, succes, errorMessage)
Subroutine that calculates the discharge Wrapper for calculateQoF: convert basic types to Fortran input structures.
- subroutine, public [calculateqof](#) (load, geometryF, dikeHeight, modelFactors, overtopping, success, errorText, logging)
Subroutine that calculates the discharge needed for the Z-function DikesOvertopping.
- subroutine, public [calczvalue](#) (criticalOvertoppingRate, modelFactors, Qo, z, success, errorMessage)
Subroutine that calculates the Z-function DikesOvertopping based on the discharge calculated with calculateQoF.
- subroutine, public [validateinputc](#) (geometryInput, dikeHeight, modelFactors, success, errorText)
Subroutine that validates the geometry Wrapper for ValidateInputF: convert C-like input structures to Fortran input structures.
- subroutine, public [validateinputj](#) (x, y, roughness, normal, nPoints, dikeHeight, modelFactorsArray, success, errorText)
Subroutine that validates the geometry Wrapper for ValidateInputF: convert basic types to Fortran input structures.
- subroutine, public [validateinputf](#) (geometryF, dikeHeight, modelFactors, errorStruct)
Subroutine that validates the geometry.
- subroutine, public [omkeervariantj](#) (load, xcoords, ycoords, roughness, normal, npoints, givenDischarge, dikeHeight, modelFactors, output, succes, errorMessage)
Wrapper for omkeerVariantF: get dikeHeight by given discharge.
- subroutine, public [omkeervariantf](#) (load, geometryF, givenDischarge, dikeHeight, modelFactors, overtopping, success, errorText, logging)
Subroutine with omkeerVariant (get dikeHeight by given discharge)
- subroutine, public [setlanguage](#) (lang)
Subroutine that sets the language for error and validation messages.
- subroutine, public [getlanguage](#) (lang)
Subroutine that gets the language for error and validation messages.
- subroutine, public [versionnumber](#) (version)

Subroutine that delivers the version number.

- type(overtoppinggeometrytype) function [geometry_c_f](#) (geometryInput)

Private subroutine that converts geometry from c-pointer to fortran struct.

- subroutine [input_j_f](#) (x, y, roughness, normal, geometryF, modelFactorsJ, modelFactorsF, loadJ, loadF)

convert java input to Fortran input

Variables

- character, parameter [separationchar](#) = char(9)

use horizontal tab for separation

4.1.1 Detailed Description

Main entry for the dll DikesOvertopping.

4.1.2 Function/Subroutine Documentation

4.1.2.1 subroutine, public dllOvertopping::calculateqo (type(tpload), intent(in) *load*, type(overtoppinggeometrytype), intent(in) *geometryInput*, real(kind=wp), intent(in) *dikeHeight*, type(tpOvertoppinginput), intent(inout) *modelFactors*, type (tpOvertopping), intent(out) *overtopping*, logical, intent(out) *success*, character(len=*), intent(out) *errorText*, integer, intent(in) *verbosity*, character(len=*), intent(in) *logFile*)


Subroutine that calculates the discharge needed for the Z-function DikesOvertopping Wrapper for calculateQoF: convert C-like input structures to Fortran input structures.

Parameters

in	<i>geometryinput</i>	struct with geometry and roughness as c-pointers
in	<i>load</i>	struct with waterlevel and wave parameters
in	<i>dikeheight</i>	dike height
in, out	<i>modelfactors</i>	struct with modelfactors
out	<i>overtopping</i>	structure with overtopping results
out	<i>success</i>	flag for success
out	<i>errortext</i>	error message (only set if not successful)
in	<i>verbosity</i>	level of verbosity
in	<i>logfile</i>	filename of logfile

Definition at line 71 of file dllOvertopping.f90.

Here is the call graph for this function:



4.1.2.2 subroutine, public dllovertopping::calculateqof (type(tpload), intent(in) *load*, type(overtoppinggeometrytypef), intent(in) *geometryF*, real(kind=wp), intent(in) *dikeHeight*, type(tpovertoppinginput), intent(inout) *modelFactors*, type(tpovertopping), intent(out) *overtopping*, logical, intent(out) *success*, character(len=*) , intent(out) *errorText*, type(tlogging), intent(in) *logging*)


Subroutine that calculates the discharge needed for the Z-function DikesOvertopping.

Parameters


in	<i>geometryf</i>	struct with geometry and roughness
in	<i>load</i>	struct with waterlevel and wave parameters
in	<i>dikeheight</i>	dike height
in, out	<i>modelfactors</i>	struct with modelFactors
out	<i>overtopping</i>	structure with overtopping results
out	<i>success</i>	flag for success
out	<i>errortext</i>	error message (only set if not successful)
in	<i>logging</i>	logging struct

Definition at line 144 of file dllovertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.1.2.3 subroutine, public dllovertopping::calculateqoj (real(kind=wp), dimension(4), intent(in) *load*, real(kind=wp), dimension(npoints), intent(in) *xcoords*, real(kind=wp), dimension(npoints), intent(in) *ycoords*, real(kind=wp), dimension(npoints-1), intent(in) *roughness*, real(kind=wp), intent(in) *normal*, integer, intent(in) *npoints*, real(kind=wp), intent(in) *dikeHeight*, real(kind=wp), dimension(8), intent(in) *modelFactors*, real(kind=wp), dimension(2), intent(out) *output*, logical, intent(out) *succes*, character(len=256), intent(out) *errorMessage*)

Subroutine that calculates the discharge Wrapper for calculateQoF: convert basic types to Fortran input structures.


Parameters

in	<i>npoints</i>	the number of coordinates
in	<i>dikeheight</i>	dike height
in	<i>normal</i>	dike normal
out	<i>succes</i>	flag for success
out	<i>errormessage</i>	error message (only set if not successful)

in	<i>load</i>	input load (wl and 3 wave numbers)
in	<i>xcoords</i>	the x coordinates
in	<i>ycoords</i>	the y coordinates
in	<i>roughness</i>	the roughness at sections
in	<i>modelfactors</i>	the overtopping modelfactors
out	<i>output</i>	output array: 1: Qo; 2: Z2

Definition at line 103 of file dllovertopping.f90.

Here is the call graph for this function:



4.1.2.4 subroutine, public dllovertopping::calcvalue (real(kind=wp), intent(in) *criticalOvertoppingRate*, type(tpovertoppinginput), intent(inout) *modelFactors*, real(kind=wp), intent(in) *Qo*, real(kind=wp), intent(out) *z*, logical, intent(out) *success*, character(len=*), intent(out) *errorMessage*)


Subroutine that calculates the Z-function DikesOvertopping based on the discharge calculated with calculateQoF.

Parameters

in	<i>criticalovertoppingrate</i>	critical overtoppingrate
in, out	<i>modelfactors</i>	struct with modelfactors
in	<i>qo</i>	calculated discharge
out	<i>z</i>	z value
out	<i>errormessage</i>	error message (only if not successful)
out	<i>success</i>	flag for success

Definition at line 175 of file dllovertopping.f90.

Here is the call graph for this function:



4.1.2.5 `type(overtoppinggeometrytype) function dllovertopping::geometry_c_f (type(overtoppinggeometrytype), intent(in)
geometryInput) [private]`

Private subroutine that converts geometry from c-pointer to fortran struct.

Parameters


<i>in</i>	<i>geometryinput</i>	struct with geometry and roughness as c-pointers
-----------	----------------------	--------------------------------------------------

Returns

fortran struct with geometry and roughness

Definition at line 501 of file dllovertopping.f90.

Here is the caller graph for this function:



4.1.2.6 subroutine, public dllovertopping::getlanguage (character(len=*), intent(out) lang)

Subroutine that gets the language for error and validation messages.


Definition at line 467 of file dllovertopping.f90.

4.1.2.7 subroutine dllovertopping::input_j_f (real(kind=wp), dimension(:), intent(in) x, real(kind=wp), dimension(:), intent(in) y, real(kind=wp), dimension(:), intent(in) roughness, real(kind=wp), intent(in) normal, type(overtoppinggeometrytypef), intent(out) geometryF, real(kind=wp), dimension(:), intent(in) modelFactorsJ, type(tpovertoppinginput), intent(out) modelFactorsF, real(kind=wp), dimension(:), intent(in), optional loadJ, type(tpload), intent(out), optional loadF)

convert java input to Fortran input

Definition at line 524 of file dllovertopping.f90.

Here is the caller graph for this function:



4.1.2.8 subroutine, public dllovertopping::omkeervariantf (type(tpload), intent(in) *load*, type(overtoppinggeometrytypef),
intent(in) *geometryF*, real(kind=wp), intent(in) *givenDischarge*, real(kind=wp), intent(out) *dikeHeight*,
type(tpovertoppinginput), intent(inout) *modelFactors*, type (tpovertopping), intent(inout) *overtopping*, logical,
intent(out) *success*, character(len=*), intent(out) *errorText*, type(tlogging), intent(in) *logging*)


Subroutine with omkeerVariant (get dikeHeight by given discharge)

Parameters

in	<i>geometryf</i>	struct with geometry and roughness
in	<i>load</i>	struct with waterlevel and wave parameters
in	<i>givedischarge</i>	discharge to iterate to
out	<i>dikeheight</i>	dike height
in,out	<i>modelfactors</i>	struct with modelFactors
in,out	<i>overtopping</i>	structure with overtopping results
out	<i>success</i>	flag for success
out	<i>errortext</i>	error message (only set if not successful)
in	<i>logging</i>	logging struct

Definition at line 431 of file dllovertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.1.2.9 subroutine, public dllovertopping::omkeervariantj (real(kind=wp), dimension(4), intent(in) *load*, real(kind=wp), dimension(npoin), intent(in) *xcoords*, real(kind=wp), dimension(npoin), intent(in) *ycoords*, real(kind=wp), dimension(npoin-1), intent(in) *roughness*, real(kind=wp), intent(in) *normal*, integer, intent(in) *npoin*, real(kind=wp), intent(in) *givenDischarge*, real(kind=wp), intent(out) *dikeHeight*, real(kind=wp), dimension(8), intent(in) *modelFactors*, real(kind=wp), dimension(2), intent(out) *output*, logical, intent(out) *succes*, character(len=256), intent(out) *errorMessage*)


Wrapper for omkeerVariantF: get dikeHeight by given discharge.

Parameters

in	<i>npoints</i>	number of coordinates
in	<i>givendischarge</i>	input discharge
out	<i>dikeheight</i>	dike height
in	<i>normal</i>	dike normal
out	<i>succes</i>	flag for success
out	<i>errormessage</i>	error message (only set if not successful)
in	<i>load</i>	input load (wl, and 3 wave parameters)
in	<i>xcoords</i>	the x-coordinates
in	<i>ycoords</i>	the y-coordinates
in	<i>roughness</i>	the roughness at sections
in	<i>modelfactors</i>	the overtopping modelfactors
out	<i>output</i>	output array: 1: Z2; 2: Qo

Definition at line 388 of file dllovertopping.f90.

Here is the call graph for this function:



4.1.2.10 subroutine, public dllovertopping::setlanguage (character(len=*), intent(in) lang)

Subroutine that sets the language for error and validation messages.

Definition at line 454 of file dllovertopping.f90.

4.1.2.11 subroutine, public dllovertopping::validateinputc (type(overtoppinggeometrytype), intent(in) geometryInput, real(kind=wp), intent(in) dikeHeight, type(tpovertoppinginput), intent(inout) modelFactors, logical, intent(out) success, character(len=*), intent(out) errorText)

Subroutine that validates the geometry Wrapper for ValidateInputF: convert C-like input structures to Fortran input structures.


Parameters

in	<i>geometryinput</i>	struct with geometry and roughness as c-pointers
in	<i>dikeheight</i>	dike height
in, out	<i>modelfactors</i>	struct with modelfactors
out	<i>success</i>	flag for success

out	errortext	error message (only set if not successful)
-----	-----------	--------------------------------------------

Definition at line 195 of file dllovertopping.f90.

Here is the call graph for this function:



4.1.2.12 subroutine, public dlovertopping::validateinputf (type(overtoppinggeometrytypef), intent(in) *geometryF*, real(kind=wp), intent(in) *dikeHeight*, type(tpovertoppinginput), intent(inout) *modelFactors*, type(terrormessages), intent(inout) *errorStruct*)


Subroutine that validates the geometry.

Parameters


in	<i>geometryf</i>	struct with geometry and roughness
in	<i>dikeheight</i>	dike height
in, out	<i>modelFactors</i>	struct with modelFactors
in, out	<i>errorstruct</i>	error message (only set if not successful)

Definition at line 308 of file dllovertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.1.2.13 subroutine, public dlovertopping::validateinputf (real(kind=wp), dimension(npoints), intent(in) *x*, real(kind=wp), dimension(npoints), intent(in) *y*, real(kind=wp), dimension(npoints-1), intent(in) *roughness*, real(kind=wp), intent(in) *normal*, integer, intent(in) *nPoints*, real(kind=wp), intent(in) *dikeHeight*, real(kind=wp), dimension(8), intent(in) *modelFactorsArray*, logical, intent(out) *success*, character(len=256), intent(out) *errorText*)


Subroutine that validates the geometry Wrapper for ValidateInputF: convert basic types to Fortran input structures.

Parameters

in	<i>npoints</i>	number of profile points
in	<i>x</i>	x coordinates of profile
in	<i>y</i>	y coordinates of profile
in	<i>roughness</i>	roughness of profile sections
in	<i>normal</i>	dike normal
in	<i>dikeheight</i>	dike height
in	<i>modelfactorsarray</i>	array with modelfactors
out	<i>success</i>	flag for success
out	<i>errortext</i>	error message (only set if not successful)

Definition at line 246 of file dllOvertopping.f90.

Here is the call graph for this function:



4.1.2.14 subroutine, public dlovertopping::versionnumber (character(len=*), intent(out) *version*)

Subroutine that delivers the version number.

Parameters

out	version	version number
-----	---------	----------------

Definition at line 479 of file dllOvertopping.f90.

4.1.3 Variable Documentation

4.1.3.1 character, parameter dllovertopping::separationchar = char(9)

use horizontal tab for separation

Definition at line 61 of file dllOvertopping.f90.

4.2 factormoduleovertopping Module Reference

functions for the slope angle and influence factors

Functions/Subroutines

- subroutine, public [calculatetanalpha](#) (h, Hm0, z2, geometry, tanAlpha, succes, errorMessage)
calculateTanAlpha representative slope angle
- subroutine, public [calculategammabeta](#) (Hm0, Tm_10, beta, gammaBeta_z, gammaBeta_o)
calculateGammaBeta influence factor angle of wave attack
- subroutine, public [calculategammabf](#) (h, ksi0, ksi0Limit, gammaB, z2, geometry, gammaF, succes, errorMessage)
calculateGammaF influence factor roughness
- subroutine, public [calculategammab](#) (h, Hm0, z2, geometry, gammaB, succes, errorMessage)
calculateGammaB influence factor berms

4.2.1 Detailed Description

functions for the slope angle and influence factors

4.2.2 Function/Subroutine Documentation

- 4.2.2.1 subroutine, public factormoduleovertopping::calculategammab (real(kind=wp), intent(in) *h*, real(kind=wp), intent(in) *Hm0*, real(kind=wp), intent(in) *z2*, type(tpgeometry), intent(in) *geometry*, real(kind=wp), intent(out) *gammaB*, logical, intent(out) *succes*, character(len=*), intent(out) *errorMessage*)

calculateGammaB influence factor berms


Parameters

in	<i>h</i>	local water level (m+NAP)
in	<i>hm0</i>	significant wave height (m)
in	<i>z2</i>	2% wave run-up (m)
in	<i>geometry</i>	structure with geometry data
out	<i>gammab</i>	influence factor berms

out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 317 of file factorModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.2.2.2 subroutine, public factorModuleOvertopping::calculategammabeta (real(kind=wp), intent(inout) *Hm0*, real(kind=wp), intent(inout) *Tm_10*, real(kind=wp), intent(in) *beta*, real(kind=wp), intent(out) *gammaBeta_z*, real(kind=wp), intent(out) *gammaBeta_o*)

calculateGammaBeta influence factor angle of wave attack

Parameters

in, out	<i>hm0</i>	significant wave height (m)
in, out	<i>tm_10</i>	spectral wave period (s)
in	<i>beta</i>	angle of wave attack (degree)
out	<i>gammabeta_z</i>	influence factor angle of wave attack 2% wave run-up
out	<i>gammabeta_o</i>	influence factor angle of wave attack overtopping

Definition at line 139 of file factorModuleOvertopping.f90.

Here is the caller graph for this function:




4.2.2.3 subroutine, public factorModuleOvertopping::calculategammaf (real(kind=wp), intent(in) *h*, real(kind=wp), intent(in) *ksi0*, real(kind=wp), intent(in) *ksi0Limit*, real(kind=wp), intent(in) *gammaB*, real(kind=wp), intent(in) *z2*, type(tpgeometry), intent(in) *geometry*, real(kind=wp), intent(out) *gammaF*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)

calculateGammaF influence factor roughness

out	<i>tanalpha</i>	representative slope angle
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 60 of file factorModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.3 formulamoduleovertopping Module Reference

the core computations for Dikes Overtopping

Functions/Subroutines

- subroutine, public [calculatewaverunup](#) (Hm0, ksi0, ksi0Limit, gammaB, gammaF, gammaBeta, modelFactors, z2, succes, errorMessage)
calculateWaveRunup: calculate wave runup
- subroutine, public [calculatewaveovertoppingdischarge](#) (h, Hm0, tanAlpha, gammaB, gammaF, gammaBeta, ksi0, hCrest, modelFactors, Qo, succes, errorMessage)
calculateWaveOvertoppingDischarge: calculate the wave overtopping discharge
- subroutine, public [calculatewavelength](#) (Tm_10, L0)
calculateWaveLength: calculate the wave length
- subroutine, public [calculatewavesteepness](#) (Hm0, Tm_10, s0, succes, errorMessage)
calculateWaveSteepness: calculate the wave steepness
- subroutine, public [calculatebreakerparameter](#) (tanAlpha, s0, ksi0, succes, errorMessage)
calculateBreakerParameter: calculate the breaker parameter
- subroutine, public [calculateanglewaveattack](#) (phi, psi, beta)
calculateAngleWaveAttack: calculate the angle of wave attack
- subroutine, public [calculatebreakerlimit](#) (gammaB, ksi0Limit, succes, errorMessage)
calculateBreakerLimit: calculate the breaker limit

- subroutine, public [adjustinfluencefactors](#) (gammaB, gammaF, gammaBeta, gammaBetaType, ksi0, ksi0Limit, succes, errorMessage)
adjustInfluenceFactors: adjust the influence factors
- subroutine [realrootscubicfunction](#) (a, b, c, d, N, x, succes, errorMessage)
realRootsCubicFunction: calculate the roots of a cubic function
- subroutine [rootsgeneralcubic](#) (a, b, c, d, z, succes, errorMessage)
rootsGeneralCubic: calculate the roots of a generic cubic function
- subroutine [rootsdepressedcubic](#) (p, q, z)
rootsDepressedCubic: calculate the roots of a depressed cubic function
- subroutine [cubicroots](#) (z, roots)
cubicRoots: calculate the roots of a cubic function
- logical function, public [isequalreal](#) (x1, x2)
isEqualReal: are two reals (almost) equal
- logical function, public [isequalzero](#) (x)
isEqualZero: is a real (almost) zero

4.3.1 Detailed Description

the core computations for Dikes Overtopping

4.3.2 Function/Subroutine Documentation

4.3.2.1 subroutine, public formulamoduleovertopping::adjustinfluencefactors (real(kind=wp), intent(inout) *gammaB*, real(kind=wp), intent(inout) *gammaF*, real(kind=wp), intent(inout) *gammaBeta*, integer, intent(in) *gammaBetaType*, real(kind=wp), intent(in) *ksi0*, real(kind=wp), intent(in) *ksi0Limit*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)


adjustInfluenceFactors: adjust the influence factors

Parameters

in, out	<i>gammab</i>	influence factor berms
in, out	<i>gammaf</i>	influence factor roughness
in, out	<i>gammabeta</i>	influence factor angle of wave attack
in	<i>gammabetatype</i>	type influence factor angle of wave attack: 1 = wave run-up, 2 = overtopping
in	<i>ksi0</i>	breaker parameter
in	<i>ksi0limit</i>	limit value breaker parameter
out	<i>succes</i>	flag for succes
out	<i>errorMessage</i>	error message

Definition at line 403 of file formulaModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.3.2.2 subroutine, public formulamoduleovertopping::calculateanglewaveattack (real(kind=wp), intent(in) *phi*, real(kind=wp), intent(in) *psi*, real(kind=wp), intent(out) *beta*)

calculateAngleWaveAttack: calculate the angle of wave attack

Parameters

in	<i>phi</i>	wave direction (degree)
in	<i>psi</i>	dike normal (degree)
out	<i>beta</i>	angle of wave attack (degree)

Definition at line 309 of file formulaModuleOvertopping.f90.

Here is the caller graph for this function:




4.3.2.3 subroutine, public formulamoduleovertopping::calculatebreakerlimit (real(kind=wp), intent(in) *gammaB*, real(kind=wp), intent(out) *ksi0Limit*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)

calculateBreakerLimit: calculate the breaker limit

Definition at line 332 of file formulaModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.3.2.4 subroutine, public formulamoduleovertopping::calculatebreakerparameter (real(kind=wp), intent(in) *tanAlpha*, real(kind=wp), intent(in) *s0*, real(kind=wp), intent(out) *ksi0*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)


calculateBreakerParameter: calculate the breaker parameter

Parameters

in	<i>tanalpha</i>	representative slope angle
in	<i>s0</i>	wave steepness
out	<i>ksi0</i>	breaker parameter
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 268 of file formulaModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.3.2.5 subroutine, public formulamoduleovertopping::calculatewavelength (real(kind=wp), intent(in) *Tm_10*, real(kind=wp), intent(out) *L0*)

calculateWaveLength: calculate the wave length

Parameters

in	<i>tm_10</i>	spectral wave period (s)
out	<i>l0</i>	wave length (m)

Definition at line 205 of file formulaModuleOvertopping.f90.

Here is the caller graph for this function:



4.3.2.6 subroutine, public formulamoduleovertopping::calculatewaveovertoppingdischarge (real(kind=wp), intent(in) *h*, real(kind=wp), intent(in) *Hm0*, real(kind=wp), intent(in) *tanAlpha*, real(kind=wp), intent(in) *gammaB*, real(kind=wp), intent(in) *gammaF*, real(kind=wp), intent(in) *gammaBeta*, real(kind=wp), intent(in) *ksi0*, real(kind=wp), intent(in) *hCrest*, type(tpovertoppinginput), intent(in) *modelFactors*, real(kind=wp), intent(out) *Qo*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)


calculateWaveOvertoppingDischarge: calculate the wave overtopping discharge

Parameters

in	<i>h</i>	local water level (m+NAP)
in	<i>hm0</i>	significant wave height (m)
in	<i>tanalpha</i>	representative slope angle
in	<i>gammab</i>	influence factor berms
in	<i>gammaf</i>	influence factor roughness
in	<i>gammabeta</i>	influence factor angle of wave attack
in	<i>ksi0</i>	breaker parameter
in	<i>hcrest</i>	crest level (m+NAP)
in	<i>modelfactors</i>	structure with model factors
out	<i>qo</i>	wave overtopping discharge (l/m per s)
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 108 of file formulaModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.3.2.7 subroutine, public formulaModuleOvertopping::calculateWaveRunup (real(kind=wp), intent(in) *Hm0*, real(kind=wp), intent(in) *ksi0*, real(kind=wp), intent(in) *ksi0Limit*, real(kind=wp), intent(inout) *gammaB*, real(kind=wp), intent(inout) *gammaF*, real(kind=wp), intent(inout) *gammaBeta*, type(tpOvertoppingInput), intent(in) *modelFactors*, real(kind=wp), intent(out) *z2*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)

calculateWaveRunup: calculate wave runup


Parameters

in	<i>hm0</i>	significant wave height (m)
in	<i>ksi0</i>	breaker parameter
in	<i>ksi0limit</i>	limit value breaker parameter
in, out	<i>gammab</i>	influence factor berms
in, out	<i>gammaf</i>	influence factor roughness
in, out	<i>gammabeta</i>	influence factor angle of wave attack
in	<i>modelfactors</i>	structure with model factors
out	<i>z2</i>	2% wave run-up (m)


out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 59 of file formulaModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.3.2.8 subroutine, public formulamoduleovertopping::calculatewavesteepness (real(kind=wp), intent(in) *Hm0*, real(kind=wp), intent(in) *Tm_10*, real(kind=wp), intent(out) *s0*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)


calculateWaveSteepness: calculate the wave steepness

Parameters

in	<i>hm0</i>	significant wave height (m)
in	<i>tm_10</i>	spectral wave period (s)
out	<i>s0</i>	wave steepness
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 226 of file formulaModuleOvertopping.f90.

Here is the call graph for this function:



Parameters

in	x	real number
----	---	-------------

Definition at line 716 of file formulaModuleOvertopping.f90.

Here is the caller graph for this function:



4.3.2.12 subroutine formulamoduleovertopping::realrootscubicfunction (real(kind=wp), intent(in) *a*, real(kind=wp), intent(in) *b*, real(kind=wp), intent(in) *c*, real(kind=wp), intent(in) *d*, integer, intent(out) *N*, real(kind=wp), dimension(3), intent(out) *x*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*) [private]


realRootsCubicFunction: calculate the roots of a cubic function

Parameters

in	<i>a</i>	coefficient a cubic function
in	<i>b</i>	coefficient b cubic function
in	<i>c</i>	coefficient c cubic function
in	<i>d</i>	coefficient d cubic function
out	<i>n</i>	number of real roots cubic function
out	<i>x</i>	real roots cubic function
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 501 of file formulaModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.3.2.13 subroutine formulamoduleovertopping::rootsdepressedcubic (real(kind=wp), intent(in) *p*, real(kind=wp), intent(in) *q*, double complex, dimension(3), intent(out) *z*) [private]


rootsDepressedCubic: calculate the roots of a depressed cubic function

Parameters

in	p	coefficient p depressed cubic
in	q	coefficient q depressed cubic
out	z	roots depressed cubic

Definition at line 610 of file formulaModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.3.2.14 subroutine `formulaModuleOvertopping::rootsgeneralcubic` (`real(kind=wp), intent(in) a`, `real(kind=wp), intent(in) b`, `real(kind=wp), intent(in) c`, `real(kind=wp), intent(in) d`, `double complex, dimension(3), intent(out) z`, `logical, intent(out) succes`, `character(len=*)`, `intent(out) errorMessage`) [`private`]


`rootsGeneralCubic`: calculate the roots of a generic cubic function

Parameters

in	a	coefficients a cubic function
in	b	coefficients b cubic function
in	c	coefficients c cubic function
in	d	coefficients d cubic function
out	z	roots cubic function
out	<i>succes</i>	flag for succes
out	<i>errorMessage</i>	error message

Definition at line 557 of file formulaModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.4 geometrymoduleovertopping Module Reference

core computations related to the geometry

Functions/Subroutines

- subroutine, public [checkcrosssection](#) (psi, nCoordinates, xCoordinates, yCoordinates, roughnessFactors, succes, errorMessage)
checkCrossSection: check cross section
- subroutine, public [initializegeometry](#) (psi, nCoordinates, xCoordinates, yCoordinates, roughnessFactors, geometry, succes, errorMessage)
initializeGeometry: initialize the geometry
- subroutine, public [allocatevectorsgeometry](#) (nCoordinates, geometry, succes, errorMessage)
allocateVectorsGeometry: allocate the geometry vectors
- subroutine, public [deallocategeometry](#) (geometry)
deallocateGeometry: deallocate the geometry vectors
- subroutine, public [calculatesegmentsslopes](#) (geometry, succes, errorMessage)
calculateSegmentSlopes: calculate the segment slopes
- subroutine, public [determinesegmenttypes](#) (geometry, succes, errorMessage)
determineSegmentTypes: determine the segment types
- subroutine, public [copygeometry](#) (geometry, geometryCopy, succes, errorMessage)
copyGeometry: copy a geometry structure
- subroutine, public [mergesquentialberms](#) (geometry, geometryMergedBerms, succes, errorMessage)
mergeSequentialBerms: merge sequential berms
- subroutine, public [adjustnonhorizontalberms](#) (geometry, geometryFlatBerms, succes, errorMessage)
adjustNonHorizontalBerms: adjust non-horizontal berms
- subroutine, public [removeberms](#) (geometry, geometryNoBerms, succes, errorMessage)
removeBerms: remove berms
- subroutine, public [removedikesegments](#) (geometry, index, geometryAdjusted, succes, errorMessage)
removeDikeSegments: remove dike segments
- subroutine, public [splitcrosssection](#) (geometry, L0, NwideBerms, geometrysectionB, geometrysectionF, succes, errorMessage)
splitCrossSection: split a cross section
- subroutine, public [calculatehorzlengths](#) (geometry, yLower, yUpper, horzLengths, succes, errorMessage)
calculateHorzLengths: calculate horizontal lengths
- subroutine, public [calculatehorzdistance](#) (geometry, yLower, yUpper, dx, succes, errorMessage)
calculateHorzDistance: calculate horizontal distance
- subroutine, public [basicgeometrytest](#) (geometryF, success, errorStruct)
basicGeometryTest: test the input geometry (the adjusted geometry is checked elsewhere)

4.4.1 Detailed Description

core computations related to the geometry

4.4.2 Function/Subroutine Documentation

- 4.4.2.1 subroutine, public geometrymoduleovertopping::adjustnonhorizontalberms (type (tpgeometry), intent(in) *geometry*, type (tpgeometry), intent(out) *geometryFlatBerms*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)

adjustNonHorizontalBerms: adjust non-horizontal berms

Here is the caller graph for this function:



4.4.2.3 subroutine, public geometrymoduleovertopping::basicgeometrytest (type(overtoppinggeometrytypef), intent(in) *geometryF*, logical, intent(out) *success*, type(terrormessages), intent(inout) *errorStruct*)


basicGeometryTest: test the input geometry (the adjusted geometry is checked elsewhere)

Parameters

in	<i>geometryf</i>	struct with geometry and roughness
in, out	<i>errorstruct</i>	error message (only set if not successful)
out	<i>success</i>	success flag

Definition at line 1074 of file geometryModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.4.2.4 subroutine, public geometrymoduleovertopping::calculatehorzdistance (type(tpgeometry), intent(in) *geometry*, real(kind=wp), intent(in) *yLower*, real(kind=wp), intent(in) *yUpper*, real(kind=wp), intent(out) *dx*, logical, intent(out) *success*, character(len=*), intent(out) *errorMessage*)

calculateHorzDistance: calculate horizontal distance


Parameters

in	<i>geometry</i>	structure with geometry data
----	-----------------	------------------------------

in	<i>ylower</i>	y-coordinate lower bound (m+NAP)
in	<i>yupper</i>	y-coordinate upper bound (m+NAP)
out	<i>dx</i>	horizontal distance between bounds (m)
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 1025 of file geometryModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.4.2.5 subroutine, public geometrymoduleovertopping::calculatehorzlengths (type (tpgeometry), intent(in) *geometry*, real(kind=wp), intent(in) *yLower*, real(kind=wp), intent(in) *yUpper*, real(kind=wp), dimension(geometry%ncoordinates-1), intent(out) *horzLengths*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)


calculateHorzLengths: calculate horizontal lengths

Parameters


in	<i>geometry</i>	structure with geometry data
in	<i>ylower</i>	y-coord. lower bound (m+NAP)
in	<i>yupper</i>	y-coord. upper bound (m+NAP)
out	<i>horzlengths</i>	horizontal lengths segments (m)
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 929 of file geometryModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.4.2.6 subroutine, public geometrymoduleovertopping::calculatesegmentSlopes (type (tpgeometry), intent(inout) *geometry*, logical, intent(out) *succes*, character(len=*), intent(out) *errorMessage*)


calculateSegmentSlopes: calculate the segment slopes

Parameters

in, out	<i>geometry</i>	structure with geometry data
out	<i>succes</i>	flag for succes
out	<i>errorMessage</i>	error message

Definition at line 308 of file geometryModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.4.2.7 subroutine, public geometrymoduleovertopping::checkcrosssection (real(kind=wp), intent(in) *psi*, integer, intent(in) *nCoordinates*, real(kind=wp), dimension (ncoordinates), intent(in) *xCoordinates*, real(kind=wp), dimension (ncoordinates), intent(in) *yCoordinates*, real(kind=wp), dimension(ncoordinates-1), intent(in) *roughnessFactors*, logical, intent(out) *succes*, character(len=*), intent(out) *errorMessage*)

checkCrossSection: check cross section


Parameters

in	<i>psi</i>	dike normal (degrees)
in	<i>ncoordinates</i>	number of coordinates
in	<i>xcoordinates</i>	x-coordinates (m)

in	<i>ycoordinates</i>	y-coordinates (m+NAP)
in	<i>roughnessfactors</i>	roughness factors
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 59 of file geometryModuleOvertopping.f90.

Here is the call graph for this function:



4.4.2.8 subroutine, public geometryModuleOvertopping::copygeometry (type (tpgeometry), intent(in) *geometry*, type (tpgeometry), intent(inout) *geometryCopy*, logical, intent(out) *succes*, character(len=*), intent(inout) *errorMessage*)


copyGeometry: copy a geometry structure

Parameters

in	<i>geometry</i>	structure with geometry data
in, out	<i>geometrycopy</i>	structure with geometry data copy
out	<i>succes</i>	succes flag
in, out	<i>errormessage</i>	error message, only set in case of error

Definition at line 411 of file geometryModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.4.2.9 subroutine, public geometrymoduleovertopping::deallocategeometry (type (tpgeometry), intent(inout) *geometry*)

deallocateGeometry: deallocate the geometry vectors

4.4.2.11 subroutine, public geometrymoduleovertopping::initializegeometry (real(kind=wp), intent(in) *psi*, integer, intent(in) *nCoordinates*, real(kind=wp), dimension (ncoordinates), intent(in) *xCoordinates*, real(kind=wp), dimension (ncoordinates), intent(in) *yCoordinates*, real(kind=wp), dimension(ncoordinates-1), intent(in) *roughnessFactors*, type (tpgeometry), intent(out) *geometry*, logical, intent(out) *succes*, character(len=*), intent(out) *errorMessage*)


initializeGeometry: initialize the geometry

Parameters


in	<i>psi</i>	dike normal (degree)
in	<i>ncoordinates</i>	number of coordinates
in	<i>xcoordinates</i>	x-coordinates (m)
in	<i>ycoordinates</i>	y-coordinates (m+NAP)
in	<i>roughnessfactors</i>	roughness factors
out	<i>geometry</i>	structure with geometry data
out	<i>succes</i>	flag for succes
out	<i>errorMessage</i>	error message

Definition at line 170 of file geometryModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.4.2.12 subroutine, public geometrymoduleovertopping::mergesequentialberms (type (tpgeometry), intent(in) *geometry*, type (tpgeometry), intent(inout) *geometryMergedBerms*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)

mergeSequentialBerms: merge sequential berms


Parameters

in	<i>geometry</i>	structure with geometry data
----	-----------------	------------------------------

in, out	<i>geometrymergedberms</i>	geometry data with merged sequential berms
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 462 of file geometryModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.4.2.13 subroutine, public geometrymoduleovertopping::removeberms (type (tpgeometry), intent(in) *geometry*, type (tpgeometry), intent(out) *geometryNoBerms*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)


removeBerms: remove berms

Parameters

in	<i>geometry</i>	structure with geometry data
out	<i>geometrynoberms</i>	geometry data without berms
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 660 of file geometryModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.4.2.14 subroutine, public geometrymoduleovertopping::removedikesegments (type (tpgeometry), intent(in) *geometry*, integer, intent(in) *index*, type (tpgeometry), intent(out) *geometryAdjusted*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)


removeDikeSegments: remove dike segments

Parameters


in	<i>geometry</i>	structure with geometry data
in	<i>index</i>	index starting point new cross section
out	<i>geometryadjusted</i>	geometry data with removed dike segments
out	<i>succes</i>	flag for succes
out	<i>errorMessage</i>	error message

Definition at line 760 of file geometryModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.4.2.15 subroutine, public geometrymoduleovertopping::splitcrosssection (type (tpgeometry), intent(in) *geometry*, real(kind=wp), intent(in) *L0*, integer, intent(out) *NwideBerms*, type (tpgeometry), intent(out) *geometrysectionB*, type (tpgeometry), intent(out) *geometrysectionF*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)


splitCrossSection: split a cross section

Parameters

in	<i>geometry</i>	structure with geometry data
in	<i>l0</i>	wave length (m)
out	<i>nwideberms</i>	number of wide berms
out	<i>geometrysectionb</i>	geometry data with wide berms to ordinary berms
out	<i>geometrysectionf</i>	geometry data with wide berms to foreshores
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 824 of file geometryModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:




4.5 mainmoduleovertopping Module Reference

core computations for Dikes Overtopping

Functions/Subroutines

- subroutine, public [calculateovertopping](#) (geometry, load, modelFactors, overtopping, logging, succes, error←Message)
calculateOvertopping: calculate the overtopping
- subroutine, public [calculateovertoppingsection](#) (geometry, h, Hm0, Tm_10, L0, gammaBeta_z, gammaBeta←_o, modelFactors, overtopping, logging, succes, errorMessage)
calculateOvertoppingSection: calculate the overtopping for a section
- subroutine, public [calculatewaveovertopping](#) (geometry, h, Hm0, Tm_10, z2, gammaBeta_o, modelFactors, Qo, succes, errorMessage)
calculateWaveOvertopping: calculate wave overtopping
- subroutine [calculateovertoppingnegativefreeboard](#) (load, geometry, overtopping, succes, errorMessage)
calculateOvertoppingNegativeFreeboard: calculate overtopping in case of negative freeboard
- subroutine, public [interpolateresultssections](#) (geometry, L0, NwideBerms, overtoppingB, overtoppingF, overtopping, succes, errorMessage)
interpolateResultsSections: interpolate results for split cross sections
- subroutine, public [checkinputdata](#) (geometry, load, modelFactors, succes, errorMessage)

Here is the caller graph for this function:



```

4.5.2.2 subroutine mainmoduleovertopping::calculateovertoppingnegativefreeboard ( type (tpload), intent(in) load, type
(tpgeometry), intent(in) geometry, type (tpovertopping), intent(inout) overtopping, logical, intent(out) success,
character(len=*, intent(out) errorMessage ) [private]

```


calculateOvertoppingNegativeFreeboard: calculate overtopping in case of negative freeboard

Parameters

in	<i>geometry</i>	structure with geometry data
in	<i>load</i>	structure with load parameters
in, out	<i>overtopping</i>	structure with overtopping results
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 505 of file mainModuleOvertopping.f90.

Here is the call graph for this function:



```

4.5.2.3 subroutine, public mainmoduleovertopping::calculateovertoppingsection ( type(tpgeometry), intent(in) geometry,
real(kind=wp), intent(in) h, real(kind=wp), intent(in) Hm0, real(kind=wp), intent(in) Tm_10, real(kind=wp), intent(in) L0,
real(kind=wp), intent(inout) gammaBeta_z, real(kind=wp), intent(inout) gammaBeta_o, type(tpovertoppinginput),
intent(in) modelFactors, type(tpovertopping), intent(out) overtopping, type(tlogging), intent(in) logging, logical,
intent(out) succes, character(len=*) , intent(out) errorMessage )

```

calculateOvertoppingSection: calculate the overtopping for a section


Parameters

in	<i>geometry</i>	structure with geometry data
in	<i>h</i>	local water level (m+NAP)
in	<i>hm0</i>	significant wave height (m)
in	<i>tm_10</i>	spectral wave period (s)
in	<i>l0</i>	wave length (m)
in, out	<i>gammabeta_z</i>	influence angle wave attack wave run-up


in, out	<i>gammabeta_o</i>	influence angle wave attack overtopping
in	<i>modelfactors</i>	structure with model factors
out	<i>qo</i>	wave overtopping discharge (m ³ /m per s)
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 418 of file mainModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



```
4.5.2.5 subroutine, public mainmodule::checkinputdata ( type (tpgeometry), intent(in) geometry, type (tpload),
intent(in) load, type (tpovertoppinginput), intent(in) modelFactors, logical, intent(out) success, character(len=*),
intent(out) errorMessage )
```

checkInputdata: check the input data


Parameters

in	<i>geometry</i>	structure with geometry data
in	<i>load</i>	structure with load parameters
in	<i>modelfactors</i>	structure with model factors
out	<i>success</i>	flag for success

out	<i>errormessage</i>	error message
-----	---------------------	---------------

Definition at line 622 of file mainModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.5.2.6 subroutine, public mainmoduleovertopping::checkmodelfactors (type (tpovertoppinginput), intent(in) *modelFactors*, integer, intent(in) *dimErrMessage*, character(len=*), dimension(dimerrmessage), intent(out) *errorMessages*, integer, intent(out) *ierr*)


checkModelFactors: check the input data

Parameters


in	<i>modelfactors</i>	structure with model factors
in	<i>dimerrmessage</i>	max. number of error messages
out	<i>ierr</i>	number of errors found
out	<i>errormessages</i>	error message

Definition at line 684 of file mainModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.5.2.7 subroutine, public mainmoduleovertopping::interpolateresultssections (type (tpgeometry), intent(in) *geometry*, real(kind=wp), intent(in) *L0*, integer, intent(in) *NwideBerms*, type (tpovertopping), intent(in) *overtoppingB*, type (tpovertopping), intent(in) *overtoppingF*, type (tpovertopping), intent(out) *overtopping*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)


interpolateResultsSections: interpolate results for split cross sections

Parameters

in	<i>geometry</i>	structure with geometry data
in	<i>l0</i>	wave length (m)
in	<i>nwideberms</i>	number of wide berms
in	<i>overtoppingb</i>	structure with overtopping results ordinary berms
in	<i>overtoppingf</i>	structure with overtopping results foreshores
out	<i>overtopping</i>	structure with combined overtopping results
out	<i>succes</i>	flag for succes
out	<i>errorMessage</i>	error message

Definition at line 541 of file mainModuleOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.6 modulelogging Module Reference

steering the extra logging

Data Types

- type [tlogging](#)

TLogging: structure for steering the logging.

Variables

- integer, parameter `maxfilenamelen` = 256
maximum length of filename

4.6.1 Detailed Description

steering the extra logging

4.6.2 Variable Documentation

4.6.2.1 integer, parameter `modulelogging::maxfilenamelen` = 256

maximum length of filename

Definition at line 35 of file `ModuleLogging.f90`.

4.7 omkeervariantmodule Module Reference

Module for the 'omkeerVariant'.

Data Types

- type `tomkeer`

Functions/Subroutines

- subroutine, public `iteratetogivendischarge` (load, geometryF, givenDischarge, dikeHeight, modelFactors, overtopping, success, errorText, logging)
Subroutine with omkeerVariant.
- subroutine `iteratetogivendischargevalidprofile` (load, geometry, givenDischarge, dikeHeight, modelFactors, overtopping, logging, success, errorText)
Subroutine with iterateToGivenDischarge, with already checked profile.
- subroutine `checkifonberm` (geometry, load, modelFactors, overtopping, givenDischarge, dikeHeight, omkeer↔ Props, logging, iUp, iLow, dis1, dis2, minDikeHeight, maxDikeHeight, foundValue, success, errorText)

Variables

- real(kind=wp), parameter `toldischarge` = 1d-3
- real(kind=wp), parameter `toldikeheight` = 1d-3
- real(kind=wp), parameter `minzberm` = 0.1_wp

4.7.1 Detailed Description

Module for the 'omkeerVariant'.

4.7.2 Function/Subroutine Documentation


- 4.7.2.1 subroutine omkeervariantmodule::checkifonberm (type(tpgeometry), intent(in) *geometry*, type(tpload), intent(in) *load*, type(tpovertoppinginput), intent(inout) *modelfactors*, type(tpovertopping), intent(inout) *overtopping*, real(kind=wp), intent(in) *givenDischarge*, real(kind=wp), intent(inout) *dikeHeight*, type(tomkeer), intent(inout) *omkeerProps*, type(tlogging), intent(in) *logging*, integer, intent(in) *iUp*, integer, intent(in) *iLow*, real(kind=wp), intent(inout) *dis1*, real(kind=wp), intent(inout) *dis2*, real(kind=wp), intent(inout) *minDikeHeight*, real(kind=wp), intent(inout) *maxDikeHeight*, logical, intent(inout) *foundValue*, logical, intent(inout) *success*, character(len=*), intent(inout) *errorText*)

Parameters


in	<i>geometry</i>	internal structure with geometry data
in	<i>load</i>	struct with waterlevel and wave parameters
in,out	<i>modelfactors</i>	struct with modelFactors
in,out	<i>overtopping</i>	structure with overtopping results
in,out	<i>omkeerprops</i>	struct with derived properties
in	<i>logging</i>	logging struct
in	<i>iup</i>	upper bound on profile
in	<i>ilow</i>	lower bound on profile
in	<i>givendischarge</i>	discharge to iterate to
in,out	<i>dis1</i>	discharge at minDikeHeight
in,out	<i>dis2</i>	discharge at maxDikeHeight
in,out	<i>mindikeheight</i>	lower bound dike heigth
in,out	<i>maxdikeheight</i>	upper bound dike heigth
in,out	<i>dikeheight</i>	dike height
in,out	<i>foundvalue</i>	flag for early succesfull return
in,out	<i>success</i>	flag for success
in,out	<i>errortext</i>	error message (only set if not successful)

Definition at line 248 of file omkeerVariantModule.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.7.2.2 subroutine, public omkeervariantmodule::iteratetogivendischarge (type(tpload), intent(in) *load*,
type(overtoppinggeometrytypef), intent(in) *geometryF*, real(kind=wp), intent(in) *givenDischarge*, real(kind=wp),
intent(out) *dikeHeight*, type(tpovertoppinginput), intent(inout) *modelFactors*, type (tpovertopping), intent(inout)
overtopping, logical, intent(out) *success*, character(len=*), intent(out) *errorText*, type(tlogging), intent(in) *logging*)


Subroutine with omkeerVariant.

Parameters


in	<i>geometryf</i>	struct with geometry and roughness
in	<i>load</i>	struct with waterlevel and wave parameters
in	<i>givedischarge</i>	discharge to iterate to
out	<i>dikeheight</i>	dike height
in,out	<i>modelfactors</i>	struct with modelFactors
in,out	<i>overtopping</i>	structure with overtopping results
out	<i>success</i>	flag for success
out	<i>errortext</i>	error message (only set if not successful)
in	<i>logging</i>	logging struct

Definition at line 63 of file omkeerVariantModule.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.7.2.3 subroutine omkeerVariantModule::iterateToGivenDischargeValidProfile (type(tpload), intent(in) *load*, type(tpgeometry), intent(in) *geometry*, real(kind=wp), intent(in) *givenDischarge*, real(kind=wp), intent(out) *dikeHeight*, type(tpovertoppinginput), intent(inout) *modelFactors*, type (tpovertopping), intent(inout) *overtopping*, type(tlogging), intent(in) *logging*, logical, intent(out) *success*, character(len=*) , intent(out) *errorText*) [private]

Subroutine with iterateToGivenDischarge, with already checked profile.


Parameters

in	<i>geometry</i>	internal structure with geometry data
----	-----------------	---------------------------------------


in	<i>load</i>	struct with waterlevel and wave parameters
in	<i>givendischarge</i>	discharge to iterate to
out	<i>dikeheight</i>	dike height
in,out	<i>modelfactors</i>	struct with modelFactors
in,out	<i>overtopping</i>	structure with overtopping results
in	<i>logging</i>	logging struct
out	<i>success</i>	flag for success
out	<i>errortext</i>	error message (only set if not successful)

Definition at line 102 of file omkeerVariantModule.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.7.3 Variable Documentation

4.7.3.1 `real(kind=wp)`, parameter `omkeervariantmodule::minzberm = 0.1_wp`

Definition at line 46 of file omkeerVariantModule.f90.

4.7.3.2 `real(kind=wp)`, parameter `omkeervariantmodule::toldikeheight = 1d-3`

Definition at line 45 of file omkeerVariantModule.f90.

4.7.3.3 `real(kind=wp)`, parameter `omkeervariantmodule::toldischarge = 1d-3`

Definition at line 44 of file omkeerVariantModule.f90.

4.8 overtoppinginterface Module Reference

Module for the interface of dllOvertopping.

Data Types

- type [overtoppinggeometrytype](#)
- type [overtoppinggeometrytypef](#)
- type [tpprofilecoordinate](#)

Variables

- integer, parameter, public [varmodelfactorcriticalovertopping](#) = 8
Model factor critical overtopping.

4.8.1 Detailed Description

Module for the interface of dllOvertopping.

4.8.2 Variable Documentation

4.8.2.1 integer, parameter, public [overtoppinginterface::varmodelfactorcriticalovertopping](#) = 8

Model factor critical overtopping.

Definition at line 38 of file [overtoppingInterface.f90](#).

4.9 overtoppingmessages Module Reference

Module for the messages in the overtopping dll, in Dutch or English.

Functions/Subroutines

- subroutine [setlanguage](#) (lang)
IDs for the strings in this module:
- subroutine [getlanguage](#) (lang)
Subroutine that gets the language for error and validation messages.
- character(len=[maxmsg](#)) function [getovertoppingmessage](#) (ID)
Subroutine that returns a message with the corresponding ID in the current language.
- character(len=[maxmsg](#)) function [getovertoppingformat](#) (ID)
Subroutine that returns a Fortran format string with the corresponding ID in the current language.
- character(len=[maxpar](#)) function [getovertoppingparameter](#) (ID)
Subroutine that returns the name of an input parameter with the corresponding ID in the current language.
- subroutine [getmsg_calculategammaftolow](#) (message)
- subroutine [getmsg_calculategammaftohigh](#) (message)
- subroutine [getmsg_calc_influence_roughness](#) (message)
- subroutine [getmsg_first_segment_berm](#) (message)
- subroutine [getmsg_last_segment_berm](#) (message)
- subroutine [getformattoomanyberms](#) (cfmt)
- subroutine [getmsgremovenonhorizontalberm](#) (message)

Variables

- integer, parameter, private `maxmsg` = 128
- integer, parameter, private `maxpar` = 32
- character(len=2), private `language` = 'NL'
default : Dutch

4.9.1 Detailed Description

Module for the messages in the overtopping dll, in Dutch or English.

4.9.2 Function/Subroutine Documentation

4.9.2.1 subroutine overtoppingmessages::getformattoomanyberms (character(len=*), intent(out) *cfmt*)

Definition at line 413 of file OvertoppingMessages.f90.

Here is the caller graph for this function:



4.9.2.2 subroutine overtoppingmessages::getlanguage (character(len=*), intent(out) *lang*)

Subroutine that gets the language for error and validation messages.

Parameters

out	<i>lang</i>	filled with current language ID
-----	-------------	---------------------------------

Definition at line 119 of file OvertoppingMessages.f90.

4.9.2.3 subroutine overtoppingmessages::getmsg_calc_influence_roughness (character(len=*), intent(out) *message*)

Definition at line 386 of file OvertoppingMessages.f90.

Here is the caller graph for this function:



4.9.2.4 subroutine overtoppingmessages::getmsg_calculategammaftohigh (character(len=*), intent(out) *message*)

Definition at line 377 of file OvertoppingMessages.f90.

Here is the caller graph for this function:



4.9.2.5 subroutine overtoppingmessages::getmsg_calculategammaaftlow (character(len=*), intent(out) message)

Definition at line 368 of file OvertoppingMessages.f90.

Here is the caller graph for this function:



4.9.2.6 subroutine overtoppingmessages::getmsg_first_segment_berm (character(len=*), intent(out) message)

Definition at line 395 of file OvertoppingMessages.f90.

Here is the caller graph for this function:



4.9.2.7 subroutine overtoppingmessages::getmsg_last_segment_berm (character(len=*), intent(out) message)

Definition at line 404 of file OvertoppingMessages.f90.

Here is the caller graph for this function:



4.9.2.8 subroutine overtoppingmessages::getmsgremoveonhorizontalberm (character(len=*), intent(out) message)

Definition at line 422 of file OvertoppingMessages.f90.

Here is the caller graph for this function:



4.9.2.9 character(len=maxmsg) function overtoppingmessages::getovertoppingformat (integer, intent(in) ID)


Subroutine that returns a Fortran format string with the corresponding ID in the current language.

Parameters

<i>in</i>	<i>id</i>	identification number of string
-----------	-----------	---------------------------------

Definition at line 271 of file OvertoppingMessages.f90.

Here is the caller graph for this function:



4.9.2.10 character(len=maxmsg) function overtoppingmessages::getovertoppingmessage (integer, intent(in) ID)


Subroutine that returns a message with the corresponding ID in the current language.

Parameters

<i>in</i>	<i>id</i>	identification number of string
-----------	-----------	---------------------------------

Definition at line 129 of file OvertoppingMessages.f90.

Here is the caller graph for this function:



4.9.2.11 character(len=maxpar) function overtoppingmessages::getovertoppingparameter (integer, intent(in) ID)

Subroutine that returns the name of an input parameter with the corresponding ID in the current language.

Parameters

<i>in</i>	<i>id</i>	identification number of string
-----------	-----------	---------------------------------

Definition at line 329 of file OvertoppingMessages.f90.

Here is the caller graph for this function:



4.9.2.12 subroutine overtoppingmessages::setlanguage (character(len=*), intent(in) lang)

IDs for the strings in this module:

Subroutine that sets the language for error and validation messages only strings 'NL' and 'UK' are recoqnized (lower and upper case)

Parameters

in	lang	new language ID to be used
----	------	----------------------------

Definition at line 101 of file OvertoppingMessages.f90.

4.9.3 Variable Documentation

4.9.3.1 character(len=2), private overtoppingmessages::language = 'NL'

default : Dutch

Definition at line 38 of file OvertoppingMessages.f90.

4.9.3.2 integer, parameter, private overtoppingmessages::maxmsg = 128

Definition at line 36 of file OvertoppingMessages.f90.

4.9.3.3 integer, parameter, private overtoppingmessages::maxpar =32

Definition at line 36 of file OvertoppingMessages.f90.

4.10 typedefinitionsovertopping Module Reference

type definitions for Dikes Overtopping

Data Types

- type [tpgeometry](#)
tpGeometry: structure with geometry data
- type [tpload](#)
tpLoad: structure with load parameters
- type [tpovertopping](#)
tpOvertopping: structure with overtopping results
- type [tpovertoppinginput](#)
OvertoppingModelFactors: C-structure with model factors.

Variables

- real(kind=wp), parameter [frunup1](#) = 1.65_wp
- real(kind=wp), parameter [frunup2](#) = 4.00_wp
- real(kind=wp), parameter [frunup3](#) = 1.50_wp
- real(kind=wp), parameter [xdiff_min](#) = 2.0d-2
minimal value distance between x-coordinates (m)
- real(kind=wp), parameter [margindiff](#) = 1.0d-14
margin for minimal distance (m)

- `real(kind=wp), parameter berm_min = 0.0d0`
minimal value gradient berm segment
- `real(kind=wp), parameter berm_max = 1.0d0/15`
maximal value gradient berm segment
- `real(kind=wp), parameter slope_min = 1.0d0/8`
minimal value gradient slope segment
- `real(kind=wp), parameter slope_max = 1.0d0`
maximal value gradient slope segment
- `real(kind=wp), parameter margingrad = 0.0025d0`
margin for minimal and maximal gradients
- `real(kind=wp), parameter rfactor_min = 0.5d0`
minimal value roughness factor dike segments
- `real(kind=wp), parameter rfactor_max = 1.0d0`
maximal value roughness factor dike segments
- `real(kind=wp), parameter mz2_min = 0.0d0`
minimal value model factor of 2% runup height
- `real(kind=wp), parameter mz2_max = huge(mz2_max)`
maximal value model factor of 2% runup height
- `real(kind=wp), parameter fb_min = 0.0d0`
minimal value model factor for breaking waves
- `real(kind=wp), parameter fb_max = huge(fb_max)`
maximal value model factor for breaking waves
- `real(kind=wp), parameter fn_min = 0.0d0`
minimal value model factor for non-breaking waves
- `real(kind=wp), parameter fn_max = huge(fn_max)`
maximal value model factor for non-breaking waves
- `real(kind=wp), parameter fs_min = 0.0d0`
minimal value model factor for shallow waves
- `real(kind=wp), parameter fs_max = huge(fs_max)`
maximal value model factor for shallow waves
- `real(kind=wp), parameter foreshore_min = 0.3d0`
minimal value reduction factor foreshore
- `real(kind=wp), parameter foreshore_max = 1.0d0`
maximal value reduction factor foreshore
- `integer, parameter z2_iter_max1 = 49`
maximal number of iterations for calculation z2 part 1
- `integer, parameter z2_iter_max2 = 70`
maximal number of iterations for calculation z2 part 1 & 2
- `real(kind=wp), parameter z2_margin = 0.001d0`
margin for convergence criterium calculation z2

4.10.1 Detailed Description

type definitions for Dikes Overtopping

4.10.2 Variable Documentation

4.10.2.1 `real(kind=wp), parameter typedefinitionsovertopping::berm_max = 1.0d0/15`

maximal value gradient berm segment

Definition at line 91 of file `typeDefinitionsOvertopping.f90`.

4.10.2.2 `real(kind=wp), parameter typedefinitionsovertopping::berm_min = 0.0d0`

minimal value gradient berm segment

Definition at line 90 of file typeDefinitionsOvertopping.f90.

4.10.2.3 `real(kind=wp), parameter typedefinitionsovertopping::fb_max = huge(fb_max)`

maximal value model factor for breaking waves

Definition at line 100 of file typeDefinitionsOvertopping.f90.

4.10.2.4 `real(kind=wp), parameter typedefinitionsovertopping::fb_min = 0.0d0`

minimal value model factor for breaking waves

Definition at line 99 of file typeDefinitionsOvertopping.f90.

4.10.2.5 `real(kind=wp), parameter typedefinitionsovertopping::fn_max = huge(fn_max)`

maximal value model factor for non-breaking waves

Definition at line 102 of file typeDefinitionsOvertopping.f90.

4.10.2.6 `real(kind=wp), parameter typedefinitionsovertopping::fn_min = 0.0d0`

minimal value model factor for non-breaking waves

Definition at line 101 of file typeDefinitionsOvertopping.f90.

4.10.2.7 `real(kind=wp), parameter typedefinitionsovertopping::foreshore_max = 1.0d0`

maximal value reduction factor foreshore

Definition at line 106 of file typeDefinitionsOvertopping.f90.

4.10.2.8 `real(kind=wp), parameter typedefinitionsovertopping::foreshore_min = 0.3d0`

minimal value reduction factor foreshore

Definition at line 105 of file typeDefinitionsOvertopping.f90.

4.10.2.9 `real(kind=wp), parameter typedefinitionsovertopping::frunup1 = 1.65_wp`

Definition at line 63 of file typeDefinitionsOvertopping.f90.

4.10.2.10 `real(kind=wp), parameter typedefinitionsovertopping::frunup2 = 4.00_wp`

Definition at line 64 of file typeDefinitionsOvertopping.f90.

4.10.2.11 `real(kind=wp), parameter typedefinitionsovertopping::frunup3 = 1.50_wp`

Definition at line 65 of file typeDefinitionsOvertopping.f90.

4.10.2.12 `real(kind=wp), parameter typedefinitionsovertopping::fs_max = huge(fs_max)`

maximal value model factor for shallow waves

Definition at line 104 of file typeDefinitionsOvertopping.f90.

4.10.2.13 `real(kind=wp), parameter typedefinitionsovertopping::fs_min = 0.0d0`

minimal value model factor for shallow waves

Definition at line 103 of file typeDefinitionsOvertopping.f90.

4.10.2.14 `real(kind=wp), parameter typedefinitionsovertopping::margindiff = 1.0d-14`

margin for minimal distance (m)

Definition at line 89 of file typeDefinitionsOvertopping.f90.

4.10.2.15 `real(kind=wp), parameter typedefinitionsovertopping::maringrad = 0.0025d0`

margin for minimal and maximal gradients

Definition at line 94 of file typeDefinitionsOvertopping.f90.

4.10.2.16 `real(kind=wp), parameter typedefinitionsovertopping::mz2_max = huge(mz2_max)`

maximal value model factor of 2% runup height

Definition at line 98 of file typeDefinitionsOvertopping.f90.

4.10.2.17 `real(kind=wp), parameter typedefinitionsovertopping::mz2_min = 0.0d0`

minimal value model factor of 2% runup height

Definition at line 97 of file typeDefinitionsOvertopping.f90.

4.10.2.18 `real(kind=wp), parameter typedefinitionsovertopping::rfactor_max = 1.0d0`

maximal value roughness factor dike segments

Definition at line 96 of file typeDefinitionsOvertopping.f90.

4.10.2.19 `real(kind=wp), parameter typedefinitionsovertopping::rfactor_min = 0.5d0`

minimal value roughness factor dike segments

Definition at line 95 of file typeDefinitionsOvertopping.f90.

4.10.2.20 `real(kind=wp), parameter typedefinitionsovertopping::slope_max = 1.0d0`

maximal value gradient slope segment

Definition at line 93 of file typeDefinitionsOvertopping.f90.

4.10.2.21 `real(kind=wp), parameter typedefinitionsovertopping::slope_min = 1.0d0/8`

minimal value gradient slope segment

Definition at line 92 of file typeDefinitionsOvertopping.f90.

4.10.2.22 `real(kind=wp), parameter typedefinitionsovertopping::xdiff_min = 2.0d-2`

minimal value distance between x-coordinates (m)

Definition at line 88 of file typeDefinitionsOvertopping.f90.

4.10.2.23 `integer, parameter typedefinitionsovertopping::z2_iter_max1 = 49`

maximal number of iterations for calculation z2 part 1

Definition at line 107 of file typeDefinitionsOvertopping.f90.

4.10.2.24 `integer, parameter typedefinitionsovertopping::z2_iter_max2 = 70`

maximal number of iterations for calculation z2 part 1 & 2

Definition at line 108 of file typeDefinitionsOvertopping.f90.

4.10.2.25 `real(kind=wp), parameter typedefinitionsovertopping::z2_margin = 0.001d0`

margin for convergence criterium calculation z2

Definition at line 109 of file typeDefinitionsOvertopping.f90.

4.11 waverunup Module Reference

Iteration procedure for 2% wave runup.

Functions/Subroutines

- subroutine, public [iterationwaverunup](#) (geometry, h, Hm0, Tm_10, gammaBeta_z, modelFactors, z2, logging, succes, errorMessage)
iterationWaveRunup: iteration for the wave runup
- `real(kind=wp)` function [innercalculation](#) (geometry, h, Hm0, gammaBeta_z, modelFactors, z2, s0, geometry↔ FlatBerms, succes, errorMessage)
innerCalculation: inner calculation for the wave runup
- `real(kind=wp)` function [determinestartingvalue](#) (i, relaxationFactor, z2_start, z2_end, Hm0)
determineStartingValue: helper function to find a start value for z2
- integer function [findsmallestresidu](#) (z2_start, z2_end, n)
findSmallestResidu: helper function to find the smallest residu
- subroutine [convergedwithresidu](#) (z2_start, z2_end, logging)
convergedWithResidu: helper function to handle convergence with a higher residu than expected if logging is enabled, it writes a small message to the logfile

4.11.1 Detailed Description

Iteration procedure for 2% wave runup.

4.11.2 Function/Subroutine Documentation

4.11.2.1 subroutine `waverunup::convergedwithresidu` (`real(kind=wp)`, `dimension(:)`, `intent(in) z2_start`, `real(kind=wp)`, `dimension(:)`, `intent(inout) z2_end`, `type(tlogging)`, `intent(in) logging`) [private]

`convergedWithResidu`: helper function to handle convergence with a higher residu than expected if logging is enabled, it writes a small message to the logfile

Parameters

in	<code>z2_start</code>	array with z2 values at the start of the iteration i
in, out	<code>z2_end</code>	array with z2 values at the end of iteration i
in	<code>logging</code>	logging struct

Definition at line 373 of file `waveRunup.f90`.

Here is the call graph for this function:



Here is the caller graph for this function:



4.11.2.2 `real(kind=wp)` function `waverunup::determinestartingvalue` (`integer`, `intent(in) i`, `real(kind=wp)`, `intent(in) relaxationFactor`, `real(kind=wp)`, `dimension(:)`, `intent(in) z2_start`, `real(kind=wp)`, `dimension(:)`, `intent(in) z2_end`, `real(kind=wp)`, `intent(in) hm0`) [private]

`determineStartingValue`: helper function to find a start value for z2

Parameters

in	<code>i</code>	current iteration number
in	<code>relaxationfactor</code>	relaxation factor as given by user
in	<code>z2_start</code>	array with z2 values at the start of the iteration i
in	<code>z2_end</code>	array with z2 values at the end of iteration i
in	<code>hm0</code>	significant wave height

Returns

return value: start value for z2 in current iteration

Definition at line 292 of file `waveRunup.f90`.

Here is the caller graph for this function:




Returns

2% wave run-up at end of inner calculation

Definition at line 181 of file waveRunup.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.11.2.5 subroutine, public `waverunup::iterationwaverunup` (type(tpgeometry), intent(in) *geometry*, real(kind=wp), intent(in) *h*, real(kind=wp), intent(in) *hm0*, real(kind=wp), intent(in) *tm_10*, real(kind=wp), intent(inout) *gammaBeta_z*, type(tpoverlappinginput), intent(in) *modelFactors*, real(kind=wp), intent(out) *z2*, type(tlogging), intent(in) *logging*, logical, intent(out) *succes*, character(len=*) , intent(out) *errorMessage*)

iterationWaveRunup: iteration for the wave runup


Parameters

in	<i>geometry</i>	structure with geometry data
in	<i>h</i>	local water level (m+NAP)
in	<i>hm0</i>	significant wave height (m)
in	<i>tm_10</i>	spectral wave period (s)
in, out	<i>gammaBeta_z</i>	influence factor angle wave attack 2% run-up
in	<i>modelfactors</i>	structure with model factors


out	<i>z2</i>	2% wave run-up (m)
in	<i>logging</i>	logging struct
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 58 of file waveRunup.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.12 zfunctionsovertopping Module Reference

Module for the Limit State Functions (Z-functions) for wave overtopping.

Functions/Subroutines

- subroutine, public [calculateqorto](#) (dikeHeight, modelFactors, overtopping, load, geometry, logging, succes, errorMessage)

Subroutine to calculate the overtopping discharge with the Overtopping dll.

- subroutine, public [profileinstructure](#) (nrCoordinates, xcoordinates, ycoordinates, dikeHeight, nrCoordsAdjusted, xCoordsAdjusted, zCoordsAdjusted, succes, errorMessage)

Subroutine to fill the profile in a structure and call the adjustment function of the profile due to a desired dike height.

- subroutine [adjustprofile](#) (nrCoordinates, coordinates, dikeHeight, nrCoordsAdjusted, xCoordsAdjusted, zCoordsAdjusted, succes, errorMessage)

Subroutine adjust the profile due to a desired dike height.

- real(kind=wp) function, public [zfunclogratios](#) (qo, qc, mqo, mqc, success, errorMessage)

Routine to compute the limit state value by using the logs of the overtopping discharges (computed and desired)

4.12.1 Detailed Description

Module for the Limit State Functions (Z-functions) for wave overtopping.

4.12.2 Function/Subroutine Documentation

4.12.2.1 subroutine `zfunctionsovertopping::adjustprofile` (integer, intent(in) *nrCoordinates*, type(tpprofilecoordinate), dimension(nrcoordinates), intent(in) *coordinates*, real(kind=wp), intent(in) *dikeHeight*, integer, intent(out) *nrCoordsAdjusted*, real(kind=wp), dimension(:), pointer *xCoordsAdjusted*, real(kind=wp), dimension(:), pointer *zCoordsAdjusted*, logical, intent(out) *succes*, character(len=*) intent(out) *errorMessage*) [private]


Subroutine adjust the profile due to a desired dike height.

Parameters


in	<i>nrcoordinates</i>	number of coordinates of the profile
in	<i>coordinates</i>	structure for the profile
in	<i>dikeheight</i>	dike height
out	<i>nrcoordsadjusted</i>	number of coordinates in the adjusted profile
	<i>xcoordsadjusted</i>	vector with x-coordinates of the adjusted profile
	<i>zcoordsadjusted</i>	vector with y-coordinates of the adjusted profile
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 131 of file `zFunctionsOvertopping.f90`.

Here is the call graph for this function:



Here is the caller graph for this function:




4.12.2.2 subroutine, public zfunctionsovertopping::calculateqorto (real(kind=wp), intent(in) *dikeHeight*,
type(tpovertoppinginput), intent(inout) *modelFactors*, type (tpovertopping), intent(out) *overtopping*, type (tpload),
intent(in) *load*, type (tpgeometry), intent(in) *geometry*, type(tlogging), intent(in) *logging*, logical, intent(out) *succes*,
character(len=*), intent(out) *errorMessage*)

Subroutine to calculate the overtopping discharge with the Overtopping dll.

in	<i>dikeheight</i>	dike height
in,out	<i>modelfactors</i>	struct with model factors
out	<i>overtopping</i>	structure with overtopping results
in	<i>geometry</i>	structure with geometry data
in	<i>load</i>	structure with load parameters
in	<i>logging</i>	logging struct
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Here is the call graph for this function:



```

graph LR
    A[zfunctiovertopping::calculateqto] --> B[dlovertopping::calculateqof]
    A --> C[dlovertopping::calculateqo]
    B --> D[omkeervariantmodule::iteratelogvindischargeweldprofile]
    C --> D
    D --> E[omkeervariantmodule::iteratelogvindischarge]
    E --> F[dlovertopping::omkeervariantf]
    F --> G[dlovertopping::omkeervariant]
  
```


Subroutine to fill the profile in a structure and call the adjustment function of the profile due to a desired dike height.

Parameters


in	<i>nrcoordinates</i>	number of coordinates of the profile
in	<i>xcoordinates</i>	vector with x-coordinates of the profile
in	<i>ycoordinates</i>	vector with y-coordinates of the profile
in	<i>dikeheight</i>	dike height
out	<i>nrcoordsadjusted</i>	number of coordinates in the adjusted profile
	<i>xcoordsadjusted</i>	vector with x-coordinates of the adjusted profile
	<i>zcoordsadjusted</i>	vector with y-coordinates of the adjusted profile
out	<i>succes</i>	flag for succes
out	<i>errormessage</i>	error message

Definition at line 106 of file zFunctionsOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:



4.12.2.4 `real (kind=wp) function, public zfunctionsovertopping::zfunclogratios (real (kind=wp), intent(in) qo, real (kind=wp), intent(in) qc, real (kind=wp), intent(in) mgo, real (kind=wp), intent(in) mqc, logical, intent(out) success, character(len=*), intent(out) errorMessage)`

Routine to compute the limit state value by using the logs of the overtopping discharges (computed and desired)

Parameters


in	<i>qo</i>	computed overtopping discharge
in	<i>qc</i>	Critical overtopping discharge
in	<i>mgo</i>	Model factor computed overtopping discharge
in	<i>mqc</i>	Model factor Critical overtopping discharge
out	<i>success</i>	Flag for succes
out	<i>errormessage</i>	error message, only set if not successful

Returns


Value z-function

Definition at line 241 of file zFunctionsOvertopping.f90.

Here is the call graph for this function:



Here is the caller graph for this function:




Chapter 5

Data Type Documentation

5.1 overtoppinginterface::overtoppinggeometrytype Type Reference

Collaboration diagram for overtoppinginterface::overtoppinggeometrytype:



Public Attributes

- `real(kind=wp)` `normal`
- `integer` `npoints`
- `type(c_ptr)` `xcoords`
- `type(c_ptr)` `ycoords`
- `type(c_ptr)` `roughness`

5.1.1 Detailed Description

Definition at line 46 of file overtoppingInterface.f90.

5.1.2 Member Data Documentation

5.1.2.1 `real(kind=wp) overtoppinginterface::overtoppinggeometrytype::normal`

Definition at line 47 of file overtoppingInterface.f90.

5.1.2.2 `integer overtoppinginterface::overtoppinggeometrytype::npoints`

Definition at line 48 of file overtoppingInterface.f90.

5.1.2.3 `type(c_ptr) overtoppinginterface::overtoppinggeometrytype::roughness`

Definition at line 51 of file overtoppingInterface.f90.

5.1.2.4 `type(c_ptr) overtoppinginterface::overtoppinggeometrytype::xcoords`


Definition at line 49 of file overtoppingInterface.f90.

5.1.2.5 `type(c_ptr) overtoppinginterface::overtoppinggeometrytype::ycoords`

Definition at line 50 of file overtoppingInterface.f90.

5.2 overtoppinginterface::overtoppinggeometrytypef Type Reference

Collaboration diagram for overtoppinginterface::overtoppinggeometrytypef:



Public Attributes

- real(kind=wp) [normal](#)
- integer [npoints](#)
- real(kind=wp), dimension(:), pointer [xcoords](#)
- real(kind=wp), dimension(:), pointer [ycoords](#)
- real(kind=wp), dimension(:), pointer [roughness](#)

5.2.1 Detailed Description

Definition at line 54 of file overtoppingInterface.f90.

5.2.2 Member Data Documentation

5.2.2.1 real(kind=wp) overtoppinginterface::overtoppinggeometrytypef::normal

Definition at line 55 of file overtoppingInterface.f90.

5.2.2.2 integer overtoppinginterface::overtoppinggeometrytypef::npoints

Definition at line 56 of file overtoppingInterface.f90.

5.2.2.3 `real(kind=wp), dimension(:), pointer overtoppinginterface::overtoppinggeometrytypef::roughness`

Definition at line 59 of file `overtoppingInterface.f90`.

5.2.2.4 `real(kind=wp), dimension(:), pointer overtoppinginterface::overtoppinggeometrytypef::xcoords`

Definition at line 57 of file `overtoppingInterface.f90`.


5.2.2.5 `real(kind=wp), dimension(:), pointer overtoppinginterface::overtoppinggeometrytypef::ycoords`

Definition at line 58 of file `overtoppingInterface.f90`.

5.3 `modulelogging::tlogging` Type Reference

TLogging: structure for steering the logging.

Collaboration diagram for `modulelogging::tlogging`:



Public Attributes

- integer `verbosity` = `verboseNone`
level of verbosity: one of `verboseNone`, `verboseBasic`, `verboseDetailed`, `verboseDebugging`
- character(len=`maxfilenamelength`) `filename` = ''
filename of logging

5.3.1 Detailed Description

TLogging: structure for steering the logging.

Definition at line 38 of file `ModuleLogging.f90`.

5.3.2 Member Data Documentation

5.3.2.1 `character(len=maxfilenamelength) modulelogging::tlogging::filename = ''`

filename of logging

Definition at line 40 of file ModuleLogging.f90.


5.3.2.2 `integer modulelogging::tlogging::verbosity = verboseNone`

level of verbosity: one of `verboseNone`, `verboseBasic`, `verboseDetailed`, `verboseDebugging`

Definition at line 39 of file ModuleLogging.f90.

5.4 omkeervariantmodule::tomkeer Type Reference

Collaboration diagram for omkeervariantmodule::tomkeer:



Public Attributes

- logical, dimension(:), allocatable [isberm](#)
- logical, dimension(:), allocatable [isvalidz](#)
- real(kind=wp), dimension(:), allocatable [dischargeprofile](#)
- real(kind=wp), dimension(:), allocatable [zprofile](#)

5.4.1 Detailed Description

Definition at line 48 of file omkeerVariantModule.f90.

5.4.2 Member Data Documentation

5.4.2.1 `real(kind=wp), dimension(:), allocatable omkeervariantmodule::tomkeer::dischargeprofile`

Definition at line 51 of file omkeerVariantModule.f90.

5.4.2.2 `logical, dimension(:), allocatable omkeervariantmodule::tomkeer::isberm`

Definition at line 49 of file omkeerVariantModule.f90.

5.4.2.3 `logical, dimension(:), allocatable omkeervariantmodule::tomkeer::isvalidz`

Definition at line 50 of file omkeerVariantModule.f90.


5.4.2.4 `real(kind=wp), dimension(:), allocatable omkeervariantmodule::tomkeer::zprofile`

Definition at line 52 of file omkeerVariantModule.f90.

5.5 `tpdefinitionsovertopping::tpgeometry` Type Reference

tpGeometry: structure with geometry data

Collaboration diagram for typedefinitionsovertopping::tpgeometry:



Public Attributes

- `real(kind=wp)` `psi`
diike normal (degrees)
- `integer` `ncoordinates`
number of coordinates cross section
- `real(kind=wp)`, `dimension(:)`, pointer `xcoordinates` \Rightarrow `null()`
vector with x-coordinates cross section (m)
- `real(kind=wp)`, `dimension(:)`, pointer `ycoordinates` \Rightarrow `null()`
vector with y-coordinates cross section (m+NAP)
- `real(kind=wp)`, `dimension(:)`, pointer `roughnessfactors` \Rightarrow `null()`
vector with roughness factors cross section
- `real(kind=wp)`, `dimension(:)`, pointer `xcoorddiff` \Rightarrow `null()`
vector with differences in x-coordinates (m)
- `real(kind=wp)`, `dimension(:)`, pointer `ycoorddiff` \Rightarrow `null()`
vector with differences in y-coordinates (m)
- `real(kind=wp)`, `dimension(:)`, pointer `segmentslopes` \Rightarrow `null()`
vector with slopes dike segments
- `integer`, `dimension(:)`, pointer `segmenttypes`

- vector with segment types (1=slope,2=berm,3=other)
- integer `nbermsements`
number of berm segments

5.5.1 Detailed Description

tpGeometry: structure with geometry data

Definition at line 42 of file typeDefinitionsOvertopping.f90.

5.5.2 Member Data Documentation

5.5.2.1 integer typedefinitionsovertopping::tpgeometry::nbermsements

number of berm segments

Definition at line 52 of file typeDefinitionsOvertopping.f90.

5.5.2.2 integer typedefinitionsovertopping::tpgeometry::ncoordinates

number of coordinates cross section

Definition at line 44 of file typeDefinitionsOvertopping.f90.

5.5.2.3 real(kind=wp) typedefinitionsovertopping::tpgeometry::psi

dike normal (degrees)

Definition at line 43 of file typeDefinitionsOvertopping.f90.

5.5.2.4 real(kind=wp), dimension(:), pointer typedefinitionsovertopping::tpgeometry::roughnessfactors => null()

vector with roughness factors cross section

Definition at line 47 of file typeDefinitionsOvertopping.f90.

5.5.2.5 real(kind=wp), dimension(:), pointer typedefinitionsovertopping::tpgeometry::segmentslopes => null()

vector with slopes dike segments

Definition at line 50 of file typeDefinitionsOvertopping.f90.

5.5.2.6 integer, dimension(:), pointer typedefinitionsovertopping::tpgeometry::segmenttypes

vector with segment types (1=slope,2=berm,3=other)

Definition at line 51 of file typeDefinitionsOvertopping.f90.

5.5.2.7 real(kind=wp), dimension(:), pointer typedefinitionsovertopping::tpgeometry::xcoorddiff => null()

vector with differences in x-coordinates (m)

Definition at line 48 of file typeDefinitionsOvertopping.f90.

5.5.2.8 `real(kind=wp), dimension(:), pointer typedefinitionsovertopping::tpgeometry::xcoordinates => null()`

vector with x-coordinates cross section (m)

Definition at line 45 of file typeDefinitionsOvertopping.f90.

5.5.2.9 `real(kind=wp), dimension(:), pointer typedefinitionsovertopping::tpgeometry::ycooordiff => null()`

vector with differences in y-coordinates (m)

Definition at line 49 of file typeDefinitionsOvertopping.f90.

5.5.2.10 `real(kind=wp), dimension(:), pointer typedefinitionsovertopping::tpgeometry::ycoordinates => null()`


vector with y-coordinates cross section (m+NAP)

Definition at line 46 of file typeDefinitionsOvertopping.f90.

5.6 typedefinitionsovertopping::tpload Type Reference

tpLoad: structure with load parameters

Collaboration diagram for typedefinitionsovertopping::tpload:



Public Attributes

- `real(kind=wp) h`

local water level (m+NAP)

- `real(kind=wp) hm0`

significant wave height (m)

- `real(kind=wp) tm_10`

spectral wave period (s)

- `real(kind=wp) phi`

wave direction (degrees)

5.6.1 Detailed Description

tpLoad: structure with load parameters

Definition at line 56 of file typeDefinitionsOvertopping.f90.

5.6.2 Member Data Documentation

5.6.2.1 `real(kind=wp) typedefinitionsovertopping::tpload::h`

local water level (m+NAP)

Definition at line 57 of file typeDefinitionsOvertopping.f90.

5.6.2.2 `real(kind=wp) typedefinitionsovertopping::tpload::hm0`

significant wave height (m)

Definition at line 58 of file typeDefinitionsOvertopping.f90.

5.6.2.3 `real(kind=wp) typedefinitionsovertopping::tpload::phi`

wave direction (degrees)

Definition at line 60 of file typeDefinitionsOvertopping.f90.

5.6.2.4 `real(kind=wp) typedefinitionsovertopping::tpload::tm_10`


spectral wave period (s)

Definition at line 59 of file typeDefinitionsOvertopping.f90.

5.7 `typedefinitionsovertopping::tpovertopping` Type Reference

tpOvertopping: structure with overtopping results

Collaboration diagram for typedefinitionsovertopping::tpovertopping:



Public Attributes

- `real(kind=wp)` [z2](#)
2% wave run-up (m)
- `real(kind=wp)` [qo](#)
wave overtopping discharge (m³/m per s)

5.7.1 Detailed Description

`tpOvertopping`: structure with overtopping results

Definition at line 80 of file `typeDefinitionsOvertopping.f90`.

5.7.2 Member Data Documentation

5.7.2.1 `real(kind=wp)` `typedefinitionsovertopping::tpovertopping::qo`

wave overtopping discharge (m³/m per s)

Definition at line 82 of file `typeDefinitionsOvertopping.f90`.

5.7.2.2 `real(kind=wp)` `typedefinitionsovertopping::tpovertopping::z2`


2% wave run-up (m)

Definition at line 81 of file `typeDefinitionsOvertopping.f90`.

5.8 typedefinitionsovertopping::tpovertoppinginput Type Reference

OvertoppingModelFactors: C-structure with model factors.

Collaboration diagram for typedefinitionsovertopping::tpovertoppinginput:



Public Attributes

- `real(kind=wp) factordeterminationq_b_f_n`
model factor for non-breaking waves
- `real(kind=wp) factordeterminationq_b_f_b`
model factor for breaking waves
- `real(kind=wp) m_z2`
model factor describing the uncertainty of 2% runup height
- `real(kind=wp) fshallow`
model factor for shallow waves
- `real(kind=wp) computedovertopping`
model factor computed overtopping
- `real(kind=wp) criticalovertopping`

- model factor critical overtopping*
- `real(kind=wp) relaxationfactor`
relaxation factor iteration procedure wave runup
- `real(kind=wp) reductionfactorforeshore = 0.5_wp`
reduction factor foreshore

5.8.1 Detailed Description

OvertoppingModelFactors: C-structure with model factors.

Definition at line 68 of file typeDefinitionsOvertopping.f90.

5.8.2 Member Data Documentation

5.8.2.1 `real(kind=wp) typedefinitionsovertopping::tpovertoppinginput::computedovertopping`

model factor computed overtopping

Definition at line 73 of file typeDefinitionsOvertopping.f90.

5.8.2.2 `real(kind=wp) typedefinitionsovertopping::tpovertoppinginput::criticalovertopping`

model factor critical overtopping

Definition at line 74 of file typeDefinitionsOvertopping.f90.

5.8.2.3 `real(kind=wp) typedefinitionsovertopping::tpovertoppinginput::factordeterminationq_b_f_b`

model factor for breaking waves

Definition at line 70 of file typeDefinitionsOvertopping.f90.

5.8.2.4 `real(kind=wp) typedefinitionsovertopping::tpovertoppinginput::factordeterminationq_b_f_n`

model factor for non-breaking waves

Definition at line 69 of file typeDefinitionsOvertopping.f90.

5.8.2.5 `real(kind=wp) typedefinitionsovertopping::tpovertoppinginput::fshallow`

model factor for shallow waves

Definition at line 72 of file typeDefinitionsOvertopping.f90.

5.8.2.6 `real(kind=wp) typedefinitionsovertopping::tpovertoppinginput::m_z2`

model factor describing the uncertainty of 2% runup height

Definition at line 71 of file typeDefinitionsOvertopping.f90.

5.8.2.7 `real(kind=wp) typedefinitionsovertopping::tpovertoppinginput::reductionfactorforeshore = 0.5_wp`

reduction factor foreshore

Definition at line 76 of file typeDefinitionsOvertopping.f90.


5.8.2.8 `real(kind=wp) typedefinitionsovertopping::tpovertoppinginput::relaxationfactor`

relaxation factor iteration procedure wave runup

Definition at line 75 of file `typeDefinitionsOvertopping.f90`.

5.9 `overtoppinginterface::tpprofilecoordinate` Type Reference

Collaboration diagram for `overtoppinginterface::tpprofilecoordinate`:



Public Attributes

- `real(kind=wp)` [xcoordinate](#)
X-coordinate foreland profile.
- `real(kind=wp)` [zcoordinate](#)
Z-coordinate foreland profile.
- `real(kind=wp)` [roughness](#)
Roughness of the area between two points.

5.9.1 Detailed Description

Definition at line 40 of file `overtoppingInterface.f90`.

5.9.2 Member Data Documentation

5.9.2.1 real(kind=wp) overtoppinginterface::tpprofilecoordinate::roughness

Roughness of the area between two points.

Definition at line 43 of file overtoppingInterface.f90.

5.9.2.2 real(kind=wp) overtoppinginterface::tpprofilecoordinate::xcoordinate

X-coordinate foreland profile.

Definition at line 41 of file overtoppingInterface.f90.

5.9.2.3 real(kind=wp) overtoppinginterface::tpprofilecoordinate::zcoordinate

Z-coordinate foreland profile.

Definition at line 42 of file overtoppingInterface.f90.

Chapter 6

File Documentation

6.1 dllovertopping.f90 File Reference

Main entry for the dll DikesOvertopping FUNCTIONS/SUBROUTINES exported from dllovertopping.dll:

Modules

- module [dllovertopping](#)
Main entry for the dll DikesOvertopping.

Functions/Subroutines

- subroutine, public [dllovertopping::calculateqo](#) (load, geometryInput, dikeHeight, modelFactors, overtopping, success, errorText, verbosity, logFile)
Subroutine that calculates the discharge needed for the Z-function DikesOvertopping Wrapper for calculateQoF: convert C-like input structures to Fortran input structures.
- subroutine, public [dllovertopping::calculateqoj](#) (load, xcoords, ycoords, roughness, normal, npoints, dikeHeight, modelFactors, output, success, errorMessage)
Subroutine that calculates the discharge Wrapper for calculateQoF: convert basic types to Fortran input structures.
- subroutine, public [dllovertopping::calculateqof](#) (load, geometryF, dikeHeight, modelFactors, overtopping, success, errorText, logging)
Subroutine that calculates the discharge needed for the Z-function DikesOvertopping.
- subroutine, public [dllovertopping::calczvalue](#) (criticalOvertoppingRate, modelFactors, Qo, z, success, errorMessage)
Subroutine that calculates the Z-function DikesOvertopping based on the discharge calculated with calculateQoF.
- subroutine, public [dllovertopping::validateinputc](#) (geometryInput, dikeHeight, modelFactors, success, errorText)
Subroutine that validates the geometry Wrapper for ValidateInputF: convert C-like input structures to Fortran input structures.
- subroutine, public [dllovertopping::validateinputj](#) (x, y, roughness, normal, npoints, dikeHeight, modelFactors, Array, success, errorText)
Subroutine that validates the geometry Wrapper for ValidateInputF: convert basic types to Fortran input structures.
- subroutine, public [dllovertopping::validateinputf](#) (geometryF, dikeHeight, modelFactors, errorStruct)
Subroutine that validates the geometry.
- subroutine, public [dllovertopping::omkeervariantj](#) (load, xcoords, ycoords, roughness, normal, npoints, givenDischarge, dikeHeight, modelFactors, output, success, errorMessage)
Wrapper for omkeerVariantF: get dikeHeight by given discharge.

- subroutine, public [dllovertopping::omkeervariantf](#) (load, geometryF, givenDischarge, dikeHeight, modelFactors, overtopping, success, errorText, logging)
Subroutine with omkeerVariant (get dikeHeight by given discharge)
- subroutine, public [dllovertopping::setlanguage](#) (lang)
Subroutine that sets the language for error and validation messages.
- subroutine, public [dllovertopping::getlanguage](#) (lang)
Subroutine that gets the language for error and validation messages.
- subroutine, public [dllovertopping::versionnumber](#) (version)
Subroutine that delivers the version number.
- type(overtoppinggeometrytypef) function [dllovertopping::geometry_c_f](#) (geometryInput)
Private subroutine that converts geometry from c-pointer to fortran struct.
- subroutine [dllovertopping::input_j_f](#) (x, y, roughness, normal, geometryF, modelFactorsJ, modelFactorsF, loadJ, loadF)
convert java input to Fortran input

Variables

- character, parameter [dllovertopping::separationchar](#) = char(9)
use horizontal tab for separation

6.1.1 Detailed Description

Main entry for the dll DikesOvertopping FUNCTIONS/SUBROUTINES exported from dllOvertopping.dll:

- calcZValue
- calculateQo
- calculateQoF
- calculateQoJ
- ValidateInputC
- ValidateInputF
- ValidateInputJ
- omkeerVariantF
- omkeerVariantJ
- SetLanguage
- GetLanguage
- versionNumber

6.2 factorModuleOvertopping.f90 File Reference

This file contains a module with functions for the slope angle and influence factors.

Modules

- module [factormoduleovertopping](#)
functions for the slope angle and influence factors

Functions/Subroutines

- subroutine, public [factormoduleovertopping::calculatetanalpha](#) (h, Hm0, z2, geometry, tanAlpha, succes, errorMessage)
calculateTanAlpha representative slope angle
- subroutine, public [factormoduleovertopping::calculategammabeta](#) (Hm0, Tm_10, beta, gammaBeta_z, gammaBeta_o)
calculateGammaBeta influence factor angle of wave attack
- subroutine, public [factormoduleovertopping::calculategammaf](#) (h, ksi0, ksi0Limit, gammaB, z2, geometry, gammaF, succes, errorMessage)
calculateGammaF influence factor roughness
- subroutine, public [factormoduleovertopping::calculategammab](#) (h, Hm0, z2, geometry, gammaB, succes, errorMessage)
calculateGammaB influence factor berms

6.2.1 Detailed Description

This file contains a module with functions for the slope angle and influence factors.

6.3 formulaModuleOvertopping.f90 File Reference

This file contains a module with the core computations for Dikes Overtopping.

Modules

- module [formulamoduleovertopping](#)
the core computations for Dikes Overtopping

Functions/Subroutines

- subroutine, public [formulamoduleovertopping::calculatewaverunup](#) (Hm0, ksi0, ksi0Limit, gammaB, gammaF, gammaBeta, modelFactors, z2, succes, errorMessage)
calculateWaveRunup: calculate wave runup
- subroutine, public [formulamoduleovertopping::calculatewaveovertoppingdischarge](#) (h, Hm0, tanAlpha, gammaB, gammaF, gammaBeta, ksi0, hCrest, modelFactors, Qo, succes, errorMessage)
calculateWaveOvertoppingDischarge: calculate the wave overtopping discharge
- subroutine, public [formulamoduleovertopping::calculatewavelength](#) (Tm_10, L0)
calculateWaveLength: calculate the wave length
- subroutine, public [formulamoduleovertopping::calculatewavesteepness](#) (Hm0, Tm_10, s0, succes, errorMessage)
calculateWaveSteepness: calculate the wave steepness
- subroutine, public [formulamoduleovertopping::calculatebreakerparameter](#) (tanAlpha, s0, ksi0, succes, errorMessage)
calculateBreakerParameter: calculate the breaker parameter
- subroutine, public [formulamoduleovertopping::calculateanglewaveattack](#) (phi, psi, beta)
calculateAngleWaveAttack: calculate the angle of wave attack
- subroutine, public [formulamoduleovertopping::calculatebreakerlimit](#) (gammaB, ksi0Limit, succes, errorMessage)
calculateBreakerLimit: calculate the breaker limit
- subroutine, public [formulamoduleovertopping::adjustinfluencefactors](#) (gammaB, gammaF, gammaBeta, gammaBetaType, ksi0, ksi0Limit, succes, errorMessage)

- adjustInfluenceFactors: adjust the influence factors*
- subroutine [formulamoduleovertopping::realrootscubicfunction](#) (a, b, c, d, N, x, succes, errorMessage)
 - realRootsCubicFunction: calculate the roots of a cubic function*
- subroutine [formulamoduleovertopping::rootsgeneralcubic](#) (a, b, c, d, z, succes, errorMessage)
 - rootsGeneralCubic: calculate the roots of a generic cubic function*
- subroutine [formulamoduleovertopping::rootsdepressedcubic](#) (p, q, z)
 - rootsDepressedCubic: calculate the roots of a depressed cubic function*
- subroutine [formulamoduleovertopping::cubicroots](#) (z, roots)
 - cubicRoots: calculate the roots of a cubic function*
- logical function, public [formulamoduleovertopping::isequalreal](#) (x1, x2)
 - isEqualReal: are two reals (almost) equal*
- logical function, public [formulamoduleovertopping::isequalzero](#) (x)
 - isEqualZero: is a real (almost) zero*

6.3.1 Detailed Description

This file contains a module with the core computations for Dikes Overtopping.

6.4 geometryModuleOvertopping.f90 File Reference

This file contains a module with the core computations for Dikes Overtopping related to the geometry.

Modules

- module [geometrymoduleovertopping](#)
 - core computations related to the geometry*

Functions/Subroutines

- subroutine, public [geometrymoduleovertopping::checkcrosssection](#) (psi, nCoordinates, xCoordinates, yCoordinates, roughnessFactors, succes, errorMessage)
 - checkCrossSection: check cross section*
- subroutine, public [geometrymoduleovertopping::initializegeometry](#) (psi, nCoordinates, xCoordinates, yCoordinates, roughnessFactors, geometry, succes, errorMessage)
 - initializeGeometry: initialize the geometry*
- subroutine, public [geometrymoduleovertopping::allocatevectorsgeometry](#) (nCoordinates, geometry, succes, errorMessage)
 - allocateVectorsGeometry: allocate the geometry vectors*
- subroutine, public [geometrymoduleovertopping::deallocateggeometry](#) (geometry)
 - deallocateGeometry: deallocate the geometry vectors*
- subroutine, public [geometrymoduleovertopping::calculatesegmentslopes](#) (geometry, succes, errorMessage)
 - calculateSegmentSlopes: calculate the segment slopes*
- subroutine, public [geometrymoduleovertopping::determinesegmenttypes](#) (geometry, succes, errorMessage)
 - determineSegmentTypes: determine the segment types*
- subroutine, public [geometrymoduleovertopping::copygeometry](#) (geometry, geometryCopy, succes, errorMessage)
 - copyGeometry: copy a geometry structure*
- subroutine, public [geometrymoduleovertopping::mergesquentialberms](#) (geometry, geometryMergedBerms, succes, errorMessage)
 - mergeSequentialBerms: merge sequential berms*

- subroutine, public [geometrymoduleovertopping::adjustnonhorizontalberms](#) (geometry, geometryFlatBerms, succes, errorMessage)
adjustNonHorizontalBerms: adjust non-horizontal berms
- subroutine, public [geometrymoduleovertopping::removeberms](#) (geometry, geometryNoBerms, succes, errorMessage)
removeBerms: remove berms
- subroutine, public [geometrymoduleovertopping::removedikessegments](#) (geometry, index, geometryAdjusted, succes, errorMessage)
removeDikeSegments: remove dike segments
- subroutine, public [geometrymoduleovertopping::splitcrosssection](#) (geometry, L0, NwideBerms, geometrysection←B, geometrysectionF, succes, errorMessage)
splitCrossSection: split a cross section
- subroutine, public [geometrymoduleovertopping::calculatehorzlengths](#) (geometry, yLower, yUpper, horz←Lengths, succes, errorMessage)
calculateHorzLengths: calculate horizontal lengths
- subroutine, public [geometrymoduleovertopping::calculatehorzdistance](#) (geometry, yLower, yUpper, dx, succes, errorMessage)
calculateHorzDistance: calculate horizontal distance
- subroutine, public [geometrymoduleovertopping::basicgeometrytest](#) (geometryF, success, errorStruct)
basicGeometryTest: test the input geometry (the adjusted geometry is checked elsewhere)

6.4.1 Detailed Description

This file contains a module with the core computations for Dikes Overtopping related to the geometry.

6.5 mainModuleOvertopping.f90 File Reference

This file contains a module with the core computations for Dikes Overtopping.

Modules

- module [mainmoduleovertopping](#)
core computations for Dikes Overtopping

Functions/Subroutines

- subroutine, public [mainmoduleovertopping::calculateovertopping](#) (geometry, load, modelFactors, overtopping, logging, succes, errorMessage)
calculateOvertopping: calculate the overtopping
- subroutine, public [mainmoduleovertopping::calculateovertoppingsection](#) (geometry, h, Hm0, Tm_10, L0, gammaBeta_z, gammaBeta_o, modelFactors, overtopping, logging, succes, errorMessage)
calculateOvertoppingSection: calculate the overtopping for a section
- subroutine, public [mainmoduleovertopping::calculatewaveovertopping](#) (geometry, h, Hm0, Tm_10, z2, gammaBeta_o, modelFactors, Qo, succes, errorMessage)
calculateWaveOvertopping: calculate wave overtopping
- subroutine [mainmoduleovertopping::calculateovertoppingnegativefreeboard](#) (load, geometry, overtopping, succes, errorMessage)
calculateOvertoppingNegativeFreeboard: calculate overtopping in case of negative freeboard
- subroutine, public [mainmoduleovertopping::interpolateresultssections](#) (geometry, L0, NwideBerms, overtoppingB, overtoppingF, overtopping, succes, errorMessage)

interpolateResultsSections: interpolate results for split cross sections

- subroutine, public [mainmoduleovertopping::checkinputdata](#) (geometry, load, modelFactors, succes, error←Message)

checkInputdata: check the input data

- subroutine, public [mainmoduleovertopping::checkmodelFactors](#) (modelFactors, dimErrMsg, error←Messages, ierr)

checkModelFactors: check the input data

6.5.1 Detailed Description

This file contains a module with the core computations for Dikes Overtopping.

6.6 ModuleLogging.f90 File Reference

Module for steering the extra logging.

Data Types

- type [modulelogging::tlogging](#)
TLogging: structure for steering the logging.

Modules

- module [modulelogging](#)
steering the extra logging

Variables

- integer, parameter [modulelogging::maxfilenamlength](#) = 256
maximum length of filename

6.6.1 Detailed Description

Module for steering the extra logging.

6.7 omkeerVariantModule.f90 File Reference

This file contains the omkeerVariant.

Data Types

- type [omkeervariantmodule::tomkeer](#)

Modules

- module [omkeervariantmodule](#)
Module for the 'omkeerVariant'.

Functions/Subroutines

- subroutine, public [omkeervariantmodule::iteratetogivendischarge](#) (load, geometryF, givenDischarge, dikeHeight, modelFactors, overtopping, success, errorText, logging)
Subroutine with omkeerVariant.
- subroutine [omkeervariantmodule::iteratetogivendischargevalidprofile](#) (load, geometry, givenDischarge, dikeHeight, modelFactors, overtopping, logging, success, errorText)
Subroutine with iterateToGivenDischarge, with already checked profile.
- subroutine [omkeervariantmodule::checkifonberm](#) (geometry, load, modelFactors, overtopping, givenDischarge, dikeHeight, omkeerProps, logging, iUp, iLow, dis1, dis2, minDikeHeight, maxDikeHeight, foundValue, success, errorText)

Variables

- real(kind=wp), parameter [omkeervariantmodule::toldischarge](#) = 1d-3
- real(kind=wp), parameter [omkeervariantmodule::toldikeheight](#) = 1d-3
- real(kind=wp), parameter [omkeervariantmodule::minzberm](#) = 0.1_wp

6.7.1 Detailed Description

This file contains the omkeerVariant.

6.8 overtoppingInterface.f90 File Reference

This file contains the parameters and types (structs) as part of the interface to and from dllOvertopping.

Data Types

- type [overtoppinginterface::tpprofilecoordinate](#)
- type [overtoppinginterface::overtoppinggeometrytype](#)
- type [overtoppinginterface::overtoppinggeometrytypef](#)

Modules

- module [overtoppinginterface](#)
Module for the interface of dllOvertopping.

Variables

- integer, parameter, public [overtoppinginterface::varmodelfactorcriticalovertopping](#) = 8
Model factor critical overtopping.

6.8.1 Detailed Description

This file contains the parameters and types (structs) as part of the interface to and from dllOvertopping.

6.9 OvertoppingMessages.f90 File Reference

This file contains the messages in the overtopping dll, in Dutch or English.

Modules

- module [overtoppingmessages](#)
Module for the messages in the overtopping dll, in Dutch or English.

Functions/Subroutines

- subroutine [overtoppingmessages::setlanguage](#) (lang)
IDs for the strings in this module:
- subroutine [overtoppingmessages::getlanguage](#) (lang)
Subroutine that gets the language for error and validation messages.
- character(len=maxmsg) function [overtoppingmessages::getovertoppingmessage](#) (ID)
Subroutine that returns a message with the corresponding ID in the current language.
- character(len=maxmsg) function [overtoppingmessages::getovertoppingformat](#) (ID)
Subroutine that returns a Fortran format string with the corresponding ID in the current language.
- character(len=maxpar) function [overtoppingmessages::getovertoppingparameter](#) (ID)
Subroutine that returns the name of an input parameter with the corresponding ID in the current language.
- subroutine [overtoppingmessages::getmsg_calculategammaftolow](#) (message)
- subroutine [overtoppingmessages::getmsg_calculategammaftohigh](#) (message)
- subroutine [overtoppingmessages::getmsg_calc_influence_roughness](#) (message)
- subroutine [overtoppingmessages::getmsg_first_segment_berm](#) (message)
- subroutine [overtoppingmessages::getmsg_last_segment_berm](#) (message)
- subroutine [overtoppingmessages::getformattoomanyberms](#) (cfmt)
- subroutine [overtoppingmessages::getmsgremovenonhorizontalberm](#) (message)

Variables

- integer, parameter, private [overtoppingmessages::maxmsg](#) = 128
- integer, parameter, private [overtoppingmessages::maxpar](#) = 32
- character(len=2), private [overtoppingmessages::language](#) = 'NL'
default : Dutch

6.9.1 Detailed Description

This file contains the messages in the overtopping dll, in Dutch or English.

6.10 typeDefinitionsOvertopping.f90 File Reference

This file contains a module with the type definitions for Dikes Overtopping.

Data Types

- type [typedefinitionsovertopping::tpgeometry](#)
tpGeometry: structure with geometry data
- type [typedefinitionsovertopping::tpload](#)
tpLoad: structure with load parameters
- type [typedefinitionsovertopping::tpovertoppinginput](#)
OvertoppingModelFactors: C-structure with model factors.
- type [typedefinitionsovertopping::tpovertopping](#)
tpOvertopping: structure with overtopping results

Modules

- module `typedefinitionsovertopping`
type definitions for Dikes Overtopping

Variables

- real(kind=wp), parameter `typedefinitionsovertopping::frunup1` = 1.65_wp
- real(kind=wp), parameter `typedefinitionsovertopping::frunup2` = 4.00_wp
- real(kind=wp), parameter `typedefinitionsovertopping::frunup3` = 1.50_wp
- real(kind=wp), parameter `typedefinitionsovertopping::xdiff_min` = 2.0d-2
minimal value distance between x-coordinates (m)
- real(kind=wp), parameter `typedefinitionsovertopping::margindiff` = 1.0d-14
margin for minimal distance (m)
- real(kind=wp), parameter `typedefinitionsovertopping::berm_min` = 0.0d0
minimal value gradient berm segment
- real(kind=wp), parameter `typedefinitionsovertopping::berm_max` = 1.0d0/15
maximal value gradient berm segment
- real(kind=wp), parameter `typedefinitionsovertopping::slope_min` = 1.0d0/8
minimal value gradient slope segment
- real(kind=wp), parameter `typedefinitionsovertopping::slope_max` = 1.0d0
maximal value gradient slope segment
- real(kind=wp), parameter `typedefinitionsovertopping::margingrad` = 0.0025d0
margin for minimal and maximal gradients
- real(kind=wp), parameter `typedefinitionsovertopping::rfactor_min` = 0.5d0
minimal value roughness factor dike segments
- real(kind=wp), parameter `typedefinitionsovertopping::rfactor_max` = 1.0d0
maximal value roughness factor dike segments
- real(kind=wp), parameter `typedefinitionsovertopping::mz2_min` = 0.0d0
minimal value model factor of 2% runup height
- real(kind=wp), parameter `typedefinitionsovertopping::mz2_max` = huge(mz2_max)
maximal value model factor of 2% runup height
- real(kind=wp), parameter `typedefinitionsovertopping::fb_min` = 0.0d0
minimal value model factor for breaking waves
- real(kind=wp), parameter `typedefinitionsovertopping::fb_max` = huge(fb_max)
maximal value model factor for breaking waves
- real(kind=wp), parameter `typedefinitionsovertopping::fn_min` = 0.0d0
minimal value model factor for non-breaking waves
- real(kind=wp), parameter `typedefinitionsovertopping::fn_max` = huge(fn_max)
maximal value model factor for non-breaking waves
- real(kind=wp), parameter `typedefinitionsovertopping::fs_min` = 0.0d0
minimal value model factor for shallow waves
- real(kind=wp), parameter `typedefinitionsovertopping::fs_max` = huge(fs_max)
maximal value model factor for shallow waves
- real(kind=wp), parameter `typedefinitionsovertopping::foreshore_min` = 0.3d0
minimal value reduction factor foreshore
- real(kind=wp), parameter `typedefinitionsovertopping::foreshore_max` = 1.0d0
maximal value reduction factor foreshore
- integer, parameter `typedefinitionsovertopping::z2_iter_max1` = 49
maximal number of iterations for calculation z2 part 1
- integer, parameter `typedefinitionsovertopping::z2_iter_max2` = 70
maximal number of iterations for calculation z2 part 1 & 2
- real(kind=wp), parameter `typedefinitionsovertopping::z2_margin` = 0.001d0
margin for convergence criterium calculation z2

6.10.1 Detailed Description

This file contains a module with the type definitions for Dikes Overtopping.

6.11 waveRunup.f90 File Reference

This file contains a module with the iteration procedure for 2% wave runup.

Modules

- module [waverunup](#)
Iteration procedure for 2% wave runup.

Functions/Subroutines

- subroutine, public [waverunup::iterationwaverunup](#) (geometry, h, Hm0, Tm_10, gammaBeta_z, modelFactors, z2, logging, succes, errorMessage)
iterationWaveRunup: iteration for the wave runup
- real(kind=wp) function [waverunup::innercalculation](#) (geometry, h, Hm0, gammaBeta_z, modelFactors, z2, s0, geometryFlatBerms, succes, errorMessage)
innerCalculation: inner calculation for the wave runup
- real(kind=wp) function [waverunup::determinestartingvalue](#) (i, relaxationFactor, z2_start, z2_end, Hm0)
determineStartingValue: helper function to find a start value for z2
- integer function [waverunup::findsmallestresidu](#) (z2_start, z2_end, n)
findSmallestResidu: helper function to find the smallest residu
- subroutine [waverunup::convergedwithresidu](#) (z2_start, z2_end, logging)
convergedWithResidu: helper function to handle convergence with a higher residu than expected if logging is enabled, it writes a small message to the logfile

6.11.1 Detailed Description

This file contains a module with the iteration procedure for 2% wave runup.

6.12 zFunctionsOvertopping.f90 File Reference

This file contains the limit state functions for wave overtopping within VTV.

Modules

- module [zfunctionsovertopping](#)
Module for the Limit State Functions (Z-functions) for wave overtopping.

Functions/Subroutines

- subroutine, public [zfunctionsovertopping::calculateqorto](#) (dikeHeight, modelFactors, overtopping, load, geometry, logging, succes, errorMessage)
Subroutine to calculate the overtopping discharge with the Overtopping dll.
- subroutine, public [zfunctionsovertopping::profileinstructure](#) (nrCoordinates, xcoordinates, ycoordinates, dikeHeight, nrCoordsAdjusted, xCoordsAdjusted, zCoordsAdjusted, succes, errorMessage)

Subroutine to fill the profile in a structure and call the adjustment function of the profile due to a desired dike height.

- subroutine `zfunctionsovertopping::adjustprofile` (nrCoordinates, coordinates, dikeHeight, nrCoordsAdjusted, xCoordsAdjusted, zCoordsAdjusted, succes, errorMessage)

Subroutine adjust the profile due to a desired dike height.

- real(kind=wp) function, public `zfunctionsovertopping::zfunclogratios` (qo, qc, mqo, mqc, success, error←Message)

Routine to compute the limit state value by using the logs of the overtopping discharges (computed and desired)

6.12.1 Detailed Description

This file contains the limit state functions for wave overtopping within VTV.

Index

- adjustinfluencefactors
 - formulamoduleovertopping, [23](#)
- adjustnonhorizontalberms
 - geometrymoduleovertopping, [31](#)
- adjustprofile
 - zfunctionsovertopping, [69](#)
- allocatevectorsgeometry
 - geometrymoduleovertopping, [32](#)
- basicgeometrytest
 - geometrymoduleovertopping, [33](#)
- berm_max
 - typedefinitionsovertopping, [61](#)
- berm_min
 - typedefinitionsovertopping, [61](#)
- calculateanglewaveattack
 - formulamoduleovertopping, [24](#)
- calculatebreakerlimit
 - formulamoduleovertopping, [24](#)
- calculatebreakerparameter
 - formulamoduleovertopping, [24](#)
- calculategammab
 - factormoduleovertopping, [19](#)
- calculategammabeta
 - factormoduleovertopping, [20](#)
- calculategammaf
 - factormoduleovertopping, [20](#)
- calculatehorzdistance
 - geometrymoduleovertopping, [33](#)
- calculatehorzlengths
 - geometrymoduleovertopping, [34](#)
- calculateovertopping
 - mainmoduleovertopping, [44](#)
- calculateovertoppingnegativefreeboard
 - mainmoduleovertopping, [45](#)
- calculateovertoppingsection
 - mainmoduleovertopping, [45](#)
- calculateqo
 - dllovertopping, [8](#)
- calculateqof
 - dllovertopping, [9](#)
- calculateqoj
 - dllovertopping, [10](#)
- calculateqorto
 - zfunctionsovertopping, [69](#)
- calculatesegmentslopes
 - geometrymoduleovertopping, [35](#)
- calculatetanalpha
 - factormoduleovertopping, [21](#)
- calculatewavelength
 - formulamoduleovertopping, [25](#)
- calculatewaveovertopping
 - mainmoduleovertopping, [46](#)
- calculatewaveovertoppingdischarge
 - formulamoduleovertopping, [25](#)
- calculatewaverunup
 - formulamoduleovertopping, [26](#)
- calculatewavesteepness
 - formulamoduleovertopping, [27](#)
- calczvalue
 - dllovertopping, [11](#)
- checkcrosssection
 - geometrymoduleovertopping, [35](#)
- checkifonberm
 - omkeervariantmodule, [51](#)
- checkinputdata
 - mainmoduleovertopping, [47](#)
- checkmodelfactors
 - mainmoduleovertopping, [48](#)
- computedovertopping
 - typedefinitionsovertopping::tpovertoppinginput, [87](#)
- convergedwithresidu
 - waverunup, [65](#)
- copygeometry
 - geometrymoduleovertopping, [36](#)
- criticalovertopping
 - typedefinitionsovertopping::tpovertoppinginput, [87](#)
- cubicroots
 - formulamoduleovertopping, [28](#)
- deallocategeometry
 - geometrymoduleovertopping, [36](#)
- determinesegmenttypes
 - geometrymoduleovertopping, [38](#)
- determinestartingvalue
 - waverunup, [65](#)
- dischargeprofile
 - omkeervariantmodule::tomkeer, [80](#)
- dllovertopping.f90, [91](#)
- dllovertopping, [7](#)
 - calculateqo, [8](#)
 - calculateqof, [9](#)
 - calculateqoj, [10](#)
 - calczvalue, [11](#)
 - geometry_c_f, [11](#)
 - getlanguage, [13](#)
 - input_j_f, [13](#)
 - omkeervariantf, [13](#)
 - omkeervariantj, [15](#)

- separationchar, 19
- setlanguage, 16
- validateinputc, 16
- validateinputf, 17
- validateinputj, 18
- versionnumber, 18
- factorModuleOvertopping.f90, 92
- factordeterminationq_b_f_b
 - typedefinitionsovertopping::tpovertoppinginput, 87
- factordeterminationq_b_f_n
 - typedefinitionsovertopping::tpovertoppinginput, 87
- factormoduleovertopping, 19
 - calculategammab, 19
 - calculategammabeta, 20
 - calculategammaf, 20
 - calculatetanalpha, 21
- fb_max
 - typedefinitionsovertopping, 62
- fb_min
 - typedefinitionsovertopping, 62
- filename
 - modulelogging::tlogging, 79
- findsmallestresidu
 - waverunup, 65
- fn_max
 - typedefinitionsovertopping, 62
- fn_min
 - typedefinitionsovertopping, 62
- foreshore_max
 - typedefinitionsovertopping, 62
- foreshore_min
 - typedefinitionsovertopping, 62
- formulaModuleOvertopping.f90, 93
- formulamoduleovertopping, 22
 - adjustinfluencefactors, 23
 - calculateanglewaveattack, 24
 - calculatebreakerlimit, 24
 - calculatebreakerparameter, 24
 - calculatewavelength, 25
 - calculatewaveovertoppingdischarge, 25
 - calculatewaverunup, 26
 - calculatewavesteepness, 27
 - cubicroots, 28
 - isequalreal, 28
 - isequalzero, 28
 - realrootscubicfunction, 29
 - rootsdepressedcubic, 29
 - rootsgeneralcubic, 30
- frunup1
 - typedefinitionsovertopping, 62
- frunup2
 - typedefinitionsovertopping, 62
- frunup3
 - typedefinitionsovertopping, 62
- fs_max
 - typedefinitionsovertopping, 62
- fs_min
 - typedefinitionsovertopping, 63
- fshallow
 - typedefinitionsovertopping::tpovertoppinginput, 87
- geometry_c_f
 - dlovertopping, 11
- geometryModuleOvertopping.f90, 94
- geometrymoduleovertopping, 31
 - adjustnonhorizontalberms, 31
 - allocatevectorsgeometry, 32
 - basicgeometrytest, 33
 - calculatehorzdistance, 33
 - calculatehorzlengths, 34
 - calculatesegmentslopes, 35
 - checkcrosssection, 35
 - copygeometry, 36
 - deallocategeometry, 36
 - determinesegmenttypes, 38
 - initializegeometry, 38
 - mergesequentialberms, 40
 - removeberms, 41
 - removedikesegments, 42
 - splitcrosssection, 42
- getformattoomanyberms
 - overtoppingmessages, 57
- getlanguage
 - dlovertopping, 13
 - overtoppingmessages, 57
- getmsg_calc_influence_roughness
 - overtoppingmessages, 57
- getmsg_calculategammaftohigh
 - overtoppingmessages, 57
- getmsg_calculategammaftolow
 - overtoppingmessages, 57
- getmsg_first_segment_berm
 - overtoppingmessages, 58
- getmsg_last_segment_berm
 - overtoppingmessages, 58
- getmsgremovenonhorizontalberm
 - overtoppingmessages, 58
- getovertoppingformat
 - overtoppingmessages, 58
- getovertoppingmessage
 - overtoppingmessages, 59
- getovertoppingparameter
 - overtoppingmessages, 59
- h
 - typedefinitionsovertopping::tpload, 84
- hm0
 - typedefinitionsovertopping::tpload, 84
- initializegeometry
 - geometrymoduleovertopping, 38
- innercalculation
 - waverunup, 66
- input_j_f
 - dlovertopping, 13
- interpolateresultssections
 - mainmoduleovertopping, 49

- isberm
 - omkeervariantmodule::tomkeer, 80
- isequalreal
 - formulamoduleovertopping, 28
- isequalzero
 - formulamoduleovertopping, 28
- isvalidz
 - omkeervariantmodule::tomkeer, 80
- iteratetogivendischarge
 - omkeervariantmodule, 52
- iteratetogivendischargevalidprofile
 - omkeervariantmodule, 54
- iterationwaverunup
 - waverunup, 67
- language
 - overtoppingmessages, 60
- m_z2
 - typedefinitionsovertopping::tpovertoppinginput, 87
- mainModuleOvertopping.f90, 95
- mainmoduleovertopping, 43
 - calculateovertopping, 44
 - calculateovertoppingnegativefreeboard, 45
 - calculateovertoppingsection, 45
 - calculatewaveovertopping, 46
 - checkinputdata, 47
 - checkmodel factors, 48
 - interpolateresultssections, 49
- margindiff
 - typedefinitionsovertopping, 63
- margingrad
 - typedefinitionsovertopping, 63
- maxfilenamelength
 - modulelogging, 50
- maxmsg
 - overtoppingmessages, 60
- maxpar
 - overtoppingmessages, 60
- mergesquentialberms
 - geometrymoduleovertopping, 40
- minzberm
 - omkeervariantmodule, 55
- ModuleLogging.f90, 96
- modulelogging, 49
 - maxfilenamelength, 50
- modulelogging::tlogging, 78
 - filename, 79
 - verbosity, 79
- mz2_max
 - typedefinitionsovertopping, 63
- mz2_min
 - typedefinitionsovertopping, 63
- nbermssegments
 - typedefinitionsovertopping::tpgeometry, 82
- ncoordinates
 - typedefinitionsovertopping::tpgeometry, 82
- normal
 - overtoppinginterface::overtoppinggeometrytype, 76
 - overtoppinginterface::overtoppinggeometrytypef, 77
- npoints
 - overtoppinginterface::overtoppinggeometrytype, 76
 - overtoppinginterface::overtoppinggeometrytypef, 77
- omkeerVariantModule.f90, 96
- omkeervariantf
 - dlovertopping, 13
- omkeervariantj
 - dlovertopping, 15
- omkeervariantmodule, 50
 - checkifonberm, 51
 - iteratetogivendischarge, 52
 - iteratetogivendischargevalidprofile, 54
 - minzberm, 55
 - toldikeheight, 55
 - toldischarge, 55
- omkeervariantmodule::tomkeer, 79
 - dischargeprofile, 80
 - isberm, 80
 - isvalidz, 80
 - zprofile, 80
- overtoppingInterface.f90, 97
- OvertoppingMessages.f90, 97
- overtoppinginterface, 56
 - varmodel factorcriticalovertopping, 56
- overtoppinginterface::overtoppinggeometrytype, 75
 - normal, 76
 - npoints, 76
 - roughness, 76
 - xcoords, 76
 - ycoords, 76
- overtoppinginterface::overtoppinggeometrytypef, 77
 - normal, 77
 - npoints, 77
 - roughness, 77
 - xcoords, 78
 - ycoords, 78
- overtoppinginterface::tpprofilecoordinate, 88
 - roughness, 88
 - xcoordinate, 89
 - zcoordinate, 89
- overtoppingmessages, 56
 - getformattoomanyberms, 57
 - getlanguage, 57
 - getmsg_calc_influence_roughness, 57
 - getmsg_calculategammaftohigh, 57
 - getmsg_calculategammaftolow, 57
 - getmsg_first_segment_berm, 58
 - getmsg_last_segment_berm, 58
 - getmsgremovenonhorizontalberm, 58
 - getovertoppingformat, 58
 - getovertoppingmessage, 59
 - getovertoppingparameter, 59

- language, 60
- maxmsg, 60
- maxpar, 60
- setlanguage, 59
- phi
 - typedefinitionsovertopping::tpload, 84
- profileinstructure
 - zfunctionsovertopping, 71
- psi
 - typedefinitionsovertopping::tpgeometry, 82
- qo
 - typedefinitionsovertopping::tpovertopping, 85
- realrootscubicfunction
 - formulamoduleovertopping, 29
- reductionfactorforeshore
 - typedefinitionsovertopping::tpovertoppinginput, 87
- relaxationfactor
 - typedefinitionsovertopping::tpovertoppinginput, 87
- removeberms
 - geometrymoduleovertopping, 41
- removedikessegments
 - geometrymoduleovertopping, 42
- rfactor_max
 - typedefinitionsovertopping, 63
- rfactor_min
 - typedefinitionsovertopping, 63
- rootsdepressedcubic
 - formulamoduleovertopping, 29
- rootsgeneralcubic
 - formulamoduleovertopping, 30
- roughness
 - overtoppinginterface::overtoppinggeometrytype, 76
 - overtoppinginterface::overtoppinggeometrytypef, 77
 - overtoppinginterface::tpprofilecoordinate, 88
- roughnessfactors
 - typedefinitionsovertopping::tpgeometry, 82
- segmentslopes
 - typedefinitionsovertopping::tpgeometry, 82
- segmenttypes
 - typedefinitionsovertopping::tpgeometry, 82
- separationchar
 - dllovertopping, 19
- setlanguage
 - dllovertopping, 16
 - overtoppingmessages, 59
- slope_max
 - typedefinitionsovertopping, 63
- slope_min
 - typedefinitionsovertopping, 63
- splitcrosssection
 - geometrymoduleovertopping, 42
- tm_10
 - typedefinitionsovertopping::tpload, 84
- toldikeheight
 - omkeervariantmodule, 55
- toldischarge
 - omkeervariantmodule, 55
- typeDefinitionsOvertopping.f90, 98
- typedefinitionsovertopping, 60
 - berm_max, 61
 - berm_min, 61
 - fb_max, 62
 - fb_min, 62
 - fn_max, 62
 - fn_min, 62
 - foreshore_max, 62
 - foreshore_min, 62
 - frunup1, 62
 - frunup2, 62
 - frunup3, 62
 - fs_max, 62
 - fs_min, 63
 - margindiff, 63
 - margingrad, 63
 - mz2_max, 63
 - mz2_min, 63
 - rfactor_max, 63
 - rfactor_min, 63
 - slope_max, 63
 - slope_min, 63
 - xdiff_min, 64
 - z2_iter_max1, 64
 - z2_iter_max2, 64
 - z2_margin, 64
- typedefinitionsovertopping::tpgeometry, 80
 - nbermssegments, 82
 - ncoordinates, 82
 - psi, 82
 - roughnessfactors, 82
 - segmentslopes, 82
 - segmenttypes, 82
 - xcoorddiff, 82
 - xcoordinates, 82
 - ycoorddiff, 83
 - ycoordinates, 83
- typedefinitionsovertopping::tpload, 83
 - h, 84
 - hm0, 84
 - phi, 84
 - tm_10, 84
- typedefinitionsovertopping::tpovertopping, 84
 - qo, 85
 - z2, 85
- typedefinitionsovertopping::tpovertoppinginput, 86
 - computedovertopping, 87
 - criticalovertopping, 87
 - factordeterminationq_b_f_b, 87
 - factordeterminationq_b_f_n, 87
 - fshallow, 87
 - m_z2, 87

- reductionfactorforeshore, [87](#)
- relaxationfactor, [87](#)
- validateinputc
 - dllovertopping, [16](#)
- validateinputf
 - dllovertopping, [17](#)
- validateinputj
 - dllovertopping, [18](#)
- varmodelfactorcriticalovertopping
 - overtoppinginterface, [56](#)
- verbosity
 - modulelogging::tlogging, [79](#)
- versionnumber
 - dllovertopping, [18](#)
- waveRunup.f90, [100](#)
- waverunup, [64](#)
 - convergedwithresidu, [65](#)
 - determinestartingvalue, [65](#)
 - findsmallestresidu, [65](#)
 - innercalculation, [66](#)
 - iterationwaverunup, [67](#)
- xcoorddiff
 - typedefinitionsovertopping::tpgeometry, [82](#)
- xcoordinate
 - overtoppinginterface::tpprofilecoordinate, [89](#)
- xcoordinates
 - typedefinitionsovertopping::tpgeometry, [82](#)
- xcoords
 - overtoppinginterface::overtoppinggeometrytype, [76](#)
 - overtoppinginterface::overtoppinggeometrytypef, [78](#)
- xdiff_min
 - typedefinitionsovertopping, [64](#)
- ycoorddiff
 - typedefinitionsovertopping::tpgeometry, [83](#)
- ycoordinates
 - typedefinitionsovertopping::tpgeometry, [83](#)
- ycoords
 - overtoppinginterface::overtoppinggeometrytype, [76](#)
 - overtoppinginterface::overtoppinggeometrytypef, [78](#)
- z2
 - typedefinitionsovertopping::tpovertopping, [85](#)
- z2_iter_max1
 - typedefinitionsovertopping, [64](#)
- z2_iter_max2
 - typedefinitionsovertopping, [64](#)
- z2_margin
 - typedefinitionsovertopping, [64](#)
- zFunctionsOvertopping.f90, [100](#)
- zcoordinate
 - overtoppinginterface::tpprofilecoordinate, [89](#)
- zfunclogratios
 - zfunctionsovertopping, [72](#)
- zfunctionsovertopping, [68](#)
 - adjustprofile, [69](#)
 - calculateqorto, [69](#)
 - profileinstructure, [71](#)
 - zfunclogratios, [72](#)
- zprofile
 - omkeervariantmodule::tomkeer, [80](#)