GraphCompose Markdown

User Manual — written in Markdown, rendered by the library itself

Artem Demchyshyn · 2026-07-01

Contents

Contents 1
What is this? 1
Installation 2
Quick start 2
  Ways in, ways out 2
What renders 3
  Inline formatting 3
  Smart punctuation 3
  Lists and tasks 3
  Tables 3
  Code with syntax highlighting 4
  Quotes, alerts and callouts 4
  Emoji 4
Theming 4
Navigation and page chrome 5
Extending 5
Command line 6
Runnable examples 6
How this PDF was made 6

What is this?

graphcompose-markdown turns Markdown into themed, paginated PDF. It parses with Flexmark, maps the parse tree onto an independent semantic model, and renders that model through the GraphCompose engine, which owns measurement, layout, pagination and output.

Three concerns stay separate, and that separation is the whole point:

- Content — your Markdown text.
- Appearance — a theme: colors, fonts, spacing, per-element styles, renderers.
- Layout — the engine: measurement, pagination, PDF.

The same Markdown can be reskinned into a completely different document without touching its

text. The document you are reading right now is the proof: it is a plain `.md` file rendered by the library, using the book-style table of contents above (with live page numbers), the “Page N of M” footer below, vector emoji, and smart punctuation — every dash, ellipsis and curly quote in this manual was typed as `--`, `...` and straight quotes.

> **Note**
>
> Everything shown in this manual is produced by the code paths it documents. If a feature renders here, it works.

Installation

The library is a single Maven dependency; the GraphCompose engine comes in transitively:

```
<dependency>
    <groupId>io.github.demchaav</groupId>
    <artifactId>graph-compose-markdown</artifactId>
    <version>0.3.1</version>
</dependency>
```

> **Note**
>
> Not yet on Maven Central (first release pending). Until then, build from source (`./mvnw install`) and depend on the snapshot, or consume a tagged version via JitPack.

Two optional companion artifacts unlock extras; add them only if you want them:

Artifact	What it adds
`graph-compose-fonts`	JetBrains Mono for code (`BundledFonts.jetBrainsMonoCode(theme)`)
`graph-compose-emoji`	Noto vector emoji: `:rocket:` just works 🚀

Requires Java 17+.

Quick start

```
import io.github.demchaav.markdown.composer.MarkdownComposer;
import io.github.demchaav.markdown.theme.DefaultMarkdownTheme;
import java.nio.file.Path;

MarkdownComposer composer = MarkdownComposer.create(DefaultMarkdownTheme.light
());

composer.render("# Hello\n\nWorld").writePdf(Path.of("hello.pdf"));
composer.renderFile(Path.of("doc.md")).writePdf(Path.of("doc.pdf"));
```

A composer is immutable and thread-safe — build it once, reuse it everywhere.

Ways in, ways out

Take this in	Call
A Markdown string	`render(String)`
A Markdown file (UTF-8, relative images resolve next to it)	`renderFile(Path)`
A file with your own image resolver	`renderFile(Path, ImageResolver)`
A parsed Flexmark `Document`	`render(Document)`
A hand-built semantic model	`render(MarkdownDocument)`

Get this out	Call
A PDF file	`writePdf(Path)`
A PDF stream	`writePdf(OutputStream)`
PDF bytes	`toPdfBytes()`
Page images (thumbnails, previews)	`toImages(dpi)` / `toImage(pageIndex, dpi)`

What renders

Everything in this section is live — the source of this manual uses each feature.

Inline formatting

Paragraphs carry bold, italic, strikethrough and `inline code` on its rounded chip. Links come in three kinds: external, bare autolinks like https://github.com, and internal jumps — back to the contents is a native PDF go-to action, not decoration. Footnotes are clickable in both directions.[1]

Smart punctuation

This manual is rendered with `smartPunctuation(true)`: dashes – and — em-dashes, ellipses… and “curly quotes” are typed as plain ASCII in the source. It is off by default (GitHub does not smart-quote); code always stays verbatim: `a --flag "x"`.

Lists and tasks

1. Ordered lists keep their numbering
2. and nest:
   - unordered bullets cycle shape by depth
   - task lists render real checkboxes:
     - [x] parse Markdown
     - [x] map to the semantic model
     - [ ] profit

Tables

Feature	Alignment	Status
GFM tables	center	✅
Per-column alignment	center	✅
Inline formatting in cells	works	`yes`

Code with syntax highlighting

```
// The built-
in RegexSyntaxHighlighter covers ~15 languages, no extra dependency.
public static void main(String[] args) {
    var composer = MarkdownComposer.create(GitHubTheme.dark());
    byte[] pdf = composer.render("# Reskinned").toPdfBytes();
// 42 ways to say hello
}
```

Quotes, alerts and callouts

> A blockquote is a left-accented aside. Design tokens drive its cosmetics.

> **Tip**
>
> The five GitHub alerts (`NOTE` , `TIP` , `IMPORTANT` , `WARNING` , `CAUTION`) render as color-coded panels with vector icons.

> **Warning**
>
> Their accent colors are theme tokens (`AlertColors`) — a dark theme can retune them.

> `:::` custom blocks are an extension seam: register your own renderer per block type, or let unbound types fall back to this callout style.

Emoji

With `graph-compose-emoji` on the classpath, shortcodes render as crisp vector glyphs at any size: 🚀 ✅ ❤️ ⭐ 🔥 — no image files to supply. Geometric emoji typed literally render as native vector shapes even without it: status 🔴 blocker, 🟡 important, 🟢 nice to have — and inside code too:

```
Priority: 🔴 blocker  🟡 important  🟢 nice to have
```

An unknown shortcode stays readable text: :definitelynotanemoji:.

Theming

A theme has three layers; override exactly as much as you need:

1. Design tokens (`MarkdownTokens`) — colors, fonts, sizes, spacing, page geometry.
2. Component styles (`MarkdownStyles`) — per-element styles derived from tokens.
3. Node renderers (`NodeRenderer`) — the behaviour turning each node into engine calls.

```
MarkdownTheme base = DefaultMarkdownTheme.light();

MarkdownTheme custom = MarkdownTheme.builder(base)
        .tokens(base.tokens().withColors(
                base.tokens().colors().withCodeBackground(DocumentColor.rgb(246
, 248, 250))))
        .renderer(CodeBlockNode.class, new MyLabeledCodeBlockRenderer())
        .build();
```

Ready-made packs ship in `io.github.demchaav.markdown.theme.packs` : `GitHubTheme` (light/dark), `AcademicTheme` , `MinimalTheme` , `BusinessReportTheme` — plus `DefaultMarkdownTheme.light()` / `.dark()` .

Navigation and page chrome

Long documents stay navigable; this manual demonstrates all of it:

- PDF outline — every heading becomes a bookmark; the panel opens automatically (opt out: `builder().openOutline(false)`).
- Anchors — every heading gets a GitHub-style slug, so `[text](#what-renders)` jumps there.
- `[TOC]` — the marker at the top of this manual expands into the contents. Two forms: the default clickable link list, and the book form used here — dot leaders and live page numbers, resolved by the engine after layout:

```
MarkdownTheme book = MarkdownTheme.builder(base)
        .renderer(TocNode.class, new BookTocRenderer("Contents"))
        .tokens(base.tokens().withFooter(FooterTokens.pageNumbers()))
        .build();
```

- Footer — the “Page N of M” at the bottom of every page here is `FooterTokens` : `left` / `center` / `right` templates with `{page}` , `{pages}` and `{date}` placeholders, disabled by default.

Extending

- Custom `:::` blocks — `builder().customBlock("chart", new ChartRenderer())` routes every `:::chart` block to your renderer.
- Swap any renderer — `builder().renderer(TableNode.class, myTableRenderer)` replaces one node type and reuses everything else (that is exactly how the book TOC works).
- Emoji override — an `EmojiResolver` supplying PNG bytes wins over the vector set.
- Syntax highlighting — plug a grammar-based `SyntaxHighlighter` via `builder().highlighter(...)` ; colors stay theme tokens.
- Strict mode — `builder().strictMode(true)` rejects unsupported content (raw HTML) instead of surfacing it as literal text.

Command line

The standalone `cli/` module wraps all of this for the shell:

```
gcmd README.md -t github-dark          # theme by name
gcmd docs/guide.md -o out/guide.pdf    # explicit output
cat notes.md | gcmd - -o notes.pdf     # stdin
```

Runnable examples

Each feature ships a runnable example under `examples/` — see `examples/README.md`: QuickStart, RenderMarkdownFile, ThemeGallery, CustomBlock, AlertsAndOutline, InPdfNavigation, Toc, BookToc, Footer, PngExport, VectorEmoji, Emoji, FrontMatter.

How this PDF was made

This manual is `assets/readme/manual.md`, rendered by `ManualTest` with exactly this composer — the self-referential proof that the pipeline works:

```
MarkdownTheme base = DefaultMarkdownTheme.light();
MarkdownTheme manualTheme = MarkdownTheme.builder(base)
        .renderer(TocNode.class, new BookTocRenderer())
// page-numbered contents
        .tokens(base.tokens().withFooter(FooterTokens.pageNumbers()))
        .imageResolver(new DefaultImageResolver(Path.of("assets", "readme")))
        .build();

MarkdownComposer.builder()
        .theme(manualTheme)
        .smartPunctuation(true)
// the dashes you saw
        .build()
        .renderFile(Path.of("assets", "readme", "manual.md"))
        .writePdf(Path.of("assets", "readme", "manual.pdf"));
```

A dark twin — `manual-dark.pdf` — is rendered from this same source file with `DefaultMarkdownTheme.dark()`: swap one theme object, reskin the whole document. That is the separation of content and appearance doing its job.

Both libraries are MIT-licensed. Happy composing. 🎉

Notes

[1] Click the marker above to land here; click the `[1]` at the start of this note to jump back to the citation.