Lecture 15-1-Digital Watermarking

Yuyao Zhang PhD

zhangyy8@shanghaitech.edu.cn

SIST Building 2 302-F

Watermarking

We all like watermarks，so charming…

Purpose of Digital Watermarking

➢ **Anti-counterfeiting（防伪）：**

Embedding information into an image, so that:

- Image seems unchanged
- Watermark can be extracted even after processing.
- Removing watermark should destroy the image.

Anti-counterfeiting

Fundamentals of Image Compression

- **Insertion/ embedding:**



- **Detection:**



Spatial watermarking

- Idea: mark less significant bits.

w is a 2-bit image; I is a 8-bits image.

$$I_w = \left[\frac{I}{4}\right] * 4 + \frac{w}{64}$$

Take the floor
6-bits approx + 2 bits's of w

- Easy to remove.
- Not robust at all to all kinds of noise.

Spatial watermarking

Anti-counterfeiting

Robust watermarking in frequency domain 1

- Idea: hide information in visually important frequency bands.
- Embedding:
  - Compute DCT of the entire image.
  - Find K largest magnitude coefficients $c_1, c_2, c_3, \cdots, c_K$ (not included DC).
  - Watermark is a K-length random vector or a logo image: $w_1, w_2, w_3, \cdots, w_K$.
  - Embed the watermark: $c'_i = c_i\,(1 + \alpha w_i)$ (α>0) .
  - Replace c_i with c'_i, and take the inverse DCT.

Robust watermarking in frequency domain 1

- Idea: hide information in visually important frequency bands.
- Embedding:
  - Compute DCT of the entire image.
  - Find K largest magnitude coefficients $c_1, c_2, c_3, \cdots, c_K$ (not included DC).
  - Watermark is a K-length random vector or a logo image: $w_1, w_2, w_3, \cdots, w_K$.
  - Embed the watermark: $c'_i = c_i\,(1 + \alpha w_i)$ (α>0) .
  - Replace c_i with c'_i, and take the inverse DCT.

Robust watermarking in frequency domain 1

- **Decoding:**
  - Compute DCT of the image.
  - Extract K coefficient in known locations (side information, may differ from original case).
  - Compute $\widehat{w'}_i = (\frac{c'_i}{c_i} - 1)/\alpha$
  - Find information in $\widehat{w'}_i$.

Robust watermarking in frequency domain 2

- Idea: hide binary information in comparable values.
- Simple frequency-flipping method: (block-based)
- Compute DCT of cropped blocks.

```
Y_Table=[ 16  11  10  16  24  40  51  61 ; ...
          12  12  14  19  26  58  60  55 ; ...
          14  13  16  24  40  57  69  56 ; ...
          14  17  22  29  51  87  80  62 ; ...
          18  22  37  56  68 109 103  77 ; ...
          24  35  55  64  81 104 113  92 ; ...
          49  64  78  87 103 121 120 101 ; ...
          72  92  95  98 112 100 103  99 ];
```

- Choose 2 DCT coefficients location that are expected to have comparable average values/range.

  N(4,1) = N(2,3) = 14;

- Per 8X8 block, compute DCT c(u,v);

  c(4,1) > c(2,3) then bit 0; c(4,1) > c(2,3) then bit 1;

- If coefficients don't already match w, flip them.

Take home message

- **Desirable properties for digital watermark**
  - Visual imperceptible
  - Statistically imperceptible
  - Robust to inadvertent or intentional attacks.
    - Cropping resizing, compression, enhancement, rotation.
    - Print image/rescan, collusion.
  - Alternative: fragile watermark breaks as soon as image is modified.
  - High capacity.
  - Speed of embedding and detection.