




# Angular Advanced

## 02 – Lazy loading



Peter Kassenaar –  
[info@kassenaar.com](mailto:info@kassenaar.com)

# What is lazy loading

- Deferred loading of modules, until the user needs them.
  - OR: for optimal user experience:
    - Load the minimum setup for the application to work, so the user can interact with the app.
    - Then asynchronously load other modules.
    - They are instantly available if the user navigates to them
- Only *modules* can be loaded lazily, not *components*.
- Lazy loading works in conjunction with the router.
- It is considered best practice nowadays to use LL from the start

# Victor Savkin – creator of the router



Sign in / Sign up



Victor Savkin

Co-founder of Narwhal Technologies (nrwl.io), where we provide Angular consulting to large teams who wa...

Oct 12, 2016 · 3 min read

## Angular Router: Preloading Modules



ANGULAR  
ROUTER



*Victor Savkin is a co-founder of [nrwl.io](https://nrwl.io), providing Angular consulting to enterprise teams. He was previously on the Angular core team at Google, and built the dependency injection, change detection, forms, and router modules.*

 Never miss a story from **Angular**, when you sign up for Medium.  
Learn more

GET UPDATES

<https://vsavkin.com/angular-router-preloading-modules-ba3c75e424cb>

# Official documentation

The screenshot shows the Angular official documentation website. The top navigation bar includes links for FEATURES, DOCS, RESOURCES, EVENTS, and BLOG. A search bar on the right contains the text "rout". The left sidebar lists the documentation structure, with "FUNDAMENTALS" expanded and "Routing & Navigation" selected. The main content area displays the "Milestone 6: Asynchronous routing" page, which is circled in red. The page content includes an introduction to asynchronous routing, a list of benefits, and a section on lazy loading route configuration. The right sidebar shows a list of topics, with "Query parameters and fragments" highlighted.

queryParamsHandling and preserveFragment bindings respectively.

## Milestone 6: Asynchronous routing

As you've worked through the milestones, the application has naturally gotten larger. As you continue to build out feature areas, the overall application size will continue to grow. At some point you'll reach a tipping point where the application takes long time to load.

How do you combat this problem? With asynchronous routing, which loads feature modules *lazily*, on request. Lazy loading has multiple benefits.

- You can load feature areas only when requested by the user.
- You can speed up load time for users that only visit certain areas of the application.
- You can continue expanding lazy loaded feature areas without increasing the size of the initial load bundle.

You're already made part way there. By organizing the application into modules— `AppModule` , `HeroesModule` , `AdminModule` and `CrisisCenterModule` —you have natural candidates for lazy loading.

Some modules, like `AppModule` , must be loaded from the start. But others can and should be lazy loaded. The `AdminModule` , for example, is needed by a few authorized users, so you should only load it when requested by the right people.

### Lazy Loading route configuration

Change the `admin` path in the `admin-routing.module.ts` from `'admin'` to an empty string, `''`, the *empty path*.

The `Router` supports *empty path* routes; use them to group routes together without adding any additional path segments to the URL. Users will still visit `/admin` and the `AdminComponent` still serves as the *Routing*

authentication

Component-less route: grouping routes without a component

*CanActivateChild*: guarding child routes

*CanDeactivate*: handling unsaved changes

Cancel and save

*Resolve*: pre-fetching component data

Fetch data before navigating

- [Query parameters and fragments](#)

Milestone 6: Asynchronous routing

Lazy Loading route configuration

*CanLoad* Guard: guarding unauthorized loading of feature modules

Preloading: background loading of feature areas

Custom Preloading Strategy

Inspect the router's configuration

[Wrap up and final app](#)

Appendices

Appendix: link parameters array

<https://angular.io/guide/router#asynchronous-routing>

# How to lazy load

Add or edit `app.routing.module.ts`

- Don't point directly to components
- Point to Modules instead. Use `loadChildren()`


```
const routes: Routes = [  
  {path: '', redirectTo: 'customers', pathMatch: 'full'},  
  {path: 'customers', loadChildren: './customer/customer.module#CustomerModule'},  
  {path: 'products', loadChildren: './products/products.module#ProductsModule'},  
];
```

```
export const AppRoutingModule = RouterModule.forRoot(routes);
```

Edit `app.module.ts` (no more loading of modules)

```
// import routing module that defines the LL
import {AppRoutingModule} from './app.routing.module';

@NgModule({
  ...
  imports      : [
    BrowserModule,
    AppRoutingModule
  ],
  bootstrap    : [AppComponent]
})
export class AppModule {
}
```



Edit separate modules,  
add `RouterModule.forChild()` with various components.

```
import {RouterModule, Routes} from '@angular/router';
```

```
// lazy loaded routes for this module
```

```
const customerRoutes: Routes = [  
  {path: '', component: CustomerComponent}  
];
```


```
@NgModule({  
  imports : [  
    ...  
    RouterModule.forChild(customerRoutes)  
  ],  
  ...  
})
```

```
export class CustomerModule {  
}  
console.log('CustomerModule loaded lazily...');
```



# Workshop

- Open `../110-lazy-loading`.
  - Create a new module
  - Create a new component inside this new module and give it some UI.
  - Add a route to the new component
  - Use the new module in the root module and lazy load it
  - Add a link to navigate to the lazy loaded module.
- 
- *OR:*
  - Add LL from scratch to your own application, using the steps described in this module.
  - Add a new (dynamic) child route to Module







# Preloading strategies

# Preloading Strategies

- Optimize Lazy Loading even further: preloading strategies
  - Load all modules in background
  - Load only modules *you want to load* in the background
- Default preloading: PreloadAllModules

```
import {ExtraOptions, PreloadAllModules,  
        RouterModule, Routes} from '@angular/router';
```

```
const config: ExtraOptions = {  
  preloadingStrategy: PreloadAllModules  
};
```

```
export const AppRoutingModule = RouterModule.forRoot(routes, config);
```

The image shows two overlapping Chrome DevTools windows. The top window displays the Console tab with three log messages:

- Angular is running in the development mode. Call `enableProdMode()` to enable the production mode. (`core.es5.js:2925`)
- CustomerModule loaded lazily... (`customer.module.ts:26`)
- ProductsModule loaded lazily... (`products.module.ts:26`)

The bottom window displays the Network tab with a list of requests. Three red arrows point to the first three entries: `2.chunk.js`, `0.chunk.js`, and `ng-validate.js`.


Name	Sta...	Type	Initiator	Size	Time	Waterfall
2.chunk.js	200	scri...	bootstra...	5.4 ...	94 ...	
0.chunk.js	200	scri...	bootstra...	7.1 ...	93 ...	
ng-validate.js	200	scri...	content...	(fro...	2 ms	
1.chunk.js	200	scri...	bootstra...	5.3 ...	6 ms	
backend.js	200	scri...	content...	(fro...	54 ...	

<https://angular.io/api/router/PreloadAllModules>

# Custom preloading strategy

- Define which module(s) are loaded lazily, while others are loaded on demand
- Solution: compose a strategy that *only* preloads routes when a custom `data.preload` flag is set to `true`

```
{
  path      : 'products',
  loadChildren: './products/products.module#ProductsModule',
  data      : {preload: true}
},
{
  path      : 'big-module',
  loadChildren: './very-big-module/very-big-module.module#VeryBigModule'
},
```



# Steps

1. Create new module, with a (potential) heavy load
2. Add data property and set { preload:true } to every route you want to load lazily
3. Assign custom preloader to preloadingStrategy:

```
...  
const config: ExtraOptions = {  
  preloadingStrategy: MyCustomPreloader  
};  
@NgModule({  
  imports : [RouterModule.forRoot(routes, config)],  
  exports : [RouterModule],  
  providers: [MyCustomPreloader]  
})  
export class AppRoutingModule {  
}
```



# Define custom loader

```
// app.routing.loader.ts

import { PreloadingStrategy, Route } from '@angular/router';

import { Observable } from 'rxjs/Observable';
import 'rxjs/add/observable/of';

export class MyCustomPreloader implements PreloadingStrategy {
  preload(route: Route, load: Function): Observable<any> {
    // only preload the route if data attribute is set and preload===true
    return route.data && route.data.preload ? load() : Observable.of(null);
  }
}
```

# Run the app

Run the app. The first 2 modules should be loaded lazily, the third module should be loaded on demand

Example application with Lazy Loading modules

CUSTOMERS PRODUCTS VERY BIG MODULE

Big Module

Some very big list

- Item 0
- Item 1
- Item 2



Console Log:

- Angular is running in the development mode. Call `enableProdMode()` to enable the production mode. (`core.es5.js:2925`)
- CustomerModule loaded lazily... (`customer.module.ts:26`)
- ProductsModule loaded lazily... (`products.module.ts:26`)
- Very big module, loaded on demand (`very-big-module.module.ts:20`)

Example: ../120-custom-preloading

# More information

[TRAINING](#) [WORK](#) [BLUEPRINT](#)



My name is [Cory Rylan](#), Senior Front End Developer at [Vintage Software](#) and [Angular Boot Camp](#) instructor. I specialize in creating fast, scalable, and responsive web applications.

[Follow @coryryan](#)

## Custom Preloading and Lazy Loading Strategies with Angular

Cory Rylan  
Apr 30, 2017 - 5 min read


[angular](#) [performance](#)

This article is for versions of Angular 2, Angular 4 and later.

Angular has many features that allow us to configure apps to be as fast and high performing as possible. One of the critical features that enable responsive fast Angular apps is the ability to lazy load code with the Angular Router. This allows our initial bundles to remain small ensuring faster download and start up times for our users.

<https://coryryan.com/blog/custom-preloading-and-lazy-loading-strategies-with-angular>

## Manfred Steyer - Improving Startup Performance with Lazy Loading in Angular



NG-NL 2017: Manfred Steyer - Improving Startup Performance with Lazy Loading in Angular


NG-NL

<https://www.youtube.com/watch?v=n6EMOeCDfjc>



# Workshop

- Add a new module w/ component to your application.
- Add the module to the routing section of your application. Add a link to navigate to the route.
- Let *other* components be loaded lazily by adding a data property
- Write a custom preloading class, in `app.preloader.ts`
- Add the custom preloader to `app.routing.module.ts`.
  - Note: make sure this is (now) actually a Module, as it has to import and provide `app.preloader.ts`



# Dynamically Loading *Components*

Sign inGet started

HOMEANGULARRXJSWEBPACKQ

Chaz GatianFollow

Web developer passionate about new technologies  
Jan 10 · 6 min read

## Dynamically Loading Components with Angular CLI



*This post and the code for it was a team effort, including my teammates [Zack](#)*

4

Beware!  
Deep stuff.

<https://blog.angularindepth.com/dynamically-loading-components-with-angular-cli-92a3c69bcd28>