

Developement of Digital Twins of Scientific Equipment and Systems for MegaScience-class Installations.

Denis Zhigalov

Master Student.

Department of Computer Technologies,
Novosibirsk State University.
email: d.zhigalov@g.nsu.ru

Stanislav Shakirow

Scientific Advisor.

Ph.D. in Physics and Mathematics,
Associate Professor,
Department of Computer Technologies,
Novosibirsk State University.
Acting Director of the Tecnological
Design Institute of Scientific
Instrument Engineering of the
Siberian Branch of the RAS.
email: shakirov@tdisie.nsc.ru

11.10.2023

Abstract

Within the sphere of MegaScience-class installations, the advent of digital twin technology marks a paradigm shift, presenting unparalleled prospects for advancing the design, operation, and upkeep of scientific apparatus and systems. A digital twin, embodying a virtual counterpart of a physical entity, facilitates real-time forecasting, optimization, surveillance, management, and enhanced strategic decision-making in the realm of scientific equipment and systems.

The article presents a detailed exploration into the development of digital twins for MegaScience installations, with a special focus on the Siberian Ring Source of Photons (SKIF). It begins by reviewing existing literature on

digital twin technology in mega-science projects, emphasizing the need for advanced simulation and operational efficiency in these high-end scientific endeavors. The article then delves into the application of the Digital Twin technology specifically in the development of a digital twin for the diamond window of the Siberian Ring Source of Photons (SKIF), a component critical for the facility's performance. Employing a combination of COMSOL Multiphysics for accurate heat and stress field generation for small subset of input parameters and Support Vector Regression for real time prediction of these fields for other parameters, the study delves into the intricacies of simulating the diamond window's behavior under various operational scenarios. From initial Python simulations development goes to more advanced CUDA and C++ prototypes, a shift that significantly boosts computational efficiency. The article presents a thorough analysis of the developmental process, highlighting the potential of digital twins in predictive maintenance and operational optimization. Developed diamond window Digital Twin prototype will be used in further work as a part of SKIF front-end digital twin.

Keywords: Digital Twin, MegaScience Facilities, Siberian Ring Source of Photons, Diamond Window, Importance, Potential, COMSOL Multiphysics, Support Vector Regression, Operational Efficiency, Predictive Maintenance, Simulation Technologies.

1 Introduction

In the realm of MegaScience-class installations, the concept of digital twins has emerged as a transformative technology, offering unprecedented opportunities for enhancing the design, operation, and maintenance of scientific equipment and systems. A digital twin is a virtual representation of a physical asset that enables real-time prediction, optimization, monitoring, controlling, and improved decision making in scientific equipment and systems [1]. This technology is not just a theoretical construct but a practical tool that has been increasingly applied in various fields, including manufacturing, healthcare, and now, in scientific research facilities.

The development of digital twins for scientific equipment and systems involves creating a framework that provides monitoring and evaluation capabilities for equipment involved in manufacturing and experiments [2]. This framework is crucial for MegaScience-class installations, where the complexity and scale of

equipment and experiments demand precise and real-time monitoring for optimal performance and safety.

Moreover, digital twins serve as a new normal form for solving problems in a changing context, such as in the case of product quality monitoring, as highlighted by Zhang et al. (2020) in their study on a product quality monitor model with the digital twin model [3]. This adaptability is particularly valuable in the dynamic environment of MegaScience installations, where equipment and systems must consistently operate at peak efficiency under varying conditions.

The integration of computational models, sensors, learning, real-time analysis, diagnosis, and prognosis in digital twins supports engineering decisions related to specific assets [4]. This comprehensive approach is essential for the intricate and high-stakes nature of scientific research, where even minor miscalculations or malfunctions can lead to significant setbacks.

The article "Development of Digital Twins of Scientific Equipment and Systems for MegaScience-class Installations" begins with an overview of digital twin technology and its application in mega-science projects, highlighting the significance of such technology in facilitating remote operation and maintenance of complex scientific installations. It then shifts focus to the specifics of developing a digital twin for the Siberian Ring Source of Photons (SKIF), especially for its critical diamond window component. The methodology section elaborates on the simulation techniques used, including COMSOL Multiphysics and machine learning methods like Support Vector Regression. Preliminary results from the Python and CUDA/C++ prototypes are presented, showcasing the progress and potential of the digital twin. The article concludes by summarizing the findings and discussing their implications for future research and application.

2 Literature Review

In the evolving landscape of mega-science projects, the integration of digital infrastructure and remote access capabilities has become increasingly crucial. A seminal paper in this domain is [5], which offers a comprehensive analysis of the role and implementation of digital twins and digital traces in mega-science facilities. This paper is instrumental in understanding the shift towards remote accessibility in scientific research, particularly in the context of large-scale, international scientific collaborations.

Balyakin et al. emphasize the necessity of minimizing the physical presence of researchers at scientific facilities, a concept exemplified by the Borexino project's

use of an independent data collection system. This approach not only facilitates remote data acquisition but also significantly reduces the logistical and financial burdens associated with travel to these facilities. The paper further delves into the development of appropriate digital infrastructure, highlighting the need for new digital elements such as data centers and advanced processing algorithms. This infrastructure is crucial for the seamless integration of mega-science installations into existing e-Infrastructure, thereby enhancing the efficiency and scope of scientific research.

Moreover, the paper discusses the legal and methodological frameworks required to support the operation of scientific facilities in remote access mode. This aspect is critical in addressing the challenges posed by data security, intellectual property rights, and the nuances of international scientific cooperation. The authors also underscore the importance of engineering personnel in maintaining and ensuring the functionality of remote access modes, pointing to the need for specialized skills and resources in this area.

A key contribution of this paper is its exploration of the concept of e-Infrastructure, particularly its emergence and evolution within the European Union. The European Open Science Cloud (EOSC) and the Go FAIR initiative are presented as pivotal developments in this field, demonstrating the EU's commitment to digitalizing scientific research and fostering a more interconnected scientific community. The paper posits that while natural sciences are the initial beneficiaries of e-Infrastructure, its most significant impacts are likely to be seen in the field of humanities, necessitating the development of new assessment methods and legal solutions.

In summary, "Digital Twins vs Digital Trace in Megascience Projects" by Balyakin et al. is a foundational paper that provides valuable insights into the digital transformation of mega-science facilities. It not only addresses the technical and infrastructural aspects of this transformation but also considers the broader implications for scientific research, policy, and international collaboration. The paper's exploration of digital twins and digital traces offers a nuanced understanding of modern data processing techniques, making it a crucial reference for researchers and policymakers involved in the planning and operation of large-scale scientific installations.

In developing a digital twin for the Siberian Ring Source of Photons, the findings from the article by Pukhovoy et al. become particularly relevant. The study's focus on optimizing diamond foil thickness for thermal management in synchrotron beams can be instrumental in creating a virtual model that accurately simulates the thermal behaviors and stress responses of the diamond window in the Siberian

Ring Source [6]. This digital twin can aid in predicting performance, optimizing design, and enhancing operational safety and efficiency, leveraging the insights gained from the detailed numerical simulations presented in the article.

The article "Features of Device Cooling in Wiggler Synchrotron Workstations" addresses the unique cooling challenges in synchrotron radiation (SR) workstations, particularly in high-vacuum environments with high energy beam densities. It emphasizes the importance of efficient cooling systems for optical elements, discussing various methods, including mini-channel cooling, and providing detailed examples of thermal management in specific workstation devices. The research includes computational simulations for understanding the thermal behavior of devices like diamond filters under intense heat fluxes, crucial for ensuring the reliability and effectiveness of the cooling systems. This study's insights are particularly relevant for developing a digital twin of the Siberian Ring Source of Photons' diamond window, as it offers comprehensive data on cooling techniques and thermal management strategies in challenging synchrotron environments [7].

3 Research Setup

3.1 The Siberian Ring Source of Photons (SKIF) and the Development of its Digital Twin

The Siberian Ring Source of Photons (SKIF) represents a significant advancement in the field of synchrotron radiation sources. As a 4+ generation synchrotron with six research workstations, SKIF generates synchrotron radiation with a power density of 92 kW/mrad², making it a key research tool in physics and scientific research [8, 9]. This 3-GeV electron energy SR source, developed in Novosibirsk, is designed to provide a new level of capabilities for scientific experiments, particularly in the fields of materials science and physics [10, 11].

The development of a digital twin for SKIF offers numerous benefits, enhancing the facility's operational efficiency and research capabilities. A digital twin, in this context, is a virtual representation that mirrors the physical attributes and dynamics of SKIF, allowing for real-time monitoring, simulation, and optimization of the facility's performance. This technology is particularly beneficial in complying with the precise requirements for the mutual positioning of electromagnetic axes of the elements during installation, which is crucial for the optimal functioning of SKIF [12].

One specific component of SKIF that is of particular interest is the diamond

window. This component is essential in the facility’s operation, serving as a robust and transparent medium for synchrotron radiation. The development of a digital twin for the diamond window involves creating a detailed virtual model that can simulate its behavior under various operational conditions. This model can predict how the diamond window will react to different radiation intensities, thermal loads, and mechanical stresses, thereby aiding in its design, testing, and maintenance.

The digital twin of the diamond window allows for the efficient modeling and testing of new control opportunities, improving the operation and longevity of this critical component. It enables the simulation of temperature, stress, and strain distribution within the diamond window, ensuring that it can withstand the intense conditions of SKIF without degradation [8]. Additionally, the digital twin can be used to study the impact of different cooling strategies on the diamond window, optimizing its thermal management and ensuring its performance remains consistent.

In summary, the development of a digital twin for the Siberian Ring Source of Photons (SKIF), particularly for its diamond window, represents a significant step forward in the digitalization of scientific research facilities. This technology not only enhances the operational efficiency and research capabilities of SKIF but also serves as a model for other mega-science-class installations looking to leverage the benefits of digital twin technology.

4 Methodology

4.1 Utilizing COMSOL Multiphysics for Simulating the Diamond Window in SKIF

COMSOL Multiphysics is a versatile and powerful engineering software package widely used for simulating physical phenomena across various domains. It is particularly adept at modeling heat and stress fields in materials, making it an ideal tool for simulating components like the diamond window in the Siberian Ring Source of Photons (SKIF) [13, 14]. COMSOL provides a comprehensive environment for finite element analysis, allowing researchers to create detailed models of complex systems and materials.

In the context of SKIF, COMSOL Multiphysics is employed to simulate the heat and stress fields of the diamond window and its cooling system. The diamond window, a critical component in synchrotron radiation sources, must withstand extreme thermal and mechanical stresses during operation. By using COMSOL, we

can accurately predict how the diamond window will behave under various conditions, such as different ray positions and cooling water flow rates. This simulation includes assessing the temperature distribution, thermal stresses, and potential deformation of the diamond window, ensuring its reliability and performance in the SKIF facility.

However, one limitation of COMSOL Multiphysics is its inability to run simulations in real-time. To address this, we use COMSOL to pre-generate heat and stress data for a set of different parameters. This pre-generated data is then integrated into the digital twin of the diamond window. The digital twin, a virtual representation of the diamond window, uses this data to predict the window's behavior under various operational scenarios. This approach allows for rapid and accurate assessment of the diamond window's performance without the need for real-time simulation, making it a practical solution for monitoring and optimizing the component's operation in SKIF.

In summary, COMSOL Multiphysics plays a crucial role in the development of the digital twin of the diamond window in SKIF. By providing detailed and accurate simulations of heat and stress fields, COMSOL enables us to create a robust and reliable digital twin that enhances the operational efficiency and safety of the SKIF facility.

4.2 Support Vector Regression (SVR) in Simulating Diamond Window Heat and Stress Fields

Support Vector Regression (SVR) is a powerful machine learning method used for regression problems. It is particularly effective in scenarios involving small samples, nonlinearity, and high-dimensional data [15]. SVR has been applied in various fields, including time-series analysis, bioprocesses, and large-scale applications [16].

In the context of simulating the heat and stress fields of the diamond window in the Siberian Ring Source of Photons (SKIF), SVR plays a crucial role. Due to the computational intensity of direct simulations in COMSOL Multiphysics, real-time analysis is not feasible. To overcome this limitation, SVR is employed to train on pre-generated COMSOL data. This approach involves running simulations in COMSOL for a range of parameters, such as different ray positions and cooling water flow rates, to create a dataset that captures the behavior of the diamond window under various conditions.

Once this dataset is established, SVR is used to learn the relationship between

the input parameters and the resulting heat and stress fields. The advantage of using SVR in this scenario is its ability to make predictions much faster than a direct COMSOL simulation. The goal is to achieve real-time prediction capabilities, allowing for immediate assessment and adjustment of the diamond window's conditions during SKIF operations.

The application of SVR in predicting physical processes has been demonstrated in various studies. For instance, Lahiri and Ghanta (2008) successfully used SVR to predict the pressure drop of slurry flow in pipelines, showcasing its effectiveness in fluid dynamics [17]. Similarly, Wu, Wei, and Terpenney (2018) applied SVR to predict surface roughness in fused deposition modeling processes, highlighting its utility in manufacturing [18]. These examples underscore the potential of SVR in accurately predicting complex physical phenomena based on historical data.

5 Preliminary Results

5.1 Development of a Python Prototype for Digital Twin Simulation

In the preliminary phase of developing the digital twin for the Siberian Ring Source of Photons (SKIF), a simple prototype has been created. This program is designed to integrate and utilize the pre-generated data from COMSOL Multiphysics simulations, specifically focusing on the heat and stress fields of the diamond window and its cooling system. The core functionalities of this program include:

- **Data Integration:** The program reads pre-generated COMSOL data and a 3D STL model of the diamond window. This data includes temperature and stress data for each model point for different input parameters.
- **User Interface for Parameter Input:** The program features a graphical user interface where users can input desired parameters, such as beam position (x, y coordinates) and cooling water flow rate. Additionally, users can select which output parameter (temperature or stress) they wish to visualize.
- **Machine Learning Model Training:** For each point on the 3D model and for each output value (temperature, stress), the program trains a NuSVR (Nu-Support Vector Regression) model from the scikit-learn library. This

machine learning approach allows for predictions of temperature and stress based on input parameters.

- **Visualization and Prediction:** Based on the inserted input parameters, the program predicts and displays the selected output parameter on the 3D model. This visualization is achieved through color mapping, providing an intuitive understanding of how temperature or stress varies across the diamond window.
- **Model Saving and Loading:** Recognizing that training machine learning models can be time-consuming, the program is equipped with the capability to save and load trained SVR models.

The development of this program is grounded in Python, a versatile and widely-used programming language known for its readability and extensive support for scientific computing. Python's vast ecosystem of libraries and tools makes it an ideal choice for developing complex simulation and data analysis applications [19].

Scikit-learn, a key library used in this program, is an open-source machine learning library for Python. It provides simple and efficient tools for data mining and data analysis, and it is built on NumPy, SciPy, and matplotlib. Scikit-learn is known for its robustness and ease of use, making it a popular choice for implementing machine learning algorithms, including support vector machines like NuSVR which was used in the described digital twin prototype [20].

While the Python prototype successfully demonstrated the integration of COMSOL data with machine learning for the digital twin simulation, its performance revealed a significant limitation: the processing speed was not adequate for real-time applications. The need for a faster, more efficient solution became apparent, leading to the exploration of alternative technologies and programming approaches to optimize the simulation process.

5.2 Development of an Optimized Prototype Using CUDA and C++

The quest for optimization led to the adoption of CUDA (Compute Unified Device Architecture), a parallel computing platform and application programming interface (API) model created by NVIDIA. CUDA allows developers to use a CUDA-enabled graphics processing unit (GPU) for general purpose processing – an approach known as GPGPU (General-Purpose computing on Graphics Processing

Units). By leveraging the massive parallel processing power of GPUs, CUDA makes it possible to perform complex computations much faster than traditional CPU-based approaches. This technology is particularly well-suited for applications that require handling large datasets and performing high-volume computations, which is the case with our digital twin simulation.

Building upon the insights gained from the Python prototype, a new program was developed in C++, known for its high-performance capabilities. The key improvement in this version is the integration of CUDA, enabling the program to handle the intensive computational tasks more efficiently.

Similar to the Python prototype, the C++ program reads pregenerated data from COMSOL simulations and the 3D STL model of the diamond window.

The source code from libsvm, a library for Support Vector Machines (SVM), was adapted to run within CUDA kernels. This adaptation allows the program to execute the NuSVR model for each point of the 3D model directly on the GPU. By running the NuSVR model in parallel across the multiple cores of the GPU, the program aims to dramatically increase the speed of the simulation. This approach is expected to bring the processing time down to levels suitable for real-time applications.

The development of the C++ and CUDA-based prototype is still underway, with significant progress made in terms of computational efficiency. However, a current challenge being faced is the efficient allocation of memory on the GPU for the models. Current program can't work with sufficient number of points due to memory limitations, and optimizing this aspect is the next critical step in the development process.

6 Conclusion

7 References

- [1] A. Rasheed, O. San, and T. Kvamsdal, "Digital twin: Values, challenges and enablers from a modeling perspective," *IEEE Access*, vol. 8, pp. 21980–22012, 2020.
- [2] J. Duan, T.-Y. Ma, Q. Zhang, Z. Liu, and J. Qin, "Design and application of digital twin system for the blade-rotor test rig," *Journal of Intelligent Manufacturing*, vol. 34, pp. 753–769, 2021.

- [3] S. Zhang, C. Kang, Z. Liu, J. Wu, and C. Ma, “A product quality monitor model with the digital twin model and the stacked auto encoder,” *IEEE Access*, vol. 8, pp. 113826–113836, 2020.
- [4] T. Ritto and F. Rochinha, “Digital twin, physics-based model, and machine learning applied to damage detection in structures,” *Mechanical Systems and Signal Processing*, vol. 155, p. 107614, 2021.
- [5] A. Balyakin, N. Nurakhov, and M. V. Nurbina, “Digital twins vs digital trace in megascience projects,” *Information Technology and Systems*, vol. 1330, pp. 534 – 539, 2021.
- [6] M. V. Pukhovoy, V. V. Vinokurov, V. A. Vinokurov, and O. A. Kabov, “Numerical simulation of the diamond window of the synchrotron workstation. choice of diamond foil thickness (0.2-1.0 mm),” in *E3S Web of Conferences*, vol. 459, p. 08010, EDP Sciences, 2023.
- [7] O. Kabov, Y. Zubavichus, K. Cooper, M. Pukhovoy, V. Vinokurov, K. Fennikov, F. Ronshin, A. Nikitin, E. Bykovskaya, V. Vinokurov, and A. Mungalov, “Features of device cooling in wiggler synchrotron workstations,” *Journal of Physics: Conference Series*, vol. 2057, p. 012028, 10 2021.
- [8] O. Kabov, Y. V. Zubavichus, K. Cooper, M. V. Pukhovoy, V. V. Vinokurov, K. Fennikov, F. Ronshin, A. Nikitin, E. Bykovskaya, V. A. Vinokurov, A. Mungalov, and I. Marchuk, “Device cooling features in wiggler synchrotron workstations,” *Journal of Physics: Conference Series*, vol. 2119, 2021.
- [9] K. A. Grishina, A. Andrianov, M. Arsenyeva, A. Barnyakov, A. Levichev, I. Pivovarov, and S. Samoylov, “Analysis of regular accelerating structures of a linear accelerator for the injector of siberian photon ring source,” *Physics of Particles and Nuclei Letters*, vol. 17, pp. 65 – 72, 2020.
- [10] S. Gurov, V. Volkov, K. Zolotarev, and A. Levichev, “Injection system for the siberian ring source of photons,” *Journal of Surface Investigation: X-ray, Synchrotron and Neutron Techniques*, vol. 14, pp. 651 – 654, 2020.
- [11] Y. I. Maltseva, S. Ivanenko, A. Khilchenko, X. Ma, O. Meshkov, A. Morsina, and E. Puryga, “Beam loss monitoring system for the skif synchrotron light source,” *Journal of Instrumentation*, vol. 17, 2022.

- [12] A. Polyansky, V. Krapivin, D. Burenkov, E. S. Vonda, and L. Serdakov, "The alignment strategy for the skif synchrotron radiation source," *Vestnik SSUGT (Siberian State University of Geosystems and Technologies)*, 2022.
- [13] M. Bachmann, J. Carstensen, L. Bergmann, J. D. dos Santos, C. Wu, and M. Rethmeier, "Numerical simulation of thermally induced residual stresses in friction stir welding of aluminum alloy 2024-t3 at different welding speeds," *The International Journal of Advanced Manufacturing Technology*, vol. 91, pp. 1443–1452, 2017.
- [14] A. Dudarev and E. K. Gumarov, "Study of thermophysics during diamond drilling of fibreglass and carbon fibre-reinforced polymer composites," *Proceedings of Irkutsk State Technical University*, 2021.
- [15] Z. Guo and G. Bai, "Application of least squares support vector machine for regression to reliability analysis," *Chinese Journal of Aeronautics*, vol. 22, pp. 160–166, 2009.
- [16] P. Rivas-Perea, J. Cota-Ruiz, D. G. Chaparro, J. A. P. Venzor, A. E. Q. Carreón, and J. Rosiles, "Support vector machines for regression: A succinct review of large-scale and linear programming formulations," *International Journal of Intelligent Systems*, vol. 3, pp. 5–14, 2013.
- [17] S. Lahiri and K. C. Ghanta, "Prediction of pressure drop of slurry flow in pipeline by hybrid support vector regression and genetic algorithm model," *Chinese Journal of Chemical Engineering*, vol. 16, pp. 841–848, 2008.
- [18] D. Wu, Y. Wei, and J. Terpenney, "Predictive modelling of surface roughness in fused deposition modelling using data fusion," *International Journal of Production Research*, vol. 57, pp. 3992 – 4006, 2018.
- [19] W. Python, "Python," *Python Releases for Windows*, vol. 24, 2021.
- [20] O. Kramer and O. Kramer, "Scikit-learn," *Machine learning for evolution strategies*, pp. 45–53, 2016.