JS AddNewsPage.js

biggolf_frontend > src > pages > private > JS AddNewsPage.js > ...

```
1   import React, {useState} from 'react';
2   import NewsDataService from "../../services/newsService";
3   import {Link} from "react-router-dom";
4
5   const AddNews = (props) => {
6       let initialNewsSubjectState = ""
7       let initialNewsDescriptionState = ""
8
9       const[newsSubject, setNewsSubject] = useState(initialNewsSubjectState);
10      const[newsDescription, setNewsDescription] = useState(initialNewsDescriptionState);
11
12      const handleSubjectInputChange = event => {
13          setNewsSubject(event.target.value);
14      }
15
16      const handleDescriptionInputChange = event => {
17          setNewsDescription(event.target.value);
18      }
19
20      const saveNewsItem = (event) => {
21          event.preventDefault();
22          var data = {
23              subject: newsSubject,
24              description: newsDescription
25          }
26
27          NewsDataService.createNews(data)
28              .then(response => {
29                  console.log(response.data);
30              })
31              .catch(e => {
32                  console.log(e);
33              });
34          props.history.push('/news')
35      };
36
```

AddNewsPage.js
biggolf_frontend > src > pages > private > AddNewsPage.js > ...

<Link to={"/news"} className="btn btn-primary col-lg-5 mx-1 mb-1">
Back to News List
</Link>

<h2>
Adding a News Item
</h2>
<form onSubmit={saveNewsItem}>
<label>
Enter Subject:
<input
type="text"
id="newsSubject"
placeholder="Enter News Subject..."
value={newsSubject}
onChange={handleSubjectInputChange}
name="newsSubject"
required
/>
</label>
<label>
Enter Description:
<input
type="text"
id="newsDescription"
placeholder="Enter News Description..."
value={newsDescription}
onChange={handleDescriptionInputChange}
name="newsDescription"
required
/>
</label>
<button type="submit" className="btn btn-success">
Create News Item
</button>
</form>
9
6
7
8