

# Intro to ML and Language models

**Radoslav Neychev**

Spring 2021


1. Introduction to Machine Learning, motivation
2. ML thesaurus and notation
3. RNN intuitions
4. Language models
5. Q & A

Motivation, historical overview and  
current state of ML and AI

# Machine Learning applications



- Object detection
- Action classification
- Image captioning
- ...




# Machine Learning applications






# Machine Learning applications



Data → Knowledge

Long before the ML




Isaac Newton



Johannes Kepler



Long before the ML



Eratosthenes

ML thesaurus

# ML thesaurus

Denote the ***dataset***.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

# ML thesaurus

***Observation*** (or datum, or data point) is one piece of information.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

In many cases the observations are supposed to be ***i.i.d.***

- ***independent***
- ***identically distributed***

# ML thesaurus

**Feature** (or predictor) represents some special property.



Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE



# ML thesaurus

These all are features



Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

# ML thesaurus


These all are features



Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

# ML thesaurus


These all are features



Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

# ML thesaurus

These all are features



Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

# ML thesaurus

And even the name is a ***feature***



Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

*(despite it might be not informative)*



# ML thesaurus

The ***design matrix*** contains all the features and observations.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

*Features can even be multidimensional, we will discuss it later in this course.*

# ML thesaurus

***Target*** represents the information we are interested in.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

*Target can be either a **number** (real, integer, etc.) – for **regression** problem*

# ML thesaurus

***Target*** represents the information we are interested in.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

Or a ***label*** – for ***classification*** problem

# ML thesaurus

***Target*** represents the information we are interested in.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

*Mark can be treated as a label too (due to finite number of labels: 1 to 5). We will discuss it later.*

Further we will work with the numerical target (mark)

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)
John	22	5	4	Brown	English	5
Aahna	17	4	5	Brown	Hindi	4
Emily	25	5	5	Blue	Chinese	5
Michael	27	3	4	Green	French	5
Some student	23	3	3	NA	Esperanto	2



# ML thesaurus

The ***prediction*** contains values we predicted using some ***model***.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Predicted (mark)
John	22	5	4	Brown	English	5	4.5
Aahna	17	4	5	Brown	Hindi	4	4.5
Emily	25	5	5	Blue	Chinese	5	5
Michael	27	3	4	Green	French	5	3.5
Some student	23	3	3	NA	Esperanto	2	3

One could notice that prediction just averages of Statistics and Python marks. So our ***model*** can be represented as follows:

$$\text{mark}_{ML}^{\hat{}} = \frac{1}{2}\text{mark}_{Statistics} + \frac{1}{2}\text{mark}_{Python}$$

# ML thesaurus

The ***prediction*** contains values we predicted using some ***model***.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Predicted (mark)
John	22	5	4	Brown	English	5	4.5
Aahna	17	4	5	Brown	Hindi	4	4.5
Emily	25	5	5	Blue	Chinese	5	5
Michael	27	3	4	Green	French	5	3.5
Some student	23	3	3	NA	Esperanto	2	3

*Different models can provide different predictions:*

$$\text{mark}_{ML}^{\hat{}} = \frac{1}{2}\text{mark}_{Statistics} + \frac{1}{2}\text{mark}_{Python}$$

# ML thesaurus

The ***prediction*** contains values we predicted using some ***model***.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Predicted (mark)
John	22	5	4	Brown	English	5	1
Aahna	17	4	5	Brown	Hindi	4	5
Emily	25	5	5	Blue	Chinese	5	2
Michael	27	3	4	Green	French	5	4
Some student	23	3	3	NA	Esperanto	2	3

*Different models can provide different predictions:*

$$\text{mark}_{ML}^{\hat{}} = \text{random}(\text{integer from } [1; 5])$$

# ML thesaurus

The ***prediction*** contains values we predicted using some ***model***.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Predicted (mark)
John	22	5	4	Brown	English	5	1
Aahna	17	4	5	Brown	Hindi	4	5
Emily	25	5	5	Blue	Chinese	5	2
Michael	27	3	4	Green	French	5	4
Some student	23	3	3	NA	Esperanto	2	3

*Different models can provide different predictions.*

*Usually some ***hypothesis*** lies beneath the model choice.*

***Loss function*** measures the error rate of our model.

Square deviation	Target (mark)	Predicted (mark)
16	5	1
1	4	5
9	5	2
1	5	4
1	2	3

- ***Mean Squared Error*** (where  $\mathbf{y}$  is vector of targets):

$$MSE(\mathbf{y}, \hat{\mathbf{y}}) = \frac{1}{N} \|\mathbf{y} - \hat{\mathbf{y}}\|_2^2 = \frac{1}{N} \sum_i (y_i - \hat{y}_i)^2$$

***Loss function*** measures the error rate of our model.

Absolute deviation	Target (mark)	Predicted (mark)
4	5	1
1	4	5
3	5	2
1	5	4
1	2	3

- ***Mean Absolute Error*** (where  $\mathbf{y}$  is vector of targets):

$$MAE(\mathbf{y}, \hat{\mathbf{y}}) = \frac{1}{N} \|\mathbf{y} - \hat{\mathbf{y}}\|_1 = \frac{1}{N} \sum_i |y_i - \hat{y}_i|$$

# ML thesaurus

To learn something, our ***model*** needs some degrees of freedom:

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Predicted (mark)
John	22	5	4	Brown	English	5	4.5
Aahna	17	4	5	Brown	Hindi	4	4.5
Emily	25	5	5	Blue	Chinese	5	5
Michael	27	3	4	Green	French	5	3.5
Some student	23	3	3	NA	Esperanto	2	3

$$\hat{\text{mark}}_{ML} = w_1 \cdot \text{mark}_{Statistics} + w_2 \cdot \text{mark}_{Python}$$

# ML thesaurus

To learn something, our ***model*** needs some degrees of freedom:

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Predicted (mark)
John	22	5	4	Brown	English	5	4.447
Aahna	17	4	5	Brown	Hindi	4	4.734
Emily	25	5	5	Blue	Chinese	5	5.101
Michael	27	3	4	Green	French	5	3.714
Some student	23	3	3	NA	Esperanto	2	3.060

$$\hat{\text{mark}}_{ML} = w_1 \cdot \text{mark}_{Statistics} + w_2 \cdot \text{mark}_{Python}$$



# ML thesaurus

To learn something, our ***model*** needs some degrees of freedom:

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Predicted (mark)
John	22	5	4	Brown	English	5	1
Aahna	17	4	5	Brown	Hindi	4	5
Emily	25	5	5	Blue	Chinese	5	2
Michael	27	3	4	Green	French	5	4
Some student	23	3	3	NA	Esperanto	2	3

$$\hat{\text{mark}}_{ML} = \text{random}(\text{integer from } [1; 5])$$

Last term we should learn for now is ***hyperparameter***.

***Hyperparameter*** should be fixed before our model starts to work with the data.

We will discuss it later with kNN as an example.

## Recap:

- Dataset
- Observation (datum)
- Feature
- Design matrix
- Target
- Prediction
- Model
- Loss function
- Parameter
- Hyperparameter

# Language generation

## Shakespeare

PANDARUS:  
Alas, I think he shall be come approached and the day  
When little strain would be attain'd into being never fed,  
And who is but a chain and subjects of his death,  
I should not sleep.

Second Senator:  
They are away this miseries, produced upon my soul,  
Breaking and strongly should be buried, when I perish  
The earth and thoughts of many states.

DUKE VINCENTIO:  
Well, your wit is in the care of side and that.

Second Lord:  
They would be ruled after this chamber, and  
my fair nues begun out of the fact, to be conveyed,  
Whose noble souls I'll have the heart of the wars.

Clown:  
Come, sir, I will make did behold your worship.

VIOLA:  
I'll drink it.

## Algebraic Geometry (Latex)

*Proof.* Omitted. □

**Lemma 0.1.** *Let  $\mathcal{C}$  be a set of the construction.*  
*Let  $\mathcal{C}$  be a gerber covering. Let  $\mathcal{F}$  be a quasi-coherent sheaves of  $\mathcal{O}$ -modules. We have to show that*

$$\mathcal{O}_{\mathcal{O}_X} = \mathcal{O}_X(\mathcal{L})$$

*Proof.* This is an algebraic space with the composition of sheaves  $\mathcal{F}$  on  $X_{\text{étale}}$  we have

$$\mathcal{O}_X(\mathcal{F}) = \{\text{morph}_1 \times_{\mathcal{O}_X} (\mathcal{G}, \mathcal{F})\}$$

where  $\mathcal{G}$  defines an isomorphism  $\mathcal{F} \rightarrow \mathcal{F}$  of  $\mathcal{O}$ -modules. □

**Lemma 0.2.** *This is an integer  $\mathbb{Z}$  is injective.* □

*Proof.* See Spaces, Lemma ??.

**Lemma 0.3.** *Let  $S$  be a scheme. Let  $X$  be a scheme and  $X$  is an affine open covering. Let  $\mathcal{U} \subset X$  be a canonical and locally of finite type. Let  $X$  be a scheme. Let  $X$  be a scheme which is equal to the formal complex.*  
*The following to the construction of the lemma follows.*  
*Let  $X$  be a scheme. Let  $X$  be a scheme covering. Let*

$$b: X \rightarrow Y' \rightarrow Y \rightarrow Y' \times_X Y \rightarrow X.$$

*be a morphism of algebraic spaces over  $S$  and  $Y$ .*

*Proof.* Let  $X$  be a nonzero scheme of  $X$ . Let  $X$  be an algebraic space. Let  $\mathcal{F}$  be a quasi-coherent sheaf of  $\mathcal{O}_X$ -modules. The following are equivalent

- (1)  $\mathcal{F}$  is an algebraic space over  $S$ .
- (2) If  $X$  is an affine open covering.

Consider a common structure on  $X$  and  $X$  the functor  $\mathcal{O}_X(U)$  which is locally of finite type. □

## Linux kernel (source code)

```
/*  
 * If this error is set, we will need anything right after that BSD.  
 */  
  
static void action_new_function(struct s_stat_info *wb)  
{  
    unsigned long flags;  
    int lel_idx_bit = e->add, *sys & -((unsigned long) *FIRST_COMPAT);  
    buf[0] = 0xffffffff & (bit << 4);  
    min(inc, slist->bytes);  
    printk(KERN_WARNING "Memory allocated %02x/%02x, "  
           "original MLL instead\n"),  
           min(min(multi_run - s->len, max) * num_data_in),  
           frame_pos, sz + first_seg);  
    div_u64_w(val, inb_p);  
    spin_unlock(&disk->queue_lock);  
    mutex_unlock(&s->sock->mutex);  
    mutex_unlock(&func->mutex);  
    return disassemble(info->pending_bh);  
}
```

*Proof.* Omitted. □

**Lemma 0.1.** *Let  $\mathcal{C}$  be a set of the construction.*

*Let  $\mathcal{C}$  be a gerber covering. Let  $\mathcal{F}$  be a quasi-coherent sheaves of  $\mathcal{O}$ -modules. We have to show that*

$$\mathcal{O}_{\mathcal{O}_X} = \mathcal{O}_X(\mathcal{L})$$

*Proof.* This is an algebraic space with the composition of sheaves  $\mathcal{F}$  on  $X_{\text{étale}}$  we have

$$\mathcal{O}_X(\mathcal{F}) = \{ \text{morph}_1 \times_{\mathcal{O}_X} (\mathcal{G}, \mathcal{F}) \}$$

where  $\mathcal{G}$  defines an isomorphism  $\mathcal{F} \rightarrow \mathcal{F}$  of  $\mathcal{O}$ -modules. □

**Lemma 0.2.** *This is an integer  $Z$  is injective.*

*Proof.* See Spaces, Lemma ?? □

**Lemma 0.3.** *Let  $S$  be a scheme. Let  $X$  be a scheme and  $X$  is an affine open covering. Let  $\mathcal{U} \subset \mathcal{X}$  be a canonical and locally of finite type. Let  $X$  be a scheme. Let  $X$  be a scheme which is equal to the formal complex.*

*The following to the construction of the lemma follows.*

*Let  $X$  be a scheme. Let  $X$  be a scheme covering. Let*

$$b : X \rightarrow Y' \rightarrow Y \rightarrow Y' \times_X Y \rightarrow X.$$


*be a morphism of algebraic spaces over  $S$  and  $Y$ .*

*Proof.* Let  $X$  be a nonzero scheme of  $X$ . Let  $X$  be an algebraic space. Let  $\mathcal{F}$  be a quasi-coherent sheaf of  $\mathcal{O}_X$ -modules. The following are equivalent

- (1)  $\mathcal{F}$  is an algebraic space over  $S$ .
- (2) If  $X$  is an affine open covering.

Consider a common structure on  $X$  and  $X$  the functor  $\mathcal{O}_X(U)$  which is locally of finite type. □

This since  $\mathcal{F} \in \mathcal{F}$  and  $x \in \mathcal{G}$  the diagram



is a limit. Then  $\mathcal{G}$  is a finite type and assume  $S$  is a flat and  $\mathcal{F}$  and  $\mathcal{G}$  is a finite type  $f_*$ . This is of finite type diagrams, and

- the composition of  $\mathcal{G}$  is a regular sequence,
- $\mathcal{O}_{X'}$  is a sheaf of rings.

□

*Proof.* We have see that  $X = \text{Spec}(R)$  and  $\mathcal{F}$  is a finite type representable by algebraic space. The property  $\mathcal{F}$  is a finite morphism of algebraic stacks. Then the cohomology of  $X$  is an open neighbourhood of  $U$ . □

*Proof.* This is clear that  $\mathcal{G}$  is a finite presentation, see Lemmas ??.

A reduced above we conclude that  $U$  is an open covering of  $\mathcal{C}$ . The functor  $\mathcal{F}$  is a "field

$$\mathcal{O}_{X,x} \longrightarrow \mathcal{F}_{\mathcal{F}}^{-1}(\mathcal{O}_{X_{\text{étale}}}) \longrightarrow \mathcal{O}_{X_t}^{-1} \mathcal{O}_{X_\lambda}(\mathcal{O}_{X_q}^v)$$

is an isomorphism of covering of  $\mathcal{O}_{X_t}$ . If  $\mathcal{F}$  is the unique element of  $\mathcal{F}$  such that  $X$  is an isomorphism.

The property  $\mathcal{F}$  is a disjoint union of Proposition ?? and we can filtered set of presentations of a scheme  $\mathcal{O}_X$ -algebra with  $\mathcal{F}$  are opens of finite type over  $S$ .

If  $\mathcal{F}$  is a scheme theoretic image points. □

If  $\mathcal{F}$  is a finite direct sum  $\mathcal{O}_{X_\lambda}$  is a closed immersion, see Lemma ?? . This is a sequence of  $\mathcal{F}$  is a similar morphism.

```

#include <asm/io.h>
#include <asm/prom.h>
#include <asm/e820.h>
#include <asm/system_info.h>
#include <asm/setew.h>
#include <asm/pgproto.h>

#define REG_PG      vesa_slot_addr_pack
#define PFM_NOCOMP  AFSR(0, load)
#define STACK_DDR(type)      (func)


#define SWAP_ALLOCATE(nr)      (e)
#define emulate_sigs()  arch_get_unaligned_child()
#define access_rw(TST)  asm volatile("movd %%esp, %0, %3" : : "r" (0)); \
    if (__type & DO_READ)

static void stat_PC_SEC __read_mostly offsetof(struct seq_argsqueue, \
    pC>[1]);

static void
os_prefix(unsigned long sys)
{
#ifdef CONFIG_PREEMPT
    PUT_PARAM_RAID(2, sel) = get_state_state();
    set_pid_sum((unsigned long)state, current_state_str(),
        (unsigned long)-1->lr_full; low;
}

```


# Recurrent neural network






# Recurrent Neural Networks intuition

# Recurrent neural network




# Recurrent neural network



We use same weight matrices for all steps

# Recurrent neural network



# Recurrent neural network: with formulas

$$h_0 = \bar{0}$$

$$h_1 = \sigma(\langle W_{\text{hid}}[h_0, x_0] \rangle + b)$$


$$h_2 = \sigma(\langle W_{\text{hid}}[h_1, x_1] \rangle + b) = \sigma(\langle W_{\text{hid}}[\sigma(\langle W_{\text{hid}}[h_0, x_0] \rangle + b), x_1] \rangle + b)$$

$$h_{i+1} = \sigma(\langle W_{\text{hid}}[h_i, x_i] \rangle + b)$$

$$P(x_{i+1}) = \text{softmax}(\langle W_{\text{out}}, h_i \rangle + b_{\text{out}})$$

# How to train it?

Loss  
(e.g. Negative  
log-likelihood)



## Shakespeare

PANDARUS:  
Alas, I think he shall be come approached and the day  
When little strain would be attain'd into being never fed,  
And who is but a chain and subjects of his death,  
I should not sleep.

Second Senator:  
They are away this miseries, produced upon my soul,  
Breaking and strongly should be buried, when I perish  
The earth and thoughts of many states.

DUKE VINCENTIO:  
Well, your wit is in the care of side and that.

Second Lord:  
They would be ruled after this chamber, and  
my fair nues begun out of the fact, to be conveyed,  
Whose noble souls I'll have the heart of the wars.

Clown:  
Come, sir, I will make did behold your worship.

VIOLA:  
I'll drink it.

## Algebraic Geometry (Latex)

*Proof.* Omitted. □

**Lemma 0.1.** *Let  $\mathcal{C}$  be a set of the construction.*  
*Let  $\mathcal{C}$  be a gerber covering. Let  $\mathcal{F}$  be a quasi-coherent sheaves of  $\mathcal{O}$ -modules. We have to show that*

$$\mathcal{O}_{\mathcal{O}_X} = \mathcal{O}_X(\mathcal{L})$$

*Proof.* This is an algebraic space with the composition of sheaves  $\mathcal{F}$  on  $X_{\text{étale}}$  we have

$$\mathcal{O}_X(\mathcal{F}) = \{\text{morph}_1 \times_{\mathcal{O}_X} (\mathcal{G}, \mathcal{F})\}$$

where  $\mathcal{G}$  defines an isomorphism  $\mathcal{F} \rightarrow \mathcal{F}$  of  $\mathcal{O}$ -modules. □

**Lemma 0.2.** *This is an integer  $\mathbb{Z}$  is injective.* □

*Proof.* See Spaces, Lemma ??.

**Lemma 0.3.** *Let  $S$  be a scheme. Let  $X$  be a scheme and  $X$  is an affine open covering. Let  $\mathcal{U} \subset X$  be a canonical and locally of finite type. Let  $X$  be a scheme. Let  $X$  be a scheme which is equal to the formal complex.*  
*The following to the construction of the lemma follows.*  
*Let  $X$  be a scheme. Let  $X$  be a scheme covering. Let*

$$b: X \rightarrow Y' \rightarrow Y \rightarrow Y' \times_X Y \rightarrow X.$$

*be a morphism of algebraic spaces over  $S$  and  $Y$ .*

*Proof.* Let  $X$  be a nonzero scheme of  $X$ . Let  $X$  be an algebraic space. Let  $\mathcal{F}$  be a quasi-coherent sheaf of  $\mathcal{O}_X$ -modules. The following are equivalent

- (1)  $\mathcal{F}$  is an algebraic space over  $S$ .
- (2) If  $X$  is an affine open covering.

Consider a common structure on  $X$  and  $X$  the functor  $\mathcal{O}_X(U)$  which is locally of finite type. □

## Linux kernel (source code)

```
/*  
 * If this error is set, we will need anything right after that BSD.  
 */  
  
static void action_new_function(struct s_stat_info *wb)  
{  
    unsigned long flags;  
    int lel_idx_bit = e->add, *sys & -((unsigned long) *FIRST_COMPAT);  
    buf[0] = 0xffffffff & (bit << 4);  
    min(inc, slist->bytes);  
    printk(KERN_WARNING "Memory allocated %02x/%02x, "  
           "original MLL instead\n"),  
           min(min(multi_run - s->len, max) * num_data_in),  
           frame_pos, sz + first_seg);  
    div_u64_w(val, inb_p);  
    spin_unlock(&disk->queue_lock);  
    mutex_unlock(&s->sock->mutex);  
    mutex_unlock(&func->mutex);  
    return disassemble(info->pending_bh);  
}
```

