



Ft_services

Summary: This is a System Administration and Networking project.

Contents

I	Introduction	2
II	General instructions	3
III	Mandatory part	4

Chapter I

Introduction

Ft_services will introduce you to kubernetes. You will discover cluster management and deployment with Kubernetes. You will virtualize a network and do "clustering".

Chapter II

General instructions

- You must put all the necessary files for the configuration of your server in a folder called `srcs`.
- Your `setup.sh` file should be at the root of your repository. This script will setup all your applications.
- This subject requires both old and new practices. We therefore advise you not to be afraid to read a lot of documentation about docker, kubernetes, and all other things useful for the project.

Chapter III

Mandatory part

The project consists of setting up an infrastructure of different services. To do this, you must use **Kubernetes**. You will need to set up a multi-service **cluster**.

Each service will have to run in a dedicated container.

Each container **must** bear the same name as the service concerned and For performance reasons, containers have to be build using Alpine Linux.

Also, they will need to have a **Dockerfile** written by you which is called in the `setup.sh`.

You will have to build yourself the images that you will use. It is forbidden to take already build images or use services like DockerHub.

You will also have to set up:

- The **Kubernetes** web dashboard. This will help you manage your cluster.
- The **Load Balancer** which manages the external access of your services. It will be the only entry point to your cluster. You **must** keep the ports associated with the service (IP:3000 for grafana etc).
- A **Nginx** server listening on ports 80 and 443. Port 80 will be in http and should be a systematic redirection of type 301 to 443, which will be in https. The page displayed does not matter.
- A **FTPS** server listening on port 21.
- A **WordPress** website listening on port 5050, which will work with a **MySQL** database. Both services have to run in separate containers. The WordPress website will have several users and an administrator.
- **PhpMyAdmin**, listening on port 5000 and linked with the **MySQL** database.
- A **Grafana** platform, listening on port 3000, linked with an **InfluxDB** database. Grafana will be monitoring **all** your containers. You must create one dashboard per service. InfluxDB and grafana will be in two distincts containers.
- In case of a crash or stop of one of the two database containers, you will have to make shure the data persist.

- You must be able to access the Nginx container by logging into SSH.
- All your containers must restart in case of a crash or stop of one of its component parts.



Usage of Node Port services, Ingress Controller object or `kubectl port-forward` command is prohibited.
Your Load Balancer should be the only entry point for the Cluster.



It's useless try to use any Load Balancer provided by Cloud Provider.
you should rather look at MetalLB.



Security is important, don't expose services that shouldn't be...