

CS3230 Tutorial 9

Deng Tianle (T15)


24 October 2025

(Polynomial) Reductions

Suppose we know how to solve problem B . Then for another problem A , we can solve it if we reduce it to problem B . This is a very common idea.

For this and the next chapter we are mainly interested in whether a problem can be solved in polynomial time ('efficiently', this is explained in the lecture ¹). Therefore we need the translation from A to B and then back to A be all polynomial time. In many cases this would be obvious.

If A has a polynomial time reduction to B , we write $A \leq_p B$.

¹I would attach an interesting excerpt related to this in the repo 

Reductions for decision problems

Let A and B be two decision problems. In this context, we know how to solve B . A transformation ϕ from instances α of A to instances of B satisfies two conditions:

- ▶ α is a YES-instance for $A \iff \phi(\alpha)$ is a YES-instance for B
- ▶ The transformation takes polynomial time in the size of α

We say $A \leq_p B$.

In other words: YES-instance of $A \mapsto$ YES-instance of B , and NO-instance of $A \mapsto$ NO-instance of B .

OR: $\phi(\alpha)$ YES $\implies \alpha$ YES, and $\phi(\alpha)$ NO $\implies \alpha$ NO.

We need this to ensure that the decision for $\phi(\alpha)$ gives us the decision for α .

Note that there is no requirement for ϕ to be one-to-one or onto.

Q1

Fix a graph G . Graph colouring so that no adjacent vertices share the same colour. Decision problem: given k , whether it is possible to colour with k colours. Optimisation problem: minimum number of colours so that it is possible.

Part (a) \iff (c): True, see if minimum is $\leq k$.

Part (b) \iff (d): True, solve sequentially or binary search to see if it is possible with k colours. The search is polynomial time.

Q2

PARTITION: given a set of positive integers S , can we partition it into two subsets of equal total sum?

BALL-PARTITION: given k balls, can we divide them into two boxes with equal number of balls? (Basically, whether k is even, LOL)

Attempted transformation A from PARTITION to BALL-PARTITION: use the sum of all numbers in S as the number k for BALL-PARTITION.

Q2

1. It does run in polynomial time because it only sums the integers in S .
2. Transformation is not correct, see below.
3. Indeed, this is the problem. For example, $S = \{1, 7\}$ maps to $k = 8$ which is a YES instance, but S is a NO instance.
4. This is not the problem. In a YES instance S , the partition shows that the total sum k is even, giving a YES instance $A(S)$.

In this case, a YES decision for $A(S)$ can mean both YES or NO decision for S , so the transformation is not useful.

Q3

PARTITION: given a set of positive integers $\{w_1, \dots, w_n\}$, can we partition it into two subsets of equal total sum?

KNAPSACK: given weight-value pairs $\{(w_1, v_1), \dots, (w_n, v_n)\}$, capacity W and threshold V (all positive integers), can we choose a subset $I \subset \{1, \dots, n\}$ such that $\sum_{i \in I} w_i \leq W$ and $\sum_{i \in I} v_i \geq V$?

Transformation: given PARTITION instance $\{w_1, \dots, w_n\}$ with $S := \sum_{i=1}^n w_i$, construct a KNAPSACK instance $\{(w_1, w_1), \dots, (w_n, w_n)\}$ with $W = V = S/2$.

Q3

1. True, transformation is polynomial-time as it just copies n weights to n pairs (to be precise $O(n \log(w_{\max}))$).
2. True. This is obvious (just choose one of the two partition subsets).
3. True, since $\{(w_1, w_1), \dots, (w_n, w_n)\}$ being a YES instance implies that there is a subset $I \subset \{1, \dots, n\}$ such that $S/2 \leq \sum_{i \in I} w_i \leq S/2$. Hence this I gives a partition of $\{w_1, \dots, w_n\}$.

Q4

Hamiltonian-cycle (HC): a cycle (meaning, start = end) that visits each vertex exactly once.

Travelling-salesperson (TSP): for a complete graph, whether there is a Hamiltonian cycle with cost $\leq n$.

Transformation: let $G = (V, E)$ be a graph (so an instance of HC), complete G into \bar{G} as follows: for every pair $u, v \in V$, let $w(u, v) = 1$ if $(u, v) \in E$, otherwise let $w(u, v) = \infty$ (or anything > 1). Apply TSP to cost $n = |V|$.

The transformation is polynomial-time, to be precise $O(n^2)$ as at most $n(n-1)/2$ edges are added.

Observe that G has a Hamiltonian cycle $\iff \bar{G}$ has a TSP tour of cost at most n . Can you see what this means?

Q4

Observe that G has a Hamiltonian cycle $\iff \bar{G}$ has a TSP tour of cost at most $n = |V|$.

3. (\Rightarrow) Since \bar{G} has the same vertices and only adds edges to G , the Hamiltonian cycle is still a Hamiltonian cycle. Cost is n since it consists of n edges (including return to start) in E .
4. (\Leftarrow) Let C be a TSP tour of cost at most n in \bar{G} . So C has exactly n edges. Then cost $\leq n$ implies that all these edges are in E . Hence C is a Hamiltonian cycle for G .

LeetCode

We give a sketch for the solution of TSP using bitmask DP.

Let S be the set (not including vertex 0 meaning the starting vertex) of visited vertices and v be the current vertex. Consider all paths starting at v that visits the remaining $(V \setminus S)$ vertices exactly once and ending at vertex 0. Let $dp[S][v]$ denote the minimum cost of such paths. We get $dp[V][0] = 0$ and

$$dp[S][v] = \min\{dp[S \cup \{u\}][u] + w(v, u) : u \notin S\}.$$

To apply DP, we have to parse the subset S into a number. A natural option is a binary number of length $n = |V|$ (where i -th bit is 1 iff i -th element is present in $S \subset V$). Then we can use memorisation with table size $2^n \times n$. Complexity is $O(n^2 2^n)$ because we are minimising over all $u \notin S$ in each step.