CS3263 Report

Deng Tianle
A0282801J
e1156929@u.nus.edu

Liu Lekang
A0281207L
e1155335@u.nus.edu

Zhao Kejun
A0282631H
e1156759@u.nus.edu

13 November 2026

1 Introduction

A matroid records which sets of elements are independent. When those dependencies arise from the columns of a matrix over $\mathbb{F}$, finite-field linear algebra gives a concrete way to work with the matroid. An *excluded minor* is a minimal obstruction under deletion and contraction to obtaining such a representation. Brettell enumerated the excluded minors for $\mathbb{F}$-representability on ten elements [3]. This project studies the next size at rank four. The exhaustive computation in `matroid1` gives 35 isomorphism classes and provides a catalogue and verification records for the result [4, 8].

The project also asks how an LLM should contribute to a mathematical search. We compare four workflows, from direct reasoning to translation followed by exact solving. The first experiment asks the workflows to classify supplied matroids. The second asks them to find every valid extension of a supplied parent. Finding valid candidates and establishing that the list is complete require different evidence, and the two experiments measure these requirements separately.

2 Background and problem statement

A *matroid* $M = (E, \mathcal{I})$ consists of a finite ground set E and a family of independent sets $\mathcal{I}$. The empty set belongs to $\mathcal{I}$, subsets of independent sets are independent, and a smaller independent set can be augmented by an element from a larger one. The maximal independent sets are the *bases* of M. They have a common size, the *rank* $r(M)$, and determine $\mathcal{I}$. Two matroids are isomorphic if a bijection between their ground sets preserves the bases. The rank of a subset S is the size of its largest independent subset. Its *closure* contains every element whose addition leaves that rank unchanged. A *hyperplane* is a maximal subset of rank $r(M) - 1$ [2].

Write $\mathbb{F} = \mathbb{Z}/5\mathbb{Z}$. A rank-$r$ matroid is *quinary* if there is an $r \times |E|$ matrix V over $\mathbb{F}$, with columns labelled by E, such that for every r-subset $S \subseteq E$,

$$S \in \mathcal{B}(M) \quad \Longleftrightarrow \quad \det V_S \neq 0.$$

Deletion $M \setminus a$ keeps the independent sets avoiding a. For a represented matroid, this removes column a. Contraction M/a is realized by projecting the other columns into the quotient by the span of column a. A minor is the result of a sequence of these operations. Quinary representability is preserved under both operations, so checking all single-element deletions and contractions suffices to check every proper minor [2].

Problem. Enumerate, up to matroid isomorphism, all matroids M with $|E(M)| = 11$ and $r(M) = 4$ such that M is nonquinary and both $M \setminus a$ and M/a are quinary for every $a \in E(M)$. The output is a list of exact basis families, together with evidence of excluded-minor status, pairwise distinctness, and completeness of the list.

3 Method

We view each target matroid M as a single-element extension of a ten-element quinary *parent* $N = M \setminus e$. Following the classification paper [5], we use three stages.

1. Generate every possible parent up to matroid isomorphism.
2. For each parent, enumerate all nonquinary extensions whose single-element deletions are quinary.

3. Check every single-element contraction and remove isomorphic repeats.

The second stage is a finite constraint satisfaction problem: each deletion supplies an allowed table, and the tables must agree on shared basis decisions.

3.1 Step 1: generating deletion parents

Lemma 3.1 (Possible deletion parents)**.** *If M is a rank-four, eleven-element excluded minor for quinary representability, then for every $e \in E(M)$, the deletion $N = M \setminus e$ is a connected simple rank-four quinary matroid on ten elements.*

Proof. An excluded minor for representability over a field on at least four elements is 3-connected. A disconnected matroid decomposes as a direct sum, and a connected matroid with a 2-separation decomposes as a 2-sum. The summands are isomorphic to proper minors and hence are quinary. Direct sums preserve representability by taking block diagonal matrices. For a 2-sum, choose representations in which the common element is a unit vector, identify its one-dimensional span in the two vector spaces, and delete its column. Closure under these sums would make M quinary, contradicting the excluded-minor condition [2].

Since M is 3-connected, it has no loops, parallel pairs, or coloops. Therefore N is simple and has rank four, and it is quinary by minor-minimality. If N were a direct sum on nonempty sets A, B, name them so that $|A| \geq 2$. Rank is unchanged by deletion on subsets of N, so $r_M(A) + r_M(B) = r(N) = r(M)$. Adding e increases the rank of B by at most one, giving

$$r_M(A) + r_M(B \cup \{e\}) - r(M) \leq 1.$$

Both sides of the partition $(A, B \cup \{e\})$ have at least two elements. This contradicts 3-connectivity of M. □

We search all connected simple rank-four quinary parents. Such a parent has no coloop, since a coloop would give a one-element direct summand. In particular, every further deletion of a parent still has rank four.

3.1.1 Completeness of represented generation

A simple rank-r representation uses distinct points of $\mathrm{PG}(r-1, 5)$, the $(5^r - 1)/4$ one-dimensional subspaces of $\mathbb{F}^r$. We choose one vector per point by scaling its first nonzero entry to 1. We start at I_r, append every unused projective point to each retained matrix, and retain one matrix per *field-isomorphism* class at each size. Field isomorphism allows invertible row operations, nonzero column scalings, and column permutations. SageMath tests this equivalence.

Proposition 3.2 (Coverage at each size)**.** *At each generated size $k \geq r$, the procedure retains a representative of every field-isomorphism class of simple rank-r quinary representations on k elements.*

Proof. Take any target representation W, move a basis to the first r columns, and reduce it to I_r. Let W_k be the first k columns of this matrix. The seed covers W_r. If a retained matrix V_k is field-isomorphic to W_k, write $W_{k+1} = [W_k \mid w]$ and let G be the invertible row transformation used in that equivalence. Extending the old column operations to fix the new column shows that $[V_k \mid Gw]$ is field-isomorphic to W_{k+1}. The direction of Gw is unused in V_k, since otherwise w would be parallel to an old column of W_k. The procedure therefore tries this point and retains its class. Induction reaches W. □

For rank four, there are 156 projective points. At each size we can convert the matrices to basis families by testing all four-column determinants and deduplicate by exact matroid isomorphism. The abstract catalogue stores one bit per four-subset in lexicographic order, so a ten-element parent uses $\binom{10}{4} = 210$ bits. The represented catalogue is retained separately because a single abstract matroid can have several field-inequivalent representations with different possible extensions. We keep one labelled representative of each connected abstract class at size ten. We also retain the size-nine represented catalogue for the deletion tables and generate the simple rank-three catalogue through size ten for contraction tests.

3.2 Step 2: recovering extensions from compatible deletions

Fix a parent N on $P = \{0, \dots, 9\}$ and give the new element the label $e = 10$. Let $\mathcal{D}(N)$ be the set of simple rank-four matroids M on $P \cup \{e\}$ such that $M \setminus e = N$, M is nonquinary, and every single-element deletion of M is quinary. We call these the *deletion-minimal nonquinary extensions* of N.

The bases avoiding e are fixed by N. The 120 Boolean variables x_T, indexed by triples $T \in \binom{P}{3}$, specify the remaining basis decisions. The proposed basis family is

$$\mathcal{B}_N(x) = \mathcal{B}(N) \cup \{T \cup \{e\} : T \in \tbinom{P}{3},\ x_T = 1\}.$$

For $Q = N$ or $Q = N \setminus f$, let $R(Q)$ contain the bit rows arising from all simple rank-four quinary extensions of Q by e. Let $\pi_f(x)$ retain the coordinates for triples avoiding f. For instance, deletions of 3 and 4 must agree on $x_{\{0,1,2\}}$, the status of $\{0, 1, 2, 10\}$. This bit is visible only in deletions outside that four-set. Requiring the proposed deletions to occur in their tables and excluding the full-parent rows gives

$$S(N) = \{x \in \{0,1\}^{\binom{P}{3}} : \pi_f(x) \in R(N \setminus f) \text{ for every } f \in P\} \setminus R(N).$$

Lemma 3.3 (Deletion compatibility)**.** *Let $|E| > 2r$ and let $\mathcal{B}$ be a nonempty family of r-subsets of E. If for every $a \in E$ the members avoiding a form the bases of a rank-r matroid on $E \setminus \{a\}$, then $\mathcal{B}$ is the basis family of a rank-r matroid on E.*

Proof. Take $U, V \in \mathcal{B}$ and $u \in U \setminus V$. Since $|U \cup V| \le 2r < |E|$, choose $a \notin U \cup V$. Basis exchange in the specified deletion at a gives $v \in V \setminus U$ such that $(U \setminus \{u\}) \cup \{v\}$ belongs to that deletion's basis family, and hence to $\mathcal{B}$. This proves basis exchange for the nonempty family $\mathcal{B}$. □

Proposition 3.4 (Exact recovery)**.** *The map sending $x \in S(N)$ to the matroid with bases $\mathcal{B}_N(x)$ is a bijection onto $\mathcal{D}(N)$.*

Proof. The family $\mathcal{B}_N(x)$ contains $\mathcal{B}(N)$. Its restriction avoiding e gives the bases of N, and its restriction avoiding $f \in P$ gives the bases of a simple rank-four quinary extension of $N \setminus f$ by the condition on $\pi_f(x)$. Since $11 > 2 \cdot 4$, Lemma 3.3 makes $\mathcal{B}_N(x)$ a matroid basis family. The deletions have rank four and are simple, so every pair of elements is independent in a deletion containing it, and hence in the recovered matroid. The matroid is nonquinary because its row is outside $R(N)$.

Conversely, if $M \in \mathcal{D}(N)$, then each $M \setminus f$ for $f \in P$ is simple and quinary. It has rank four because it contains $N \setminus f$, which has rank four. Its extra basis decisions therefore lie in $R(N \setminus f)$. Since M is nonquinary, its full row lies outside $R(N)$. This row determines M uniquely because $\mathcal{B}(N)$ and the bits x_T together specify all bases. □

3.2.1 Labelled representations

To build $R(Q)$ exhaustively, we first construct $L(Q)$, one matrix per *labelled projective equivalence* class representing Q. This equivalence allows invertible row operations and nonzero column scalings with the element labels fixed. For each field-isomorphism class representing a matroid isomorphic to Q, we align one catalogue matrix with Q using a matroid isomorphism α.

To see why the aligned matrices suffice after relabelling, take any labelled representation of Q. Proposition 3.2 provides a field-isomorphic catalogue matrix, and the column bijection β in that field isomorphism preserves the bases. Both α and β are matroid isomorphisms onto Q, so $\beta \circ \alpha^{-1}$ is an automorphism of Q. Applying this automorphism to the aligned matrix reaches the target class up to row operations and column scalings.

We compute the automorphisms from a bipartite incidence graph, with one colour for element vertices and another for basis vertices. An edge records membership of an element in a basis. A colour-preserving automorphism permutes the elements and preserves the basis family, and every matroid automorphism extends to the basis vertices. SageMath supplies group generators. Repeatedly applying them to the aligned matrices and retaining each new normalized matrix exhausts the orbits. Relabelling respects projective equivalence, so the normalized matrix suffices for continuing the orbit calculation.

For normalization, fix an ordered basis $B = (b_1, \ldots, b_r)$, reduce its columns to I_r, and write the remaining block as Z. The determinant for a single basis exchange gives

$$Z_{ij} \neq 0 \quad \Longleftrightarrow \quad (B \setminus \{b_i\}) \cup \{j\} \in \mathcal{B}(Q), \qquad j \in E(Q) \setminus B.$$

Lemma 3.5 (Normalization by a support forest)**.** *With the ordered basis fixed, scaling all entries on a fixed spanning forest of the support graph to 1 gives a unique matrix in each labelled projective equivalence class.*

Proof. In the support graph, row vertex i is adjacent to column vertex j when $Z_{ij} \neq 0$. Choose a root multiplier of 1 in each tree. Traversing the forest, each edge determines the multiplier at its unvisited endpoint that makes the entry 1. Inverse scalings on the basis columns preserve I_r.

For uniqueness, a row transformation between two equivalent matrices in identity form must preserve each basis-column direction and is therefore diagonal. If both matrices have forest entries 1, the product of the row and column multipliers on each forest edge must equal 1. It follows along paths that all row multipliers in each tree are equal and all column multipliers are their inverses. Every support edge has both endpoints in the same tree, so every nonzero entry is unchanged. Isolated vertices affect no entry of Z. □

3.2.2 Extension tables and hyperplane compression

For every $V \in L(Q)$, append each unused point $v \in \mathrm{PG}(3,5)$ as column e. The resulting matrix represents a simple quinary extension, with row

$$z(V,v)_T = \mathbf{1}\{\det[V_T \mid v] \neq 0\}, \qquad T \in \binom{E(Q)}{3}.$$

Every resulting row lies in $R(Q)$. Conversely, take a row in $R(Q)$ and a representation $[W \mid w]$ of its extension, with w labelled e. Since W represents Q, some $V \in L(Q)$ is equivalent to W with labels fixed. Apply the row transformation to all columns and the old-column scalings to W. Normalize the transformed new column v by scaling it. The direction of v is unused because the extension is simple, so $[V \mid v]$ is tried and yields the original row. Thus the distinct rows are exactly $R(Q)$.

To batch these tests, expand each determinant along v as $c_T^{\mathsf{T}} v$. Stacking the cofactor rows in C and all 156 projective point columns in D, the product CD over $\mathbb{F}$ evaluates every triple–point test for that matrix at once. We omit used points and convert nonzero entries to 1.

In any rank-four extension M of N, a dependent triple T has bit 0 because $r_M(T \cup \{e\}) \leq 3$. If T is independent, its closure $H = \mathrm{cl}_N(T)$ is a hyperplane. Since N is a restriction of M, we have $T \subseteq H \subseteq \mathrm{cl}_M(T)$, so $\mathrm{cl}_M(H) = \mathrm{cl}_M(T)$. Thus $T \cup \{e\}$ is a basis exactly when $e \notin \mathrm{cl}_M(H)$. All triples spanning H share this decision, which we denote by y_H.

Let $\mathcal{H}(N)$ denote the hyperplanes of N. The coordinates visible after deleting f are

$$C_f = \left\{ \mathrm{cl}_N(T) : T \in \binom{P \setminus \{f\}}{3},\ r_N(T) = 3 \right\}.$$

For each surviving independent triple, $\mathrm{cl}_{N\setminus f}(T) = \mathrm{cl}_N(T) \setminus \{f\}$. Thus triples grouped by a coordinate in C_f share a closure in $N \setminus f$ and have equal bits in every row of $R(N \setminus f)$. Dependent triples stay dependent under deletion. We therefore compress $R(N \setminus f)$ to a table A_f on C_f and $R(N)$ to a table A on $\mathcal{H}(N)$. Define

$$\widehat{S}(N) = \{ y \in \{0,1\}^{\mathcal{H}(N)} : y|_{C_f} \in A_f \text{ for every } f \in P \} \setminus A.$$

Expanding a row y copies y_H to every independent triple spanning H and puts zero on dependent triples. This reverses the compression in each table. Hence $y|_{C_f} \in A_f$ exactly when the expanded row satisfies $\pi_f(x) \in R(N \setminus f)$, and $y \in A$ exactly when $x \in R(N)$. Conversely, each $x \in S(N)$ gives a matroid by Proposition 3.4, so its bits are constant on each hyperplane group and compress to a unique y. This gives a bijection between $\widehat{S}(N)$ and $S(N)$.

3.2.3 Enumeration by natural joins

A natural join combines two table rows exactly when they agree on every shared coordinate. For a nonempty set $I \subseteq P$ of deletions already joined, let $C_I = \bigcup_{f \in I} C_f$. The accumulated relation is

$$J_I = \{ y \in \{0,1\}^{C_I} : y|_{C_f} \in A_f \text{ for all } f \in I \}.$$

For a single deletion this is its table. Joining J_I with the next table enforces the previous conditions on C_I and the new condition on that table's columns, proving the formula inductively. Every hyperplane H appears in at least one table because deleting an $f \notin H$ leaves a spanning triple of H intact. The joined rows therefore assign every variable, and removing the full-parent rows gives

$$\widehat{S}(N) = (A_0 \bowtie A_1 \bowtie \cdots \bowtie A_9) \setminus A.$$

The implementation groups rows by their bits on the shared columns and chooses the next table by the exact size of the resulting join. Once all columns have appeared, rows in A can be removed immediately because further joins only filter full assignments. Every connected parent in the eleven-element search was exhausted by this method.

3.2.4 SAT encoding and enumeration

The same tables admit a propositional SAT encoding with one Boolean variable y_H per hyperplane. To construct a binary decision diagram (BDD) for A_f, split its rows on successive columns in a fixed order. An empty branch rejects, and a branch that reaches the end with an allowed row accepts. Identical subdiagrams can be shared. For example, the table $\{00, 01, 11\}$ on (y_1, y_2) accepts immediately when $y_1 = 0$. When $y_1 = 1$, it accepts exactly when $y_2 = 1$.

At a node testing y_H, let v be the Boolean value of the subdiagram, and let ℓ, h be the values of its 0- and 1-branches. The node equivalence and its four clauses in conjunctive normal form are

$$v \iff ((\neg y_H \wedge \ell) \vee (y_H \wedge h)),$$

$$(\neg v \vee y_H \vee \ell), \quad (\neg v \vee \neg y_H \vee h),$$
$$(v \vee y_H \vee \neg \ell), \quad (v \vee \neg y_H \vee \neg h).$$

For a fixed y_H, the clauses force v to equal the value of the selected child. Starting at the terminals and working up, each node is therefore forced to its evaluation on the hyperplane row. Setting each root to true enforces every deletion constraint. To rule out a quinary full extension, for each row $a \in A$ we add the blocking clause

$$\bigvee_{H \in \mathcal{H}(N)} (y_H \neq a_H).$$

Here the literal is y_H when $a_H = 0$, and $\neg y_H$ when $a_H = 1$. The satisfying assignments projected onto the y_H variables are exactly $\widehat{S}(N)$. We record each resulting row and add the same kind of clause on the y_H variables to block it. Enumeration is complete when the solver returns `UNSAT`. A resource limit returns `UNKNOWN` and leaves the search unresolved.

3.3 Step 3: testing contractions and removing duplicates

For every candidate $M \in \mathcal{D}(N)$ and every $a \in E(M)$, the contraction M/a has rank three because a is a nonloop. We test its simplification, obtained by deleting loops and retaining one element per parallel class. If M/a is quinary, its simplification is quinary by closure under deletion. Conversely, a representation of the simplification extends to M/a by restoring zero columns for loops and scalar copies for parallel elements. Hence it suffices to test the simplification. It has at most ten elements. At size three it is the free rank-three matroid represented by I_3, and at sizes four through ten we compare it by exact isomorphism with the complete simple rank-three catalogue from Step 1.

Candidates passing every contraction test are excluded minors, since Step 2 establishes nonrepresentability and representability of all deletions. SageMath then removes duplicates up to matroid isomorphism, including candidates arising from different parents. An independent check of distinctness compares canonical forms of coloured incidence graphs. For each matroid, the subset vertices represent either all bases or all nonbases of size four, using bases in a tie. Any matroid isomorphism preserves this choice and induces a colour-preserving graph isomorphism. Conversely, the graph determines the chosen subset family up to a relabelling of the elements. A flag records which family was encoded, so the graph and flag together determine the bases.

3.3.1 Independent certificates

For each final representative, the positive witnesses are matrices for its eleven deletions and eleven contractions, with columns in the order of the remaining labels. Modular Gaussian elimination checks the basis status of every subset of the appropriate size against the required minor. SageMath performs a second matrix check.

For nonrepresentability, let Φ_M be the SAT formula for a quinary representation of a final matroid M. Fix an ordered basis $B = (b_1, \ldots, b_r)$ and reduce its columns to I_r, writing the remaining block as Z. As in the labelled normalization, a position Z_{ij} is nonzero exactly when $(B \setminus \{b_i\}) \cup \{j\}$ is a basis. Lemma 3.5 allows the forest entries to be fixed to 1, leaving the other nonzero entries with domain $\{1, 2, 3, 4\}$.

For each r-subset $S \subseteq E(M)$, let $I(S) = \{i : b_i \notin S\}$ and $J(S) = S \setminus B$. Expanding along the identity columns reduces the determinant on S, up to sign, to the square minor on the missing rows and extra columns. Thus we impose

$$\det Z[I(S), J(S)] \neq 0 \quad \Longleftrightarrow \quad S \in \mathcal{B}(M),$$

with the empty determinant equal to 1. The encoder computes these determinants by cached Laplace expansion over $\mathbb{F}$.

Each field expression u with domain D_u has Boolean indicators $p_{u,a}$ for $a \in D_u$, with exactly one true. For an addition $w = u + v$, the formula includes

$$\neg p_{u,a} \ \vee \ \neg p_{v,b} \ \vee \ p_{w,a+b}$$

for every allowed pair a, b, with the sum taken modulo five. Multiplication uses the analogous clause with ab. Since the output has exactly one value, the selected inputs force the correct output. Constants can be substituted directly. Induction over the arithmetic operations therefore forces the determinant values, and the formula constrains their indicators according to the specified basis status.

Any representation of M can be normalized as above and gives a satisfying assignment by evaluating the field expressions. Conversely, a satisfying assignment gives a full-rank matrix in identity form whose nonsingular r-column submatrices are exactly the bases of M. Hence Φ_M is satisfiable exactly when M is quinary. The saved DRAT refutation for each representative is checked against its saved formula by DRAT-trim [9]. Together with the 22 minor matrices, this certifies excluded-minor status directly from the representative's basis family.

3.4 Search coverage and classification

At size ten, generation retained 64,508 field-isomorphism classes, which gave 58,756 abstract classes. Aligning matrices and closing their automorphism orbits gave 71,547 labelled projective classes across that full catalogue. The merge checked that the four search ranges had matching input and source fingerprints and covered the catalogue without gaps or overlaps. Of the 58,756 parents, 84 were disconnected and every remaining problem finished by natural join with no unresolved cases. The 659 pairs in Table 1 count labelled extensions together with their parents, before the contraction filter [5, 8].

Table 1: Stages of the exhaustive rank-four search.

Stage	Count
Simple quinary ten-element parent classes	58,756
Connected parent classes searched to exhaustion	58,672
Labelled pairs (N, M) with $M \in \mathcal{D}(N)$	659
Excluded-minor classes after contractions and deduplication	35

Theorem 3.6. *There are exactly 35 isomorphism classes of rank-four, eleven-element excluded minors for quinary representability.*

Proof. For the upper bound, take any excluded minor of the required rank and size. By Lemma 3.1 and Proposition 3.2, one of its deletions is isomorphic to a searched parent N. Relabel the deletion as N and the removed element as e. The resulting matroid belongs to $\mathcal{D}(N)$, so Proposition 3.4,

the complete extension tables, and the exhaustive joins ensure it is recovered. All its contractions are quinary, so its isomorphism class survives Step 3.

For the lower bound, the 35 checked DRAT refutations establish nonquinary status, and the $35 \times 22 = 770$ checked matrices establish representability of all immediate minors. The independent incidence-graph check confirms that these representatives are pairwise nonisomorphic [8]. □

As calibration, the implementation reproduced Brettell's rank-four catalogues by exact matroid isomorphism, with 5, 92, 219, and 130 classes at sizes seven through ten, respectively [3, 8]. At sizes seven and eight, the condition $|E| > 2r$ fails, so the searches impose basis exchange explicitly. SAT and natural join also agreed on the solutions from the shared tables for every connected parent at target size nine and on all 5,991 labelled deletion-minimal candidates at target size ten [5, 8].

The repository's `results/r4-n11/` directory contains the merged search record (`summary.json`), the exact basis families (`excluded.jsonl`), and the 770 witness matrices (`minors/minor-witnesses.jsonl`). Each case under `nonrepresentation/` includes the DIMACS formula, DRAT refutation, and checker output. The generation, search, and replay commands are documented in `docs/REPRODUCING.md` [4].

4 Experiments and results

We evaluate how an LLM should contribute to the classification task through two experiments. The first tests classification of supplied matroids; the second tests the more demanding task of finding every excluded-minor extension of a supplied parent. Together they distinguish answer correctness, computational efficiency, and evidence of completeness.

4.1 Workflows and shared setup

We compare four workflows with different divisions of responsibility between the frontier LLM model and the tools and solvers:

Direct reasoning. The model returns its answer and justification in one call, without tools.

Exact queries. The model requests ranks, determinants modulo five, deletions, or contractions, then interprets these calculations and constructs the final answer.

Model-directed SAT. The model chooses representability tests in classification, or candidate checks and constrained extension searches in enumeration. It uses the solver replies to decide the final label or solution set.

Translation and exact solving. The model translates the supplied hyperplanes into structured data. After checking that the translation preserves the full labelled basis family, the exact backend performs the classification or exhaustive search and returns the answer.

Both experiments use `gpt-6.1-sol` at medium reasoning effort, with one trial per instance and workflow. All workflows receive the same complete hyperplane descriptions, while answer keys remain with the grader. Built-in model tools are disabled; only the designated interfaces are available. The benchmark cases are separate from the pilots. Query budgets, case-generation details, and supplementary results are provided in Appendix **??**.

4.2 Experiment 1: classifying supplied matroids

Design. We use 30 rank-four matroids on eleven elements, with ten in each class: quinary, excluded minor, and nonquinary but nonminimal. Quinary cases are generated from matrices, excluded minors are drawn from the certified catalogue, and nonminimal cases extend known excluded minors so that deletion recovers an obstruction. All cases are relabelled and their labels checked by the exact solver. We measure classification accuracy and median elapsed time. For the ten quinary cases, we also check matrices supplied by the direct and exact-query workflows against every basis and nonbasis. This separates a correct label from a verifiable representation.

Table 2: Classification results on 30 supplied matroids.

Workflow	Correct labels	Median time (s)
Direct reasoning	30/30	50.8
Exact queries	30/30	80.2
Model-directed SAT	30/30	16.3
Translation and exact solving	30/30	12.2

Results. All four workflows classify every case correctly (Table 2). Translation and exact solving has the shortest median time, about one quarter of direct reasoning, and all 30 translations preserve the input basis family. All ten matrices from direct reasoning pass the determinant checks, as do nine from exact queries. The remaining exact-query response gives the correct label but includes a placeholder instead of a matrix.

Discussion. Exact queries increase elapsed time without improving label accuracy. Computing a deletion or contraction still leaves the model to decide its representability; SAT queries resolve that predicate directly. The extra interaction also contributes to time. Thus the useful tool interface is the one that addresses the remaining mathematical decision, rather than simply supplying intermediate calculations. The missing matrix further shows why accuracy should be accompanied by a certificate check.

The perfect scores require qualification. The case constructions induce different basis-count distributions: a leave-one-out rule assigning the nearest class mean from basis count alone scores 24/30. All workflows solve the six cases it misses, but the benchmark still supplies a strong structural cue. Relabelling preserves that cue. These results demonstrate success on the selected cases; a stronger generalization test would match classes on basis counts, diversify their constructions, and repeat trials.

4.3 Experiment 2: searching for all excluded-minor extensions

Design. Each trial supplies a connected, simple, rank-four quinary parent on ten elements and asks for all excluded-minor extensions by element 10. The 24 pairwise nonisomorphic parents comprise three groups of eight: parents with valid solutions, parents whose deletion-compatible nonquinary candidates fail contraction checks, and parents with no such candidates. This design tests recovery and two distinct reasons for an empty answer. Five positive parents have multiple solutions. Exhaustive joins, SAT enumeration, contraction checks, and comparison with the certified catalogue establish 16 reference solutions up to isomorphism fixing element 10.

We measure candidate precision, solution recall, and *exact-set match*, which requires a complete, valid answer for a parent. We separately measure *verified exhaustion*: an accepted computational trace must cover all extensions and account for every valid output. Matching the reference set and establishing completeness are different requirements. Median time covers the workflow's search and verification. Prepared compatibility tables are available to the SAT and translation workflows; their median construction time of 0.3 seconds is recorded separately.

Table 3: Search results on 24 parents. Exhaustion counts accepted computational traces; free-text completeness arguments are not scored by this measure.

Workflow	Precision	Recall	Exact sets	Exhausted	Median (s)
Direct reasoning	16/16	16/16	24/24	0/24	131.1
Exact queries	16/16	16/16	24/24	0/24	144.8
Model-directed SAT	15/16	15/16	23/24	14/24	79.9
Translation and exact solving	16/16	16/16	24/24	24/24	9.9

Results. Direct reasoning, exact queries, and translation recover all 16 solutions and match every reference set (Table 3). Translation is fastest on every parent and provides accepted exhaustion evidence in all 24 trials. Model-directed SAT supplies correct sets in 23 trials, but only 14 have accepted exhaustion traces; nine correct answers leave coverage gaps. In its remaining trial, the solver finds both required extensions, but the final response omits a triple from one candidate, making the submitted basis family invalid. All workflows correctly return empty sets on the 16 negative parents.

Discussion. The distinction between finding solutions and proving completeness is decisive. Direct reasoning succeeds at recovering the answers, but its free-text arguments are not accepted computational traces. Its 0/24 exhaustion score therefore does not establish that those arguments are mathematically wrong. Model-directed SAT provides exact local answers, yet still depends on the model to cover every branch and preserve checked candidates. The transcription failure demonstrates that solver correctness need not survive the final response. Returning identifiers for checked basis families would address this failure mode; that interface improvement remains to be evaluated.

Translation transfers enumeration, contraction checks, and output construction to the backend. Its 9.9-second median is about thirteen times lower than direct reasoning's, while also providing complete traces. The exact method exploits the problem's structure: these parents require 28–48 hyperplane variables, but the largest intermediate join contains only 1,166 rows. Compatibility constraints sharply restrict the represented search space, although this is not a measured speedup over an uncompressed baseline. The negative groups also confirm the need for both filters: each contraction near miss leaves one deletion-compatible candidate that must still be rejected.

The balanced sample makes these behaviours observable but does not reflect their frequency in the full search. Only 224 of 58,672 connected parents, about 0.38%, admit excluded-minor extensions. An always-empty answer would match about 99.62% of that catalogue while discovering nothing. Consequently, solution recall and exhaustion evidence are essential alongside exact-set accuracy. The benchmark evaluates selected search behaviours; the global classification rests on the separate exhaustive computation.

4.4 Overall Discussion

Across both experiments, validated translation followed by exact solving gives the fastest answers and the strongest computational evidence. This supports assigning formal verification and exhaustive enumeration to exact tools for fully specified instances. It does not demonstrate a need for an LLM to parse the present regular format: a deterministic parser is an appropriate unmeasured baseline. Ambiguous or incomplete descriptions would require specification checks before a solver's certificate could support the intended claim.

These are comparisons of complete workflows, whose tool capabilities and model-call counts differ, rather than controlled component ablations. Timings exclude catalogue construction and the separately recorded search-table preparation. With one trial per instance, one model, and constructed cases, the results do not establish statistical stability or performance on larger or less structured inputs. The supported conclusion concerns the division of work in this setting, rather than a general superiority of tool use over direct reasoning.

5 Responsible AI

Scientific reliability. In AI-assisted mathematical research, an incorrect classification can propagate into later proofs and impose substantial checking costs on other researchers. Transparency and the prevention of unintended consequences are therefore central responsible-AI concerns in this domain [**?**]. A plausible explanation or a correct benchmark answer is insufficient evidence for a classification theorem. Our claim is supported by the coverage argument, exhaustive searches, checked nonrepresentability refutations, immediate-minor matrices, and isomorphism checks. The distinction matters: certificates establish the status of the listed objects, while completeness also requires coverage of every possible parent and extension. A timeout remains unresolved, and a checked result applies only to the mathematical object actually encoded.

Transparency and human responsibility. The AI assistance described in Section 6 makes traceability important: polished mathematical prose can obscure how a result was obtained. The saved prompts, outputs, tool replies, and verification records allow readers to trace claims to computational evidence. Such records support scrutiny but do not explain the model's internal reasoning or guarantee that the implementation matches the intended mathematics. The authors remain responsible for the formulation, completeness argument, attribution of prior work, and claims presented to readers. Neither model confidence nor a solver verdict transfers that responsibility to the software.

Responsible evaluation and use. Reporting only accuracy or speed could encourage reliance on answers without adequate justification. Section 4 shows that a correct label can lack its promised witness and that a valid solver result can be corrupted when transcribed. We therefore distinguish answer accuracy, validity of submitted objects, and evidence of exhaustion. Input translations are checked against the original basis family; the observed output error also motivates preserving checked candidates through the final response. The constructed benchmarks support conclusions about these workflows on fully specified matroids, not a general claim that the model can independently conduct reliable mathematical research. Ambiguous descriptions require clarification before certification, and broader use would require additional evaluation.

6 Statement of Contributions and AI assistance

Deng Tianle. *[]*

Liu Lekang. *[]*

Zhao Kejun. *[Designed and run experiments, analyzed results]*

AI assistance. We used an LLM with computational tools to develop and carry out the exhaustive search. Codex also assisted with the evaluation harness, analysis of saved results, and drafting and editing this report. These activities were AI-assisted; the authors retain responsibility for the submitted work and its claims.

Appendix

A.1 Matroid Theory Background

6.0.1 Basic definitions

Definition 6.1. *A matroid M is an ordered pair $(E, \mathcal{I})$ consisting of a finite set E and a collection $\mathcal{I}$ of subsets of E having the following three properties:*

1. $\emptyset \in \mathcal{I}$.
2. *If $I \in \mathcal{I}$ and $I' \subset I$, then $I' \in \mathcal{I}$.*
3. *If I_1 and I_2 are in $\mathcal{I}$ and $|I_1| < |I_2|$, then there exists $e \in I_2 - I_1$ such that $I_1 \cup \{e\} \in \mathcal{I}$.*

If M is the matroid $(E, \mathcal{I})$, M is a called a matroid on E. The members of $\mathcal{I}$ are the independent sets of M, and E is the ground set of M. A subset of E that is not in $\mathcal{I}$ are called dependent. We often write $\mathcal{I}(M)$ for $\mathcal{I}$ and $E(M)$ for E.

Definition 6.2. *Let E be the set of column labels of an $m \times n$ matrix A over a field $\mathbb{F}$, and let $\mathcal{I}$ be the set of subsets X of E for which the multiset of columns labelled by X is linearly independent. Then $(E, \mathcal{I})$ is a vector matroid of A, denoted by $M[A]$.*

It is easy to check that $M[A]$ is indeed a matroid.

Definition 6.3. *Two matroids M_1 and M_2 are isomorphic, written $M_1 \cong M_2$, if there is a bijection ψ from $E(M_1)$ to $E(M_2)$ such that, for all $X \subset E(M_1)$, the set $\psi(X)$ is independent in M_2 if and only if X is independent in M_1.*

Definition 6.4. *If a matroid M is isomorphic to the vector matroid of a matrix A over a field $\mathbb{F}$, then M is $\mathbb{F}$-representable; A is a $\mathbb{F}$-representation of M.*

As we would see later, not all matroids are representable.

6.0.2 Circuits

There is an alternative perspective on matroids that is related to the interpretation of matroids via graph theory rather than linear algebra.

Definition 6.5. *A minimal dependent set in a matroid M is called a circuit. We denote the set of circuits of M by $\mathcal{C}$ or $\mathcal{C}(M)$. A circuit with n elements is called an n-circuit.*

A matroid is uniquely determined by its set of circuits $\mathcal{C}$: the members of $\mathcal{I}$ are exactly those subsets of E that contain no member of $\mathcal{C}$.

Lemma 6.1. *The set $\mathcal{C}$ of circuits of a matroid has the following properties:*

1. $\emptyset \notin \mathcal{C}$.
2. *If C_1 and C_2 are members of $\mathcal{C}$ and $C_1 \subset C_2$, then $C_1 = C_2$.*
3. *If C_1 and C_2 are disticnt members of $\mathcal{C}$ and $e \in C_1 \cap C_2$, then there is a member C_3 of $\mathcal{C}$ such that $C_3 \subset (C_1 \cup C_2) - \{e\}$.*

It turns out that the converse also holds in the sense that we can define a matroid using the above properties:

Theorem 6.2. *Let E be a set and $\mathcal{C}$ be a collection of subsets of E satisfying the three conditions above. Let $\mathcal{I}$ be the collection of subsets of E that contain no member of $\mathcal{C}$. Then $(E, \mathcal{I})$ is a matroid having $\mathcal{C}$ as its collection of circuits.*

Lemma 6.3. *Suppose I is an independent set in a matroid M and e is an element of M such that $I \cup \{e\}$ is dependent. Then M has a unique circuit contained in $I \cup \{e\}$, and this circuit contains e.*

Recall that a cycle (or circuit) of a graph is a connected subgraph all of whose vertices have degree two.

Definition 6.6. *Let E be the set of edges of a graph G and $\mathcal{C}$ be the set of edge sets of cycles of G. Then $\mathcal{C}$ is a set of circuits of a matroid on E called the cycle matroid or polygon matroid of G. It is denoted by $M(G)$.*

In other words, X is an independent set of $M(G)$ if and only if the subgraph induced by X is a forest. One can check that the set $\mathcal{C}$ indeed satisfies the three properties for a set of circuits.

A matroid that is isomorphic to the cycle matroid of a graph is called graphic. However, again not all matroids are graphic.

Definition 6.7. *We record some graph inspired terminologies for general matroid:*

1. *An element e of a matroid M is called a loop if $\{e\}$ is a circuit of M.*
2. *If f and g are elements of M such that $\{f, g\}$ is a circuit, then f and g are parallel in M.*
3. *A parallel class of M is a maximal subset of $E(M)$ such that any two distinct members of X are parallel and no member of X is a loop. A parallel class is trivial if it contains just one element.*
4. *If a matroid has no loops and no non-trivial parallel classes, it is called a simple matroid.*

(This discussion involves concepts introduced in later sections) It is clear that no basis intersects the set of loops of M. Also, if e_1 is not a loop of M, then e_2 is parallel with e_1 if and only if, for every basis B containing e_1, the set $(B - \{e_1\}) \cup \{e_2\}$ is also a basis. Now let X be a non-trivial parallel class of M and, for each $x \in X$, let $\mathcal{B}_x$ denote the set of bases of M containing x. If x and y are distinct members of X, then $\mathcal{B}_x \cap \mathcal{B}_y = \emptyset$, but $\{B - \{x\} : B \in \mathcal{B}_x\} = \{B - \{y\} : B \in \mathcal{B}_y\}$. Thus, if we delete all the loops from M and then, in each non-trivial parallel class X, we distinguish one element and delete all other elements in X, the matroid we obtain is uniquely determined up to a renaming of the distinguished elements. We denote this matroid by $\mathrm{si}(M)$ and call it the simple matroid associated with M or the simplification of M.

The cycle matroid and vector matroid are two canonical examples of matroids that inspire a lot of the terminology used in matroid theory.

6.0.3 Bases

We see that matroids have a concept of basis and rank like in linear algebra. Let M be a matroid.

Definition 6.8. *A maximal independent set in M is called a basis or a base of M.*

Lemma 6.4. *All bases of a matroid has the same cardinality.*

Let $\mathcal{B}$ be the set of bases of M. Clearly $\mathcal{B}$ is non-empty. Furthermore, it has the following property (which can be seen as an analogue of Steinitz exchange lemma):

Lemma 6.5. *Let $B_1, B_2 \in \mathcal{B}$, $x \in B_1 - B_2$. Then there exists $y \in B_2 - B_1$ such that $(B_1 - \{x\}) \cup \{y\} \in \mathcal{B}$.*

We also have a converse characterisation result similar to the one for circuits.

Theorem 6.6. *Let E be a set and $\mathcal{B}$ be a non-empty collection of subests of E satisfying the exchange property above. Let $\mathcal{I}$ be the collection of subsets of E that are contained in some member of $\mathcal{B}$. Then $(E, \mathcal{I})$ is a matroid having $\mathcal{B}$ as its collection of bases.*

Lemma 6.7. *Let B be a basis of M. If $e \in M - B$, then $B \cup \{e\}$ contains a unique circuit, $C(e, B)$. Moreover $e \in C(e, B)$*

We call $C(e, B)$ the fundamental circuit of e with respect to B.

Proposition 6.8. *Every circuit in a matroid is the fundamental circuit of some element with respect to some basis.*

6.0.4 Rank

We first define a fundamental and very natrual matroid construction. Let M be the matroid $(E, \mathcal{I})$ and suppose that $X \subset E$. Let $\mathcal{I}|X$ denote the set $\{I \subset X : I \in \mathcal{I}\}$. Then it is easy to see that the pair $(X, \mathcal{I}|X)$ is a matroid. We call this matroid the restriction of M to X or the deletion of $E - X$ from M, denoted by $M|X$ or $M \setminus (E - X)$. One easily checks that $\mathcal{C}(M|X) = \{C \subset X : C \in \mathcal{C}(M)\}$.

Matroid deletion is a direct generalisation of the corresponding concept for graphs. For a graph G and a subset T of $E(G)$, recall that $G \backslash T$ is the graph obtained from G by deleting the edges in T. We have

$$M(G \backslash T) = M(G) \backslash T.$$

Definition 6.9. *We define the rank $r(X)$ of X to be the cardinality of a basis B of $M|X$ and call such a set B a basis of X.*

Lemma 6.9. *The rank function r has the following properties:*

1. *If $X \subset E$, then $0 \leqslant r(X) \leqslant |X|$.*
2. *If $X \subset Y \subset E$, then $r(X) \leqslant r(Y)$.*
3. *If X and Y are subsets of E, then*

$$r(X \cup Y) + r(X \cap Y) \leqslant r(X) + r(Y).$$

These properties characterise the rank function and in fact the matroid.

Theorem 6.10. *Let E be a set and $r \colon 2^E \to \mathbb{Z}_{\geqslant 0}$ be a function satisfying the above three properties. Let $\mathcal{I}$ be the collection of subsets of X of E for which $r(X) = |X|$. Then $(E, \mathcal{I})$ is a matroid having rank function r.*

Proposition 6.11. *Let M be a matroid with rank function r and let $X \subset E(M)$. Then*

1. *X is independent if and only if $|X| = r(X)$*
2. *X is a basis if and only if $|X| = r(X) = r(M)$*
3. *X is a circuit if and only if X is nonempty and, for all $x \in X$, $r(X - \{x\}) = |X| - 1 = r(X)$.*

6.0.5 Closure

We now consider the analogue of span in matroid theory. Let M be a matroid over E, with rank function r.

Definition 6.10. *Let* $\mathrm{cl}\colon 2^E \to 2^E$ *be defined by*

$$\mathrm{cl}(X) = \{x \in E : r(X \cup \{x\}) = r(X)\}.$$

This function is called the closure operator of M*, and we call* $\mathrm{cl}(X)$ *the closure or span of* X *in* M*.*

Lemma 6.12. *For all* X*, we have* $r(X) = r(\mathrm{cl}(X))$*.*

Lemma 6.13. *The closure operator of a matroid on a set* E *has the following properties:*

1. *If* $X \subset E$*, then* $X \subset \mathrm{cl}(X)$*.*
2. *If* $X \subset Y \subset E$*, then* $\mathrm{cl}(X) \subset \mathrm{cl}(Y)$*.*
3. *If* $X \subset E$*, then* $\mathrm{cl}(\mathrm{cl}(X)) = \mathrm{cl}(X)$*.*
4. *If* $X \subset E$*,* $x \in E$ *and* $y \in \mathrm{cl}(X \cup \{x\}) - \mathrm{cl}(X)$*, then* $x \in \mathrm{cl}(X \cup y)$*.*

The fourth property is sometimes referred to as the MacLane-Steinitz exchange property. Once again we have a characterisation of matroids in terms of such functions.

Theorem 6.14. *Let* E *be a set and* $\mathrm{cl}\colon 2^E \to 2^E$ *be a function satisfying the above four properties. Let*

$$\mathcal{I} = \{X \subset E : x \notin \mathrm{cl}(X - \{x\}) \text{ for all } x \in X\}.$$

Then $(E, \mathcal{I})$ *is a matroid having closure operator* cl*.*

We next introduce the concept of hyperplane and results that are familiar from linear algebra. Let M be a matroid and $X \subset E(M)$.

Definition 6.11. *A subset* X *for which* $\mathrm{cl}(X) = X$ *is called a flat or a closed set of* M*. A hyperplane of* M *is a flat of rank* $r(M) - 1$*.*

A subset X is a spanning set of M if $\mathrm{cl}(X) = E(M)$. We also say that X spans a subset Y of $E(M)$ if $Y \subset \mathrm{cl}(X)$.

Proposition 6.15. *The subset* X *has the following properties:*

1. X *is a spanning set if and only if* $r(X) = r(M)$*.*
2. X *is a basis if and only if it is both spanning and independent.*
3. X *is a basis if and only if it is a minimal spanning set.*
4. X *is a hyperplane if and only if it is a maximal non-spanning set.*

Proposition 6.16.

$$\mathrm{cl}(X) = X \cup \{x : M \text{ has a circuit } C \text{ such that } x \in C \subset X \cup \{x\}\}$$

6.0.6 Duality

Theorem 6.17. *Let M be a matroid and $\mathcal{B}^*(M)$ be $\{E(M) - B : B \in \mathcal{B}(M)\}$. Then $\mathcal{B}^*(M)$ is the set of bases of a matroid on $E(M)$.*

Definition 6.12. *The matroid defined in the last theorem is called the dual of M, denoted as M^*.*

One sees that $\mathcal{B}(M^*) = \mathcal{B}^*(M)$. It is clear that $(M^*)^* = M$. The bases of M^* are called cobases of M. We use this naming convention for other distinguished subsets of $E(M^*)$.

Proposition 6.18. *Let M be a matroid on a set E and suppose $X \subset E$. Then*

1. *X is independent if and only if $E - X$ is cospanning.*
2. *X is spanning if and only if $E - X$ is coindependent.*
3. *X is a hyperplane if and only if $E - X$ is a cocircuit.*
4. *X is a circuit if and only if $E - X$ is a cohyperplane.*

In general, we attach an asterisk to a symbol to denote association with the dual. For example, r^* denotes the rank function of M^* while $\mathcal{C}^*$ denotes its set of circuits.

Proposition 6.19. *For all $X \subset E(M)$,*

$$r^*(X) = r(E - X) + |X| - r(M).$$

Proposition 6.20. *In a matroid M, let C be a circuit and C^* be a cocircuit. Then $|C \cap C^*| \neq 1$.*

The above property is often called orthogonality.
Finally we record a result that is evidently relevant in our case.

Theorem 6.21. *If a matroid M is $\mathbb{F}$-representable, then M^* is also $\mathbb{F}$-representable.*

6.0.7 Minors

We introduce the operation contraction as the dual of the operation fo deletion discussed previously. Let M be a matroid on E and T be a subset of E.

Definition 6.13. *The contraction of T from M, $M/T = (M^* \setminus T)^*$.*

Evidently M/T has ground set $E - T$. We record a series of facts about the distinguished subsets, rank and closure of a contraction.

Proposition 6.22. *If $T \subset E$, then for all $X \subset E - T$,*

$$r_{M/T}(X) = r_M(X \cup T) - r_M(T).$$

Proposition 6.23.

$$\mathcal{I}(M/T) = \{I \subset E - T : M|T \text{ has a basis } B \text{ such that } I \cup B \in \mathcal{I}(M)\}$$

Corollary 6.24.

$$\mathcal{B}(M/T) = \{B' \subset E - T : M|T \text{ has a basis } B \text{ such that } B' \cup B \in \mathcal{B}(M)\}$$

Proposition 6.25. *The circuits of M/T consist of the minimal nonempty members of $\{C - T : C \in \mathcal{C}(M)\}$.*

Proposition 6.26. *For all $X \subset E - T$,*

$$\mathrm{cl}_{M/T}(X) = \mathrm{cl}_M(X \cup T) - T.$$

Notice that $M \setminus T$ and M/T are matroids on the same ground set. Evidently it is always true that

$$\mathcal{I}(M \setminus T) \supset \mathcal{I}(M/T).$$

Proposition 6.27. *$M \setminus T = M/T$ if and only if $r(T) + r(E - T) = r(M)$.*

The operations of deletion and contraction commute both with each other and with themselves. Evidently, this is an important fact.

Proposition 6.28. *In a matroid M, let T_1 and T_2 be disjoint subsets of $E(M)$. Then*

1. $(M \setminus T_1) \setminus T_2 = M \setminus (T_1 \cup T_2) = (M \setminus T_2) \setminus T_1$
2. $(M/T_1)/T_2 = M/(T_1 \cup T_2) = (M/T_2)/T_1$
3. $(M \setminus T_1)/T_2 = (M/T_2) \setminus T_1$.

Definition 6.14. *A minor of M is a matroid of the form $M \setminus X/Y$ for some pair of disjoint sets X and Y either of which may be empty.*

By the previous proposition, any sequence of deletions and contractions from M gives a minor of M. If $X \cup Y$ is nonempty, we say that $M\backslash X/Y$ is a proper minor. A matroid N_1 is called an N-minor of M if N_1 is a minor of m that is isomorphic to N.

Proposition 6.29. *A matroid N is a minor of a matroid M if and only if N^* is a minor of M^*. More particularly,*

$$N = M\backslash X/Y \iff N^* = M^*/X\backslash Y.$$

Proposition 6.30. *Let M_1 and M_2 be matroids on a common ground set E and suppose $e \in E$. Then the following statements are equivalent:*

1. *$M_1\backslash\{e\} = M_2\backslash\{e\}$ and $M_1/\{e\} = M_2/\{e\}$*
2. *$M_1 = M_2$; or e is a loop of one of M_1 and M_2 and a coloop of the other.*

Matroid contraction is a direct generalisation of the corresponding concept for graphs. If e is an edge of a graph G, then $G/\{e\}$ is obtained from G by contracting e, i.e. deleting e and identifying its ends. Repeating this process for all the edges in a subset T of $E(G)$ gives the graph G/T (which is well-defined since $(G/\{e\})/\{f\} = (G/\{f\})/\{e\}$ for all edges e and f).

Proposition 6.31. *If G is a graph, then $M(G)/T = M(G/T)$ for all $T \subset E(G)$*

Corollary 6.32. *Every minor of a graphic matroid is graphic.*

For a matrix A, we denote by $A\backslash T$ the matrix obtained from A by deleting all the columns whose labels are in T. Evidently

$$M[A]\backslash T = M[A\backslash T].$$

Since F-representability is closed under duality, we have:

Proposition 6.33. *Every minor of an $\mathbb{F}$-representable matroid is $\mathbb{F}$-representable.*

Definition 6.15. *An excluded minor for $\mathbb{F}$-representability is a matroid that is not $\mathbb{F}$-representable but every proper minor of which is $\mathbb{F}$-representable.*

6.0.8 Connectivity

We continue to look at analogues of graph concepts in matroid theory. Here we discuss the concept of k-connectedness.

The concept of 1-connectedness is not really relevant in matroid theory due to the following proposition.

Proposition 6.34. *Let M be a graphic matroid. Then $M \cong M(G)$ for some connected graph G.*

We now recall the definition of general k-connectedness for graphs. A subset X of the vertex set of a graph G is called a vertex cut if $G - X$ has more connected components than G. If a vertex cut consists a single vertex v, then v is called a cut-vertex of G. For a connected graph G that has at least one pair of distinct non-adjacent vertices, the connectivity $\kappa(G)$ of G is the smallest integer j for which G has a j-element vertex cut. When G is connected but has no pair of distinct non-adjacent vertices, we take $\kappa(G) = |V(G)| - 1$; if G is disconnected, let $\kappa(G) = 0$. For a positive integer K, a graph G is said to be k-connected if $\kappa(G) \geqslant k$.

To generalise 2-connectivity to matroids, we use the following result.

Lemma 6.35. *Let G be a loopless graph without isolated vertices and suppose that $|V(G)| \geqslant 3$. Then G is 2-connected if and only if, for every pair of distinct edges of G, there is a cycle containing both.*

Definition 6.16. *We call a matroid M 2-connected or sometimes just connected if for every pair of distinct elements of $E(M)$, there is a circuit containing both.*

Proposition 6.36. *A matroid M is connected if and only if M^* is connected.*

In a matroid M with ground set E, a subset X of E is called a separator of M if X is a union of components of M. Both E and $\emptyset$ are separators of M. All other separators are called non-trivial separators. Clearly if X is a separator so is $E - X$.

Proposition 6.37. *X is a separator of M if and only if*

$$r(X) + r(E - X) = r(M).$$

We now discuss some summations operations that are very related to connectivity and more generally k-connectivity.

Definition 6.17. *Let M_1 and M_2 be matroids on disjoint sets E_1 and E_2 respectively. Let $E = E_1 \cup E_2$ and $\mathcal{I} = \{I_1 \cup I_2 : I_1 \in \mathcal{I}(M_1), I_2 \in \mathcal{I}(M_2)\}$. Then the matroid $(E, \mathcal{I})$ is called the direct sum or 1-sum of M_1 and M_2*

Proposition 6.38. *A matroid M is disconnected if and only if $E(M)$ has a proper nonempty subset T such that*

$$M = (M|T) \oplus (M|(E - T)).$$

Definition 6.18. *Let M and N be matroids each with at least two elements, with $E(M) \cap E(N) = \{p\}$ and suppose that neither M nor N has $\{p\}$ as a separator. Then $M \oplus_2 N$ is the matroid with ground set $(E(M) \cup E(N)) - \{p\}$ and set of circuits*

$$\mathcal{C}(M \backslash p) \cup \mathcal{C}(N \backslash p) \cup \{(C \cup D) - \{p\} : p \in C \in \mathcal{C}(M) \text{ and } p \in D \in \mathcal{C}(N)\}.$$

Proposition 6.39. *The classes of graphic and $\mathbb{F}$-representable matroids are closed under 1-sums and under 2-sums.*

It is not hard to come up with examples where the (geometric) dual of a planar k-connected graph is not k-connected. The generalisation of k-connectedness we would discuss now is preserved under duality. Let M be a matroid over E.

Definition 6.19. *For $X \subset E$, define*

$$\lambda_M(X) = r(X) + r(E - X) - r(M).$$

We call λ_M the connectivity function of M and will often abbreviate it as λ.

It directly follows from the formula for r^* that:

$$\lambda_M(X) = r(X) + r^*(X) - |X|.$$

Definition 6.20. *Let k be a positive integer. For $X \subset E(M)$, if $\lambda_M(X) < k$, then both X and $(X, E-X)$ are called k-separating. A k-separating pair $(X, E-X)$ for which $\min\{|X|, |E-X|\} \geqslant k$ is called a k-separation of M with sides X and $E - X$. We say that M is n-connected if, for all $1 \leqslant k \leqslant n-1$, it has no k-separations.*

In particular, we see that a separator is the same as a 1-separating set.

Corollary 6.40. *We have $\lambda_M(X) = \lambda_{M^*}(X)$. Moreover, M is n-connected if and only if M^* is n-connected.*

We are ready to state the following theorem which is used crucially for our classification.

Theorem 6.41. *A 2-connected matroid M is not 3-connected if and only if $M = M_1 \oplus_2 M_2$ for some matroids M_1 and M_2, each of which has at least three elements and is isomorphic to a proper minor of M.*

References

[1] J. Oxley, *What is a matroid?*, Cubo **5** (2003), 176–215.

[2] J. Oxley, *Matroid Theory*, 2nd ed., Oxford University Press, 2011.

[3] N. Brettell, *The excluded minors for* GF(5)*-representable matroids on ten elements*, Advances in Applied Mathematics **166** (2025), 102864. `https://doi.org/10.1016/j.aam.2025.102864`

[4] Deng Tianle, *matroid1: computational classification and verification artifacts.* `https://github.com/DengTianle/matroid1`.

[5] *The rank-four, eleven-element excluded minors for representability over* $\mathbb{F}_5$. Project paper, revised exposition, 5 November 2026, `matroid1/paper/main.pdf`.

[6] *Deletion compatibility and exhaustive extension search*, project documentation, `matroid1/docs/DELETION_COMPATIBILITY.md`.

[7] *Completed rank-four search: status and computational resources*, project record, `matroid1/docs/STATUS.md`.

[8] *Rank-four, eleven-element verification record*, `matroid1/results/r4-n11/verification.json`.

[9] N. Wetzler, M. J. H. Heule, and W. A. Hunt, Jr., *DRAT-trim: Efficient checking and trimming using expressive clausal proofs*, Theory and Applications of Satisfiability Testing (SAT 2014), Lecture Notes in Computer Science **8561**, 422–429.

[10] *Diagnostic matroid instances and certificate validation*, project artifacts: `study/build_dataset.py`, `study/data/certification.json`, and `study/output/lekang/validation/summary.json`. The last record documents the 13 November 2026 recheck of all 24 cases.