

Package ‘SQMtools’

June 28, 2019

Title Analyze results generated by the SqueezeMeta pipeline

Version 0.3.1

Description SqueezeMeta is a versatile pipeline for the automated analysis of metagenomics/metatranscriptomics data (<http://github.com/jtamames/SqueezeMeta>). This package provides functions loading SqueezeMeta results into R, filtering them based on different criteria, and visualizing the results using basic plots. The SqueezeMeta project (and any subsets of it generated by the different filtering functions) is parsed into a single object, whose different components (e.g. tables with the taxonomic or functional composition across samples, contig/gene abundance profiles) can be easily analyzed using other R packages such as *vegan* or *DESeq2*

Author Fernando Puente-Sánchez, Natalia García-García

Maintainer Fernando Puente-Sánchez <fpuente@cnb.csic.es>

Depends R (>= 3.4.0)

Imports reshape2, ggplot2

Suggests vegan, DESeq2

License GPLv3

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1.9000

BugReports <https://github.com/jtamames/SqueezeMeta/issues>

URL <https://github.com/jtamames/SqueezeMeta>

R topics documented:

combineSQM	2
exportTable	3
Hadza	4
loadSQM	4
mostAbundant	7
plotBars	8
plotFunctions	8

plotHeatmap	9
plotTaxonomy	10
RecA	11
rowMaxs	12
rowMins	12
subsetBins	13
subsetContigs	14
subsetFun	15
subsetORFs	16
subsetRand	17
subsetTax	17
summary.SQM	18
USiCGs	19

Index	20
--------------	-----------

combineSQM	<i>Combine several SQM objects</i>
------------	------------------------------------

Description

Combine an arbitrary number of SQM objects into a single SQM object.

Usage

```
combineSQM(..., tax_source = "orfs", trusted_functions_only = F,
            ignore_unclassified_functions = F, rescale_copy_number = T)
```

Arguments

...	an arbitrary number of SQM objects
tax_source	character. Features used for calculating aggregated abundances at the different taxonomic ranks. Either "orfs" or "contigs" (default "orfs"). If the objects being combined contain a subset of taxa or bins, this parameter can be set to TRUE.
trusted_functions_only	logical. If TRUE, only highly trusted functional annotations (best hit + best average) will be considered when generating aggregated function tables. If FALSE (default), best hit annotations will be used.
ignore_unclassified_functions	logical. If FALSE, ORFs with no functional classification will be aggregated together into an "Unclassified" category. If TRUE, they will be ignored.
rescale_copy_number	logical. If TRUE, copy numbers will be recalculated using the RecA/RadA coverages in the subset. Otherwise, RecA/RadA coverages will be taken from the original object. By default it is set to TRUE, which means that the returned copy numbers will represent the average copy number per function <i>in the genomes of</i>

the selected bins or contigs. If any SQM objects that are being combined contain a functional subset rather than a contig/bins subset, this parameter should be set to FALSE.

Value

A SQM object

See Also

[subsetFun](#), [subsetTax](#)

Examples

```
data(Hadza)
# Select Carbohydrate metabolism ORFs in Bacteroidetes, and Amino acid metabolism ORFs in Proteobacteria
bact = subsetTax(Hadza, 'phylum', 'Bacteroidetes <phylum>')
bact.carb = subsetFun(bact, 'Carbohydrate metabolism')
proteo = subsetTax(Hadza, 'phylum', 'Proteobacteria')
proteo.amins = subsetFun(proteo, 'Amino acid metabolism')
bact.carb_proteo.amins = combineSQM(bact.carb, proteo.amins, rescale_copy_number=F)
```

exportTable	<i>Export results in tabular format</i>
-------------	---

Description

This function is a wrapper for R’s write.table function.

Usage

```
exportTable(table, output_name)
```

Arguments

- table vector, matrix or data.frame. The table to be written.logical.
- output_name character. Name of the output file.

Examples

```
data(Hadza)
Hadza.iron = subsetFun(Hadza, 'iron')
# Write the taxonomic distribution at the genus level of all the genes related to iron.
exportTable(Hadza.iron$taxa$genus$percent, 'Hadza.ironGenes.genus.tsv')
# Now write the distribution of the different iron-related COGs (Clusters of Orthologous Groups) across samples.
exportTable(Hadza.iron$functions$COG$tpm, 'Hadza.ironGenes.COG.tsv')
# Now write all the information contained in the ORF table.
exportTable(Hadza.iron$orfs$table, 'Hadza.ironGenes.orftable.tsv')
```

Hadza

Hadza hunter-gatherer gut metagenomes

Description

Subset of 5 bins (and the associated contigs and genes) obtained from running SqueezeMeta on two gut metagenomic samples obtained from two hunter-gatherers of the Hadza ethnic group.

Usage

```
data(Hadza)
```

Format

A SQM object; see [loadSQM](#).

Source

[SRR1927149](#), [SRR1929485](#).

References

Rampelli *et al.*, 2015. Metagenome Sequencing of the Hadza Hunter-Gatherer Gut Microbiota. *Curr. biol.* **25**:1682-93 ([PubMed](#)).

Examples

```
data(Hadza)
plotTaxonomy(Hadza, 'genus', rescale=T)
plotFunctions(Hadza, 'COG')
```

loadSQM

Load a SqueezeMeta project into R

Description

This function takes the path to a project directory generated by [SqueezeMeta](#) (whose name is specified in the `-p` parameter of the SqueezeMeta.pl script) and parses the results into a SQM object

Usage

```
loadSQM(project_path, tax_mode = "allfilter")
```

Arguments

project_path	character, project directory generated by SqueezeMeta.
tax_mode	character, which taxonomic classification should be loaded? SqueezeMeta applies the identity thresholds described in Luo <i>et al.</i> , 2014. Use allfilter for applying the minimum identity threshold to all taxa (default) and prokfilter for applying the threshold to Bacteria and Archaea, but not to Eukaryotes.

Value

SQM object containing the parsed project.

Prerequisites

1. Run **SqueezeMeta!** An example call for running it would be:
/path/to/SqueezeMeta/scripts/SqueezeMeta.pl -m coassembly -f fastq_dir -s samples_file -p project_dir
2. Generate tabular outputs with the sqm2tables.py script included in the path/to/SqueezeMeta/Utils directory:
/path/to/SqueezeMeta/Utils/sqm2tables.py project_dir project_dir/results/tables

The SQM object structure

The SQM object is a nested list which contains the following information:

lvl1	lvl2	lvl3	type	rows/names	columns	data
\$orfs	\$table		<i>dataframe</i>	orfs	misc. data	misc. data
	\$abund		<i>numeric matrix</i>	orfs	samples	abundances
	\$tpm		<i>numeric matrix</i>	orfs	samples	tpm
	\$seqs		<i>character vector</i>	orfs	(n/a)	sequences
	\$tax		<i>character matrix</i>	orfs	tax. ranks	taxonomy
\$contigs	\$table		<i>dataframe</i>	contigs	misc. data	misc. data
	\$abund		<i>numeric matrix</i>	contigs	samples	abundances
	\$tpm		<i>numeric matrix</i>	contigs	samples	tpm
	\$seqs		<i>character vector</i>	contigs	(n/a)	sequences
	\$tax		<i>character matrix</i>	contigs	tax. ranks	taxonomies
\$bins	\$bins		<i>character matrix</i>	contigs	bin. methods	bins
	\$table		<i>dataframe</i>	bins	misc. data	misc. data
	\$tpm		<i>numeric matrix</i>	bins	samples	tpm
\$taxa	\$tax		<i>character matrix</i>	bins	tax. ranks	taxonomy
	\$superkingdom	\$abund	<i>numeric matrix</i>	superkingdoms	samples	abundances
		\$percent	<i>numeric matrix</i>	superkingdoms	samples	percentages
	\$phylum	\$abund	<i>numeric matrix</i>	phyla	samples	abundances
		\$percent	<i>numeric matrix</i>	phyla	samples	percentages
	\$class	\$abund	<i>numeric matrix</i>	classes	samples	abundances
		\$percent	<i>numeric matrix</i>	classes	samples	percentages
	\$order	\$abund	<i>numeric matrix</i>	orders	samples	abundances
		\$percent	<i>numeric matrix</i>	orders	samples	percentages
	\$family	\$abund	<i>numeric matrix</i>	families	samples	abundances
		\$percent	<i>numeric matrix</i>	families	samples	percentages

\$functions	\$genus	\$abund	numeric matrix	genera	samples	abundances
		\$percent	numeric matrix	genera	samples	percentages
	\$species	\$abund	numeric matrix	species	samples	abundances
		\$percent	numeric matrix	species	samples	percentages
	\$KEGG	\$abund	numeric matrix	KEGG ids	samples	abundances
		\$tpm	numeric matrix	KEGG ids	samples	tpm
		\$copy_number	numeric matrix	KEGG ids	samples	avg. copies
	\$COG	\$abund	numeric matrix	COG ids	samples	abundances
		\$tpm	numeric matrix	COG ids	samples	tpm
		\$copy_number	numeric matrix	COG ids	samples	avg. copies
	\$PFAM	\$abund	numeric matrix	PFAM ids	samples	abundances
		\$tpm	numeric matrix	PFAM ids	samples	tpm
		\$copy_number	numeric matrix	PFAM ids	samples	avg. copies
	\$total_reads		numeric vector	samples	(n/a)	total reads
	\$misc					
	\$project_name		character vector	(empty)	(n/a)	project name
	\$samples		character vector	(empty)	(n/a)	samples
	\$tax_names_long	\$superkingdom	character vector	short names	(n/a)	full names
		\$phylum	character vector	short names	(n/a)	full names
		\$class	character vector	short names	(n/a)	full names
		\$order	character vector	short names	(n/a)	full names
		\$family	character vector	short names	(n/a)	full names
		\$genus	character vector	short names	(n/a)	full names
		\$species	character vector	short names	(n/a)	full names
	\$tax_names_short		character vector	full names	(n/a)	short names
	\$KEGG_names		character vector	KEGG ids	(n/a)	KEGG names
	\$COG_names		character vector	COG ids	(n/a)	COG names

Examples

```
## Not run:
# (outside R)
/path/to/SqueezeMeta/scripts/SqueezeMeta.pl -p Hadza -f raw -m coassembly -s test.samples # Run SqueezeMeta on the
/path/to/SqueezeMeta/utis/sqm2tables.py Hadza Hadza/results/tables # Generate the tabular outputs! They must be p
# now go into R
R
library(SQMtools)
Hadza = loadSQM("Hadza") # Where Hadza is the path to the SqueezeMeta output directory

## End(Not run)

data(Hadza)
# Which are the ten most abundant KEGG IDs in our data?
topKEGG = sort(rowSums(Hadza$functions$KEGG$tpm), decreasing=T)[1:10]
# Which functions do those KEGG IDs represent?
Hadza$misc$KEGG_names[topKEGG]
What is the relative abundance of the Gammaproteobacteria class across samples?
Hadza$taxa$class$percent['Gammaproteobacteria',]
# Which information is stored in the orf, contig and bin tables?
colnames(Hadza$orfs$table)
```

```
colnames(Hadza$contigs$table)
colnames(Hadza$bins$table)
# What is the GC content distribution of my metagenome?
boxplot(Hadza$contigs$table[, 'GC perc']) # Not weighted by contig length or abundance!
```

mostAbundant

Get the N most abundant rows from a numeric table

Description

Return a subset of an input matrix or data frame, containing only the N most abundant rows, sorted. Alternatively, a custom set of rows can be returned.

Usage

```
mostAbundant(data, N = 10, items = NULL, others = F, rescale = F)
```

Arguments

data	numeric matrix or data frame
N	integer Number of rows to return (default 10).
items	Character vector. Custom row names to return. If provided, it will override N (default NULL).
others	logical. If TRUE, an extra row will be returned containing the aggregated abundances of the elements not selected with N or items (default FALSE).
rescale	logical. Scale result to percentages column-wise (default FALSE).

Value

A matrix or data frame (same as input) with the selected rows.

Examples

```
data(Hadza)
Hadza.carb = subsetFun(Hadza, 'Carbohydrate metabolism')
# Which are the 20 most abundant KEGG functions in the ORFs related to carbohydrate metabolism?
topCarb = mostAbundant(Hadza.carb$functions$KEGG$tpm, N=20)
# Now print them with nice names
rownames(topCarb) = paste(rownames(topCarb), Hadza.carb$misc$KEGG_names[rownames(topCarb)], sep='; ')
topCarb
We can pass this to any R function
heatmap(topCarb)
But for convenience we provide wrappers for plotting ggplot2 heatmaps and barplots
plotHeatmap(topCarb, label_y='TPM')
plotBars(topCarb, label_y='TPM')
```

plotBars	<i>Plot a barplot using ggplot2</i>
----------	-------------------------------------

Description

Plot a ggplot2 barplot from a matrix or data frame. The data should be in tabular format (e.g. features in rows and samples in columns).

Usage

```
plotBars(data, label_x = "Samples", label_y = "Abundances",
  label_fill = "Features", color = NULL, base_size = 11)
```

Arguments

data	Numeric matrix or data frame.
label_x	character Label for the x axis (default "Samples").
label_y	character Label for the y axis (default "Abundances").
label_fill	character Label for color categories (default "Features").
color	Vector with custom colors for the different features. If empty, the default ggplot2 palette will be used (default NULL).
base_size	numeric. Base font size (default 11).

Value

a ggplot2 plot object.

See Also

[plotTaxonomy](#) for plotting the most abundant taxa of a SQM object; [plotHeatmap](#) for plotting a heatmap with arbitrary data; [mostAbundant](#) for selecting the most abundant rows in a dataframe or matrix. data(Hadza) sk = Hadza\$taxa\$superkingdom\$abund plotBars(sk, label_y = 'Raw reads', label_fill = 'Superkingdom')

plotFunctions	<i>Heatmap of the most abundant functions in a SQM object</i>
---------------	---

Description

This function selects the most abundant functions across all samples in a SQM object and represents their abundances in a heatmap. Alternatively, a custom set of functions can be represented.

Usage

```
plotFunctions(SQM, fun_level = "KEGG", count = "tpm", N = 25,
  fun = c(), ignore_unclassified = T, gradient_col = c("ghostwhite",
    "dodgerblue4"), base_size = 11)
```

Arguments

SQM	A SQM object.
fun_level	character. Either "KEGG", "COG" or "PFAM" (default "KEGG").
count	character. Either "tpm" for TPM normalized values, "abund" for raw abundances or "copy_number" for copy numbers (default "tpm").
N	integer Plot the N most abundant functions (default 25).
fun	character. Custom functions to plot. If provided, it will override N (default NULL).
ignore_unclassified	logical. Don't include unclassified ORFs in the plot (default TRUE).
gradient_col	A vector of two colors representing the low and high ends of the color gradient (default c("ghostwhite", "dodgerblue4")).
base_size	numeric. Base font size (default 11).

Value

a ggplot2 plot object.

See Also

[plotTaxonomy](#) for plotting the most abundant taxa of a SQM object; [plotBars](#) and [plotHeatmap](#) for plotting barplots or heatmaps with arbitrary data.

Examples

```
data(Hadza)
plotFunctions(Hadza)
```

plotHeatmap	<i>Plot a heatmap using ggplot2</i>
-------------	-------------------------------------

Description

Plot a ggplot2 heatmap from a matrix or data frame. The data should be in tabular format (e.g. features in rows and samples in columns).

Usage

```
plotHeatmap(data, label_x = "Samples", label_y = "Features",
  label_fill = "Abundance", gradient_col = c("ghostwhite",
    "dodgerblue4"), base_size = 11)
```

Arguments

<code>data</code>	numeric matrix or data frame.
<code>label_x</code>	character Label for the x axis (default "Samples").
<code>label_y</code>	character Label for the y axis (default "Features").
<code>label_fill</code>	character Label for color scale (default "Abundance").
<code>gradient_col</code>	A vector of two colors representing the low and high ends of the color gradient (default <code>c("ghostwhite", "dodgerblue4")</code>).
<code>base_size</code>	numeric. Base font size (default 11).

Value

A ggplot2 plot object.

See Also

[plotFunctions](#) for plotting the top functional categories of a SQM object; [plotBars](#) for plotting a barplot with arbitrary data; [mostAbundant](#) for selecting the most abundant rows in a dataframe or matrix.

Examples

```
data(Hadza)
topPFAM = mostAbundant(Hadza$functions$PFAM$tpm)
topPFAM = topPFAM[rownames(topPFAM) != 'Unclassified',] # Take out the Unclassified ORFs.
plotHeatmap(topPFAM, label_x = 'Samples', label_y = 'PFAMs', label_fill = 'TPM')
data(Hadza)
phyla_percent = Hadza$taxa$phylum$percent
plotHeatmap(phyla_percent, label_y = 'Phylum', label_fill = 'Percentage')
```

plotTaxonomy

Barplot of the most abundant taxa in a SQM object

Description

This function selects the most abundant taxa across all samples in a SQM object and represents their abundances in a barplot. Alternatively, a custom set of taxa can be represented.

Usage

```
plotTaxonomy(SQM, rank = "phylum", count = "percent", N = 15,
  tax = NULL, others = T, ignore_unclassified = F, rescale = F,
  color = NULL, base_size = 11)
```

Arguments

SQM	A SQM object.
rank	Taxonomic rank to plot (default phylum).
count	character. Either "percent" for percentages, or "abund" for raw abundances (default "percent").
N	integer Plot the N most abundant taxa (default 15).
tax	character. Custom taxa to plot. If provided, it will override N (default NULL).
others	logical. Collapse the abundances of least abundant taxa, and include the result in the plot (default TRUE).
ignore_unclassified	logical. Don't include unclassified contigs in the plot (default FALSE).
rescale	logical. Re-scale results to percentages (default FALSE).
color	Vector with custom colors for the different features. If empty, we will use our own hand-picked palette if N<=15, and the default ggplot2 palette otherwise (default NULL).
base_size	numeric. Base font size (default 11).

Value

a ggplot2 plot object.

See Also

[plotFunctions](#) for plotting the most abundant functions of a SQM object; [plotBars](#) and [plotHeatmap](#) for plotting barplots or heatmaps with arbitrary data.

Examples

```
data(Hadza)
Hadza.amin = subsetFun(Hadza, 'Amino acid metabolism')
# Taxonomic distribution of amino acid metabolism ORFs at the family level.
plotTaxonomy(Hadza.amin, 'family')
```

RecA

RecA/RadA recombinase

Description

The recombination protein RecA/RadA is essential for the repair and maintenance of DNA, and has homologs in every bacteria and archaea. By dividing the coverage of functions by the coverage of RecA, abundances can be transformed into copy numbers, which can be used to compare functional profiles in samples with different sequencing depths. RecA-derived copy numbers are available in the SQM object (SQM\$functions\$<annotation_type>\$copy_number).

Usage

```
data(RecA)
```

Format

Character vector with the COG identifier for RecA/RadA.

Source

EggNOG Database.

Examples

```
data(Hadza)
data(RecA)
### Let's calculate the average copy number of each function in our samples.
# We do it for COG annotations here, but we could also do it for KEGG or PFAMs.
COG.coverage = SQMtools::aggregate.fun(Hadza, 'COG', trusted_functions_only=T, ignore_unclassified_functions=F)$
COG.copynumber = t(t(COG.coverage) / COG.coverage[RecA,]) # Sample-wise division by RecA tpm.
```

rowMaxs	<i>Return a vector with the row-wise maxima of a matrix or dataframe.</i>
---------	---

Description

Return a vector with the row-wise maxima of a matrix or dataframe.

Usage

```
rowMaxs(table)
```

rowMins	<i>Return a vector with the row-wise minima of a matrix or dataframe.</i>
---------	---

Description

Return a vector with the row-wise minima of a matrix or dataframe.

Usage

```
rowMins(table)
```

subsetBins	<i>Create a SQM object containing only the requested bins, and the contigs and ORFs contained in them.</i>
------------	--

Description

Create a SQM object containing only the requested bins, and the contigs and ORFs contained in them.

Usage

```
subsetBins(SQM, bins, trusted_functions_only = F,
           ignore_unclassified_functions = F, rescale_copy_number = T)
```

Arguments

SQM	SQM object to be subsetted.
bins	character. Vector of bins to be selected.
trusted_functions_only	logical. If TRUE, only highly trusted functional annotations (best hit + best average) will be considered when generating aggregated function tables. If FALSE, best hit annotations will be used (default FALSE).
ignore_unclassified_functions	logical. If FALSE, ORFs with no functional classification will be aggregated together into an "Unclassified" category. If TRUE, they will be ignored (default FALSE).
rescale_copy_number	logical. If TRUE, copy numbers will be recalculated using the RecA/RadA coverages in the subset. Otherwise, RecA/RadA coverages will be taken from the original object. By default it is set to TRUE, which means that the returned copy numbers will represent the average copy number per function <i>in the genomes of the selected bins</i> .

Value

SQM object containing only the requested bins.

See Also

[subsetContigs](#), [subsetORFs](#)

Examples

```
data(Hadza)
# Which are the five most complete bin?
topBinNames = rownames(Hadza$bins$table)[order(Hadza$bins$table[, 'Completeness'], decreasing=T)][1:5]
topBins = subsetBins(Hadza, topBinNames)
```

subsetContigs	<i>Select contigs</i>
---------------	-----------------------

Description

Create a SQM object containing only the requested contigs, the ORFs contained in them and the bins that contain them.

Usage

```
subsetContigs(SQM, contigs, trusted_functions_only = F,
  ignore_unclassified_functions = F, rescale_copy_number = F)
```

Arguments

SQM	SQM object to be subsetted.
contigs	character. Vector of contigs to be selected.
trusted_functions_only	logical. If TRUE, only highly trusted functional annotations (best hit + best average) will be considered when generating aggregated function tables. If FALSE, best hit annotations will be used (default FALSE).
ignore_unclassified_functions	logical. If FALSE, ORFs with no functional classification will be aggregated together into an "Unclassified" category. If TRUE, they will be ignored (default FALSE).
rescale_copy_number	logical. If TRUE, copy numbers will be recalculated using the RecA/RadA coverages in the subset. Otherwise, RecA/RadA coverages will be taken from the original object (default FALSE).

Value

SQM object containing only the selected contigs.

See Also

[subsetORFs](#)

Examples

```
data(Hadza)
# Which contigs have a GC content below 40?
lowGCcontigNames = rownames(Hadza$contigs$table[Hadza$contigs$table[, 'GC perc'] < 40,])
lowGCcontigs = subsetContigs(Hadza, lowGCcontigNames)
hist(lowGCcontigs$contigs$table[, 'GC perc'])
```

subsetFun	<i>Filter results by function</i>
-----------	-----------------------------------

Description

Create a SQM object containing only the ORFs with a given function, and the contigs and bins that contain them.

Usage

```
subsetFun(SQM, fun, fixed = F, trusted_functions_only = F,
  ignore_unclassified_functions = F, rescale_copy_number = F)
```

Arguments

SQM	SQM object to be subsetted.
fun	character, pattern to search for in the different functional classifications.
fixed	logical. If TRUE, pattern is a string to be matched as is. If FALSE the pattern is treated as a regular expression (default FALSE).
trusted_functions_only	logical. If TRUE, only highly trusted functional annotations (best hit + best average) will be considered when generating aggregated function tables. If FALSE, best hit annotations will be used (default FALSE).
ignore_unclassified_functions	logical. If FALSE, ORFs with no functional classification will be aggregated together into an "Unclassified" category. If TRUE, they will be ignored (default FALSE).
rescale_copy_number	logical. If TRUE, copy numbers will be recalculated using the RecA/RadA coverages in the subset. Otherwise, RecA/RadA coverages will be taken from the original object (default FALSE).

Value

SQM object containing only the requested function.

See Also

[subsetTax](#), [subsetORFs](#), [combineSQM](#). The most abundant items of a particular table contained in a SQM object can be selected with [mostAbundant](#).

Examples

```
data(Hadza)
Hadza.iron = subsetFun(Hadza, 'iron')
Hadza.carb = subsetFun(Hadza, 'Carbohydrate metabolism')
```

subsetORFs

*Select ORFs***Description**

Create a SQM object containing only the requested ORFs, and the contigs and bins that contain them. Internally, all the other subset functions in this package end up calling subsetORFs to do the work for them.

Usage

```
subsetORFs(SQM, orfs, tax_source = "orfs", trusted_functions_only = F,
  ignore_unclassified_functions = F, rescale_copy_number = F)
```

Arguments

SQM	SQM object to be subsetted.
orfs	character. Vector of ORFs to be selected.
tax_source	character. Features used for calculating aggregated abundances at the different taxonomic ranks. Either "orfs" or "contigs" (default "orfs").
trusted_functions_only	logical. If TRUE, only highly trusted functional annotations (best hit + best average) will be considered when generating aggregated function tables. If FALSE, best hit annotations will be used (default FALSE).
ignore_unclassified_functions	logical. If FALSE, ORFs with no functional classification will be aggregated together into an "Unclassified" category. If TRUE, they will be ignored (default FALSE).
rescale_copy_number	logical. If TRUE, copy numbers will be recalculated using the RecA/RadA coverages in the subset. Otherwise, RecA/RadA coverages will be taken from the original object (default FALSE).

Value

SQM object containing the requested ORFs.

A note on contig/bins subsetting

While this function selects the contigs and bins that contain the desired orfs, it DOES NOT recalculate contig/bin abundance and statistics based on the selected ORFs only. This means that the abundances presented in tables such as `SQM$contig$abund` or `SQM$bins$tpm` will still refer to the complete contigs and bins, regardless of whether only a fraction of their ORFs are actually present in the returned SQM object. This is also true for the statistics presented in `SQM$contigs$table` and `SQM$bins$table`.

Examples

```
data(Hadza)
# Select the 100 most abundant ORFs in our dataset.
mostAbundantORFnames = names(sort(rowSums(Hadza$orfs$tpm), decreasing=T))[1:100]
mostAbundantORFs = subsetORFs(Hadza, mostAbundantORFnames)
```

subsetRand	Select random ORFs
------------	--------------------

Description

Create a random subset of a SQM object.

Usage

```
subsetRand(SQM, N)
```

Arguments

- SQM SQM object to be subsetted.
- N numeric. number of random ORFs to select.

Value

SQM object containing a random subset of ORFs.

See Also

[subsetORFs](#)

subsetTax	Filter results by taxonomy
-----------	----------------------------

Description

Create a SQM object containing only the contigs with a given consensus taxonomy, the ORFs contained in them and the bins that contain them.

Usage

```
subsetTax(SQM, rank, tax, trusted_functions_only = F,
          ignore_unclassified_functions = F, rescale_copy_number = T)
```

Arguments

SQM	SQM object to be subsetted.
rank	character. The taxonomic rank from which to select the desired taxa (superkingdom, phylum, class, order, family, genus, species)
tax	character. The taxon to select.
trusted_functions_only	logical. If TRUE, only highly trusted functional annotations (best hit + best average) will be considered when generating aggregated function tables. If FALSE, best hit annotations will be used (default FALSE).
ignore_unclassified_functions	logical. If FALSE, ORFs with no functional classification will be aggregated together into an "Unclassified" category. If TRUE, they will be ignored (default FALSE).
rescale_copy_number	logical. If TRUE, copy numbers will be recalculated using the RecA/RadA coverages in the subset. Otherwise, RecA/RadA coverages will be taken from the original object. By default it is set to TRUE, which means that the returned copy numbers will represent the average copy number per function <i>in the genomes of the selected taxa</i> .

Value

SQM object containing only the requested taxon.

See Also

[subsetFun](#), [subsetContigs](#), [combineSQM](#). The most abundant items of a particular table contained in a SQM object can be selected with [mostAbundant](#).

Examples

```
data(Hadza)
Hadza.Escherichia = subsetTax(Hadza, 'genus', 'Escherichia')
Hadza.Bacteroidetes = subsetTax(Hadza, 'phylum', 'Bacteroidetes')
```

summary.SQM

summary method for class SQM

Description

Computes different statistics of the data contained in the SQM object.

Usage

```
## S3 method for class 'SQM'
summary(SQM)
```

Value

A list of summary statistics.

USiCGs	<i>Universal Single-Copy Genes</i>
--------	------------------------------------

Description

Lists of Universal Single Copy Genes for Bacteria and Archaea. These are useful for transforming coverages or tpms into copy numbers. This is an alternative way of normalizing data in order to be able to compare functional profiles in samples with different sequencing depths.

Usage

```
data(USiCGs)
```

Format

Character vector with the KEGG identifiers for 15 Universal Single Copy Genes.

Source

[Carr *et al.*, 2013. Table S1.](#)

References

Carr, Shen-Orr & Borenstein (2013). Reconstructing the Genomic Content of Microbiome Taxa through Shotgun Metagenomic Deconvolution *PLoS Comput. Biol.* **9**:e1003292. ([PubMed](#)).

Examples

```
data(Hadza)
data(USiCGs)
### Let's look at the Universal Single Copy Gene distribution in our samples.
KEGG.tpm = Hadza$functions$KEGG$tpm
all(USiCGs %in% rownames(KEGG.tpm)) # Are all the USiCGs present in our dataset?
# Plot a boxplot of USiCGs tpms and calculate median USiCGs tpm.
# This looks weird in the test dataset bc it's only a subset of the metagenomes.
# In a set of complete metagenomes USiCGs should have fairly similar TPM averages and low dispersion across samples.
boxplot(t(KEGG.tpm[USiCGs,]), names=USiCGs, ylab='TPM', col='slateblue2')

### Now let's calculate the average copy numbers of each function.
# We do it for KEGG annotations here, but we could also do it for COGs or PFAMs.
KEGG.coverage = SQMtools::aggregate.fun(Hadza, 'KEGG', trusted_functions_only=T, ignore_unclassified_functions=F)
USiCGs.cov = apply(KEGG.coverage[USiCGs,], 2, median)
KEGG.copynumber = t(t(KEGG.coverage) / USiCGs.cov) # Sample-wise division by the median USiCG coverage.
```

Index

*Topic **datasets**

Hadza, [4](#)

RecA, [11](#)

USiCGs, [19](#)

combineSQM, [2](#), [15](#), [18](#)

exportTable, [3](#)

Hadza, [4](#)

loadSQM, [4](#), [4](#)

mostAbundant, [7](#), [8](#), [10](#), [15](#), [18](#)

plotBars, [8](#), [9–11](#)

plotFunctions, [8](#), [10](#), [11](#)

plotHeatmap, [8](#), [9](#), [9](#), [11](#)

plotTaxonomy, [8](#), [9](#), [10](#)

RecA, [11](#)

rowMaxs, [12](#)

rowMins, [12](#)

subsetBins, [13](#)

subsetContigs, [13](#), [14](#), [18](#)

subsetFun, [3](#), [15](#), [18](#)

subsetORFs, [13–15](#), [16](#), [17](#)

subsetRand, [17](#)

subsetTax, [3](#), [15](#), [17](#)

summary.SQM, [18](#)

USiCGs, [19](#)