

A photograph of Craig Dunn, a man with short brown hair, smiling and wearing a green t-shirt. A small brown stuffed monkey is perched on his right shoulder. The background is a dark blue gradient with a diagonal light blue line.

Xamarin Evolve 2014

Localization Techniques

Craig Dunn
craig@xamarin.com



Xamarin University

Millions of smartphone users CAN'T READ...

Xamarin University


Millions of smartphone
users CAN'T READ...
...the language your
app is published in.

Xamarin University

Agenda

1. Terminology
2. Process
3. iOS native
4. Android native
5. Windows Phone & Xamarin.Forms

Xamarin University



Terminology

Xamarin University

Terminology

- Internationalization – i18n
- Localization – L10n
- Globalization, sometimes used to refer to both
- Language – en, fr, de
- Region– en-AU, es-ES, fr-CA, pt-BR
- Locale/Culture




Xamarin University

Process

Xamarin University

Internationalization and Localization

Application build process



Xamarin University

Internationalization Process

- No hardcoded strings
- Don't concatenate
- Language-aware loading of resources (images, video, etc)
- Culture-aware display & parsing of user-input

Xamarin University



Internationalization Process

No hardcoded strings

```
var button = new Button() ;  
button.Text = "OK";  
var label = new Label() ;  
label.Text = "Name:";
```

```
var button = new Button() ;  
button.Text = GetString("OK"); // explain GetString later  
var label = new Label();  
label.Text = GetString("Name:"); // explain GetString later
```

Xamarin University

Internationalization Process

Don't concatenate

```
var numEmails = emailList.Count();  
label.Text = "You have " + numEmails + " email/s";
```

```
var numEmails = emailList.Count();  
var msg = GetString("You have no emails");  
if (numEmails == 1)  
    msg = GetString("You have 1 email");  
else if (numEmails > 1)  
    msg = String.Format(GetString("You have {0} emails"));  
label.Text = msg;
```

Xamarin University

Internationalization Process

Loading of resources

```
var image = new Image() ;  
image.Source = "MyImage.jpg";
```

```
var image = new Image() ;  
image.Source = GetPath("MyImage.jpg"); //
```



Xamarin University

Internationalization Process

Display correct formatting

```
priceLabel.Text = "$" + priceFromDatabase;

deliveryDate.Text = dateFromDatabase.ToString ("dd-MMM-yy");

priceLabel.Text = priceFromDatabase.ToString("C",
                                             new CultureInfo("de-DE"));
deliveryDate.Text = dateFromDatabase.ToString ("D",
                                             new CultureInfo("en-AU"));;
```

Xamarin University

Internationalization Process

Parsing user-input

```
var amountText = Price.Text; // user input
var amount = Double.Parse(amountText);

var amountText = Price.Text; // user input
var a = Double.Parse(amount,
    NumberStyles.AllowCurrencySymbol |
    NumberStyles.AllowDecimalPoint |
    NumberStyles.AllowThousands,
    new CultureInfo("es-ES")); // correct culture
```

Xamarin University

Localization Process

- Export strings
- Export resources (images, videos, etc)
- Engage translators/designers
- Add translated strings and resources to the project

Xamarin University



Export Strings & Resources

- Use industry-standard format
 - strings
 - icons, images, videos, etc (might need to provide source, eg. Photoshop files)
- Define the formats and structure for the localized resources:
 - filenames, directory structure

Xamarin University

Localization!

Translators

- Culturally aware
 - tone & vocabulary of translated text
 - colors, imagery, iconography

Xamarin University

Import Strings & Resources

Re-build

- Add localized strings and resources to the application project
- Re-build and distribute for testing in all languages

Xamarin University



iOS native


- xx.lproj directories
- Localizable.strings files
- LocalizedString()


Xamarin University

A photograph of a white iPhone displaying a timer app. The screen shows a timer set for 10 minutes, with the time 09:54 and a progress bar. The status bar at the top shows "ROGERS", signal strength, time "9:59 AM", and 100% battery.


iOS Native

.lproj directories





```
"LionTodo" = "LionTodo";
"Task Details" = "Task Details";
"Name" = "Name";
```



```
"CFBundleDisplayName" = "ライオン";
"LionTodo" = "ライオンTodo";
"Task Details" = "タスクの詳細";
"Name" = "タイトル";
```

Xamarin University

iOS Native

Localizable.strings files

<pre>"LionTodo" = "LionTodo"; "<new task>" = "<new task>"; "Task Details" = "Task Details"; "Name" = "Name"; "task name" = "task name"; "Notes" = "Notes"; "other task info" = "other info"; "Done" = "Done"; "Save" = "Save"; "Delete" = "Delete";</pre>	<pre>"LionTodo" = "ライオンTodo"; "<new task>" = "<新しいタスク>"; "Task Details" = "タスクの詳細"; "Name" = "タイトル"; "task name" = "タスク名"; "Notes" = "注釈"; "other task info" = "他のタスクの情報"; "Done" = "削除する"; "Save" = "はい"; "Delete" = "削除する";</pre>
---	---

Xamarin University

iOS Native

LocalizedString()

```
public string LocalizedString (
    string key,
    string comment
)
```

Parameter
comment: Hint to the application developer's translators.

Summary
Retrieves the localized string for the *key* or, if not available, returns the key itself.

```
var bundle = NSBundle.MainBundle;
// labels
nameLabel.Text = bundle.LocalizedString("Name", "Title of a todo task");
notesLabel.Text = bundle.LocalizedString("Notes", "Extra info about task");
// button
saveButton.SetTitle(bundle.LocalizedString("Save", "Save task info"),
    UIControlState.Normal);
```

Xamarin University

Android Native

Xamarin University

Android native


- values-xx directories
- Strings.xml files

Xamarin University



Android Native

values- directories



```
<string name="AppName">LionTodo</string>
<string name="NameLabel">Name</string>
<string name="NamePlacholder">task name</string>
```

```
<string name="AppName">LeónTodo</string>
<string name="NameLabel">Detalles de la tarea</st
<string name="NamePlacholder">nombre de la tarea<
```

Android Native

Strings.xml files

```
<?xml version="1.0" encoding="utf-8"?>
<resources>
  <string name="AppName">LeónTodo</string>
  <string name="NewTaskPlaceholder">&lt;nueva tarea&gt;</string>
  <string name="NameLabel">Detalles de la tarea</string>
  <string name="NamePlacholder">nombre de la tarea</string>
  <string name="NotesLabel">Notas</string>
  <string name="NotesPlaceholder">otra información</string>
  <string name="DoneLabel">Completa</string>
  <string name="SaveButton">Guarda</string>
  <string name="DeleteButton">Borra</string>
  <string name="AddButton">Add tarea</string>
</resources>
```

Xamarin University

Android Native

Code

d

Xamarin University

Windows Phone & Xamarin.Forms



Xamarin University

Windows Phone & Xamarin.Forms

- RESX
- Strings.xml files

Xamarin University





.NET Native

ResourceManager

```
ResourceManager temp = new ResourceManager(  
    "LionTodo.Resources.AppResources", typeof(Application).Assembly);  
  
string result = temp.GetString (key, new CultureInfo (netLanguage));
```

Xamarin University

Summary

- Localization opens up new markets
- Internationalizing your code requires some planning
- There are native options for each platform
- You can use familiar .NET approach on all platforms with Xamarin

Xamarin University