Weekly Meeting

NeuroStrike: Neuron-Level Attacks on Aligned LLMs

Wu et al.,
Technical University of Darmstadt
Published in NDSS'26

2026.03.30

SecAI Lab

SUNG KYUN KWAN UNIVERSITY

TL;DR

- Core flaw (of current landscape): sparse, few safety neurons
  - Alignment relies on <1% of neurons
  - Creates a single point of failure

- Propose two attacks
  - White-box: prunes safety neurons at inference
  - Black-box (i.e., LLM profiling attack): train surrogate model (with same model family) to evade activation of safety neurons

- Takeaway
  - Behavioral guardrails are structurally insufficient

Motivation

- Current jailbreak landscape
  - Mostly prompt-space attacks
  - Trial-and-error heavy
  - Weak transfer across models

- Gap
  - Limited understanding of “where safety lives” inside the model



Safety neurons

- Safety alignment
  - Can be seen as benign vs. malicious prompts separated in latent space

- Safety neurons?
  - Neurons with consistently high activation on malicious than benign outputs
  - Thresholded as mean-activation gap (benign activation vs. malicious activation)
  - Refusal: consequence of activating safety neurons

- Properties
  - Discriminates harmful vs benign inputs
  - Very small fraction of neurons (~0.6%, lottery ticket hypothesis)
  - Similar behavior across same-family (even survives fine-tuning!)



Safety neurons activation





Threat model

- Goal
  - Elicit unsafe responses
  - Keep general utility mostly intact

- White-box
  - Access to model's weights + neuron activations
  - Ability to modify inference path (i.e., discarding neurons)

- Black-box
  - No internal infos, only API access (query – then – grab)
  - Aided from related open-weight surrogate

Flood of neurons?

- Bottleneck
  - Real-time activation tracing in LLMs are computationally prohibitive

- Solutions (in this paper)
  - Offline profiling: Identify safety neurons prior to actual attack using small contrastive set (100 benign, 100 mal)
  - Last-token focus: Capture activation values “only at the final token of the input prompt” (?)

- Memory overhead? (70B case)
  - Neurons: 28,672 (hidden dim) * 80 (# layers) = 2,293,760
  - Profiling matrix: 200 (# queries) * 2M * 32 (float32) ~= 1.8GB
  - Perform logistic regression (to figure out outliers) is quick as light

Overview (white-box)

- Identify safety neurons, then prune



Fig. 1: An overview of the NeuroStrike in the white-box attack scenario.

White-box attacks (details)

- Core idea
  - Identify safety neurons from benign vs malicious activation differences

- Pipeline
  - Collect activations on benign and malicious prompts
  - Perform logistic regression to identify outliers (with z-score)
  - Prune / mask safety neurons during inference

- Effect
  - Weaken refusal mechanism directly
  - No retraining, keep utility (original capabilities) at best



Fig. 3: Logistic regression weights and chosen outliers.

Overview (black-box)

- Given knowing which neurons are safety ones
- Reward prompt which does not activate safety neurons (while jailbreak succeeded)



Fig. 2: An overview of the NeuroStrike in the black-box attack scenario.

Black-box attacks (details)

- Core idea
  - Use surrogate to profile safety behavior
  - Train jailbreak prompt generator (both trigger harmful answer and avoid strong safety neuron activation)

- Pipeline
  - Identify surrogate safety neurons (from same families)
  - Train jailbreak prompt generator on surrogate
  - Rewards generator prompts for attack success
    + low safety neuron activation
  - Transfer generated prompts to black-box target

- Effect
  - Mostly offline, less trial-and-error
  - Strong transfer than vanilla malicious prompts



(a) Base model [32]. (b) Fine-tuned model [45].

Fig. 4: PCA projection of safety neuron activations.

Evaluation setup

- Model coverage
  - 24 open-source LLMs
  - 11 fine-tuned variants
  - 5 black box targets (Five from Google vs. gemma-3)

- Dataset
  - 7,000 malicious and benign prompts (from Harmbench and TDC23-Redteaming), StrongReject Benchmark

- Main metrics
  - ASR
  - Safety neuron ratio (% of pruned safety neurons)
  - Utility preservation

Results (on open-sourced models; white)

- Left: LLM, Right: VLM (via text-to-image)

Target Model	0%	25%	50%	100%	Ratio
Llama-3.2-1B-Instruct	2.9%	3.5%	15.7%	74.4%	0.5%
Llama-3.2-3B-Instruct	1.6%	4.2%	46.3%	72.2%	0.4%
Qwen2.5-7B-Instruct	5.1%	4.5%	28.1%	79.6%	0.3%
Qwen2.5-14B-Instruct	1.9%	2.6%	35.8%	85.9%	0.4%
Phi-4-mini-instruct	1.3%	1.3%	67.7%	81.8%	0.5%
Phi-4	0.6%	1.0%	78.3%	89.1%	0.4%
gemma-2b-it	1.0%	1.3%	10.5%	41.2%	0.5%
gemma-7b-it	0.6%	1.3%	24.0%	68.1%	0.5%
DeepSeek-R1-Dist.-Qwen-1.5B	76.7%	78.6%	83.7%	81.5%	0.3%
DeepSeek-R1-Dist.-Llama-8B	39.3%	73.8%	81.2%	86.9%	0.4%
QwQ-32B	2.9%	3.2%	32.3%	85.3%	0.5%
Average	*12.1%*	*15.9%*	*45.8%*	*76.9%*	*0.4%*

TABLE I: ASR and Safety Neuron Ratio on different LLMs.

Target Model	T2I w/ SN	NSFW w/ SN	T2I w/o SN	NSFW w/o SN	Ratio
gemma-3-12b-it	0.6%	19.4%	82.1%	100%	0.6%
gemma-3-27b-it	0.3%	12.8%	73.2%	100%	0.6%
Qwen2.5-VL-7B-Instruct	0.9%	99.8%	78.6%	100%	0.5%
Qwen2.5-VL-32B-Instruct	0.6%	97.8%	88.8%	100%	0.5%
Average	*0.6%*	*57.5%*	*80.7%*	*100%*	*0.6%*

TABLE II: ASR and Safety Neuron (SN) Ratio with text-to-image (T2I) and NSFW images on multimodal LLMs.

Results (on transferability; white)

- Maybe due to artificial homogeneities? (even grok-3-beta vs. Gemma-3: 43.8%)

Base Model	Target (Fine-tuned) Model	Fine-tuned for	ASR w/ SN	ASR w/o SN	Ratio
Llama-3.1-8B-Instruct	Llama-3.1-8B-UltraMedical	Biomedicine	38.0% $_{+37.0\%}$	83.4% $_{-3.5\%}$	0.7%
Llama-3.2-1B-Instruct	Vikhr-Llama-3.2-1B-Instruct	Russian language	0.3% $_{-2.6\%}$	74.4% $_{+0.0\%}$	0.5%
Llama-3.2-3B-Instruct	Llama-Doctor-3.2-3B-Instruct	Medical consultation	22.4% $_{+20.8\%}$	76.0% $_{+3.8\%}$	0.4%
Qwen2.5-7B-Instruct	Qwen2.5-Coder-7B-Instruct	Programming	2.6% $_{-2.5\%}$	78.0% $_{-1.6\%}$	0.3%
Qwen2.5-7B-Instruct	Fin-R1	Financial reasoning	20.1% $_{+15.0\%}$	86.9% $_{+7.3\%}$	0.3%
Qwen2.5-14B-Instruct	oxy-1-small	Role play	78.9% $_{+77.0\%}$	88.1% $_{+2.2\%}$	0.4%
Qwen2.5-32B-Instruct	s1.1-32B	Reasoning	47.2% $_{+44.6\%}$	87.5% $_{+0.9\%}$	0.6%
Phi-4-mini-instruct	phi-4-mini-chinese-it-e1	Reasoning & STEM	4.8% $_{+3.5\%}$	90.1% $_{+8.3\%}$	0.5%
Phi-4	DNA-R1	Korean language	61.3% $_{+60.7\%}$	91.6% $_{+2.5\%}$	0.4%
gemma-2-2b-it	gemma-2-2b-jpn-it	Japanese language	0.0% $_{+0.0\%}$	63.9% $_{-2.2\%}$	0.6%
gemma-2-9b-it	Quill-v1	Humanlike writing	0.0% $_{+0.0\%}$	43.8% $_{+2.3\%}$	0.6%
Average			*25.1%* $_{+23.0\%}$	*78.5%* $_{+1.8\%}$	*0.5%*

TABLE III: Safety Neurons (SN) Transfer Attack on Fine-tuned LLMs. The difference with the base model is in red/green.

Results (on black-boxed)

- Surrogate model: Google's gemma-3

Target Model	Vanilla	Jailbreak	NeuroStrike
Gemini-2.0-Flash	0.8%	15.7%	54.7%
Gemini-2.0-Flash-Lite	1.0%	15.6%	49.2%
Gemini-1.5-Pro	1.4%	5.3%	55.7%
Gemma-3-1b-it	10.6%	24.6%	79.9%
QwQ-32B	3.6%	6.3%	78.9%
Average	*3.5%*	*13.5%*	*63.7%*

TABLE V: ASRs benchmark with different prompt types.

Model	PAIR	TAP	Puzzler	NeuroStrike
Gemini-2.0-Flash	37.3%	14.0%	73.0%	54.7%
Gemini-2.0-Flash-Lite	9.8%	8.0%	86.1%	49.2%
Gemini-1.5-Pro	54.9%	32.0%	75.0%	55.7%
Gemma-3-1b-it	33.9%	20.4%	94.0%	79.9%
QwQ-32B	18.9%	12.2%	97.2%	78.9%
Average	*31.0%*	*17.3%*	*85.7%*	*63.7%*

TABLE VI: ASR benchmark with state-of-the-art jailbreaks.

Results (on utility preservation)



(a) HellaSwag



(b) RTE

Results (on Defenses)

- Perplexity filtering: flags prompt with low linguistic naturalness
- SmoothLLM: perturbs prompts and aggregates outputs
- Layer-specific editing: realigns internal model layers

Model	Perplexity Filter	SmoothLLM	LSE
Gemini-2.0-Flash	48.7%	52.8%	–
Gemini-2.0-Flash-Lite	43.2%	47.3%	–
Gemini-1.5-Pro	49.7%	53.8%	–
Gemma-3-1b-it	79.8%	78.0%	60.0%
QwQ-32B	78.8%	76.4%	43.4%
Average	*60.0%*	*61.7%*	*54.4%*

TABLE VII: ASR of NeuroStrike under various defenses.

Pros, Cons, Future directions

- Pros
  - Efficient: shifts from computationally expensive gradient searches to linear probing
  - Strong transferability

- Cons
  - Sensitive to threshold-given classification (though ASR vs. utility challenges)
  - Hard pruning has room for improvements

- Future directions
  - Activation steering: replace blunt zeroing with precise vector math (subtract vector which directs toward a refusal)

Target Model	$z = 2$	$z = 3$	$z = 4$
Llama-3.2-1B-Instruct	85.0%	74.4%	79.2%
Llama-3.2-3B-Instruct	76.0%	72.2%	58.8%
Qwen2.5-7B-Instruct	85.9%	79.6%	71.6%
Qwen2.5-14B-Instruct	84.7%	85.9%	81.8%
Phi-4-mini-instruct	89.8%	81.8%	75.1%
Phi-4	88.2%	89.1%	80.5%
gemma-2b-it	65.2%	41.2%	20.1%
gemma-7b-it	79.9%	68.1%	37.6%
DeepSeek-R1-Distill-Qwen-1.5B	78.9%	83.7%	81.8%
DeepSeek-R1-Distill-Llama-8B	N/A	81.2%	48.6%
QwQ-32B	84.6%	85.3%	62.0%
Average	*74.4%*	*76.9%*	*63.4%*

TABLE VIII: ASR with different z-score Threshold.

SecAI Lab

Thank you

Artificial Hivemind: The open-ended homogeneity of LMs



Figure 1: Responses to the query **"Write a metaphor about time"** clustered by applying PCA to reduce sentence embeddings to two dimensions. Each of the 25 models generates 50 responses using top-p sampling ($p = 0.9$) and temperature $= 1.0$. Despite the diversity of model families and sizes, the responses form just two primary clusters: a dominant cluster on the left centered on the metaphor "time is a river," and a smaller cluster on the right revolving around variations of "time is a weaver."