

# Introduction to N-adic numbers

## Practical Applications

Denis Morozov, PhD

`morozov.den@samsung.com`

<sup>1</sup>Samsung R&D

<sup>2</sup>Department of Computer Science, doctoral studies  
University of "Kiev-Mogyla Academy"

Presentation , 2013

# Outline

## 1 Motivation

- Objective
- Basic Properties
- Previous Work

## 2 Results

- Main Results
- Basic Ideas for Implementation

# Outline

## 1 Motivation

- Objective
- Basic Properties
- Previous Work

## 2 Results

- Main Results
- Basic Ideas for Implementation

# Outline

- 1 Motivation
  - Objective
  - **Basic Properties**
  - Previous Work

- 2 Results
  - Main Results
  - Basic Ideas for Implementation

# Sufficiency

Consideration for the following reasons ultrametrics (non-Archimedean metric spaces) is natural:

- in the context of a real analysis of the computer is a discrete system, but in terms of a 2-adic - continuous
- the modern computer is essentially an analog in terms of non Archimedean analysis

# Sufficiency

Consideration for the following reasons ultrametrics (non-Archimedean metric spaces) is natural:

- in the context of a real analysis of the computer is a discrete system, but in terms of a 2-adic - continuous
- the modern computer is essentially an analog in terms of non Archimedean analysis

# Sufficiency

Consideration for the following reasons ultrametrics (non-Archimedean metric spaces) is natural:

- in the context of a real analysis of the computer is a discrete system, but in terms of a 2-adic - continuous
- the modern computer is essentially an analog in terms of non Archimedean analysis

# Quick calculations

2-adic continuity of the basic operations of the processor allows the creation of models that use floating point numbers, and all calculations are made in the set of integers.

- 32 bit integer algorithms have good specifications for optimizing on existing processors
- number-theoretical Fourier transform works well for convolutions with large kernels



# Quick calculations

2-adic continuity of the basic operations of the processor allows the creation of models that use floating point numbers, and all calculations are made in the set of integers.

- 32 bit integer algorithms have good specifications for optimizing on existing processors
- number-theoretical Fourier transform works well for convolutions with large kernels

# Quick calculations

2-adic continuity of the basic operations of the processor allows the creation of models that use floating point numbers, and all calculations are made in the set of integers.

- 32 bit integer algorithms have good specifications for optimizing on existing processors
- number-theoretical Fourier transform works well for convolutions with large kernels

# Outline

## 1 Motivation

- Objective
- Basic Properties
- Previous Work

## 2 Results

- Main Results
- Basic Ideas for Implementation

# Main Result

formulation of the problem Valentin Vovk, Mobile Lab 2

Implemented a two-dimensional convolution with algebraic methods for the size of  $2^n \times 2^m$

- $0 \leq m, n \leq 10$ .

# Main Result

formulation of the problem Valentin Vovk, Mobile Lab 2


Implemented a two-dimensional convolution with algebraic methods for the size of  $2^n \times 2^m$

- $0 \leq m, n \leq 10$ .

# Plot Test Results

tests conducted by Andrei Zavorotny, Mobile Lab 2

As we see algebraic methods for convolution yield the best results on large sizes



# Test Results

- Test results for large sizes

Size	1024	512	256
Furie	2092	467	91.27
Ferma	1402	506	61.12

# Test Results

- Test results for large sizes

Size	1024	512	256
Furie	2092	467	91.27
Ferma	1402	506	61.12



# Outline

## 1 Motivation

- Objective
- Basic Properties
- Previous Work

## 2 Results

- Main Results
- Basic Ideas for Implementation

# Base Technical Points

During construction of the algorithm we are

- reducing the number of using modulo field's size
- using the FFT algorithm of length 32 based on symmetry of transform matrix
- transition from 64-bit to 32-bit arithmetic

# Base Technical Points

During construction of the algorithm we are


- reducing the number of using modulo field's size
- using the FFT algorithm of length 32 based on symmetry of transform matrix
- transition from 64-bit to 32-bit arithmetic

# Base Technical Points


During construction of the algorithm we are

- reducing the number of using modulo field's size
- using the FFT algorithm of length 32 based on symmetry of transform matrix
- transition from 64-bit to 32-bit arithmetic


# Cooley-Tukey scheme for for FFT




# Cooley-Tukey scheme for for FFT



# Cooley-Tukey scheme for for FFT




# Cooley-Tukey scheme for for FFT







# Cooley-Tukey scheme for for FFT




# Cooley-Tukey scheme for for FFT




# Cooley-Tukey scheme for for FFT




# Cooley-Tukey scheme for for FFT



# Cooley-Tukey scheme for for FFT



# Cooley-Tukey scheme for for FFT



# Summary

- In this work implemented a two-dimensional integer convolution
- Possible sizes are - 2, 4, 8, 16, 32, 64, 128, 256, 512, 1024
- Outlook
  - Next task to investigate the possibility of constructing fast two-dimensional convolution for sizes that are not powers of two

# Summary

- In this work implemented a two-dimensional integer convolution
- Possible sizes are - 2, 4, 8, 16, 32, 64, 128, 256, 512, 1024
- Outlook
  - Next task to investigate the possibility of constructing fast two-dimensional convolution for sizes that are not powers of two



# For Further Reading I



B. Bleihut

*Fast Algorithms for Digital Signal Processing [Russian translation].*

Mir, Moscow (1989)



D. Morozov.

The calculation of the convolution with the  
number-theoretical transforms

*Report for Mobile Lab 2, 8 pages, December 2011.*